SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

NovaScale R460
(Intel Xeon processor E5320,1.86GHz)

SPECfp®2006 = 12.4

SPECfp_base2006 = 12.0

CPU2006 license: 20
Test sponsor: Bull SAS
Tested by: Bull SAS

Test date: Jul-2007
Hardware Availability: Feb-2007
Software Availability: Dec-2006



Hardware

CPU Name:	Intel Xeon E5320
CPU Characteristics:	1.86 GHz, 8 MB L2, 1066 MHz system bus
CPU MHz:	1860
FPU:	Integrated
CPU(s) enabled:	8 cores, 2 chips, 4 cores/chip
CPU(s) orderable:	1 to 2 chips
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	8 MB I+D on chip per chip, 4 MB shared / 2 cores

Continued on next page

Software

Operating System:	Windows Server 2003 Enterprise Edition X64 Edition Service Pack1
Compiler:	Intel C++ Compiler for EM64T version 9.1 Package ID W_CC_C_9.1.033 Build no 20061104 Intel Fortran Compiler for EM64T version 9.1 Package ID W_FC_C_9.1.033 Build no 20061104 Microsoft Visual Studio 2005 (lib & linker)
Auto Parallel:	Yes
File System:	NTFS
System State:	Default

Continued on next page

SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

NovaScale R460
(Intel Xeon processor E5320,1.86GHz)

SPECfp2006 = 12.4

SPECfp_base2006 = 12.0

CPU2006 license: 20
Test sponsor: Bull SAS
Tested by: Bull SAS

Test date: Jul-2007
Hardware Availability: Feb-2007
Software Availability: Dec-2006

L3 Cache: None
Other Cache: None
Memory: 12 GB (12x1 GB) FB-DIMM PC2-4200F ECC CL4
Disk Subsystem: 1x73 GB SAS, 15000 RPM
Other Hardware: None

Base Pointers: 64-bit
Peak Pointers: 64-bit
Other Software: None

Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	528	25.7	**532**	**25.6**	532	25.5	**530**	**25.6**	531	25.6	529	25.7
416.gamess	**1594**	**12.3**	1594	12.3	1595	12.3	**1564**	**12.5**	1564	12.5	1564	12.5
433.milc	**1127**	**8.15**	1128	8.14	1125	8.16	1126	8.16	**1126**	**8.15**	1127	8.15
434.zeusmp	886	10.3	**885**	**10.3**	883	10.3	886	10.3	**885**	**10.3**	883	10.3
435.gromacs	617	11.6	**618**	**11.6**	618	11.5	**604**	**11.8**	604	11.8	604	11.8
436.cactusADM	267	44.7	**267**	**44.7**	266	44.9	267	44.7	**267**	**44.7**	266	44.9
437.leslie3d	805	11.7	**807**	**11.6**	812	11.6	805	11.7	**807**	**11.6**	812	11.6
444.namd	**826**	**9.71**	826	9.71	826	9.71	**826**	**9.71**	826	9.71	826	9.71
447.dealII	1141	10.0	**1141**	**10.0**	1141	10.0	1090	10.5	**1090**	**10.5**	1090	10.5
450.soplex	874	9.54	**872**	**9.57**	871	9.57	860	9.70	**858**	**9.72**	858	9.73
453.povray	424	12.6	423	12.6	**423**	**12.6**	**322**	**16.5**	322	16.5	322	16.5
454.calculix	907	9.10	905	9.12	**906**	**9.11**	862	9.57	**862**	**9.57**	862	9.57
459.GemsFDTD	**823**	**12.9**	822	12.9	823	12.9	**823**	**12.9**	822	12.9	823	12.9
465.tonto	1001	9.83	**1002**	**9.82**	1003	9.81	**907**	**10.8**	907	10.8	907	10.8
470.lbm	2278	6.03	**2239**	**6.14**	2238	6.14	2257	6.09	**2251**	**6.10**	2247	6.12
481.wrf	884	12.6	885	12.6	**884**	**12.6**	884	12.6	885	12.6	**884**	**12.6**
482.sphinx3	1376	14.2	1374	14.2	**1375**	**14.2**	**1328**	**14.7**	1327	14.7	1328	14.7

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

General Notes

```
The NovaScale R440 and the NovaScale R460 models are
electronically equivalent.
The results have been measured on a NovaScale R460 model.
```

Base Compiler Invocation

C benchmarks:

```
icl -Qvc8 -Qc99
```

C++ benchmarks:

```
icl -Qvc8
```

Continued on next page

Base Compiler Invocation (Continued)

Fortran benchmarks:
ifort

Benchmarks using both Fortran and C:
icl -Qvc8 -Qc99 ifort

Base Portability Flags

410.bwaves: -DSPEC_CPU_P64
416.gamess: -DSPEC_CPU_P64
433.milc: -D_Complex= -DSPEC_CPU_P64
434.zeusmp: -DSPEC_CPU_P64
435.gromacs: -D_Complex= -DSPEC_CPU_P64
436.cactusADM: -D_Complex= -DSPEC_CPU_P64 -Qlowercase /assume:underscore
437.leslie3d: -DSPEC_CPU_P64
444.namd: -DSPEC_CPU_P64 /TP
447.dealII: -D_Complex= -DSPEC_CPU_P64 -DBOOST_NO_INTRINSIC_WCHAR_T -DDEAL_II_MEMBER_VAR_SPECIALIZATION_BUG
450.soplex: -DSPEC_CPU_P64
453.povray: -DSPEC_CPU_P64 -DSPEC_CPU_WINDOWS_ICL
454.calculix: -D_Complex= -DSPEC_CPU_P64 -DSPEC_CPU_NOZMODIFIER -Qlowercase
459.GemsFDTD: -DSPEC_CPU_P64
465.tonto: -DSPEC_CPU_P64
470.lbm: -D_Complex= -DSPEC_CPU_P64
481.wrf: -DSPEC_CPU_P64 -DSPEC_CPU_WINDOWS_ICL
482.sphinx3: -D_Complex= -DSPEC_CPU_P64

Base Optimization Flags

C benchmarks:
-fast -Qparallel

C++ benchmarks:
-fast -Qparallel -Qcxx-features

Fortran benchmarks:
-fast -Qparallel

Benchmarks using both Fortran and C:
-fast -Qparallel

Base Other Flags

C benchmarks:
`-F950000000`

C++ benchmarks:
`-F950000000`

Fortran benchmarks:
`-F950000000`

Benchmarks using both Fortran and C:
`-F950000000`

Peak Compiler Invocation

C benchmarks:
`icl -Qvc8 -Qc99`

C++ benchmarks:
`icl -Qvc8`

Fortran benchmarks:
`ifort`

Benchmarks using both Fortran and C:
`icl -Qvc8 -Qc99 ifort`

Peak Portability Flags

`Same as Base Portability Flags`

Peak Optimization Flags

C benchmarks:
`-Qprof_gen`(pass 1) `-Qprof_use`(pass 2) `-fast`

C++ benchmarks:

444.namd: `basepeak = yes`

447.dealII: `-Qprof_gen`(pass 1) `-Qprof_use`(pass 2) `-fast -Qcxx-features`

450.soplex: `Same as 447.dealII`

Continued on next page

Peak Optimization Flags (Continued)

453.povray: `Same as 447.dealII`

Fortran benchmarks:

410.bwaves: `-Qprof_gen`(pass 1) `-Qprof_use`(pass 2) `-fast -Qparallel`

416.gamess: `-fast`

434.zeusmp: `basepeak = yes`

437.leslie3d: `basepeak = yes`

459.GemsFDTD: `basepeak = yes`

465.tonto: `Same as 410.bwaves`

Benchmarks using both Fortran and C:

435.gromacs: `-Qprof_gen`(pass 1) `-Qprof_use`(pass 2) `-fast`

436.cactusADM: `basepeak = yes`

454.calculix: `Same as 435.gromacs`

481.wrf: `basepeak = yes`

Peak Other Flags

C benchmarks:
`-F950000000`

C++ benchmarks:
`-F950000000`

Fortran benchmarks:
`-F950000000`

Benchmarks using both Fortran and C:
`-F950000000`

The flags file that was used to format this result can be browsed at
`http://www.spec.org/cpu2006/flags/flags.html`

You can also download the XML flags source by saving the following link:
`http://www.spec.org/cpu2006/flags/flags.xml`

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.
Report generated on Tue Jul 22 13:56:38 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 2 October 2007.