SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

IBM System p 570 (4.7 GHz, 8 core, RHEL)

SPECint®_rate2006 = 243

SPECint_rate_base2006 = 210

CPU2006 license: 11
Test sponsor: IBM Corporation
Tested by: IBM Corporation

Test date: Oct-2007
Hardware Availability: Jun-2007
Software Availability: Oct-2007



Hardware

CPU Name:	POWER6
CPU Characteristics:	
CPU MHz:	4700
FPU:	Integrated
CPU(s) enabled:	8 cores, 4 chips, 2 cores/chip, 2 threads/core
CPU(s) orderable:	2,4,8,12,16 cores
Primary Cache:	64 KB I + 64 KB D on chip per core
Secondary Cache:	4 MB I+D on chip per core
L3 Cache:	32 MB I+D off chip per chip
Other Cache:	None
Memory:	64 GB (32x2 GB) DDR2 667 MHz
Disk Subsystem:	2x73 GB SAS 15K RPM
Other Hardware:	None

Software

Operating System:	Red Hat Enterprise Linux Advanced Platform 5.1 for IBM POWER
Compiler:	IBM XL C/C++ Advanced Edition for Linux, V9.0
Auto Parallel:	No
File System:	ext3
System State:	Multi-User
Base Pointers:	32-bit
Peak Pointers:	32/64-bit
Other Software:	-IBM Post-Link Optimization for Linux on POWER, Version 5.4.0-10 -MicroQuill SmartHeap 8.1

SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

IBM System p 570 (4.7 GHz, 8 core, RHEL)

SPECint_rate2006 = 243

SPECint_rate_base2006 = 210

CPU2006 license: 11
Test sponsor: IBM Corporation
Tested by: IBM Corporation

Test date: Oct-2007
Hardware Availability: Jun-2007
Software Availability: Oct-2007

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	16	1086	144	**1085**	**144**	1085	144	16	860	182	856	183	**856**	**183**
401.bzip2	16	860	180	858	180	**858**	**180**	16	**766**	**201**	766	202	767	201
403.gcc	16	**645**	**200**	646	199	644	200	16	565	228	569	226	**566**	**227**
429.mcf	16	403	362	**403**	**362**	404	361	16	**402**	**363**	401	363	402	363
445.gobmk	16	**837**	**200**	837	200	838	200	16	**730**	**230**	730	230	731	229
456.hmmer	16	846	176	**844**	**177**	840	178	16	800	187	792	189	**794**	**188**
458.sjeng	16	**1089**	**178**	1096	177	1089	178	16	**974**	**199**	974	199	974	199
462.libquantum	16	**780**	**425**	779	425	780	425	8	251	662	250	663	**250**	**662**
464.h264ref	16	1217	291	1226	289	**1217**	**291**	16	**1006**	**352**	1006	352	1006	352
471.omnetpp	16	**646**	**155**	646	155	645	155	16	620	161	**620**	**161**	620	161
473.astar	16	726	155	727	154	**727**	**155**	16	609	184	608	185	**609**	**185**
483.xalancbmk	16	**512**	**216**	512	216	512	216	16	482	229	**482**	**229**	482	229

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

General Notes

```
kernel release 2.6.18-52.el5.

See flags file for details on following settings.

ulimit -s (stack) set to 262144.


System set to Enhanced mode when defining partition on HMC

Large pages reserved as follows by root user:
    echo 1600 > /proc/sys/vm/nr_hugepages
System configured with libhugetlbfs library for application access to large pages
Environment variables set before executing benchmarks.
    export HUGETLB_VERBOSE=0
    export HUGETLB_MORECORE=yes
    export XLFRTEOPTS=intrinthds=1

fdpr binary optimization tool used for
    400.perlbench 401.bzip2 403.gcc 429.mcf 456.hmmer 458.sjeng
    462.libquantum 464.h264ref 473.astar 483.xalancbmk

Benchmarks bound to a processor using numactl on the submit command.
```

Base Compiler Invocation

C benchmarks:
```
xlc -qlanglvl=extc99
```

C++ benchmarks:
```
xlC
```

Base Portability Flags

400.perlbench: `-DSPEC_CPU_LINUX_PPC`
462.libquantum: `-DSPEC_CPU_LINUX`
464.h264ref: `-qchars=signed`
483.xalancbmk: `-DSPEC_CPU_LINUX`

Base Optimization Flags

C benchmarks:
```
-O5 -qalias=noansi -qalloca -lhugetlbfs
```

C++ benchmarks:
```
-O5 -qrtti -lsmartheap
```

Base Other Flags

C benchmarks:
```
-qipa=noobject -qipa=threads
```

C++ benchmarks:
```
-qipa=noobject -qipa=threads
```

Peak Compiler Invocation

C benchmarks:
```
xlc -qlanglvl=extc99
```

C++ benchmarks:
```
xlC
```

Peak Portability Flags

400.perlbench: -DSPEC_CPU_LINUX_PPC
403.gcc: -DSPEC_CPU_LP64
462.libquantum: -DSPEC_CPU_LINUX
464.h264ref: -qchars=signed
483.xalancbmk: -DSPEC_CPU_LINUX

Peak Optimization Flags

C benchmarks:

400.perlbench: -Wl,-q -qpdf1(pass 1) -qpdf2(pass 2) -O4 -qalias=noansi -lsmartheap

401.bzip2: -Wl,-q -qpdf1(pass 1) -qpdf2(pass 2) -O4 -lhugetlbfs

403.gcc: -Wl,-q -qpdf1(pass 1) -qpdf2(pass 2) -O4 -qalloca -q64 -lhugetlbfs

429.mcf: -Wl,-q -O5 -qnoenablevmx -lhugetlbfs

445.gobmk: -qpdf1(pass 1) -qpdf2(pass 2) -O4 -qnoenablevmx -lhugetlbfs

456.hmmer: Same as 401.bzip2

458.sjeng: Same as 401.bzip2

462.libquantum: -Wl,-q -qpdf1(pass 1) -qpdf2(pass 2) -O5 -qnoenablevmx -q64 -lhugetlbfs

464.h264ref: -Wl,-q -qpdf1(pass 1) -qpdf2(pass 2) -O5 -q64 -lhugetlbfs

C++ benchmarks:

471.omnetpp: -qpdf1(pass 1) -qpdf2(pass 2) -O5 -qrtti -lsmartheap

473.astar: -Wl,-q -qpdf1(pass 1) -qpdf2(pass 2) -O5 -qnoenablevmx -lsmartheap

483.xalancbmk: -Wl,-q -O4 -lsmartheap

Peak Other Flags

C benchmarks:
-qipa=noobject -qipa=threads

Continued on next page

Peak Other Flags (Continued)

C++ benchmarks:
`-qipa=noobject -qipa=threads`

The flags file that was used to format this result can be browsed at
`http://www.spec.org/cpu2006/flags/lop-xl-flags.20090714.html`

You can also download the XML flags source by saving the following link:
`http://www.spec.org/cpu2006/flags/lop-xl-flags.20090714.xml`

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.
Report generated on Tue Jul 22 14:21:12 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 27 November 2007.