SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Acer Incorporated

Acer Altos R5250 (AMD Opteron 2222 SE)

SPECint®_rate2006 = 27.1

SPECint_rate_base2006 = 24.3

CPU2006 license: 97
Test sponsor: Acer Incorporated
Tested by: Acer Incorporated

Test date: Jun-2007
Hardware Availability: Dec-2007
Software Availability: Jun-2007



Hardware

CPU Name:	AMD Opteron 2222 SE
CPU Characteristics:	
CPU MHz:	3000
FPU:	Integrated
CPU(s) enabled:	2 cores, 1 chip, 2 cores/chip
CPU(s) orderable:	1,2 chips
Primary Cache:	64 KB I + 64 KB D on chip per core
Secondary Cache:	1 MB I+D on chip per core
L3 Cache:	None
Other Cache:	None
Memory:	16 GB (16x1GB, DDR2-667 CL5 ECC Reg)
Disk Subsystem:	1 x SATA, 160 GB
Other Hardware:	None

Software

Operating System:	SuSE Linux Enterprise Server 10 EM64T kernel
Compiler:	QLogic PathScale Compiler Suite, Release 3.0
Auto Parallel:	No
File System:	ReiserFS
System State:	Default
Base Pointers:	32/64-bit
Peak Pointers:	32/64-bit
Other Software:	SmartHeap 8.0 32 bit Library for Linux

SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Acer Incorporated

Acer Altos R5250 (AMD Opteron 2222 SE)

SPECint_rate2006 = 27.1

SPECint_rate_base2006 = 24.3

CPU2006 license: 97
Test sponsor: Acer Incorporated
Tested by: Acer Incorporated

Test date: Jun-2007
Hardware Availability: Dec-2007
Software Availability: Jun-2007

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	2	**737**	**26.5**	771	25.3	733	26.7	2	596	32.8	**597**	**32.7**	597	32.7
401.bzip2	2	1019	18.9	**1009**	**19.1**	992	19.4	2	991	19.5	**983**	**19.6**	982	19.7
403.gcc	2	942	17.1	920	17.5	**928**	**17.4**	2	729	22.1	737	21.8	**733**	**22.0**
429.mcf	2	**941**	**19.4**	945	19.3	940	19.4	2	749	24.4	741	24.6	**745**	**24.5**
445.gobmk	2	**696**	**30.1**	696	30.1	697	30.1	2	594	35.3	**595**	**35.3**	595	35.3
456.hmmer	2	634	29.4	**632**	**29.5**	632	29.5	2	476	39.2	**474**	**39.4**	474	39.4
458.sjeng	2	883	27.4	877	27.6	**881**	**27.5**	2	805	30.0	810	29.9	**806**	**30.0**
462.libquantum	2	1828	22.7	**1738**	**23.8**	1719	24.1	2	1707	24.3	1713	24.2	**1710**	**24.2**
464.h264ref	2	**987**	**44.8**	1013	43.7	980	45.2	2	**972**	**45.6**	978	45.3	969	45.7
471.omnetpp	2	711	17.6	700	17.9	**709**	**17.6**	2	702	17.8	702	17.8	**702**	**17.8**
473.astar	2	754	18.6	**750**	**18.7**	749	18.7	2	754	18.6	**750**	**18.7**	749	18.7
483.xalancbmk	2	468	29.5	**468**	**29.5**	467	29.5	2	457	30.2	458	30.1	**458**	**30.1**

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

General Notes

```
taskset utility used to bind cores to processes

This result was measured on the Acer Altos G5450
The Altos G5450 and Altos R5250 are electronically equivalent.
```

Base Compiler Invocation

C benchmarks:
pathcc

C++ benchmarks:
pathCC

Base Portability Flags

400.perlbench: -DSPEC_CPU_LP64 -DSPEC_CPU_LINUX_X64
401.bzip2: -DSPEC_CPU_LP64
403.gcc: -DSPEC_CPU_LP64
429.mcf: -DSPEC_CPU_LP64
445.gobmk: -DSPEC_CPU_LP64
456.hmmer: -DSPEC_CPU_LP64
458.sjeng: -DSPEC_CPU_LP64
462.libquantum: -DSPEC_CPU_LP64 -DSPEC_CPU_LINUX

Continued on next page

Base Portability Flags (Continued)

464.h264ref: -DSPEC_CPU_LP64
483.xalancbmk: -DSPEC_CPU_LINUX

Base Optimization Flags

C benchmarks:
-Ofast -OPT:malloc_alg=1

C++ benchmarks:
-Ofast -m32 -L/cpu2006/mpaton/1.0/amd514K8.lib/32 -lsmartheap

Peak Compiler Invocation

C benchmarks:
pathcc

C++ benchmarks:
pathCC

Peak Portability Flags

400.perlbench: -DSPEC_CPU_LP64 -DSPEC_CPU_LINUX_X64
401.bzip2: -DSPEC_CPU_LP64
445.gobmk: -DSPEC_CPU_LP64
456.hmmer: -DSPEC_CPU_LP64
458.sjeng: -DSPEC_CPU_LP64
462.libquantum: -DSPEC_CPU_LP64 -DSPEC_CPU_LINUX
464.h264ref: -DSPEC_CPU_LP64
483.xalancbmk: -DSPEC_CPU_LINUX

Peak Optimization Flags

C benchmarks:

400.perlbench: -fb_create fbdata(pass 1) -fb_opt fbdata(pass 2) -Ofast
-LNO:opt=0

401.bzip2: -O3 -LNO:ou_prod_max=10 -OPT:Ofast -OPT:alias=disjoint

403.gcc: -fb_create fbdata(pass 1) -fb_opt fbdata(pass 2) -m32 -O3
-OPT:Ofast

Continued on next page

Peak Optimization Flags (Continued)

429.mcf: `-m32 -O3 -ipa -L/cpu2006/mpaton/1.0/amd514K8.lib/32 -lsmartheap`

445.gobmk: `-fb_create fbdata`(pass 1) `-fb_opt fbdata`(pass 2) `-O3 -OPT:alias=disjoint -LNO:simd=0 -LNO:minvariant=off -WOPT:retype_expr=on`

456.hmmer: `-O2 -OPT:alias=disjoint -OPT:malloc_alg=1 -CG:cflow=0`

458.sjeng: `-fb_create fbdata`(pass 1) `-fb_opt fbdata`(pass 2) `-O3 -IPA:plimit=50000 -IPA:pu_reorder=2`

462.libquantum: `-O3 -ipa -CG:local_fwd_sched=on -IPA:space=1000`

464.h264ref: `-fb_create fbdata`(pass 1) `-fb_opt fbdata`(pass 2) `-O3 -IPA:plimit=20000 -OPT:alias=disjoint -LNO:prefetch=0`

C++ benchmarks:

471.omnetpp: `-Ofast -CG:gcm=off -m32 -L/cpu2006/mpaton/1.0/amd514K8.lib/32 -lsmartheap`

473.astar: `basepeak = yes`

483.xalancbmk: `-Ofast -m32 -OPT:unroll_times_max=8 -L/cpu2006/mpaton/1.0/amd514K8.lib/32 -lsmartheap`

The flags file that was used to format this result can be browsed at
`http://www.spec.org/cpu2006/flags/CPU2006_flags.20090714.html`

You can also download the XML flags source by saving the following link:
`http://www.spec.org/cpu2006/flags/CPU2006_flags.20090714.xml`

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.
Report generated on Tue Jul 22 13:44:30 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 11 December 2007.