



# SPEC<sup>®</sup> CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Acer Incorporated

### SPECfp<sup>®</sup>\_rate2006 = 108

## Acer Altos R920 (Intel Xeon E7340)

### SPECfp\_rate\_base2006 = 101

CPU2006 license: 97


Test sponsor: Acer Incorporated

Tested by: Acer Incorporated

Test date: Nov-2007

Hardware Availability: Nov-2007

Software Availability: Nov-2007



### Hardware

CPU Name: Intel Xeon E7340  
 CPU Characteristics: 1066MHz system bus  
 CPU MHz: 2400  
 FPU: Integrated  
 CPU(s) enabled: 16 cores, 4 chips, 4 cores/chip  
 CPU(s) orderable: 1, 2, 4 chips  
 Primary Cache: 32 KB I + 32 KB D on chip per core  
 Secondary Cache: 8 MB I+D on chip per chip, 4 MB shared / 2 cores

Continued on next page

### Software

Operating System: SuSE Linux Enterprise Server 10 SP1 EM64T (kernel 2.6.16.46-0.12-smp)  
 Compiler: Intel C++ and Fortran Compiler for Linux32 and Linux64 version 10.1 Build 20070725  
 Auto Parallel: Yes  
 File System: ReiserFS  
 System State: Multi-user, level 3  
 Base Pointers: 64-bit

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Acer Incorporated

SPECfp\_rate2006 = 108

Acer Altos R920 (Intel Xeon E7340)

SPECfp\_rate\_base2006 = 101

CPU2006 license: 97  
Test sponsor: Acer Incorporated  
Tested by: Acer Incorporated

Test date: Nov-2007  
Hardware Availability: Nov-2007  
Software Availability: Nov-2007

L3 Cache: None  
Other Cache: None  
Memory: 16 GB (16 x 1048MB ECC FB-DIMM DDR2-667 CL5-5-5)  
Disk Subsystem: 1 x 73GB 10000PRM SAS HDD  
Other Hardware: None

Peak Pointers: 32/64-bit  
Other Software: MicroQuill SmartHeap Library 8.1

## Results Table

Benchmark	Base								Peak							
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio		
410.bwaves	16	4048	53.7	<b>4035</b>	<b>53.9</b>	4034	53.9	16	3956	55.0	<b>3956</b>	<b>55.0</b>	3952	55.0		
416.gamess	16	<b>1162</b>	<b>270</b>	1161	270	1167	269	16	1143	274	1149	273	<b>1145</b>	<b>274</b>		
433.milc	16	3116	47.1	<b>3115</b>	<b>47.1</b>	3114	47.2	16	3113	47.2	3114	47.2	<b>3114</b>	<b>47.2</b>		
434.zeusmp	16	1333	109	<b>1333</b>	<b>109</b>	1332	109	16	<b>1335</b>	<b>109</b>	1337	109	1332	109		
435.gromacs	16	<b>508</b>	<b>225</b>	511	224	506	226	16	499	229	500	228	<b>499</b>	<b>229</b>		
436.cactusADM	16	1595	120	1593	120	<b>1594</b>	<b>120</b>	1	<b>78.9</b>	<b>151</b>	79.5	150	78.9	151		
437.leslie3d	16	3781	39.8	<b>3774</b>	<b>39.8</b>	3773	39.9	16	3637	41.3	3640	41.3	<b>3638</b>	<b>41.3</b>		
444.namd	16	<b>641</b>	<b>200</b>	640	201	647	198	16	637	202	<b>636</b>	<b>202</b>	636	202		
447.dealII	16	<b>889</b>	<b>206</b>	872	210	898	204	16	<b>857</b>	<b>214</b>	851	215	866	211		
450.soplex	16	2536	52.6	2540	52.5	<b>2537</b>	<b>52.6</b>	16	<b>2319</b>	<b>57.5</b>	2318	57.6	2320	57.5		
453.povray	16	285	299	281	303	<b>281</b>	<b>303</b>	16	<b>237</b>	<b>360</b>	236	360	237	359		
454.calculix	16	<b>748</b>	<b>176</b>	742	178	751	176	16	546	242	550	240	<b>549</b>	<b>240</b>		
459.GemsFDTD	16	4237	40.1	4248	40.0	<b>4241</b>	<b>40.0</b>	16	4229	40.1	4234	40.1	<b>4232</b>	<b>40.1</b>		
465.tonto	16	1136	139	1145	138	<b>1136</b>	<b>139</b>	16	1115	141	1127	140	<b>1125</b>	<b>140</b>		
470.lbm	16	6575	33.4	6576	33.4	<b>6575</b>	<b>33.4</b>	16	5767	38.1	5768	38.1	<b>5768</b>	<b>38.1</b>		
481.wrf	16	<b>2269</b>	<b>78.8</b>	2269	78.8	2267	78.8	16	2269	78.7	<b>2268</b>	<b>78.8</b>	2268	78.8		
482.sphinx3	16	3578	87.1	<b>3584</b>	<b>87.0</b>	3584	87.0	16	3321	93.9	3329	93.7	<b>3324</b>	<b>93.8</b>		

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## General Notes

### BIOS Settings

Hardware Prefetcher set to OFF

Adjacent Cache Line Prefetch set to OFF

Optimization for high-frequency FSB applications set to OFF

All results used taskset to bind processes to cores.



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Acer Incorporated

SPECfp\_rate2006 = 108

Acer Altos R920 (Intel Xeon E7340)

SPECfp\_rate\_base2006 = 101

CPU2006 license: 97

Test sponsor: Acer Incorporated

Tested by: Acer Incorporated

Test date: Nov-2007

Hardware Availability: Nov-2007

Software Availability: Nov-2007

## Base Compiler Invocation

C benchmarks:

icc

C++ benchmarks:

icpc

Fortran benchmarks:

ifort

Benchmarks using both Fortran and C:

icc ifort

## Base Portability Flags

410.bwaves: -DSPEC\_CPU\_LP64  
416.gamess: -DSPEC\_CPU\_LP64  
433.milc: -DSPEC\_CPU\_LP64  
434.zeusmp: -DSPEC\_CPU\_LP64  
435.gromacs: -DSPEC\_CPU\_LP64 -nofor\_main  
436.cactusADM: -DSPEC\_CPU\_LP64 -nofor\_main  
437.leslie3d: -DSPEC\_CPU\_LP64  
444.namd: -DSPEC\_CPU\_LP64  
447.dealII: -DSPEC\_CPU\_LP64  
450.soplex: -DSPEC\_CPU\_LP64  
453.povray: -DSPEC\_CPU\_LP64  
454.calculix: -DSPEC\_CPU\_LP64 -nofor\_main  
459.GemsFDTD: -DSPEC\_CPU\_LP64  
465.tonto: -DSPEC\_CPU\_LP64  
470.lbm: -DSPEC\_CPU\_LP64  
481.wrf: -DSPEC\_CPU\_LP64 -DSPEC\_CPU\_CASE\_FLAG -DSPEC\_CPU\_LINUX  
482.sphinx3: -DSPEC\_CPU\_LP64

## Base Optimization Flags

C benchmarks:

-fast

C++ benchmarks:

-fast

Fortran benchmarks:

-fast

Benchmarks using both Fortran and C:

-fast



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**Acer Incorporated**

**SPECfp\_rate2006 = 108**

**Acer Altos R920 (Intel Xeon E7340)**

**SPECfp\_rate\_base2006 = 101**

**CPU2006 license:** 97

**Test sponsor:** Acer Incorporated

**Tested by:** Acer Incorporated

**Test date:** Nov-2007

**Hardware Availability:** Nov-2007

**Software Availability:** Nov-2007

## Peak Compiler Invocation

C benchmarks (except as noted below):

```
/home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux32/bin/icc
-L/home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux32/lib
-I/home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux32/include
```

433.milc: icc

C++ benchmarks (except as noted below):

icpc

```
450.soplex: /home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux32/bin/icpc
-L/home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux32/lib
-I/home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux32/include
```

Fortran benchmarks (except as noted below):

ifort

```
437.leslie3d: /home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux32/bin/ifort
-L/home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux32/lib
-I/home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux32/include
```

Benchmarks using both Fortran and C:

icc ifort

## Peak Portability Flags

```
410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
444.namd: -DSPEC_CPU_LP64
447.deallI: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
```

## Peak Optimization Flags

C benchmarks:

```
433.milc: -prof-gen(pass 1) -prof-use(pass 2) -fast -fno-alias
-auto-ilp32
```

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Acer Incorporated

SPECfp\_rate2006 = 108

Acer Altos R920 (Intel Xeon E7340)

SPECfp\_rate\_base2006 = 101

CPU2006 license: 97

Test sponsor: Acer Incorporated

Tested by: Acer Incorporated

Test date: Nov-2007

Hardware Availability: Nov-2007

Software Availability: Nov-2007

## Peak Optimization Flags (Continued)

470.lbm: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2  
-scalar-rep- -prefetch -opt-malloc-options=3

482.sphinx3: -fast -unroll2

### C++ benchmarks:

444.namd: -prof-gen(pass 1) -prof-use(pass 2) -fast -fno-alias  
-auto-ilp32

447.dealII: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2  
-ansi-alias -scalar-rep-

450.soplex: -prof-gen(pass 1) -prof-use(pass 2) -fast  
-opt-malloc-options=3

453.povray: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll4  
-ansi-alias

### Fortran benchmarks:

410.bwaves: -fast -prefetch

416.gamess: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2 -Ob0  
-ansi-alias -scalar-rep-

434.zeusmp: -prof-gen(pass 1) -prof-use(pass 2) -fast

437.leslie3d: -prof-gen(pass 1) -prof-use(pass 2) -fast -prefetch  
-opt-malloc-options=3

459.GemsFDTD: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2 -Ob0  
-prefetch

465.tonto: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll4 -auto

### Benchmarks using both Fortran and C:

435.gromacs: -prof-gen(pass 1) -prof-use(pass 2) -fast -prefetch  
-auto-ilp32

436.cactusADM: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2  
-prefetch -parallel -auto-ilp32

454.calculix: -fast -unroll-aggressive -auto-ilp32

481.wrf: -fast -auto-ilp32



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Acer Incorporated

SPECfp\_rate2006 = 108

Acer Altos R920 (Intel Xeon E7340)

SPECfp\_rate\_base2006 = 101

CPU2006 license: 97

Test sponsor: Acer Incorporated

Tested by: Acer Incorporated

Test date: Nov-2007

Hardware Availability: Nov-2007

Software Availability: Nov-2007

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic10.1-FP-intel64-linux-flags.20090714.17.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/Intel-ic10.1-FP-intel64-linux-flags.20090714.17.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.0.  
Report generated on Tue Jul 22 13:51:54 2014 by SPEC CPU2006 PS/PDF formatter v6932.  
Originally published on 11 December 2007.