



SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Acer Incorporated

SPECint_rate2006 = 32.9

Acer Altos R520 (Intel Xeon 5150)

SPECint_rate_base2006 = 28.9

CPU2006 license: 97


Test date: Nov-2007

Test sponsor: Acer Incorporated

Hardware Availability: Nov-2006

Tested by: Acer Incorporated

Software Availability: Nov-2007



Hardware

CPU Name: Intel Xeon 5150
 CPU Characteristics: 1333MHz system bus
 CPU MHz: 2660
 FPU: Integrated
 CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip
 CPU(s) orderable: 1, 2 chips
 Primary Cache: 32 KB I + 32 KB D on chip per core
 Secondary Cache: 4 MB I+D on chip per chip
 L3 Cache: None
 Other Cache: None
 Memory: 16 GB (8 x 2048MB ECC FB-DIMM DDR2-667 CL5-5-5)
 Disk Subsystem: 1 x 73GB 10000PRM SAS HDD
 Other Hardware: None

Software

Operating System: SuSE Linux Enterprise Server 10 SP1 EM64T (kernel 2.6.16.46-0.12-smp)
 Compiler: Intel C++ Compiler for Linux32 and Linux64 version 10.1 Build 20070725
 Auto Parallel: Yes
 File System: ReiserFS
 System State: Multi-user, level 3
 Base Pointers: 32-bit
 Peak Pointers: 32/64-bit
 Other Software: MicroQuill SmartHeap Library 8.1



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Acer Incorporated

SPECint_rate2006 = 32.9

Acer Altos R520 (Intel Xeon 5150)

SPECint_rate_base2006 = 28.9

CPU2006 license: 97

Test date: Nov-2007

Test sponsor: Acer Incorporated

Hardware Availability: Nov-2006

Tested by: Acer Incorporated

Software Availability: Nov-2007

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	2	567	34.5	565	34.6	569	34.3	2	485	40.3	486	40.2	486	40.2
401.bzip2	2	940	20.5	938	20.6	943	20.5	2	893	21.6	894	21.6	889	21.7
403.gcc	2	584	27.6	591	27.3	587	27.4	2	590	27.3	588	27.4	587	27.4
429.mcf	2	689	26.5	692	26.4	691	26.4	2	656	27.8	656	27.8	654	27.9
445.gobmk	2	621	33.8	615	34.1	618	34.0	2	569	36.9	572	36.7	571	36.7
456.hmmer	2	667	28.0	667	28.0	668	27.9	2	393	47.4	393	47.5	393	47.5
458.sjeng	2	765	31.7	774	31.3	770	31.4	2	708	34.2	709	34.1	706	34.3
462.libquantum	2	1526	27.2	1526	27.2	1530	27.1	1	522	39.7	522	39.7	522	39.7
464.h264ref	2	835	53.0	835	53.0	835	53.0	2	789	56.1	789	56.1	791	56.0
471.omnetpp	2	628	19.9	624	20.0	625	20.0	2	584	21.4	583	21.4	585	21.4
473.astar	2	656	21.4	657	21.4	655	21.4	2	608	23.1	608	23.1	607	23.1
483.xalancbmk	2	376	36.7	377	36.6	377	36.6	2	376	36.7	377	36.6	377	36.6

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

General Notes

This result was measured on the Acer Altos R520.
The Altos R720 and Altos R520 are electronically equivalent.

BIOS Settings

Hardware Prefetcher set to ON

Adjacent Cache Line Prefetch set to OFF

Optimization for high-frequency FSB applications set to ON

All results used taskset to bind processes to cores.

Base Compiler Invocation

C benchmarks:

icc

C++ benchmarks:

icpc



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Acer Incorporated

SPECint_rate2006 = 32.9

Acer Altos R520 (Intel Xeon 5150)

SPECint_rate_base2006 = 28.9

CPU2006 license: 97

Test date: Nov-2007

Test sponsor: Acer Incorporated

Hardware Availability: Nov-2006

Tested by: Acer Incorporated

Software Availability: Nov-2007

Base Portability Flags

400.perlbench: -DSPEC_CPU_LINUX_IA32

462.libquantum: -DSPEC_CPU_LINUX

483.xalancbmk: -DSPEC_CPU_LINUX

Base Optimization Flags

C benchmarks:

-fast -inline-calloc -opt-malloc-options=3

C++ benchmarks:

-xT -ipo -O3 -no-prec-div -Wl,-z,muldefs
-L/home/cmpllr/usr3/alrahate/cpu2006.1.0/lib -lsmartheap

Base Other Flags

C benchmarks:

403.gcc: -Dalloca=_alloca

Peak Compiler Invocation

C benchmarks (except as noted below):

icc

401.bzip2: /home/cmpllr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux64/bin/icc
-L/home/cmpllr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux64/lib
-I/home/cmpllr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux64/include

456.hmmr: /home/cmpllr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux64/bin/icc
-L/home/cmpllr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux64/lib
-I/home/cmpllr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux64/include

C++ benchmarks:

icpc

Peak Portability Flags

400.perlbench: -DSPEC_CPU_LINUX_IA32

401.bzip2: -DSPEC_CPU_LP64

456.hmmr: -DSPEC_CPU_LP64

462.libquantum: -DSPEC_CPU_LINUX

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Acer Incorporated

SPECint_rate2006 = 32.9

Acer Altos R520 (Intel Xeon 5150)

SPECint_rate_base2006 = 28.9

CPU2006 license: 97

Test date: Nov-2007

Test sponsor: Acer Incorporated

Hardware Availability: Nov-2006

Tested by: Acer Incorporated

Software Availability: Nov-2007

Peak Portability Flags (Continued)

483.xalancbmk: -DSPEC_CPU_LINUX

Peak Optimization Flags

C benchmarks:

```
400.perlbench: -prof-gen(pass 1) -prof-use(pass 2) -fast -ansi-alias  
                  -prefetch  
  
401.bzip2: -prof-gen(pass 1) -prof-use(pass 2) -fast -prefetch  
  
403.gcc: -fast -inline-calloc -opt-malloc-options=3  
  
429.mcf: -fast -prefetch  
  
445.gobmk: -prof-gen(pass 1) -prof-use(pass 2) -xT -O2 -ipo  
                  -no-prec-div -ansi-alias  
  
456.hmmer: -fast -unroll12 -ansi-alias -opt-multi-version-aggressive  
  
458.sjeng: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll4  
  
462.libquantum: -fast -unroll14 -O0 -prefetch  
                  -opt-streaming-stores always -vec-guard-write  
                  -opt-malloc-options=3 -parallel -par-runtime-control  
  
464.h264ref: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll12  
                  -ansi-alias
```

C++ benchmarks:

```
471.omnetpp: -prof-gen(pass 1) -prof-use(pass 2) -xT -O3 -ipo  
                  -no-prec-div -ansi-alias -opt-ra-region-strategy=block  
                  -Wl,-z,muldefs  
                  -L/home/cmplr/usr3/alrahate/cpu2006.1.0/lib -lsmartheap  
  
473.astar: -prof-gen(pass 1) -prof-use(pass 2) -xT -O3 -ipo  
                  -no-prec-div -ansi-alias -opt-ra-region-strategy=routine  
                  -Wl,-z,muldefs  
                  -L/home/cmplr/usr3/alrahate/cpu2006.1.0/lib -lsmartheap
```

483.xalancbmk: basepeak = yes



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Acer Incorporated

SPECint_rate2006 = 32.9

Acer Altos R520 (Intel Xeon 5150)

SPECint_rate_base2006 = 28.9

CPU2006 license: 97

Test date: Nov-2007

Test sponsor: Acer Incorporated

Hardware Availability: Nov-2006

Tested by: Acer Incorporated

Software Availability: Nov-2007

Peak Other Flags

C benchmarks:

403.gcc: -Dalloca=_alloca

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic10-ia32-intel64-linux-flags.20090714.22.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/Intel-ic10-ia32-intel64-linux-flags.20090714.22.xml>

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.

Report generated on Tue Jul 22 13:48:14 2014 by SPEC CPU2006 PS/PDF formatter v6932.

Originally published on 11 December 2007.