



SPEC[®] CINT2006 Result

Copyright 2006-2009 Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

SPECint[®]_rate2006 = 58.2

CELSIUS M460, Intel Core 2 Quad Q6700 processor

SPECint_rate_base2006 = 53.9

CPU2006 license: 22


Test sponsor: Fujitsu Siemens Computers

Tested by: Fujitsu Siemens Computers

Test date: Dec-2007

Hardware Availability: Nov-2007

Software Availability: Nov-2007



Hardware

CPU Name: Intel Core 2 Quad Q6700
 CPU Characteristics:
 CPU MHz: 2667
 FPU: Integrated
 CPU(s) enabled: 4 cores, 1 chip, 4 cores/chip
 CPU(s) orderable: 1 chip
 Primary Cache: 32 KB I + 32 KB D on chip per core
 Secondary Cache: 8 MB I+D on chip per chip, 4 MB shared / 2 cores
 L3 Cache: None
 Other Cache: None
 Memory: 4 GB (4x1 GB PC2-6400 CL6 SDRAM)
 Disk Subsystem: 1 x 400 GB SATA II 7200 RPM
 Other Hardware: None

Software

Operating System: Microsoft Windows Vista Ultimate (x64)
 Compiler: Intel C++ Compilers for IA-32 and for Intel64, Version 10.1, Build 20070913
 Microsoft Visual Studio 2005 with SP1 (for libraries)
 Auto Parallel: No
 File System: NTFS
 System State: Default
 Base Pointers: 32-bit
 Peak Pointers: 32/64-bit
 Other Software: MicroQuill SmartHeap Library, Version 8.1



SPEC CINT2006 Result

Copyright 2006-2009 Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

SPECint_rate2006 = 58.2

CELSIUS M460, Intel Core 2 Quad Q6700 processor

SPECint_rate_base2006 = 53.9

CPU2006 license: 22

Test date: Dec-2007

Test sponsor: Fujitsu Siemens Computers

Hardware Availability: Nov-2007

Tested by: Fujitsu Siemens Computers

Software Availability: Nov-2007

Results Table

Benchmark	Base						Peak							
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	4	620	63.0	618	63.2	621	62.9	4	478	81.7	478	81.7	480	81.5
401.bzip2	4	852	45.3	846	45.6	851	45.4	4	820	47.1	821	47.0	807	47.9
403.gcc	4	667	48.3	655	49.2	666	48.3	4	666	48.3	676	47.6	691	46.6
429.mcf	4	740	49.3	740	49.3	739	49.4	4	740	49.3	740	49.3	739	49.4
445.gobmk	4	609	68.9	609	68.9	609	68.9	4	556	75.4	558	75.2	556	75.5
456.hmmmer	4	673	55.4	673	55.5	673	55.4	4	506	73.8	511	73.0	512	72.9
458.sjeng	4	796	60.8	797	60.8	797	60.8	4	713	67.9	717	67.5	717	67.5
462.libquantum	4	1733	47.8	1732	47.9	1732	47.9	4	1733	47.8	1732	47.9	1732	47.9
464.h264ref	4	820	108	821	108	819	108	4	776	114	787	112	779	114
471.omnetpp	4	796	31.4	796	31.4	796	31.4	4	762	32.8	766	32.7	765	32.7
473.astar	4	726	38.7	726	38.7	726	38.7	4	679	41.4	681	41.3	680	41.3
483.xalancbmk	4	455	60.6	455	60.7	455	60.7	4	444	62.1	446	61.8	446	61.8

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Platform Notes

BIOS default settings have been used.

General Notes

All binaries were built with 32-bit Intel compiler except:
401.bzip2 and 456.hmmmer in peak were built with 64-bit Intel compiler by changing the path for include and library files.

For information about Fujitsu Siemens Computers please see:
<http://www.fujitsu-siemens.com>

Base Compiler Invocation

C benchmarks:
icl -Qvc8 -Qc99

C++ benchmarks:
icl -Qvc8



SPEC CINT2006 Result

Copyright 2006-2009 Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

SPECint_rate2006 = 58.2

CELSIUS M460, Intel Core 2 Quad Q6700 processor

SPECint_rate_base2006 = 53.9

CPU2006 license: 22

Test date: Dec-2007

Test sponsor: Fujitsu Siemens Computers

Hardware Availability: Nov-2007

Tested by: Fujitsu Siemens Computers

Software Availability: Nov-2007

Base Portability Flags

403.gcc: -DSPEC_CPU_WIN32
464.h264ref: -DSPEC_CPU_NO_INTTYPES -DWIN32
483.xalancbmk: -Qoption, cpp, --no_wchar_t_keyword

Base Optimization Flags

C benchmarks:
-fast -Qvec-guard-write -F512000000
C++ benchmarks:
-fast -Qcxx_features -F512000000 shlW32M.lib -link -FORCE:MULTIPLE

Base Other Flags

C benchmarks:
403.gcc: -Dalloca=_alloca

Peak Compiler Invocation

C benchmarks (except as noted below):
icl -Qvc8 -Qc99
401.bzip2: C:\\DevelTools\\Intel\\Compiler\\C++\\10.1.011\\EM64T\\Bin\\icl.exe
-IC:\\DevelTools\\Intel\\Compiler\\C++\\10.1.011\\EM64T\\Include
-link -LIBPATH:C:\\DevelTools\\Intel\\Compiler\\C++\\10.1.011\\EM64T\\Lib
-link -LIBPATH:"C:\\Program Files\\Microsoft Visual Studio 8\\vc\\lib"
-link -LIBPATH:"C:\\Program Files\\Microsoft Visual Studio 8\\vc\\lib\\amd64"
456.hmmer: C:\\DevelTools\\Intel\\Compiler\\C++\\10.1.011\\EM64T\\Bin\\icl.exe
-IC:\\DevelTools\\Intel\\Compiler\\C++\\10.1.011\\EM64T\\Include
-link -LIBPATH:C:\\DevelTools\\Intel\\Compiler\\C++\\10.1.011\\EM64T\\Lib
-link -LIBPATH:"C:\\Program Files\\Microsoft Visual Studio 8\\vc\\lib"
-link -LIBPATH:"C:\\Program Files\\Microsoft Visual Studio 8\\vc\\lib\\amd64"
C++ benchmarks:
icl -Qvc8

Peak Portability Flags

401.bzip2: -DSPEC_CPU_P64

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2009 Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

SPECint_rate2006 = 58.2

CELSIUS M460, Intel Core 2 Quad Q6700 processor

SPECint_rate_base2006 = 53.9

CPU2006 license: 22

Test date: Dec-2007

Test sponsor: Fujitsu Siemens Computers

Hardware Availability: Nov-2007

Tested by: Fujitsu Siemens Computers

Software Availability: Nov-2007

Peak Portability Flags (Continued)

403.gcc: -DSPEC_CPU_WIN32
 456.hmmr: -DSPEC_CPU_P64
 464.h264ref: -DSPEC_CPU_NO_INTTYPES -DWIN32
 483.xalancbmk: -Qoption,cpp,--no_wchar_t_keyword

Peak Optimization Flags

C benchmarks:

400.perlbench: -Qprof_gen(pass 1) -Qprof_use(pass 2) -fast -Qansi-alias
 -Qprefetch -F512000000 shlW32M.lib -link -FORCE:MULTIPLE

401.bzip2: -Qprof_gen(pass 1) -Qprof_use(pass 2) -fast -Qprefetch
 -F512000000

403.gcc: -Qprof_gen(pass 1) -Qprof_use(pass 2) -fast -F512000000

429.mcf: basepeak = yes

445.gobmk: -Qprof_gen(pass 1) -Qprof_use(pass 2) -QxT -O2 -Qipo
 -Qprec-div- -Qansi-alias -F512000000

456.hmmr: -Qprof_gen(pass 1) -Qprof_use(pass 2) -fast -Qunroll2
 -Qansi-alias -Qopt-multi-version-aggressive -F512000000

458.sjeng: -Qprof_gen(pass 1) -Qprof_use(pass 2) -fast -Qunroll4
 -F512000000

462.libquantum: basepeak = yes

464.h264ref: -Qprof_gen(pass 1) -Qprof_use(pass 2) -fast -Qunroll2
 -Qansi-alias -F512000000

C++ benchmarks:

471.omnetpp: -Qprof_gen(pass 1) -Qprof_use(pass 2) -fast -Qansi-alias
 -Qopt-ra-region-strategy=block -Qcxx_features -F512000000
 shlW32M.lib -link -FORCE:MULTIPLE

473.astar: -Qprof_gen(pass 1) -Qprof_use(pass 2) -fast -Qansi-alias
 -Qopt-ra-region-strategy=routine -Qcxx_features -F512000000
 shlW32M.lib -link -FORCE:MULTIPLE

483.xalancbmk: -Qprof_gen(pass 1) -Qprof_use(pass 2) -fast -Qansi-alias
 -Qcxx_features -F512000000 shlW32M.lib
 -link -FORCE:MULTIPLE



SPEC CINT2006 Result

Copyright 2006-2009 Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

SPECint_rate2006 = 58.2

CELSIUS M460, Intel Core 2 Quad Q6700 processor

SPECint_rate_base2006 = 53.9

CPU2006 license: 22

Test date: Dec-2007

Test sponsor: Fujitsu Siemens Computers

Hardware Availability: Nov-2007

Tested by: Fujitsu Siemens Computers

Software Availability: Nov-2007

Peak Other Flags

Same as Base Other Flags

The flags file that was used to format this result can be browsed at

http://www.spec.org/cpu2006/flags/CPU2006_flags.20090713.02.html

You can also download the XML flags source by saving the following link:

http://www.spec.org/cpu2006/flags/CPU2006_flags.20090713.02.xml

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.
Report generated on Tue Jul 14 10:49:39 2009 by SPEC CPU2006 PS/PDF formatter v6323.