



SPEC® CINT2006 Result

Copyright 2006-2009 Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

SPECint®_rate2006 = 68.7

CELSIUS M460, Intel Core 2 Extreme QX9650

SPECint_rate_base2006 = 63.5

CPU2006 license: 22


Test sponsor: Fujitsu Siemens Computers

Tested by: Fujitsu Siemens Computers

Test date: Feb-2008

Hardware Availability: Mar-2008

Software Availability: Nov-2007



Hardware

CPU Name: Intel Core 2 Extreme QX9650
 CPU Characteristics:
 CPU MHz: 3000
 FPU: Integrated
 CPU(s) enabled: 4 cores, 1 chip, 4 cores/chip
 CPU(s) orderable: 1 chip
 Primary Cache: 32 KB I + 32 KB D on chip per core
 Secondary Cache: 12 MB I+D on chip per chip, 6 MB shared / 2 cores
 L3 Cache: None
 Other Cache: None
 Memory: 4 GB (4x1 GB PC2-6400 CL6 SDRAM)
 Disk Subsystem: 1 x 400 GB SATA 7200 RPM
 Other Hardware: None

Software

Operating System: Windows Vista64 Ultimate
 Compiler: Intel C++ Compiler for applications running on IA-32, Version 10.1, Build 20070913
 Intel C++ Compiler for applications running on Intel 64, Version 10.1, Build 20070913
 Microsoft Visual Studio 2005 with SP1 (for libraries)
 Auto Parallel: No
 File System: NTFS
 System State: Default
 Base Pointers: 32-bit
 Peak Pointers: 32/64-bit
 Other Software: SmartHeap Library Version 8.1 from <http://www.microquill.com/>



SPEC CINT2006 Result

Copyright 2006-2009 Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

SPECint_rate2006 = 68.7

CELSIUS M460, Intel Core 2 Extreme QX9650

SPECint_rate_base2006 = 63.5

CPU2006 license: 22

Test date: Feb-2008

Test sponsor: Fujitsu Siemens Computers

Hardware Availability: Mar-2008

Tested by: Fujitsu Siemens Computers

Software Availability: Nov-2007

Results Table

Benchmark	Base						Peak							
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	4	556	70.3	<u>556</u>	<u>70.3</u>	555	70.4	4	428	91.4	<u>430</u>	<u>90.9</u>	432	90.6
401.bzip2	4	667	57.9	653	59.1	<u>653</u>	<u>59.1</u>	4	625	61.8	617	62.5	<u>620</u>	<u>62.2</u>
403.gcc	4	560	57.5	580	55.5	<u>565</u>	<u>57.0</u>	4	573	56.2	<u>571</u>	<u>56.4</u>	567	56.8
429.mcf	4	570	64.0	<u>570</u>	<u>64.0</u>	569	64.1	4	570	64.0	<u>570</u>	<u>64.0</u>	569	64.1
445.gobmk	4	531	79.1	<u>530</u>	<u>79.1</u>	530	79.2	4	493	85.1	<u>492</u>	<u>85.3</u>	491	85.5
456.hmmmer	4	595	62.8	<u>594</u>	<u>62.8</u>	594	62.8	4	452	82.5	446	83.6	<u>446</u>	<u>83.6</u>
458.sjeng	4	687	70.4	688	70.4	<u>687</u>	<u>70.4</u>	4	625	77.4	612	79.0	<u>613</u>	<u>78.9</u>
462.libquantum	4	1609	51.5	<u>1605</u>	<u>51.6</u>	1603	51.7	4	1609	51.5	<u>1605</u>	<u>51.6</u>	1603	51.7
464.h264ref	4	710	125	710	125	<u>710</u>	<u>125</u>	4	<u>675</u>	<u>131</u>	676	131	675	131
471.omnetpp	4	<u>653</u>	<u>38.3</u>	653	38.3	653	38.3	4	<u>628</u>	<u>39.8</u>	628	39.8	629	39.8
473.astar	4	610	46.1	<u>609</u>	<u>46.1</u>	608	46.2	4	567	49.5	<u>568</u>	<u>49.4</u>	569	49.3
483.xalancbmk	4	386	71.4	386	71.6	<u>386</u>	<u>71.5</u>	4	379	72.8	379	72.7	<u>379</u>	<u>72.8</u>

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Platform Notes

BIOS default settings have been used.

General Notes

All binaries were built with 32-bit Intel compiler except:
401.bzip2 and 456.hmmmer in peak were built with 64-bit Intel compiler by changing the path for include and library files.

For information about Fujitsu Siemens Computers please see:
<http://www.fujitsu-siemens.com/>

Base Compiler Invocation

C benchmarks:
icl -Qvc8 -Qc99

C++ benchmarks:
icl -Qvc8



SPEC CINT2006 Result

Copyright 2006-2009 Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

SPECint_rate2006 = 68.7

CELSIUS M460, Intel Core 2 Extreme QX9650

SPECint_rate_base2006 = 63.5

CPU2006 license: 22

Test sponsor: Fujitsu Siemens Computers

Tested by: Fujitsu Siemens Computers

Test date: Feb-2008

Hardware Availability: Mar-2008

Software Availability: Nov-2007

Base Portability Flags

403.gcc: -DSPEC_CPU_WIN32
464.h264ref: -DSPEC_CPU_NO_INTTYPES -DWIN32
483.xalancbmk: -Qoption, cpp, --no_wchar_t_keyword

Base Optimization Flags

C benchmarks:

-fast -Qvec-guard-write -F512000000

C++ benchmarks:

-fast -Qcxx_features -F512000000 shlW32M.lib -link -FORCE:MULTIPLE

Base Other Flags

C benchmarks:

403.gcc: -Dalloca=_alloca

Peak Compiler Invocation

C benchmarks (except as noted below):

icl -Qvc8 -Qc99

401.bzip2: C:\\DevelTools\\Intel\\Compiler\\C++\\10.1.011\\EM64T\\Bin\\icl.exe
-IC:\\DevelTools\\Intel\\Compiler\\C++\\10.1.011\\EM64T\\Include
-link -LIBPATH:C:\\DevelTools\\Intel\\Compiler\\C++\\10.1.011\\EM64T\\Lib
-link -LIBPATH:"C:\\Program Files\\Microsoft Visual Studio 8\\vc\\lib"
-link -LIBPATH:"C:\\Program Files\\Microsoft Visual Studio 8\\vc\\lib\\amd64"

456.hmmer: C:\\DevelTools\\Intel\\Compiler\\C++\\10.1.011\\EM64T\\Bin\\icl.exe
-IC:\\DevelTools\\Intel\\Compiler\\C++\\10.1.011\\EM64T\\Include
-link -LIBPATH:C:\\DevelTools\\Intel\\Compiler\\C++\\10.1.011\\EM64T\\Lib
-link -LIBPATH:"C:\\Program Files\\Microsoft Visual Studio 8\\vc\\lib"
-link -LIBPATH:"C:\\Program Files\\Microsoft Visual Studio 8\\vc\\lib\\amd64"

C++ benchmarks:

icl -Qvc8

Peak Portability Flags

401.bzip2: -DSPEC_CPU_P64

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2009 Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

SPECint_rate2006 = 68.7

CELSIUS M460, Intel Core 2 Extreme QX9650

SPECint_rate_base2006 = 63.5

CPU2006 license: 22

Test sponsor: Fujitsu Siemens Computers

Tested by: Fujitsu Siemens Computers

Test date: Feb-2008

Hardware Availability: Mar-2008

Software Availability: Nov-2007

Peak Portability Flags (Continued)

403.gcc: -DSPEC_CPU_WIN32
 456.hmmr: -DSPEC_CPU_P64
 464.h264ref: -DSPEC_CPU_NO_INTTYPES -DWIN32
 483.xalancbmk: -Qoption,cpp,--no_wchar_t_keyword

Peak Optimization Flags

C benchmarks:

400.perlbench: -Qprof_gen(pass 1) -Qprof_use(pass 2) -fast -Qansi-alias
 -Qprefetch -F512000000 shlW32M.lib -link -FORCE:MULTIPLE

401.bzip2: -Qprof_gen(pass 1) -Qprof_use(pass 2) -fast -Qprefetch
 -F512000000

403.gcc: -Qprof_gen(pass 1) -Qprof_use(pass 2) -fast -F512000000

429.mcf: basepeak = yes

445.gobmk: -Qprof_gen(pass 1) -Qprof_use(pass 2) -QxT -O2 -Qipo
 -Qprec-div- -Qansi-alias -F512000000

456.hmmr: -Qprof_gen(pass 1) -Qprof_use(pass 2) -fast -Qunroll2
 -Qansi-alias -Qopt-multi-version-aggressive -F512000000

458.sjeng: -Qprof_gen(pass 1) -Qprof_use(pass 2) -fast -Qunroll4
 -F512000000

462.libquantum: basepeak = yes

464.h264ref: -Qprof_gen(pass 1) -Qprof_use(pass 2) -fast -Qunroll2
 -Qansi-alias -F512000000

C++ benchmarks:

471.omnetpp: -Qprof_gen(pass 1) -Qprof_use(pass 2) -fast -Qansi-alias
 -Qopt-ra-region-strategy=block -Qcxx_features -F512000000
 shlW32M.lib -link -FORCE:MULTIPLE

473.astar: -Qprof_gen(pass 1) -Qprof_use(pass 2) -fast -Qansi-alias
 -Qopt-ra-region-strategy=routine -Qcxx_features -F512000000
 shlW32M.lib -link -FORCE:MULTIPLE

483.xalancbmk: -Qprof_gen(pass 1) -Qprof_use(pass 2) -fast -Qansi-alias
 -Qcxx_features -F512000000 shlW32M.lib
 -link -FORCE:MULTIPLE



SPEC CINT2006 Result

Copyright 2006-2009 Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

SPECint_rate2006 = 68.7

CELSIUS M460, Intel Core 2 Extreme QX9650

SPECint_rate_base2006 = 63.5

CPU2006 license: 22

Test sponsor: Fujitsu Siemens Computers

Tested by: Fujitsu Siemens Computers

Test date: Feb-2008

Hardware Availability: Mar-2008

Software Availability: Nov-2007

Peak Other Flags

Same as Base Other Flags

The flags file that was used to format this result can be browsed at

http://www.spec.org/cpu2006/flags/CPU2006_flags.20090713.02.html

You can also download the XML flags source by saving the following link:

http://www.spec.org/cpu2006/flags/CPU2006_flags.20090713.02.xml

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.
Report generated on Mon Jul 13 17:59:11 2009 by SPEC CPU2006 PS/PDF formatter v6323.