



SPEC® CINT2006 Result

Copyright 2006-2009 Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

SPECint®2006 = 13.6

CELSIUS V840, AMD Opteron 2350 (2.0 GHz)

SPECint_base2006 = 12.0

CPU2006 license: 22


Test date: Apr-2008

Test sponsor: Fujitsu Siemens Computers

Hardware Availability: May-2008

Tested by: Fujitsu Siemens Computers

Software Availability: May-2008



Hardware

CPU Name: AMD Opteron 2350
 CPU Characteristics: 2000
 CPU MHz: Integrated
 FPU: Integrated
 CPU(s) enabled: 8 cores, 2 chips, 4 cores/chip
 CPU(s) orderable: 1,2 chips
 Primary Cache: 64 KB I + 64 KB D on chip per core
 Secondary Cache: 512 KB I+D on chip per core
 L3 Cache: 2 MB I+D on chip per chip
 Other Cache: None
 Memory: 16 GB (8x2GB PC2-5300P, CL5, dual rank ECC)
 Disk Subsystem: 1 x 400 GB SATA II, 7200 rpm
 Other Hardware: None

Software

Operating System: SUSE Linux Enterprise Server 10 (x86_64) SP1, Kernel 2.6.16.46-0.12-smp
 Compiler: PGI Workstation Complete Version 7.2-1
 Auto Parallel: Yes
 File System: ext3
 System State: Multi-User SuSE Run Level 3
 Base Pointers: 32/64-bit
 Peak Pointers: 32/64-bit
 Other Software: binutils 2.18.50
 Microquill SmartHeap 8.1 32-bit Library for Linux



SPEC CINT2006 Result

Copyright 2006-2009 Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

SPECint2006 = 13.6

CELSIUS V840, AMD Opteron 2350 (2.0 GHz)

SPECint_base2006 = 12.0

CPU2006 license: 22

Test date: Apr-2008

Test sponsor: Fujitsu Siemens Computers

Hardware Availability: May-2008

Tested by: Fujitsu Siemens Computers

Software Availability: May-2008

Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	<u>962</u>	<u>10.2</u>	968	10.1	954	10.2	769	12.7	<u>771</u>	<u>12.7</u>	779	12.5
401.bzip2	<u>1109</u>	<u>8.70</u>	1102	8.76	1114	8.67	1020	9.46	1021	9.45	<u>1020</u>	<u>9.46</u>
403.gcc	885	9.09	<u>885</u>	<u>9.10</u>	885	9.10	<u>868</u>	<u>9.27</u>	869	9.27	868	9.27
429.mcf	835	10.9	836	10.9	<u>835</u>	<u>10.9</u>	681	13.4	683	13.4	<u>682</u>	<u>13.4</u>
445.gobmk	1029	10.2	<u>1030</u>	<u>10.2</u>	1030	10.2	913	11.5	<u>913</u>	<u>11.5</u>	913	11.5
456.hammer	<u>705</u>	<u>13.2</u>	707	13.2	704	13.2	418	22.3	418	22.3	<u>418</u>	<u>22.3</u>
458.sjeng	<u>1128</u>	<u>10.7</u>	1129	10.7	1127	10.7	1036	11.7	<u>1036</u>	<u>11.7</u>	1036	11.7
462.libquantum	371	55.9	388	53.4	<u>388</u>	<u>53.4</u>	362	57.3	<u>362</u>	<u>57.2</u>	376	55.1
464.h264ref	<u>1335</u>	<u>16.6</u>	1356	16.3	1331	16.6	1243	17.8	<u>1259</u>	<u>17.6</u>	1262	17.5
471.omnetpp	710	8.80	709	8.81	<u>710</u>	<u>8.81</u>	710	8.80	709	8.81	<u>710</u>	<u>8.81</u>
473.astar	839	8.36	837	8.38	<u>839</u>	<u>8.37</u>	800	8.78	801	8.77	<u>801</u>	<u>8.77</u>
483.xalancbmk	653	10.6	655	10.5	<u>655</u>	<u>10.5</u>	585	11.8	<u>586</u>	<u>11.8</u>	586	11.8

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Operating System Notes

```

powersave -f is applied to set CPU to maximum frequency prior to run
stacksize is set to unlimited prior to run
ulimit -l 2457600
PGI_HUGE_PAGES set to 150
(Total number of huge pages available is 1200)

```

General Notes

For information about Fujitsu Siemens Computers please see:
<http://www.fujitsu-siemens.com>

Base Compiler Invocation

C benchmarks:
pgcc

C++ benchmarks:
pgcpp



SPEC CINT2006 Result

Copyright 2006-2009 Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

SPECint2006 = 13.6

CELSIUS V840, AMD Opteron 2350 (2.0 GHz)

SPECint_base2006 = 12.0

CPU2006 license: 22

Test sponsor: Fujitsu Siemens Computers

Tested by: Fujitsu Siemens Computers

Test date: Apr-2008

Hardware Availability: May-2008

Software Availability: May-2008

Base Portability Flags

```

400.perlbench: -DSPEC_CPU_LP64 -DSPEC_CPU_LINUX_X64
401.bzip2: -DSPEC_CPU_LP64
403.gcc: -DSPEC_CPU_LP64
429.mcf: -DSPEC_CPU_LP64
445.gobmk: -DSPEC_CPU_LP64
456.hmmer: -DSPEC_CPU_LP64
458.sjeng: -DSPEC_CPU_LP64
462.libquantum: -DSPEC_CPU_LP64 -DSPEC_CPU_LINUX
464.h264ref: -DSPEC_CPU_LP64
483.xalancbmk: -DSPEC_CPU_LINUX

```

Base Optimization Flags

C benchmarks:

```

-fastsse -Msmartalloc=huge:896 -Mloop32 -Mconcur=innermost
-Mfprelaxed -Mipa=jobs:4 -Mipa=fast -Mipa=inline -tp barcelona-64
-Bstatic_pgi

```

C++ benchmarks:

```

-fastsse -Msmartalloc=huge:896 -Mloop32 -Mfprelaxed --zc_eh
-Mipa=jobs:4 -Mipa=fast -Mipa=inline -tp barcelona -Bstatic_pgi

```

Peak Compiler Invocation

Same as Base Compiler Invocation

Peak Portability Flags

```

400.perlbench: -DSPEC_CPU_LP64 -DSPEC_CPU_LINUX_X64
401.bzip2: -DSPEC_CPU_LP64
445.gobmk: -DSPEC_CPU_LP64
456.hmmer: -DSPEC_CPU_LP64
458.sjeng: -DSPEC_CPU_LP64
462.libquantum: -DSPEC_CPU_LP64 -DSPEC_CPU_LINUX
464.h264ref: -DSPEC_CPU_LP64
483.xalancbmk: -DSPEC_CPU_LINUX

```

Peak Optimization Flags

C benchmarks:

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2009 Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

SPECint2006 = 13.6

CELSIUS V840, AMD Opteron 2350 (2.0 GHz)

SPECint_base2006 = 12.0

CPU2006 license: 22

Test date: Apr-2008

Test sponsor: Fujitsu Siemens Computers

Hardware Availability: May-2008

Tested by: Fujitsu Siemens Computers

Software Availability: May-2008

Peak Optimization Flags (Continued)

- 400.perlbench: -Mpfi(pass 1) -Mpfo(pass 2) -Mipa=jobs:4(pass 2)
-Mipa=inline(pass 2) -fastsse -O4 -Msmartalloc=huge:896
-Mnovect -Mnounroll -Mfprelaxed -tp barcelona-64
-Bstatic_pgi
- 401.bzip2: -Mpfi=indirect(pass 1) -Mpfo=indirect(pass 2) -fastsse -O4
-Msmartalloc=huge:896 -Mprefetch=t0 -Mnounroll
-tp barcelona-64 -Bstatic_pgi
- 403.gcc: -Mpfi(pass 1) -Mpfo(pass 2) -Mipa=jobs:4(pass 2)
-Mipa=fast(pass 2) -Mipa=inline(pass 2) -fastsse
-Msmartalloc=huge:896 -Mprefetch=t0 -Mnodalign -Mloop32
-Mfprelaxed -tp barcelona -Bstatic_pgi
- 429.mcf: -fastsse -Msmartalloc=huge:896 -Mipa=jobs:4 -Mipa=fast
-Mipa=inline:1 -tp barcelona -Bstatic_pgi
- 445.gobmk: -Mpfi(pass 1) -Mpfo(pass 2) -Mipa=jobs:4(pass 2)
-Mipa=fast(pass 2) -fastsse -O4 -Msmartalloc=huge:896
-Mnovect -Mfprelaxed -tp barcelona-64 -Bstatic_pgi
- 456.hmmcr: -fastsse -Mvect=partial -Munroll=n:8 -Msmartalloc=huge:896
-Msafeptr -Mprefetch=t0 -Mfprelaxed -Mipa=jobs:4
-Mipa=const -Mipa=ptr -Mipa=arg -Mipa=inline
-tp barcelona-64 -Bstatic_pgi
- 458.sjeng: -Mpfi(pass 1) -Mpfo(pass 2) -Mipa=jobs:4(pass 2)
-Mipa=fast(pass 2) -Mipa=inline:1(pass 2)
-Mipa=noarg(pass 2) -fastsse -Msmartalloc=huge:896
-Mfprelaxed -tp barcelona-64 -Bstatic_pgi
- 462.libquantum: -fastsse -Munroll=m:8 -Msmartalloc=huge:896
-Mprefetch=distance:8 -Mconcur=innermost -Mconcur=noaltcode
-Mfprelaxed -Mipa=jobs:4 -Mipa=fast -Mipa=inline
-Mipa=noarg -tp barcelona-64 -Bstatic_pgi
- 464.h264ref: -Mpfi=indirect(pass 1) -Mpfo=indirect(pass 2)
-Mipa=jobs:4(pass 2) -Mipa=fast(pass 2)
-Mipa=inline(pass 2) -fastsse -Msmartalloc=huge:896
-Mfprelaxed -tp barcelona-64 -Bstatic_pgi

C++ benchmarks:

- 471.omnetpp: basepeak = yes
- 473.astar: -Mpfi(pass 1) -Mpfo(pass 2) -Mipa=jobs:4(pass 2)
-Mipa=fast(pass 2) -Mipa=inline:6(pass 2) -fastsse -O4
-Msmartalloc=huge:896 -Msafeptr=global -Mloop32
-Mfprelaxed --zc_ah -tp barcelona -Bstatic_pgi

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2009 Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

SPECint2006 = 13.6

CELSIUS V840, AMD Opteron 2350 (2.0 GHz)

SPECint_base2006 = 12.0

CPU2006 license: 22

Test date: Apr-2008

Test sponsor: Fujitsu Siemens Computers

Hardware Availability: May-2008

Tested by: Fujitsu Siemens Computers

Software Availability: May-2008

Peak Optimization Flags (Continued)

```
483.xalancbmk: --zc_eh -fastsse -O4 -Mfprelaxed -Msmartalloc
-Mipa=jobs:4 -Mipa=fast -Mipa=inline -tp barcelona
-Bstatic_pgi -lsmartheap
```

Peak Other Flags

C++ benchmarks:

```
483.xalancbmk: -L/opt/SmartHeap_8.1/lib
```

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/fsc-mix-pgi-path.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/fsc-mix-pgi-path.xml>

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.
Report generated on Mon Jul 13 17:55:37 2009 by SPEC CPU2006 PS/PDF formatter v6323.