



SPEC[®] CINT2006 Result

Copyright 2006-2009 Standard Performance Evaluation Corporation

Bull SAS

NovaScale R440 E1
(Intel Xeon E5410, 2.33 GHz)

SPECint[®]2006 = 21.6

SPECint_base2006 = 18.9

CPU2006 license: 20


Test sponsor: Bull SAS

Tested by: Bull SAS

Test date: Jun-2008

Hardware Availability: Jan-2008

Software Availability: Nov-2007



Hardware

CPU Name: Intel Xeon E5410
 CPU Characteristics: 1333 MHz system bus
 CPU MHz: 2333
 FPU: Integrated
 CPU(s) enabled: 8 cores, 2 chips, 4 cores/chip
 CPU(s) orderable: 1,2 chips
 Primary Cache: 32 KB I + 32 KB D on chip per core
 Secondary Cache: 12 MB I+D on chip per chip, 6 MB shared / 2 cores
 L3 Cache: None
 Other Cache: None
 Memory: 16 GB (8x2 GB) FB-DIMM PC2-5300F ECC CL5
 Disk Subsystem: 1x73 GB SAS, 15000 RPM
 Other Hardware: None

Software

Operating System: SUSE LINUX Enterprise Server 10 SP1
 Kernel 2.6.16.46-0.12-smp for x86_64
 Compiler: Intel C++ Compiler 10.1 for Linux
 Build 20070913 Package ID: l_cc_p_10.1.008
 Auto Parallel: Yes
 File System: ext2
 System State: Run level 3 (multi-user)
 Base Pointers: 32-bit
 Peak Pointers: 32/64-bit
 Other Software: Binutils 2.17.50.0.15
 SmartHeap library V8.1



SPEC CINT2006 Result

Copyright 2006-2009 Standard Performance Evaluation Corporation

Bull SAS

NovaScale R440 E1
(Intel Xeon E5410, 2.33 GHz)

SPECint2006 = 21.6

SPECint_base2006 = 18.9

CPU2006 license: 20
Test sponsor: Bull SAS
Tested by: Bull SAS

Test date: Jun-2008
Hardware Availability: Jan-2008
Software Availability: Nov-2007

Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	635	15.4	640	15.3	<u>637</u>	<u>15.3</u>	507	19.3	507	19.3	<u>507</u>	<u>19.3</u>
401.bzip2	756	12.8	757	12.7	<u>756</u>	<u>12.8</u>	697	13.8	<u>698</u>	<u>13.8</u>	698	13.8
403.gcc	641	12.6	<u>641</u>	<u>12.6</u>	643	12.5	<u>487</u>	<u>16.5</u>	487	16.5	486	16.6
429.mcf	<u>434</u>	<u>21.0</u>	434	21.0	435	21.0	<u>431</u>	<u>21.2</u>	430	21.2	432	21.1
445.gobmk	680	15.4	680	15.4	<u>680</u>	<u>15.4</u>	<u>609</u>	<u>17.2</u>	610	17.2	609	17.2
456.hmmer	<u>762</u>	<u>12.2</u>	761	12.3	763	12.2	437	21.3	<u>438</u>	<u>21.3</u>	438	21.3
458.sjeng	852	14.2	854	14.2	<u>852</u>	<u>14.2</u>	<u>764</u>	<u>15.8</u>	762	15.9	767	15.8
462.libquantum	111	187	117	176	<u>112</u>	<u>185</u>	<u>112</u>	<u>185</u>	112	185	112	185
464.h264ref	917	24.1	<u>917</u>	<u>24.1</u>	919	24.1	854	25.9	859	25.8	<u>855</u>	<u>25.9</u>
471.omnetpp	469	13.3	464	13.5	<u>465</u>	<u>13.4</u>	<u>425</u>	<u>14.7</u>	425	14.7	425	14.7
473.astar	595	11.8	<u>590</u>	<u>11.9</u>	589	11.9	533	13.2	<u>536</u>	<u>13.1</u>	538	13.0
483.xalancbmk	332	20.8	<u>331</u>	<u>20.8</u>	331	20.8	332	20.8	<u>331</u>	<u>20.8</u>	331	20.8

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Operating System Notes

```
'ulimit -s unlimited' was used to set the stacksize to unlimited prior to run
OMP_NUM_THREADS set to number of cores
KMP_AFFINITY set to physical,0
KMP_STACKSIZE set to null
```

General Notes

All benchmarks compiled in 32-bit mode except 401.bzip2 and 456.hmmer, for peak, are compiled in 64-bit mode
The Bull NovaScale R440 E1 (Intel Xeon E5410, 2.33 GHz) and the Bull NovaScale R460 E1 (Intel Xeon E5410, 2.33 GHz) models are electronically equivalent. The results have been measured on a Bull NovaScale R460 E1 (Intel Xeon E5410, 2.33 GHz) model.

Base Compiler Invocation

C benchmarks:
icc

C++ benchmarks:
icpc



SPEC CINT2006 Result

Copyright 2006-2009 Standard Performance Evaluation Corporation

Bull SAS

NovaScale R440 E1
(Intel Xeon E5410, 2.33 GHz)

SPECint2006 = 21.6

SPECint_base2006 = 18.9

CPU2006 license: 20
Test sponsor: Bull SAS
Tested by: Bull SAS

Test date: Jun-2008
Hardware Availability: Jan-2008
Software Availability: Nov-2007

Base Portability Flags

400.perlbench: -DSPEC_CPU_LINUX_IA32
462.libquantum: -DSPEC_CPU_LINUX
483.xalancbmk: -DSPEC_CPU_LINUX

Base Optimization Flags

C benchmarks:
-fast -vec-guard-write -parallel -par-runtime-control

C++ benchmarks:
-xT -ipo -O3 -no-prec-div -Wl,-z,muldefs
-L/spec/cpu2006/lib -lsmartheap

Base Other Flags

C benchmarks:
403.gcc: -Dalloca=_alloca

Peak Compiler Invocation

C benchmarks (except as noted below):
icc

401.bzip2: /opt/intel/cce/10.1.008/bin/icc
-L/opt/intel/cce/10.1.008/lib
-I/opt/intel/cce/10.1.008/include

456.hmmmer: /opt/intel/cce/10.1.008/bin/icc
-L/opt/intel/cce/10.1.008/lib
-I/opt/intel/cce/10.1.008/include

C++ benchmarks:
icpc

Peak Portability Flags

400.perlbench: -DSPEC_CPU_LINUX_IA32
401.bzip2: -DSPEC_CPU_LP64
456.hmmmer: -DSPEC_CPU_LP64
462.libquantum: -DSPEC_CPU_LINUX

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2009 Standard Performance Evaluation Corporation

Bull SAS

NovaScale R440 E1
(Intel Xeon E5410, 2.33 GHz)

SPECint2006 = 21.6

SPECint_base2006 = 18.9

CPU2006 license: 20
Test sponsor: Bull SAS
Tested by: Bull SAS

Test date: Jun-2008
Hardware Availability: Jan-2008
Software Availability: Nov-2007

Peak Portability Flags (Continued)

483.xalanbmk: -DSPEC_CPU_LINUX

Peak Optimization Flags

C benchmarks:

400.perlbench: -prof-gen(pass 1) -prof-use(pass 2) -fast -ansi-alias
-prefetch

401.bzip2: -prof-gen(pass 1) -prof-use(pass 2) -fast -prefetch
-auto-ilp32

403.gcc: -fast -inline-calloc -opt-malloc-options=3

429.mcf: -fast -prefetch

445.gobmk: -prof-gen(pass 1) -prof-use(pass 2) -xT -O2 -ipo
-no-prec-div -ansi-alias

456.hmmr: -fast -unroll2 -ansi-alias -opt-multi-version-aggressive
-auto-ilp32

458.sjeng: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll4

462.libquantum: -fast -unroll4 -Ob0 -prefetch
-opt-streaming-stores always -vec-guard-write
-opt-malloc-options=3 -parallel -par-runtime-control

464.h264ref: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2
-ansi-alias

C++ benchmarks:

471.omnetpp: -prof-gen(pass 1) -prof-use(pass 2) -xT -O3 -ipo
-no-prec-div -ansi-alias -opt-ra-region-strategy=block
-Wl,-z,muldefs -L/spec/cpu2006/lib -lsmarheap

473.astar: -prof-gen(pass 1) -prof-use(pass 2) -xT -O3 -ipo
-no-prec-div -ansi-alias -opt-ra-region-strategy=routine
-Wl,-z,muldefs -L/spec/cpu2006/lib -lsmarheap

483.xalanbmk: basepeak = yes



SPEC CINT2006 Result

Copyright 2006-2009 Standard Performance Evaluation Corporation

Bull SAS

NovaScale R440 E1
(Intel Xeon E5410, 2.33 GHz)

SPECint2006 = 21.6

SPECint_base2006 = 18.9

CPU2006 license: 20
Test sponsor: Bull SAS
Tested by: Bull SAS

Test date: Jun-2008
Hardware Availability: Jan-2008
Software Availability: Nov-2007

Peak Other Flags

Same as Base Other Flags

The flags file that was used to format this result can be browsed at

http://www.spec.org/cpu2006/flags/EM64T_Intel101_int_flags.20090713.00.html

You can also download the XML flags source by saving the following link:

http://www.spec.org/cpu2006/flags/EM64T_Intel101_int_flags.20090713.00.xml

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.
Report generated on Mon Jul 13 18:53:50 2009 by SPEC CPU2006 PS/PDF formatter v6323.