SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

PowerEdge T105 (AMD Opteron 1352, 2.1 GHz)

SPECint®_rate2006 = 50.6

SPECint_rate_base2006 = 41.4

CPU2006 license: 55
Test sponsor: Dell Inc.
Tested by: Dell Inc.

Test date: Jun-2008
Hardware Availability: May-2008
Software Availability: Jun-2008



Hardware

CPU Name:	AMD Opteron 1352
CPU Characteristics:	
CPU MHz:	2100
FPU:	Integrated
CPU(s) enabled:	4 cores, 1 chip, 4 cores/chip
CPU(s) orderable:	1 chip
Primary Cache:	64 KB I + 64 KB D on chip per core
Secondary Cache:	512 KB I+D on chip per core
L3 Cache:	2 MB I+D on chip per chip
Other Cache:	None
Memory:	8 GB (4 x 2GB 800 MHz DDR2)
Disk Subsystem:	2 x 250GB SATA, 7200 RPM (RAID-0)
Other Hardware:	None

Software

Operating System:	SUSE Linux Enterprise Server 10 (x86_64) SP1, Kernel 2.6.16.46-0.12-smp
Compiler:	PGI Server Complete Version 7.2 PathScale Compiler Suite Version 3.2
Auto Parallel:	No
File System:	ReiserFS
System State:	Run level 3 (multi-user)
Base Pointers:	32/64-bit
Peak Pointers:	32/64-bit
Other Software:	SmartHeap 8.0 32-bit Library for Linux

SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

PowerEdge T105 (AMD Opteron 1352, 2.1 GHz)

SPECint_rate2006 = 50.6

SPECint_rate_base2006 = 41.4

CPU2006 license: 55
Test sponsor: Dell Inc.
Tested by: Dell Inc.

Test date: Jun-2008
Hardware Availability: May-2008
Software Availability: Jun-2008

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	4	869	45.0	**873**	**44.8**	874	44.7	4	668	58.5	663	58.9	**664**	**58.8**
401.bzip2	4	1165	33.1	**1171**	**33.0**	1179	32.8	4	**1127**	**34.3**	1131	34.1	1122	34.4
403.gcc	4	1010	31.9	**985**	**32.7**	979	32.9	4	854	37.7	**855**	**37.7**	857	37.6
429.mcf	4	1940	18.8	2005	18.2	**1979**	**18.4**	4	**775**	**47.1**	776	47.0	774	47.1
445.gobmk	4	**979**	**42.8**	979	42.9	980	42.8	4	772	54.3	773	54.3	**773**	**54.3**
456.hmmer	4	**666**	**56.1**	664	56.2	667	56.0	4	445	83.8	**449**	**83.1**	453	82.4
458.sjeng	4	**1061**	**45.6**	1061	45.6	1062	45.6	4	**980**	**49.4**	982	49.3	980	49.4
462.libquantum	4	998	83.0	**1003**	**82.6**	1004	82.5	4	**991**	**83.6**	997	83.1	986	84.1
464.h264ref	4	1260	70.2	1265	70.0	**1261**	**70.2**	4	**1217**	**72.8**	1215	72.9	1217	72.7
471.omnetpp	4	**765**	**32.7**	765	32.7	769	32.5	4	757	33.0	754	33.2	**754**	**33.2**
473.astar	4	**892**	**31.5**	895	31.4	890	31.5	4	**804**	**34.9**	802	35.0	804	34.9
483.xalancbmk	4	**637**	**43.3**	638	43.3	637	43.3	4	544	50.8	545	50.6	**545**	**50.7**

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Operating System Notes

```
'numactl' was used to bind copies to the cores
Environment variable PGI_HUGE_PAGES set to 150
'ulimit -s unlimited' was used to set environment stack size
mount -t hugetlbfs nodev /mnt/hugepages
'ulimit -l 1228800'  was used to set environment locked pages in memory limit
Set vm/nr_hugepages=600 in /etc/sysctl.conf
```

Base Compiler Invocation

C benchmarks:
pgcc

C++ benchmarks:
pgcpp

Base Portability Flags

400.perlbench: -DSPEC_CPU_LP64 -DSPEC_CPU_LINUX_X64
401.bzip2: -DSPEC_CPU_LP64
403.gcc: -DSPEC_CPU_LP64
429.mcf: -DSPEC_CPU_LP64
445.gobmk: -DSPEC_CPU_LP64
456.hmmer: -DSPEC_CPU_LP64

Continued on next page

Base Portability Flags (Continued)

458.sjeng: `-DSPEC_CPU_LP64`
462.libquantum: `-DSPEC_CPU_LP64 -DSPEC_CPU_LINUX`
464.h264ref: `-DSPEC_CPU_LP64`
471.omnetpp: `-DSPEC_CPU_LP64`
473.astar: `-DSPEC_CPU_LP64`
483.xalancbmk: `-DSPEC_CPU_LP64 -DSPEC_CPU_LINUX`

Base Optimization Flags

C benchmarks:
`-fastsse -Msmartalloc=huge:150 -Mfprelaxed -Mipa=fast -Mipa=inline -tp barcelona-64 -Bstatic_pgi`

C++ benchmarks:
`-fastsse -Msmartalloc=huge:150 -Mfprelaxed --zc_eh -Mipa=fast -Mipa=inline -tp barcelona -Bstatic_pgi`

Base Other Flags

C benchmarks:
`-Mipa=jobs:4`

C++ benchmarks:
`-Mipa=jobs:4`

Peak Compiler Invocation

C benchmarks (except as noted below):
`pgcc`

400.perlbench: `pathcc`

403.gcc: `pathcc`

445.gobmk: `pathcc`

464.h264ref: `pathcc`

C++ benchmarks (except as noted below):
`pathCC`

473.astar: `pgcpp`

Peak Portability Flags

400.perlbench: -DSPEC_CPU_LP64 -DSPEC_CPU_LINUX_X64
401.bzip2: -DSPEC_CPU_LP64
445.gobmk: -DSPEC_CPU_LP64
456.hmmer: -DSPEC_CPU_LP64
458.sjeng: -DSPEC_CPU_LP64
462.libquantum: -DSPEC_CPU_LP64 -DSPEC_CPU_LINUX
464.h264ref: -DSPEC_CPU_LP64
473.astar: -DSPEC_CPU_LP64
483.xalancbmk: -DSPEC_CPU_LINUX

Peak Optimization Flags

C benchmarks:

400.perlbench: -march=barcelona -fb_create fbdata(pass 1)
-fb_opt fbdata(pass 2) -Ofast -IPA:plimit=20000 -LNO:opt=0
-WOPT:if_conv=0 -CG:local_sched_alg=1

401.bzip2: -Mpfi=indirect(pass 1) -Mpfo=indirect(pass 2) -fastsse -O4
-Msmartalloc=huge:150 -Mprefetch=t0 -Mnounroll
-tp barcelona-64 -Bstatic_pgi

403.gcc: -march=barcelona -fb_create fbdata(pass 1)
-fb_opt fbdata(pass 2) -O3 -OPT:Ofast -m32

429.mcf: -fastsse -Msmartalloc=huge:150 -Mipa=fast -Mipa=inline:1
-tp barcelona -Bstatic_pgi

445.gobmk: -march=barcelona -fb_create fbdata(pass 1)
-fb_opt fbdata(pass 2) -O3 -OPT:alias=restrict
-LNO:prefetch=1 -LNO:ignore_feedback=off -CG:p2align=on

456.hmmer: -fastsse -Mvect=partial -Munroll=n:8 -Msmartalloc=huge:150
-Msafeptr -Mprefetch=t0 -Mfprelaxed -Mipa=const -Mipa=ptr
-Mipa=arg -Mipa=inline -tp barcelona-64 -Bstatic_pgi

458.sjeng: -Mpfi(pass 1) -Mpfo(pass 2) -Mipa=fast(pass 2)
-Mipa=inline:1(pass 2) -Mipa=noarg(pass 2) -fastsse
-Msmartalloc=huge:150 -Mfprelaxed -tp barcelona-64
-Bstatic_pgi

462.libquantum: -fastsse -Munroll=m:8 -Msmartalloc=huge:150
-Mprefetch=distance:4 -Mfprelaxed -Mipa=fast -Mipa=inline
-Mipa=noarg -tp barcelona-64 -Bstatic_pgi

464.h264ref: -march=barcelona -fb_create fbdata(pass 1)
-fb_opt fbdata(pass 2) -O3 -IPA:plimit=20000
-OPT:alias=disjoint -LNO:prefetch=0 -CG:ptr_load_use=0
-CG:push_pop_int_saved_regs=off

Continued on next page

Peak Optimization Flags (Continued)

C++ benchmarks:

471.omnetpp: `-march=barcelona -Ofast -CG:gcm=off -INLINE:aggressive=on -OPT:alias=disjoint -WOPT:if_conv=0 -m32 -lsmartheap`

473.astar: `-Mpfi`(pass 1) `-Mpfo`(pass 2) `-Mipa=fast`(pass 2) `-Mipa=inline:6`(pass 2) `-fastsse -O4 -Msmartalloc=huge:150 -Msafeptr=global -Mfprelaxed --zc_eh -tp barcelona -Bstatic_pgi`

483.xalancbmk: `-march=barcelona -Ofast -OPT:unroll_times_max=8 -CG:push_pop_int_saved_regs=off -CG:ptr_load_use=0 -m32 -lsmartheap`

Peak Other Flags

C benchmarks:

429.mcf: `-Mipa=jobs:4`

456.hmmer: `-Mipa=jobs:4`

458.sjeng: `-Mipa=jobs:4`(pass 2)

462.libquantum: `-Mipa=jobs:4`

C++ benchmarks (except as noted below):
`-L/root/work/cpu2006-amd421gh/amd421gh.libs/32`

473.astar: `-Mipa=jobs:4`(pass 2)

The flags file that was used to format this result can be browsed at
`http://www.spec.org/cpu2006/flags/amd421GH-flags.20090713.01.html`

You can also download the XML flags source by saving the following link:
`http://www.spec.org/cpu2006/flags/amd421GH-flags.20090713.01.xml`

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

PowerEdge T105 (AMD Opteron 1352, 2.1 GHz)

SPECint_rate2006 = 50.6

SPECint_rate_base2006 = 41.4

CPU2006 license: 55
Test sponsor: Dell Inc.
Tested by: Dell Inc.

Test date: Jun-2008
Hardware Availability: May-2008
Software Availability: Jun-2008

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.
Report generated on Tue Jul 22 19:26:23 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 19 August 2008.