



SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

NovaScale R460 E1
(Intel Xeon X5470, 3.33 GHz)

SPECfp®2006 = 26.2

SPECfp_base2006 = 25.0

CPU2006 license: 20


Test sponsor: Bull SAS

Tested by: NEC Corporation

Test date: Oct-2008

Hardware Availability: Oct-2008

Software Availability: Nov-2008



Hardware

CPU Name: Intel Xeon X5470
CPU Characteristics: 3.33 GHz, 2x6 MB L2 shared, 1333 MHz system bus
CPU MHz: 3333
FPU: Integrated
CPU(s) enabled: 8 cores, 2 chips, 4 cores/chip
CPU(s) orderable: 1,2 chips
Primary Cache: 32 KB I + 32 KB D on chip per core
Secondary Cache: 12 MB I+D on chip per chip, 6 MB shared / 2 cores

Software

Operating System: SUSE Linux Enterprise Server 10 (x86_64) SP2, Kernel 2.6.16.60-0.21-smp
Compiler: Intel C++ and Fortran Compiler 11.0 for Linux Build 20080730 Package ID: l_cproc_b_11.0.044, l_fproc_b_11.0.044
Auto Parallel: Yes
File System: ext2
System State: Run level 3 (multi-user)
Base Pointers: 64-bit

Continued on next page

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

NovaScale R460 E1
(Intel Xeon X5470, 3.33 GHz)

SPECfp2006 = 26.2

SPECfp_base2006 = 25.0

CPU2006 license: 20

Test sponsor: Bull SAS

Tested by: NEC Corporation

Test date: Oct-2008

Hardware Availability: Oct-2008

Software Availability: Nov-2008

L3 Cache: None
Other Cache: None
Memory: 16 GB (8x2 GB PC2-5300F, 2 rank, CL5-5-5, ECC)
Disk Subsystem: 1x146.5 GB SAS, 15000RPM
Other Hardware: None

Peak Pointers: 32/64-bit
Other Software: Binutils 2.18.50.0.7.20080502

Results Table

Benchmark	Base						Peak					
	Seconds	Ratio										
410.bwaves	397	34.2	397	34.2	398	34.2	397	34.2	397	34.2	398	34.1
416.gamess	864	22.7	864	22.7	865	22.6	770	25.4	769	25.5	770	25.4
433.milc	572	16.0	573	16.0	571	16.1	577	15.9	578	15.9	576	15.9
434.zeusmp	411	22.1	410	22.2	411	22.2	411	22.1	410	22.2	411	22.2
435.gromacs	324	22.0	324	22.0	322	22.2	320	22.3	321	22.2	319	22.4
436.cactusADM	105	114	105	114	105	114	106	113	106	113	105	113
437.leslie3d	469	20.0	469	20.1	470	20.0	469	20.0	469	20.1	470	20.0
444.namd	443	18.1	441	18.2	441	18.2	444	18.1	444	18.1	444	18.1
447.dealII	371	30.8	371	30.9	371	30.8	345	33.1	345	33.2	345	33.2
450.soplex	598	13.9	599	13.9	600	13.9	544	15.3	544	15.3	544	15.3
453.povray	197	27.0	197	27.0	196	27.1	160	33.3	159	33.5	159	33.5
454.calculix	331	24.9	331	24.9	331	24.9	314	26.3	316	26.1	315	26.2
459.GemsFDTD	480	22.1	480	22.1	480	22.1	481	22.0	482	22.0	482	22.0
465.tonto	490	20.1	490	20.1	492	20.0	386	25.5	387	25.4	387	25.4
470.lbm	512	26.9	512	26.9	511	26.9	512	26.9	512	26.9	511	26.9
481.wrf	500	22.3	500	22.3	501	22.3	500	22.3	500	22.3	500	22.3
482.sphinx3	664	29.4	667	29.2	683	28.5	638	30.5	643	30.3	642	30.4

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Operating System Notes

'ulimit -s unlimited' was used to set the stacksize to unlimited prior to run
OMP_NUM_THREADS set to number of cores
KMP_AFFINITY set to "physical,0"
KMP_STACKSIZE set to 200M

Platform Notes

Bios settings:

Hardware Prefetcher: Enabled
Adjacent Cache Line Prefetch: Enabled



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

NovaScale R460 E1
(Intel Xeon X5470, 3.33 GHz)

SPECfp2006 = 26.2

SPECfp_base2006 = 25.0

CPU2006 license: 20

Test sponsor: Bull SAS

Tested by: NEC Corporation

Test date: Oct-2008

Hardware Availability: Oct-2008

Software Availability: Nov-2008

General Notes

The NEC Express5800/120Rh-1(Intel Xeon X5470),
the NEC Express5800/120Rj-2(Intel Xeon X5470),
the Bull NovaScale R440 E1(Intel Xeon X5470, 3.33 GHz) and
the Bull NovaScale R460 E1(Intel Xeon X5470, 3.33 GHz) models are electronically equivalent.
The results have been measured on a NEC Express5800/120Rj-2(Intel Xeon X5470) model.

Base Compiler Invocation

C benchmarks:
icc

C++ benchmarks:
icpc

Fortran benchmarks:
ifort

Benchmarks using both Fortran and C:
icc ifort

Base Portability Flags

```
410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
  433.milc: -DSPEC_CPU_LP64
  434.zeusmp: -DSPEC_CPU_LP64
  435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
  437.leslie3d: -DSPEC_CPU_LP64
    444.namd: -DSPEC_CPU_LP64
    447.dealII: -DSPEC_CPU_LP64
    450.soplex: -DSPEC_CPU_LP64
    453.povray: -DSPEC_CPU_LP64
    454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
  465.tonto: -DSPEC_CPU_LP64
    470.lbm: -DSPEC_CPU_LP64
    481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
482.sphinx3: -DSPEC_CPU_LP64
```

Base Optimization Flags

C benchmarks:
-xSSE4.1 -ipo -O3 -no-prec-div -static -parallel -opt-prefetch

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

NovaScale R460 E1
(Intel Xeon X5470, 3.33 GHz)

SPECfp2006 = 26.2

SPECfp_base2006 = 25.0

CPU2006 license: 20

Test sponsor: Bull SAS

Tested by: NEC Corporation

Test date: Oct-2008

Hardware Availability: Oct-2008

Software Availability: Nov-2008

Base Optimization Flags (Continued)

C++ benchmarks:

```
-xSSE4.1 -ipo -O3 -no-prec-div -static -parallel -opt-prefetch
```

Fortran benchmarks:

```
-xSSE4.1 -ipo -O3 -no-prec-div -static -parallel -opt-prefetch
```

Benchmarks using both Fortran and C:

```
-xSSE4.1 -ipo -O3 -no-prec-div -static -parallel -opt-prefetch
```

Peak Compiler Invocation

C benchmarks (except as noted below):

icc

```
482.sphinx3: /opt/intel/Compiler/11.0/044/bin/ia32/icc
    -L/opt/intel/Compiler/11.0/044/ipp/ia32/lib
    -I/opt/intel/Compiler/11.0/044/ipp/ia32/include
```

C++ benchmarks (except as noted below):

icpc

```
450.soplex: /opt/intel/Compiler/11.0/044/bin/ia32/icpc
    -L/opt/intel/Compiler/11.0/044/ipp/ia32/lib
    -I/opt/intel/Compiler/11.0/044/ipp/ia32/include
```

Fortran benchmarks:

ifort

Benchmarks using both Fortran and C:

icc ifort

Peak Portability Flags

```
410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
437.leslie3d: -DSPEC_CPU_LP64
444.namd: -DSPEC_CPU_LP64
447.dealII: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
```

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

NovaScale R460 E1
(Intel Xeon X5470, 3.33 GHz)

SPECfp2006 = 26.2

SPECfp_base2006 = 25.0

CPU2006 license: 20

Test sponsor: Bull SAS

Tested by: NEC Corporation

Test date: Oct-2008

Hardware Availability: Oct-2008

Software Availability: Nov-2008

Peak Portability Flags (Continued)

465.tonto: -DSPEC_CPU_LP64

470.lbm: -DSPEC_CPU_LP64

481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX

Peak Optimization Flags

C benchmarks:

433.milc: -prof-gen(pass 1) -prof-use(pass 2) -xSSE4.1 -ipo -O3
-no-prec-div -static -fno-alias

470.lbm: basepeak = yes

482.sphinx3: -xSSE4.1 -ipo -O3 -no-prec-div -static -unroll2

C++ benchmarks:

444.namd: -prof-gen(pass 1) -prof-use(pass 2) -xSSE4.1 -ipo -O3
-no-prec-div -static -fno-alias -auto-ilp32

447.dealII: -prof-gen(pass 1) -prof-use(pass 2) -xSSE4.1 -ipo -O3
-no-prec-div -static -unroll2 -ansi-alias -scalar-rep-
-opt-prefetch

450.soplex: -prof-gen(pass 1) -prof-use(pass 2) -xSSE4.1 -ipo -O3
-no-prec-div -static -opt-malloc-options=3

453.povray: -prof-gen(pass 1) -prof-use(pass 2) -xSSE4.1 -ipo -O3
-no-prec-div -static -unroll4 -ansi-alias

Fortran benchmarks:

410.bwaves: -xSSE4.1 -ipo -O3 -no-prec-div -static -opt-prefetch
-parallel

416.gamess: -prof-gen(pass 1) -prof-use(pass 2) -xSSE4.1 -ipo -O3
-no-prec-div -static -unroll2 -Ob0 -ansi-alias
-scalar-rep-

434.zeusmp: basepeak = yes

437.leslie3d: basepeak = yes

459.GemsFDTD: -prof-gen(pass 1) -prof-use(pass 2) -xSSE4.1 -ipo -O3
-no-prec-div -static -unroll2 -Ob0 -opt-prefetch
-parallel

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

NovaScale R460 E1
(Intel Xeon X5470, 3.33 GHz)

SPECfp2006 = 26.2

SPECfp_base2006 = 25.0

CPU2006 license: 20

Test sponsor: Bull SAS

Tested by: NEC Corporation

Test date: Oct-2008

Hardware Availability: Oct-2008

Software Availability: Nov-2008

Peak Optimization Flags (Continued)

465.tonto: -prof-gen(pass 1) -prof-use(pass 2) -xsse4.1 -ipo -O3
-no-prec-div -static -unroll4 -auto

Benchmarks using both Fortran and C:

435.gromacs: -prof-gen(pass 1) -prof-use(pass 2) -xsse4.1 -ipo -O3
-no-prec-div -static -opt-prefetch -auto-ilp32

436.cactusADM: -prof-gen(pass 1) -prof-use(pass 2) -xsse4.1 -ipo -O3
-no-prec-div -static -unroll2 -opt-prefetch -parallel
-auto-ilp32

454.calculix: -xsse4.1 -ipo -O3 -no-prec-div -static -auto-ilp32

481.wrf: -xsse4.1 -ipo -O3 -no-prec-div -static -opt-prefetch
-parallel -auto-ilp32

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic11.0-fp-linux64-revD.html>
<http://www.spec.org/cpu2006/flags/NEC-Intel-Linux-Settings-flags-revB.html>

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/cpu2006/flags/Intel-ic11.0-fp-linux64-revD.xml>
<http://www.spec.org/cpu2006/flags/NEC-Intel-Linux-Settings-flags-revB.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.1.

Report generated on Tue Jul 22 22:51:11 2014 by SPEC CPU2006 PS/PDF formatter v6932.

Originally published on 6 January 2009.