



SPEC® CFP2006 Result

Copyright 2006-2009 Standard Performance Evaluation Corporation

ACTION S.A.

SPECfp®_rate2006 = 70.9

ACTINA SOLAR 212 X2 (Intel Xeon E5420, 2.5 GHz)

SPECfp_rate_base2006 = 65.0

CPU2006 license: 9008


Test sponsor: ACTION S.A.

Tested by: ACTION S.A.

Test date: Dec-2008

Hardware Availability: Sep-2008

Software Availability: Nov-2008



Hardware

CPU Name: Intel Xeon E5420
 CPU Characteristics: 1333 MHz System Bus
 CPU MHz: 2500
 FPU: Integrated
 CPU(s) enabled: 8 cores, 2 chips, 4 cores/chip
 CPU(s) orderable: 1,2 chips
 Primary Cache: 32 KB I + 32 KB D on chip per core
 Secondary Cache: 12 MB I+D on chip per chip, 6 MB shared / 2 cores

Continued on next page

Software

Operating System: SUSE Linux Enterprise Server 10 (x86_64) with SP2, kernel 2.6.16.60-0.21-smp
 Compiler: Intel C++ and Fortran Compiler 11.0 for Linux Build 20080730 Package ID: l_cproc_b_11.0.042, l_fproc_b_11.0.042
 Auto Parallel: Yes
 File System: ReiserFS
 System State: Run level 3 (multi-user)
 Base Pointers: 64-bit

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2009 Standard Performance Evaluation Corporation

ACTION S.A.

SPECfp_rate2006 = 70.9

ACTINA SOLAR 212 X2 (Intel Xeon E5420, 2.5 GHz)

SPECfp_rate_base2006 = 65.0

CPU2006 license: 9008

Test date: Dec-2008

Test sponsor: ACTION S.A.

Hardware Availability: Sep-2008

Tested by: ACTION S.A.

Software Availability: Nov-2008

Hardware (Continued)

L3 Cache: None
Other Cache: None
Memory: 16 GB (8x 2 GB, PC2-5300, CL 5-5-5, FB ECC)
Disk Subsystem: 500 GB SATA, 7200 RPM
Other Hardware: None

Software (Continued)

Peak Pointers: 32/64-bit
Other Software: Binutils 2.18.50.0.7.20080502

Results Table

Benchmark	Base								Peak							
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio		
410.bwaves	8	3218	33.8	3210	33.9	<u>3211</u>	<u>33.9</u>	4	1584	34.3	1584	34.3	<u>1584</u>	<u>34.3</u>		
416.gamess	8	1050	149	1053	149	<u>1052</u>	<u>149</u>	8	1033	152	<u>1032</u>	<u>152</u>	1032	152		
433.milc	8	2511	29.2	2511	29.2	<u>2511</u>	<u>29.2</u>	8	2509	29.3	2508	29.3	<u>2508</u>	<u>29.3</u>		
434.zeusmp	8	1035	70.3	<u>1038</u>	<u>70.1</u>	1047	69.6	8	1012	72.0	<u>1011</u>	<u>72.0</u>	999	72.8		
435.gromacs	8	<u>439</u>	<u>130</u>	439	130	442	129	8	436	131	<u>436</u>	<u>131</u>	434	131		
436.cactusADM	8	1203	79.5	1203	79.4	<u>1203</u>	<u>79.4</u>	1	121	98.5	121	99.0	<u>121</u>	<u>98.7</u>		
437.leslie3d	8	2521	29.8	2528	29.7	<u>2521</u>	<u>29.8</u>	4	1164	32.3	1149	32.7	<u>1151</u>	<u>32.7</u>		
444.namd	8	592	108	598	107	<u>597</u>	<u>107</u>	8	<u>596</u>	<u>108</u>	595	108	603	106		
447.dealII	8	<u>701</u>	<u>131</u>	701	131	758	121	8	725	126	718	128	<u>723</u>	<u>127</u>		
450.soplex	8	<u>2061</u>	<u>32.4</u>	2060	32.4	2062	32.4	8	1858	35.9	<u>1858</u>	<u>35.9</u>	1854	36.0		
453.povray	8	258	165	263	162	<u>259</u>	<u>164</u>	8	218	195	217	196	<u>217</u>	<u>196</u>		
454.calculix	8	463	143	<u>461</u>	<u>143</u>	456	145	8	<u>459</u>	<u>144</u>	471	140	454	145		
459.GemsFDTD	8	<u>3353</u>	<u>25.3</u>	3351	25.3	3358	25.3	8	3424	24.8	<u>3409</u>	<u>24.9</u>	3408	24.9		
465.tonto	8	732	108	<u>733</u>	<u>107</u>	736	107	8	<u>689</u>	<u>114</u>	689	114	685	115		
470.lbm	8	4086	26.9	<u>4084</u>	<u>26.9</u>	4082	26.9	4	<u>1471</u>	<u>37.4</u>	1468	37.4	1472	37.3		
481.wrf	8	<u>1791</u>	<u>49.9</u>	1789	50.0	1791	49.9	8	<u>1791</u>	<u>49.9</u>	1789	50.0	1791	49.9		
482.sphinx3	8	2939	53.1	<u>2934</u>	<u>53.1</u>	2933	53.2	4	902	86.4	<u>917</u>	<u>85.0</u>	917	85.0		

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Submit Notes

The config file option 'submit' was used.

Platform Notes

This result is measured on ACTINA SOLAR 222 X2.
Note that the ACTINA SOLAR 222 X2 and ACTINA SOLAR 212 X2 are electrically equivalent.



SPEC CFP2006 Result

Copyright 2006-2009 Standard Performance Evaluation Corporation

ACTION S.A.

SPECfp_rate2006 = 70.9

ACTINA SOLAR 212 X2 (Intel Xeon E5420, 2.5 GHz)

SPECfp_rate_base2006 = 65.0

CPU2006 license: 9008

Test date: Dec-2008

Test sponsor: ACTION S.A.

Hardware Availability: Sep-2008

Tested by: ACTION S.A.

Software Availability: Nov-2008

General Notes

taskset was used to bind processes to cores except for 436.cactusADM peak
'ulimit -s unlimited' was used to set the stacksize to unlimited prior to run
OMP_NUM_THREADS set to number of processors
KMP_AFFINITY set to "physical,0"
KMP_STACKSIZE set to 64M

Base Compiler Invocation

C benchmarks:

icc

C++ benchmarks:

icpc

Fortran benchmarks:

ifort

Benchmarks using both Fortran and C:

icc ifort

Base Portability Flags

410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
437.leslie3d: -DSPEC_CPU_LP64
444.namd: -DSPEC_CPU_LP64
447.dealII: -DSPEC_CPU_LP64
450.soplex: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
470.lbm: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
482.sphinx3: -DSPEC_CPU_LP64

Base Optimization Flags

C benchmarks:

-xSSE4.1 -ipo -O3 -no-prec-div -static -opt-prefetch

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2009 Standard Performance Evaluation Corporation

ACTION S.A.

SPECfp_rate2006 = 70.9

ACTINA SOLAR 212 X2 (Intel Xeon E5420, 2.5 GHz)

SPECfp_rate_base2006 = 65.0

CPU2006 license: 9008

Test date: Dec-2008

Test sponsor: ACTION S.A.

Hardware Availability: Sep-2008

Tested by: ACTION S.A.

Software Availability: Nov-2008

Base Optimization Flags (Continued)

C++ benchmarks:

-xSSE4.1 -ipo -O3 -no-prec-div -static -opt-prefetch

Fortran benchmarks:

-xSSE4.1 -ipo -O3 -no-prec-div -static -opt-prefetch

Benchmarks using both Fortran and C:

-xSSE4.1 -ipo -O3 -no-prec-div -static -opt-prefetch

Peak Compiler Invocation

C benchmarks (except as noted below):

icc

482.sphinx3: /opt/intel/Compiler/11.0/042/bin/ia32/icc
-L/opt/intel/Compiler/11.0/042/ipp/ia32/lib
-I/opt/intel/Compiler/11.0/042/ipp/ia32/include

C++ benchmarks (except as noted below):

icpc

450.soplex: /opt/intel/Compiler/11.0/042/bin/ia32/icpc
-L/opt/intel/Compiler/11.0/042/ipp/ia32/lib
-I/opt/intel/Compiler/11.0/042/ipp/ia32/include

Fortran benchmarks (except as noted below):

ifort

437.leslie3d: /opt/intel/Compiler/11.0/042/bin/ia32/ifort
-L/opt/intel/Compiler/11.0/042/ipp/ia32/lib
-I/opt/intel/Compiler/11.0/042/ipp/ia32/include

Benchmarks using both Fortran and C:

icc ifort

Peak Portability Flags

410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
444.namd: -DSPEC_CPU_LP64
447.dealII: -DSPEC_CPU_LP64

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2009 Standard Performance Evaluation Corporation

ACTION S.A.

SPECfp_rate2006 = 70.9

ACTINA SOLAR 212 X2 (Intel Xeon E5420, 2.5 GHz)

SPECfp_rate_base2006 = 65.0

CPU2006 license: 9008

Test date: Dec-2008

Test sponsor: ACTION S.A.

Hardware Availability: Sep-2008

Tested by: ACTION S.A.

Software Availability: Nov-2008

Peak Portability Flags (Continued)

```

453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
470.lbm: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX

```

Peak Optimization Flags

C benchmarks:

```

433.milc: -prof-gen(pass 1) -prof-use(pass 2) -xSSE4.1 -ipo -O3
         -no-prec-div -static -fno-alias

470.lbm: -xSSE4.1 -ipo -O3 -no-prec-div -static -opt-prefetch
        -auto-ilp32

482.sphinx3: -xSSE4.1 -ipo -O3 -no-prec-div -static -unroll2

```

C++ benchmarks:

```

444.namd: -prof-gen(pass 1) -prof-use(pass 2) -xSSE4.1 -ipo -O3
         -no-prec-div -static -fno-alias -auto-ilp32

447.deallI: -prof-gen(pass 1) -prof-use(pass 2) -xSSE4.1 -ipo -O3
          -no-prec-div -static -unroll2 -ansi-alias -scalar-rep-

450.soplex: -prof-gen(pass 1) -prof-use(pass 2) -xSSE4.1 -ipo -O3
          -no-prec-div -static -opt-malloc-options=3

453.povray: -prof-gen(pass 1) -prof-use(pass 2) -xSSE4.1 -ipo -O3
          -no-prec-div -static -unroll4 -ansi-alias

```

Fortran benchmarks:

```

410.bwaves: -xSSE4.1 -ipo -O3 -no-prec-div -static -opt-prefetch

416.gamess: -prof-gen(pass 1) -prof-use(pass 2) -xSSE4.1 -ipo -O3
          -no-prec-div -static -unroll2 -Ob0 -ansi-alias
          -scalar-rep-

434.zeusmp: -prof-gen(pass 1) -prof-use(pass 2) -xSSE4.1 -ipo -O3
          -no-prec-div -static

437.leslie3d: -prof-gen(pass 1) -prof-use(pass 2) -xSSE4.1 -ipo -O3
          -no-prec-div -static -opt-malloc-options=3 -opt-prefetch

```

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2009 Standard Performance Evaluation Corporation

ACTION S.A.

SPECfp_rate2006 = 70.9

ACTINA SOLAR 212 X2 (Intel Xeon E5420, 2.5 GHz)

SPECfp_rate_base2006 = 65.0

CPU2006 license: 9008

Test date: Dec-2008

Test sponsor: ACTION S.A.

Hardware Availability: Sep-2008

Tested by: ACTION S.A.

Software Availability: Nov-2008

Peak Optimization Flags (Continued)

459.GemsFDTD: -prof-gen(pass 1) -prof-use(pass 2) -xSSE4.1 -ipo -O3
-no-prec-div -static -unroll2 -Ob0 -opt-prefetch

465.tonto: -prof-gen(pass 1) -prof-use(pass 2) -xSSE4.1 -ipo -O3
-no-prec-div -static -unroll4 -auto

Benchmarks using both Fortran and C:

435.gromacs: -prof-gen(pass 1) -prof-use(pass 2) -xSSE4.1 -ipo -O3
-no-prec-div -static -opt-prefetch -auto-ilp32

436.cactusADM: -prof-gen(pass 1) -prof-use(pass 2) -xSSE4.1 -ipo -O3
-no-prec-div -static -unroll2 -opt-prefetch -parallel
-auto-ilp32

454.calculix: -xSSE4.1 -ipo -O3 -no-prec-div -static -auto-ilp32

481.wrf: basepeak = yes

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic11.0-fp-linux64-revA.20090713.02.html>

<http://www.spec.org/cpu2006/flags/Intel-Linux64-Platform.20090713.html>

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/cpu2006/flags/Intel-ic11.0-fp-linux64-revA.20090713.02.xml>

<http://www.spec.org/cpu2006/flags/Intel-Linux64-Platform.20090713.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.1.

Report generated on Mon Jul 13 09:19:26 2009 by SPEC CPU2006 PS/PDF formatter v6323.