SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

IBM Power 550 (5.0 GHz, 8 core, SLES)

SPECint®_rate2006 = 258

SPECint_rate_base2006 = 216

CPU2006 license: 11
Test sponsor: IBM Corporation
Tested by: IBM Corporation

Test date: Mar-2009
Hardware Availability: May-2009
Software Availability: Mar-2009



Hardware

CPU Name:	POWER6+
CPU Characteristics:	
CPU MHz:	5000
FPU:	Integrated
CPU(s) enabled:	8 cores, 4 chips, 2 cores/chip, 2 threads/core
CPU(s) orderable:	2,4,6,8 cores
Primary Cache:	64 KB I + 64 KB D on chip per core
Secondary Cache:	4 MB I+D on chip per core
L3 Cache:	32 MB I+D off chip per chip
Other Cache:	None
Memory:	128 GB (32x4 GB) DDR2 667 MHz
Disk Subsystem:	2x146 GB SAS 15K RPM
Other Hardware:	None

Software

Operating System:	SUSE Linux Enterprise Server 11
Compiler:	IBM XL C/C++ for Linux, V10.1 Updated with the Mar2009 PTF.
Auto Parallel:	No
File System:	ext3
System State:	Run Level 3 (Multi-User)
Base Pointers:	32-bit
Peak Pointers:	32/64-bit
Other Software:	-Post-Link Optimization for Linux on POWER, Version 5.4.0-21 -MicroQuill SmartHeap 8.1

SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

IBM Power 550 (5.0 GHz, 8 core, SLES)

SPECint_rate2006 = 258

SPECint_rate_base2006 = 216

CPU2006 license: 11
Test sponsor: IBM Corporation
Tested by: IBM Corporation

Test date: Mar-2009
Hardware Availability: May-2009
Software Availability: Mar-2009

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	16	991	158	**991**	**158**	990	158	16	**820**	**191**	820	191	820	191
401.bzip2	16	813	190	818	189	**817**	**189**	16	**725**	**213**	724	213	726	213
403.gcc	16	613	210	**607**	**212**	607	212	16	558	231	**557**	**231**	557	231
429.mcf	16	**431**	**338**	431	338	431	339	16	427	342	**427**	**342**	428	341
445.gobmk	16	812	207	811	207	**811**	**207**	16	645	260	**646**	**260**	647	259
456.hmmer	16	822	182	**823**	**181**	826	181	16	**570**	**262**	570	262	570	262
458.sjeng	16	982	197	**983**	**197**	987	196	16	**888**	**218**	888	218	888	218
462.libquantum	16	1080	307	1081	307	**1081**	**307**	8	249	666	**249**	**666**	249	666
464.h264ref	16	**976**	**363**	976	363	976	363	16	**925**	**383**	926	382	925	383
471.omnetpp	16	685	146	**685**	**146**	685	146	16	**666**	**150**	667	150	666	150
473.astar	16	713	158	712	158	**713**	**158**	16	625	180	**625**	**180**	624	180
483.xalancbmk	16	432	256	432	256	**432**	**256**	16	411	268	411	269	**411**	**268**

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Submit Notes

```
The config file option 'submit' was used.
Benchmarks bound to a processor using numactl on the submit command.
```

General Notes

```
kernel release 2.6.27.19-5-ppc64.
See flags file for details on following settings.
ulimit -s (stack) set to 1048576.
System configured with libhugetlbfs library for application access to large pages
Large pages reserved as follows by root user:
    echo 1600 > /proc/sys/vm/nr_hugepages
Environment variables set before executing benchmarks.
    export HUGETLB_VERBOSE=0
    export HUGETLB_MORECORE=yes
    export XLFRTEOPTS=intrinthds=1
IBM Post-Link Optimization tool was used for these benchmarks, with options:
  400.perlbench : "-imullX" (instrumentation phase), "-O4 -omullX" (optimization phase)
  401.bzip2 : same as 400.perlbench
  403.gcc : same as 400.perlbench
  456.hmmer : same as 400.perlbench
  458.sjeng : same as 400.perlbench
  483.xalancbmk : same as 400.perlbench
  429.mcf : "-imullX" (instrumentation phase), "-bf -dp -hr -las -pca -RC -RD
            -rmte -si -tlo -A 64 -isf 104 -lu 8 -rt 0.16
          -hrf 0.18 -ihf 40 -sdp 6 -sdpms 128 -shci 65 -si -sidf 45 -omullX" (optimization phase)
  445.gobmk : "-imullX" (instrumentation phase), "-q -O3 -A 32 -omullX" (optimization phase)
  462.libquantum : "-imullX" (instrumentation phase), "-bf -dp -lro -nop -RC -RD -tb -tlo -vro -A 4
```

Continued on next page

General Notes (Continued)

```
          -isf 88 -lu 8 -hrf 0.10 -sdp 4 -lun 27 -omullX" (optimization phase)
473.astar : "-imullX" (instrumentation phase), "-O4 -omullX -see 1" (optimization phase)
464.h264ref : "-O4" (optimization phase)
```

Base Compiler Invocation

C benchmarks:
```
xlc -qlanglvl=extc99
```

C++ benchmarks:
```
xlC
```

Base Portability Flags

400.perlbench: `-DSPEC_CPU_LINUX_PPC`
462.libquantum: `-DSPEC_CPU_LINUX`
464.h264ref: `-qchars=signed`
483.xalancbmk: `-DSPEC_CPU_LINUX`

Base Optimization Flags

C benchmarks:
```
-O5 -qarch=pwr6 -qtune=pwr6 -qalias=noansi -qalloca -lhugetlbfs
```

C++ benchmarks:
```
-O5 -qarch=pwr6 -qtune=pwr6 -qrtti -lsmartheap
```

Base Other Flags

C benchmarks:
```
-qipa=noobject -qipa=threads
```

C++ benchmarks:
```
-qipa=noobject -qipa=threads
```

Peak Compiler Invocation

C benchmarks:
```
xlc -qlanglvl=extc99
```

C++ benchmarks:
```
xlC
```

Peak Portability Flags

400.perlbench: -DSPEC_CPU_LINUX_PPC
403.gcc: -DSPEC_CPU_LP64
462.libquantum: -DSPEC_CPU_LINUX
464.h264ref: -qchars=signed
483.xalancbmk: -DSPEC_CPU_LINUX

Peak Optimization Flags

C benchmarks:

400.perlbench: -Wl,-q -qpdf1(pass 1) -qpdf2(pass 2) -O4 -qarch=pwr6 -qtune=pwr6 -qalias=noansi -lsmartheap

401.bzip2: -Wl,-q -qpdf1(pass 1) -qpdf2(pass 2) -O3 -qarch=pwr6 -qtune=pwr6 -lhugetlbfs

403.gcc: -Wl,-q -qpdf1(pass 1) -qpdf2(pass 2) -O4 -qarch=pwr6 -qtune=pwr6 -qalloca -q64 -lhugetlbfs

429.mcf: -Wl,-q -O5 -qarch=pwr6 -qtune=pwr6 -qnoenablevmx -lhugetlbfs

445.gobmk: -Wl,-q -qpdf1(pass 1) -qpdf2(pass 2) -O4 -qarch=pwr6 -qtune=pwr6 -qnoenablevmx -lhugetlbfs

456.hmmer: -Wl,-q -qpdf1(pass 1) -qpdf2(pass 2) -O5 -qarch=pwr6 -qtune=pwr6 -lhugetlbfs

458.sjeng: -Wl,-q -O5 -qarch=pwr6 -qtune=pwr6 -lhugetlbfs

462.libquantum: -Wl,-q -qpdf1(pass 1) -qpdf2(pass 2) -O5 -qarch=pwr6 -qtune=pwr6 -qnoenablevmx -q64 -lhugetlbfs

464.h264ref: -Wl,-q -qpdf1(pass 1) -qpdf2(pass 2) -O5 -qarch=pwr6 -qtune=pwr6 -q64 -lhugetlbfs

C++ benchmarks:

471.omnetpp: -qpdf1(pass 1) -qpdf2(pass 2) -O4 -qarch=pwr6 -qtune=pwr6 -qrtti -lsmartheap

473.astar: -Wl,-q -qpdf1(pass 1) -qpdf2(pass 2) -O4 -qarch=pwr6 -qtune=pwr6 -qnoenablevmx -lsmartheap

483.xalancbmk: -Wl,-q -O5 -qarch=pwr6 -qtune=pwr6 -lsmartheap

Peak Other Flags

C benchmarks:
```
-qipa=noobject -qipa=threads
```

C++ benchmarks:
```
-qipa=noobject -qipa=threads
```

The flags file that was used to format this result can be browsed at
`http://www.spec.org/cpu2006/flags/IBM-Linux-XL.html`

You can also download the XML flags source by saving the following link:
`http://www.spec.org/cpu2006/flags/IBM-Linux-XL.xml`

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.1.
Report generated on Tue Jul 22 23:38:57 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 12 May 2009.