# SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Bull SAS

NovaScale R410 F2 (Intel Xeon X3440, 2.53 GHz)

SPECfp®2006 = 32.5

SPECfp_base2006 = 31.2

**CPU2006 license:** 20
**Test sponsor:** Bull SAS
**Tested by:** Dell Inc.

**Test date:** Sep-2009
**Hardware Availability:** Dec-2009
**Software Availability:** Jul-2009




## Hardware

| | |
|---|---|
| CPU Name: | Intel Xeon X3440 |
| CPU Characteristics: | Intel Turbo Boost Technology up to 2.93 GHz |
| CPU MHz: | 2533 |
| FPU: | Integrated |
| CPU(s) enabled: | 4 cores, 1 chip, 4 cores/chip, 2 threads/core |
| CPU(s) orderable: | 1 chip |
| Primary Cache: | 32 KB I + 32 KB D on chip per core |
| Secondary Cache: | 256 KB I+D on chip per core |

Continued on next page

## Software

| | |
|---|---|
| Operating System: | Red Hat Enterprise Linux Server release 5.3, Kernel 2.6.18-128.el5 |
| Compiler: | Intel Fortran Compiler and Intel C++ Compiler Professional Edition 11.1 For Linux Build 20090511 Package ID: l_cproc_p_11.1.040, l_cprof_p_11.1.040 |
| Auto Parallel: | Yes |
| File System: | ReiserFS |
| System State: | Run level 3 (multi-user) |

Continued on next page

# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Bull SAS

NovaScale R410 F2 (Intel Xeon X3440, 2.53 GHz)

SPECfp2006 = 32.5

SPECfp_base2006 = 31.2

**CPU2006 license:** 20
**Test sponsor:** Bull SAS
**Tested by:** Dell Inc.

**Test date:** Sep-2009
**Hardware Availability:** Dec-2009
**Software Availability:** Jul-2009

| | |
|---|---|
| L3 Cache: | 8 MB I+D on chip per chip |
| Other Cache: | None |
| Memory: | 8 GB (4 x 2 GB DDR3-1333 DR UDIMM) |
| Disk Subsystem: | 1 x 160 GB 7200 RPM SATA |
| Other Hardware: | None |

| | |
|---|---|
| Base Pointers: | 64-bit |
| Peak Pointers: | 64-bit |
| Other Software: | Binutils 2.18.50.0.7.20080502 |

## Results Table

| Benchmark | Base | | | | | | Peak | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | Seconds | Ratio | Seconds | Ratio | Seconds | Ratio | Seconds | Ratio | Seconds | Ratio | Seconds | Ratio |
| 410.bwaves | 195 | 69.6 | 197 | 69.1 | **196** | **69.4** | 196 | 69.3 | 196 | 69.5 | **196** | **69.4** |
| 416.gamess | 948 | 20.6 | **948** | **20.7** | 947 | 20.7 | **911** | **21.5** | 911 | 21.5 | 909 | 21.5 |
| 433.milc | 221 | 41.6 | 221 | 41.5 | **221** | **41.6** | 221 | 41.5 | **221** | **41.5** | 222 | 41.4 |
| 434.zeusmp | **284** | **32.1** | 284 | 32.1 | 284 | 32.1 | **284** | **32.1** | 284 | 32.1 | 284 | 32.1 |
| 435.gromacs | **369** | **19.4** | 369 | 19.3 | 368 | 19.4 | 375 | 19.0 | 374 | 19.1 | **375** | **19.1** |
| 436.cactusADM | 135 | 88.3 | **137** | **87.4** | 137 | 87.3 | 125 | 95.9 | 125 | 95.9 | **125** | **95.9** |
| 437.leslie3d | 345 | 27.3 | **346** | **27.2** | 346 | 27.2 | 345 | 27.3 | **346** | **27.2** | 346 | 27.2 |
| 444.namd | **480** | **16.7** | 480 | 16.7 | 480 | 16.7 | **480** | **16.7** | 480 | 16.7 | 480 | 16.7 |
| 447.dealII | 372 | 30.8 | **384** | **29.8** | 384 | 29.8 | 359 | 31.9 | **359** | **31.9** | 359 | 31.9 |
| 450.soplex | **343** | **24.3** | 358 | 23.3 | 343 | 24.3 | **343** | **24.3** | 358 | 23.3 | 343 | 24.3 |
| 453.povray | 229 | 23.3 | 222 | 23.9 | **223** | **23.9** | **175** | **30.4** | 175 | 30.4 | 175 | 30.3 |
| 454.calculix | **338** | **24.4** | 338 | 24.4 | 336 | 24.5 | 334 | 24.7 | **335** | **24.6** | 335 | 24.6 |
| 459.GemsFDTD | **317** | **33.4** | 318 | 33.4 | 317 | 33.5 | **302** | **35.1** | 302 | 35.1 | 302 | 35.2 |
| 465.tonto | **482** | **20.4** | 482 | 20.4 | 484 | 20.3 | 392 | 25.1 | 396 | 24.8 | **393** | **25.0** |
| 470.lbm | 298 | 46.1 | **300** | **45.8** | 305 | 45.1 | 298 | 46.1 | **300** | **45.8** | 305 | 45.1 |
| 481.wrf | **316** | **35.3** | 315 | 35.4 | 316 | 35.3 | 317 | 35.3 | 315 | 35.4 | **316** | **35.4** |
| 482.sphinx3 | **533** | **36.6** | 534 | 36.5 | 526 | 37.1 | **533** | **36.6** | 534 | 36.5 | 526 | 37.1 |

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Submit Notes

```
The config file option 'submit' was used.
```

## Operating System Notes

```
'ulimit -s unlimited' was used to set the stacksize to unlimited prior to run
```

## Platform Notes

```
BIOS Settings:
Power Management = Maximum Performance (Default = Active Power Controller)
```

## General Notes

```
OMP_NUM_THREADS set to number of cores
KMP_AFFINITY set to granularity=fine,scatter
KMP_STACKSIZE set to 200M
The Dell PowerEdge R210 (Intel Xeon X3440, 2.53 GHz) and
the Bull NovaScale R410 F2 (Intel Xeon X3440, 2.53 GHz) models are electronically equivalent.
The results have been measured on a Dell PowerEdge R210 (Intel Xeon X3440, 2.53 GHz) model.
```

## Base Compiler Invocation

C benchmarks:
```
icc   -m64
```

C++ benchmarks:
```
icpc  -m64
```

Fortran benchmarks:
```
ifort -m64
```

Benchmarks using both Fortran and C:
```
icc   -m64 ifort -m64
```

## Base Portability Flags

```
410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
437.leslie3d: -DSPEC_CPU_LP64
444.namd: -DSPEC_CPU_LP64
447.dealII: -DSPEC_CPU_LP64
450.soplex: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
470.lbm: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
482.sphinx3: -DSPEC_CPU_LP64
```

## Base Optimization Flags

C benchmarks:
```
-xSSE4.2 -ipo -O3 -no-prec-div -static -opt-prefetch
```

Continued on next page

## Base Optimization Flags (Continued)

C++ benchmarks:
`-xSSE4.2 -ipo -O3 -no-prec-div -static -opt-prefetch`

Fortran benchmarks:
`-xSSE4.2 -ipo -O3 -no-prec-div -static -opt-prefetch -parallel`

Benchmarks using both Fortran and C:
`-xSSE4.2 -ipo -O3 -no-prec-div -static -opt-prefetch -parallel`

## Peak Compiler Invocation

C benchmarks:
`icc -m64`

C++ benchmarks:
`icpc -m64`

Fortran benchmarks:
`ifort -m64`

Benchmarks using both Fortran and C:
`icc -m64 ifort -m64`

## Peak Portability Flags

`Same as Base Portability Flags`

## Peak Optimization Flags

C benchmarks:

433.milc: `-xSSE4.2`(pass 2) `-prof-gen`(pass 1) `-ipo`(pass 2) `-O3`(pass 2) `-no-prec-div`(pass 2) `-static`(pass 2) `-prof-use`(pass 2) `-fno-alias`

470.lbm: `basepeak = yes`

482.sphinx3: `basepeak = yes`

C++ benchmarks:

444.namd: `basepeak = yes`

Continued on next page

## Peak Optimization Flags (Continued)

447.dealII: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2) -unroll2 -ansi-alias -scalar-rep- -opt-prefetch

450.soplex: basepeak = yes

453.povray: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2) -unroll4 -ansi-alias

Fortran benchmarks:

410.bwaves: -xSSE4.2 -ipo -O3 -no-prec-div -static -opt-prefetch -parallel

416.gamess: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2) -unroll2 -Ob0 -ansi-alias -scalar-rep-

434.zeusmp: Same as 410.bwaves

437.leslie3d: basepeak = yes

459.GemsFDTD: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2) -unroll2 -Ob0 -opt-prefetch -parallel

465.tonto: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2) -unroll4 -auto

Benchmarks using both Fortran and C:

435.gromacs: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2) -opt-prefetch -auto-ilp32

436.cactusADM: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2) -unroll2 -opt-prefetch -parallel -auto-ilp32

454.calculix: -xSSE4.2 -ipo -O3 -no-prec-div -static -auto-ilp32

481.wrf: -xSSE4.2 -ipo -O3 -no-prec-div -static -opt-prefetch -parallel -auto-ilp32

The flags file that was used to format this result can be browsed at
http://www.spec.org/cpu2006/flags/Intel-ic11.1-fp-linux64-revA.html

You can also download the XML flags source by saving the following link:
`http://www.spec.org/cpu2006/flags/Intel-ic11.1-fp-linux64-revA.xml`


SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.


For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.1.
Report generated on Wed Jul 23 03:53:13 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 22 December 2009.