



# SPEC® CINT2006 Result

Copyright 2006-2009 Standard Performance Evaluation Corporation

Acer Incorporated

SPECint®2006 = 19.3

Gateway GR160 F1 (Intel Xeon E5502)

SPECint\_base2006 = 17.2

CPU2006 license: 97


Test date: Dec-2009

Test sponsor: Acer Incorporated

Hardware Availability: Jan-2010

Tested by: Acer Incorporated

Software Availability: Feb-2009



## Hardware

CPU Name: Intel Xeon E5502  
 CPU Characteristics:  
 CPU MHz: 1867  
 FPU: Integrated  
 CPU(s) enabled: 4 cores, 2 chips, 2 cores/chip  
 CPU(s) orderable: 1, 2 chips  
 Primary Cache: 32 KB I + 32 KB D on chip per core  
 Secondary Cache: 256 KB I+D on chip per core  
 L3 Cache: 4 MB I+D on chip per chip  
 Other Cache: None  
 Memory: 24 GB (6 x 4 GB DDR3-1333 RDIMM)  
 Disk Subsystem: 300 GB SATA II, 10000 RPM  
 Other Hardware: None

## Software

Operating System: SUSE Linux Enterprise Server 11 (x86\_64)  
 Kernel 2.6.27.19-5  
 Compiler: Intel C++ Compiler Professional 11.0 for Linux  
 Build 20090131 Package ID: l\_cproc\_p\_11.0.080  
 Auto Parallel: Yes  
 File System: ReiserFS  
 System State: Run level 3 (multi-user)  
 Base Pointers: 32-bit  
 Peak Pointers: 32/64-bit  
 Other Software: Microquill SmartHeap V8.1  
 Binutils 2.18.50.0.7.20080502



# SPEC CINT2006 Result

Copyright 2006-2009 Standard Performance Evaluation Corporation

Acer Incorporated

SPECint2006 = 19.3

Gateway GR160 F1 (Intel Xeon E5502)

SPECint\_base2006 = 17.2

CPU2006 license: 97

Test date: Dec-2009

Test sponsor: Acer Incorporated

Hardware Availability: Jan-2010

Tested by: Acer Incorporated

Software Availability: Feb-2009

## Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	730	13.4	<b><u>729</u></b>	<b><u>13.4</u></b>	729	13.4	585	16.7	586	16.7	<b><u>586</u></b>	<b><u>16.7</u></b>
401.bzip2	987	9.78	984	9.81	<b><u>986</u></b>	<b><u>9.79</u></b>	884	10.9	<b><u>882</u></b>	<b><u>10.9</u></b>	879	11.0
403.gcc	522	15.4	<b><u>522</u></b>	<b><u>15.4</u></b>	521	15.4	474	17.0	<b><u>473</u></b>	<b><u>17.0</u></b>	472	17.0
429.mcf	345	26.5	343	26.6	<b><u>343</u></b>	<b><u>26.6</u></b>	347	26.3	354	25.7	<b><u>347</u></b>	<b><u>26.3</u></b>
445.gobmk	<b><u>819</u></b>	<b><u>12.8</u></b>	819	12.8	819	12.8	712	14.7	<b><u>712</u></b>	<b><u>14.7</u></b>	714	14.7
456.hammer	727	12.8	728	12.8	<b><u>727</u></b>	<b><u>12.8</u></b>	<b><u>520</u></b>	<b><u>17.9</u></b>	520	17.9	526	17.8
458.sjeng	875	13.8	<b><u>875</u></b>	<b><u>13.8</u></b>	876	13.8	<b><u>794</u></b>	<b><u>15.2</u></b>	794	15.2	794	15.2
462.libquantum	<b><u>212</u></b>	<b><u>97.8</u></b>	211	98.2	212	97.7	<b><u>212</u></b>	<b><u>97.8</u></b>	211	98.2	212	97.7
464.h264ref	1061	20.9	<b><u>1062</u></b>	<b><u>20.8</u></b>	1062	20.8	<b><u>965</u></b>	<b><u>22.9</u></b>	966	22.9	965	22.9
471.omnetpp	455	13.7	<b><u>456</u></b>	<b><u>13.7</u></b>	456	13.7	400	15.6	<b><u>399</u></b>	<b><u>15.7</u></b>	399	15.7
473.astar	712	9.86	<b><u>718</u></b>	<b><u>9.78</u></b>	720	9.75	620	11.3	<b><u>619</u></b>	<b><u>11.3</u></b>	619	11.3
483.xalanbmk	352	19.6	348	19.8	<b><u>349</u></b>	<b><u>19.8</u></b>	352	19.6	348	19.8	<b><u>349</u></b>	<b><u>19.8</u></b>

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## General Notes

OMP\_NUM\_THREADS set to number of cores  
KMP\_AFFINITY set to granularity=fine,scatter

This result was measured on the Gateway GR160 F1.  
The Acer AR160 F1 and Gateway GR160 F1 are electronically equivalent.

## Base Compiler Invocation

C benchmarks:  
icc

C++ benchmarks:  
icpc

## Base Portability Flags

400.perlbench: -DSPEC\_CPU\_LINUX\_IA32  
462.libquantum: -DSPEC\_CPU\_LINUX  
483.xalanbmk: -DSPEC\_CPU\_LINUX



# SPEC CINT2006 Result

Copyright 2006-2009 Standard Performance Evaluation Corporation

Acer Incorporated

SPECint2006 = 19.3

Gateway GR160 F1 (Intel Xeon E5502)

SPECint\_base2006 = 17.2

CPU2006 license: 97

Test date: Dec-2009

Test sponsor: Acer Incorporated

Hardware Availability: Jan-2010

Tested by: Acer Incorporated

Software Availability: Feb-2009

## Base Optimization Flags

C benchmarks:

-xSSE4.2 -ipo -O3 -no-prec-div -static -parallel  
-par-runtime-control -opt-prefetch

C++ benchmarks:

-xSSE4.2 -ipo -O3 -no-prec-div -opt-prefetch -Wl,-z,muldefs  
-L/spec/cpu2006.1.1/lib -lsmartheap

## Base Other Flags

C benchmarks:

403.gcc: -Dalloca=\_alloca

## Peak Compiler Invocation

C benchmarks (except as noted below):

icc

401.bzip2: /opt/intel/Compiler/11.0/080/bin/intel64/icc

456.hmmer: /opt/intel/Compiler/11.0/080/bin/intel64/icc

458.sjeng: /opt/intel/Compiler/11.0/080/bin/intel64/icc

C++ benchmarks (except as noted below):

icpc

473.astar: /opt/intel/Compiler/11.0/080/bin/intel64/icpc

## Peak Portability Flags

400.perlbench: -DSPEC\_CPU\_LINUX\_IA32

401.bzip2: -DSPEC\_CPU\_LP64

456.hmmer: -DSPEC\_CPU\_LP64

458.sjeng: -DSPEC\_CPU\_LP64

462.libquantum: -DSPEC\_CPU\_LINUX

473.astar: -DSPEC\_CPU\_LP64

483.xalancbmk: -DSPEC\_CPU\_LINUX



# SPEC CINT2006 Result

Copyright 2006-2009 Standard Performance Evaluation Corporation

**Acer Incorporated**

**SPECint2006 = 19.3**

**Gateway GR160 F1 (Intel Xeon E5502)**

**SPECint\_base2006 = 17.2**

**CPU2006 license:** 97

**Test date:** Dec-2009

**Test sponsor:** Acer Incorporated

**Hardware Availability:** Jan-2010

**Tested by:** Acer Incorporated

**Software Availability:** Feb-2009

## Peak Optimization Flags

C benchmarks:

400.perlbench: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)  
 -O3(pass 2) -no-prec-div(pass 2) -static(pass 2)  
 -prof-use(pass 2) -ansi-alias -opt-prefetch

401.bzp2: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)  
 -O3(pass 2) -no-prec-div(pass 2) -static(pass 2)  
 -prof-use(pass 2) -auto-ilp32 -opt-prefetch -ansi-alias

403.gcc: -xSSE4.2 -ipo -O3 -no-prec-div -static -inline-alloc  
 -opt-malloc-options=3

429.mcf: -xSSE4.2 -ipo -O3 -no-prec-div -static -opt-prefetch

445.gobmk: -xSSE4.2(pass 2) -prof-gen(pass 1) -prof-use(pass 2) -O2  
 -ipo -no-prec-div -ansi-alias

456.hmmer: -xSSE4.2 -ipo -O3 -no-prec-div -static -unroll2  
 -ansi-alias -auto-ilp32

458.sjeng: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)  
 -O3(pass 2) -no-prec-div(pass 2) -static(pass 2)  
 -prof-use(pass 2) -unroll4 -auto-ilp32

462.libquantum: basepeak = yes

464.h264ref: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)  
 -O3(pass 2) -no-prec-div(pass 2) -static(pass 2)  
 -prof-use(pass 2) -unroll2 -ansi-alias

C++ benchmarks:

471.omnetpp: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)  
 -O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)  
 -ansi-alias -opt-ra-region-strategy=block -Wl,-z,muldefs  
 -L/spec/cpu2006.1.1/lib -lsmartheap

473.astar: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)  
 -O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)  
 -ansi-alias -opt-ra-region-strategy=routine -auto-ilp32  
 -Wl,-z,muldefs -L/spec/cpu2006.1.1/lib -lsmartheap64

483.xalancbmk: basepeak = yes



# SPEC CINT2006 Result

Copyright 2006-2009 Standard Performance Evaluation Corporation

Acer Incorporated	SPECint2006 =	19.3
Gateway GR160 F1 (Intel Xeon E5502)	SPECint_base2006 =	17.2

<b>CPU2006 license:</b> 97	<b>Test date:</b> Dec-2009
<b>Test sponsor:</b> Acer Incorporated	<b>Hardware Availability:</b> Jan-2010
<b>Tested by:</b> Acer Incorporated	<b>Software Availability:</b> Feb-2009

## Peak Other Flags

Same as Base Other Flags

The flags file that was used to format this result can be browsed at  
<http://www.spec.org/cpu2006/flags/Intel-ic11.0-int-linux64-revE.20100216.html>

You can also download the XML flags source by saving the following link:  
<http://www.spec.org/cpu2006/flags/Intel-ic11.0-int-linux64-revE.20100216.xml>

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.1.  
Report generated on Tue Feb 16 12:34:03 2010 by SPEC CPU2006 PS/PDF formatter v6323.