



# SPEC® CINT2006 Result

Copyright 2006-2009 Standard Performance Evaluation Corporation

## Acer Incorporated

**SPECint®2006 = 36.2**

Acer AW1000-AW170 F1 (Intel Xeon X5570)

**SPECint\_base2006 = 32.0**

CPU2006 license: 97


Test date: Aug-2009

Test sponsor: Acer Incorporated

Hardware Availability: Jan-2010

Tested by: Acer Incorporated

Software Availability: Feb-2009



### Hardware

CPU Name: Intel Xeon X5570  
 CPU Characteristics: Intel Turbo Boost Technology up to 3.33 GHz  
 CPU MHz: 2933  
 FPU: Integrated  
 CPU(s) enabled: 8 cores, 2 chips, 4 cores/chip, 2 threads/core  
 CPU(s) orderable: 1, 2 chips  
 Primary Cache: 32 KB I + 32 KB D on chip per core  
 Secondary Cache: 256 KB I+D on chip per core  
 L3 Cache: 8 MB I+D on chip per chip  
 Other Cache: None  
 Memory: 24 GB (6 x 4 GB DDR3-1333 RDIMM)  
 Disk Subsystem: 1 x 750 GB SATA II, 7200 RPM  
 Other Hardware: None

### Software

Operating System: SUSE Linux Enterprise Server 11 (x86\_64)  
 Kernel 2.6.27.19-5  
 Compiler: Intel C++ Compiler Professional 11.0 for Linux  
 Build 20090131 Package ID: l\_cproc\_p\_11.0.080  
 Auto Parallel: Yes  
 File System: ReiserFS  
 System State: Run level 3 (multi-user)  
 Base Pointers: 32-bit  
 Peak Pointers: 32/64-bit  
 Other Software: Microquill SmartHeap V8.1  
 Binutils 2.18.50.0.7.20080502



# SPEC CINT2006 Result

Copyright 2006-2009 Standard Performance Evaluation Corporation

Acer Incorporated

SPECint2006 = 36.2

Acer AW1000-AW170 F1 (Intel Xeon X5570)

SPECint\_base2006 = 32.0

CPU2006 license: 97

Test date: Aug-2009

Test sponsor: Acer Incorporated

Hardware Availability: Jan-2010

Tested by: Acer Incorporated

Software Availability: Feb-2009

## Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	<b><u>406</u></b>	<b><u>24.1</u></b>	404	24.2	407	24.0	<b><u>321</u></b>	<b><u>30.4</u></b>	320	30.5	<b><u>321</u></b>	<b><u>30.4</u></b>
401.bzip2	<b><u>546</u></b>	<b><u>17.7</u></b>	543	17.8	549	17.6	<b><u>481</u></b>	<b><u>20.1</u></b>	481	20.1	482	20.0
403.gcc	302	26.6	303	26.6	<b><u>303</u></b>	<b><u>26.6</u></b>	<b><u>268</u></b>	<b><u>30.0</u></b>	268	30.0	268	30.0
429.mcf	195	46.7	<b><u>195</u></b>	<b><u>46.9</u></b>	191	47.9	190	48.1	193	47.3	<b><u>191</u></b>	<b><u>47.7</u></b>
445.gobmk	<b><u>462</u></b>	<b><u>22.7</u></b>	460	22.8	462	22.7	396	26.5	395	26.6	<b><u>395</u></b>	<b><u>26.6</u></b>
456.hammer	409	22.8	<b><u>406</u></b>	<b><u>23.0</u></b>	404	23.1	291	32.1	291	32.0	<b><u>291</u></b>	<b><u>32.1</u></b>
458.sjeng	495	24.4	<b><u>489</u></b>	<b><u>24.7</u></b>	489	24.7	448	27.0	<b><u>447</u></b>	<b><u>27.0</u></b>	447	27.1
462.libquantum	<b><u>67.6</u></b>	<b><u>306</u></b>	67.6	306	67.2	308	<b><u>67.6</u></b>	<b><u>306</u></b>	67.6	306	67.2	308
464.h264ref	611	36.2	608	36.4	<b><u>611</u></b>	<b><u>36.2</u></b>	<b><u>540</u></b>	<b><u>41.0</u></b>	539	41.0	540	41.0
471.omnetpp	267	23.4	269	23.3	<b><u>268</u></b>	<b><u>23.3</u></b>	236	26.4	<b><u>237</u></b>	<b><u>26.4</u></b>	237	26.3
473.astar	388	18.1	388	18.1	<b><u>388</u></b>	<b><u>18.1</u></b>	339	20.7	338	20.7	<b><u>338</u></b>	<b><u>20.7</u></b>
483.xalancbmk	191	36.1	191	36.2	<b><u>191</u></b>	<b><u>36.1</u></b>	191	36.1	191	36.2	<b><u>191</u></b>	<b><u>36.1</u></b>

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Operating System Notes

'ulimit -s unlimited' was set for stacksize unlimited

## General Notes

OMP\_NUM\_THREADS set to number of cores  
KMP\_AFFINITY set to granularity=fine,scatter

This result was measured on the Gateway GW1000-GW170 F1 .  
The Acer AW1000-AW170 F1 and Gateway GW1000-GW170 F1 are electronically equivalent.

## Base Compiler Invocation

C benchmarks:

icc

C++ benchmarks:

icpc

## Base Portability Flags

400.perlbench: -DSPEC\_CPU\_LINUX\_IA32  
462.libquantum: -DSPEC\_CPU\_LINUX

Continued on next page



# SPEC CINT2006 Result

Copyright 2006-2009 Standard Performance Evaluation Corporation

Acer Incorporated

SPECint2006 = 36.2

Acer AW1000-AW170 F1 (Intel Xeon X5570)

SPECint\_base2006 = 32.0

CPU2006 license: 97

Test date: Aug-2009

Test sponsor: Acer Incorporated

Hardware Availability: Jan-2010

Tested by: Acer Incorporated

Software Availability: Feb-2009

## Base Portability Flags (Continued)

483.xalanbmk: -DSPEC\_CPU\_LINUX

## Base Optimization Flags

C benchmarks:

-xSSE4.2 -ipo -O3 -no-prec-div -static -parallel  
-par-runtime-control -opt-prefetch

C++ benchmarks:

-xSSE4.2 -ipo -O3 -no-prec-div -opt-prefetch -Wl,-z,muldefs  
-L/spec/cpu2006.1.1/lib -lsmartheap

## Base Other Flags

C benchmarks:

403.gcc: -Dalloca=\_alloca

## Peak Compiler Invocation

C benchmarks (except as noted below):

icc

401.bzip2: /opt/intel/Compiler/11.0/080/bin/intel64/icc

456.hmmer: /opt/intel/Compiler/11.0/080/bin/intel64/icc

458.sjeng: /opt/intel/Compiler/11.0/080/bin/intel64/icc

C++ benchmarks (except as noted below):

icpc

473.astar: /opt/intel/Compiler/11.0/080/bin/intel64/icpc

## Peak Portability Flags

400.perlbench: -DSPEC\_CPU\_LINUX\_IA32

401.bzip2: -DSPEC\_CPU\_LP64

456.hmmer: -DSPEC\_CPU\_LP64

458.sjeng: -DSPEC\_CPU\_LP64

462.libquantum: -DSPEC\_CPU\_LINUX

Continued on next page

Standard Performance Evaluation Corporation

info@spec.org

http://www.spec.org/

Page 3



# SPEC CINT2006 Result

Copyright 2006-2009 Standard Performance Evaluation Corporation

Acer Incorporated

SPECint2006 = 36.2

Acer AW1000-AW170 F1 (Intel Xeon X5570)

SPECint\_base2006 = 32.0

CPU2006 license: 97

Test date: Aug-2009

Test sponsor: Acer Incorporated

Hardware Availability: Jan-2010

Tested by: Acer Incorporated

Software Availability: Feb-2009

## Peak Portability Flags (Continued)

473.astar: -DSPEC\_CPU\_LP64  
483.xalancbmk: -DSPEC\_CPU\_LINUX

## Peak Optimization Flags

C benchmarks:

400.perlbench: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)  
-O3(pass 2) -no-prec-div(pass 2) -static(pass 2)  
-prof-use(pass 2) -ansi-alias -opt-prefetch

401.bzip2: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)  
-O3(pass 2) -no-prec-div(pass 2) -static(pass 2)  
-prof-use(pass 2) -auto-ilp32 -opt-prefetch -ansi-alias

403.gcc: -xSSE4.2 -ipo -O3 -no-prec-div -static -inline-calloc  
-opt-malloc-options=3

429.mcf: -xSSE4.2 -ipo -O3 -no-prec-div -static -opt-prefetch

445.gobmk: -xSSE4.2(pass 2) -prof-gen(pass 1) -prof-use(pass 2) -O2  
-ipo -no-prec-div -ansi-alias

456.hmmer: -xSSE4.2 -ipo -O3 -no-prec-div -static -unroll2  
-ansi-alias -auto-ilp32

458.sjeng: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)  
-O3(pass 2) -no-prec-div(pass 2) -static(pass 2)  
-prof-use(pass 2) -unroll4 -auto-ilp32

462.libquantum: basepeak = yes

464.h264ref: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)  
-O3(pass 2) -no-prec-div(pass 2) -static(pass 2)  
-prof-use(pass 2) -unroll2 -ansi-alias

C++ benchmarks:

471.omnetpp: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)  
-O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)  
-ansi-alias -opt-ra-region-strategy=block -Wl,-z,muldefs  
-L/spec/cpu2006.1.1/lib -lsmartheap

473.astar: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)  
-O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)  
-ansi-alias -opt-ra-region-strategy=routine -auto-ilp32  
-Wl,-z,muldefs -L/spec/cpu2006.1.1/lib -lsmartheap64

Continued on next page



# SPEC CINT2006 Result

Copyright 2006-2009 Standard Performance Evaluation Corporation

**Acer Incorporated**

**SPECint2006 = 36.2**

**Acer AW1000-AW170 F1 (Intel Xeon X5570)**

**SPECint\_base2006 = 32.0**

**CPU2006 license:** 97

**Test sponsor:** Acer Incorporated

**Tested by:** Acer Incorporated

**Test date:** Aug-2009

**Hardware Availability:** Jan-2010

**Software Availability:** Feb-2009

## Peak Optimization Flags (Continued)

483.xalanbmk: basepeak = yes

## Peak Other Flags

Same as Base Other Flags

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic11.0-int-linux64-revH.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/Intel-ic11.0-int-linux64-revH.xml>

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.1.  
Report generated on Tue Feb 16 14:48:14 2010 by SPEC CPU2006 PS/PDF formatter v6323.