# SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Fujitsu

## CELSIUS W380, Intel Core i5-670

SPECint®2006 = 33.5

SPECint_base2006 = 30.5

**CPU2006 license:** 19
**Test sponsor:** Fujitsu
**Tested by:** Fujitsu

**Test date:** Feb-2010
**Hardware Availability:** Jan-2010
**Software Availability:** Oct-2009




## Hardware

| | |
|---|---|
| CPU Name: | Intel Core i5-670 |
| CPU Characteristics: | Intel Turbo Boost Technology up to 3.73 GHz |
| CPU MHz: | 3467 |
| FPU: | Integrated |
| CPU(s) enabled: | 2 cores, 1 chip, 2 cores/chip |
| CPU(s) orderable: | 1 chip |
| Primary Cache: | 32 KB I + 32 KB D on chip per core |
| Secondary Cache: | 256 KB I+D on chip per core |
| L3 Cache: | 4 MB I+D on chip per chip |
| Other Cache: | None |
| Memory: | 8 GB (2x4 GB PC3-10600U, 2 rank, CL9) |
| Disk Subsystem: | 1 x SATA II, 400 GB, 7200 rpm |
| Other Hardware: | None |

## Software

| | |
|---|---|
| Operating System: | SUSE Linux Enterprise Server 11 (x86_64), kernel 2.6.27.19-5-default |
| Compiler: | Intel C++ Compiler for IA32 and Intel 64, Version 11.1<br>Build 20091012 Package ID: l_cproc_p_11.1.059 |
| Auto Parallel: | Yes |
| File System: | ext3 |
| System State: | Multi-User Run Level 3 |
| Base Pointers: | 64-bit |
| Peak Pointers: | 32/64-bit |
| Other Software: | Microquill SmartHeap V8.1<br>Binutils 2.18.50.0.7.20080502 |

# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Fujitsu

## CELSIUS W380, Intel Core i5-670

SPECint2006 = 33.5

SPECint_base2006 = 30.5

**CPU2006 license:** 19
**Test sponsor:** Fujitsu
**Tested by:** Fujitsu

**Test date:** Feb-2010
**Hardware Availability:** Jan-2010
**Software Availability:** Oct-2009

## Results Table

| Benchmark | Base | | | | | | Peak | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | Seconds | Ratio | Seconds | Ratio | Seconds | Ratio | Seconds | Ratio | Seconds | Ratio | Seconds | Ratio |
| 400.perlbench | 401 | 24.4 | 400 | 24.4 | **400** | **24.4** | 330 | 29.6 | 331 | 29.5 | **330** | **29.6** |
| 401.bzip2 | 509 | 18.9 | **510** | **18.9** | 513 | 18.8 | 508 | 19.0 | **507** | **19.0** | 507 | 19.0 |
| 403.gcc | 383 | 21.0 | **384** | **21.0** | 385 | 20.9 | **331** | **24.3** | 331 | 24.3 | 331 | 24.3 |
| 429.mcf | 312 | 29.2 | **314** | **29.0** | 314 | 29.0 | 250 | 36.5 | 248 | 36.8 | **249** | **36.6** |
| 445.gobmk | 427 | 24.6 | **427** | **24.6** | 427 | 24.6 | 388 | 27.0 | 389 | 27.0 | **389** | **27.0** |
| 456.hmmer | 185 | 50.5 | **185** | **50.5** | 184 | 50.6 | **174** | **53.6** | 174 | 53.6 | 174 | 53.6 |
| 458.sjeng | 455 | 26.6 | 454 | 26.6 | **455** | **26.6** | 437 | 27.7 | 438 | 27.6 | **438** | **27.7** |
| 462.libquantum | 110 | 188 | 110 | 188 | **110** | **188** | 109 | 189 | 109 | 189 | **109** | **189** |
| 464.h264ref | 572 | 38.7 | 574 | 38.6 | **573** | **38.6** | 519 | 42.7 | 518 | 42.7 | **518** | **42.7** |
| 471.omnetpp | 390 | 16.0 | **391** | **16.0** | 393 | 15.9 | 309 | 20.2 | **308** | **20.3** | 308 | 20.3 |
| 473.astar | 396 | 17.7 | **397** | **17.7** | 397 | 17.7 | 391 | 18.0 | 391 | 18.0 | **391** | **18.0** |
| 483.xalancbmk | **206** | **33.6** | 205 | 33.6 | 206 | 33.5 | **206** | **33.6** | 205 | 33.6 | 206 | 33.5 |

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Operating System Notes

'ulimit -s unlimited' was used to set the stacksize to unlimited prior to run

## General Notes

OMP_NUM_THREADS set to number of cores
KMP_AFFINITY set to granularity=fine,scatter

## Base Compiler Invocation

C benchmarks:
icc -m64

C++ benchmarks:
icpc -m64

## Base Portability Flags

400.perlbench: -DSPEC_CPU_LP64 -DSPEC_CPU_LINUX_X64
401.bzip2: -DSPEC_CPU_LP64
403.gcc: -DSPEC_CPU_LP64
429.mcf: -DSPEC_CPU_LP64
445.gobmk: -DSPEC_CPU_LP64

Continued on next page

## Base Portability Flags (Continued)

456.hmmer: -DSPEC_CPU_LP64
458.sjeng: -DSPEC_CPU_LP64
462.libquantum: -DSPEC_CPU_LP64 -DSPEC_CPU_LINUX
464.h264ref: -DSPEC_CPU_LP64
471.omnetpp: -DSPEC_CPU_LP64
473.astar: -DSPEC_CPU_LP64
483.xalancbmk: -DSPEC_CPU_LP64 -DSPEC_CPU_LINUX

## Base Optimization Flags

C benchmarks:
-xSSE4.2 -ipo -O3 -no-prec-div -static -parallel
-par-runtime-control -opt-prefetch

C++ benchmarks:
-xSSE4.2 -ipo -O3 -no-prec-div -opt-prefetch -Wl,-z,muldefs
-L/home/cmplr/usr3/alrahate/cpu2006.1.1.ic11.1/libic11.1-64bit -lsmartheap64

## Base Other Flags

C benchmarks:

403.gcc: -Dalloca=_alloca

## Peak Compiler Invocation

C benchmarks (except as noted below):
icc -m64

400.perlbench: icc -m32

429.mcf: icc -m32

445.gobmk: icc -m32

464.h264ref: icc -m32

C++ benchmarks (except as noted below):
icpc -m64

471.omnetpp: icpc -m32

## Peak Portability Flags

400.perlbench: -DSPEC_CPU_LINUX_X64
401.bzip2: -DSPEC_CPU_LP64
403.gcc: -DSPEC_CPU_LP64
456.hmmer: -DSPEC_CPU_LP64
458.sjeng: -DSPEC_CPU_LP64
462.libquantum: -DSPEC_CPU_LP64 -DSPEC_CPU_LINUX
473.astar: -DSPEC_CPU_LP64
483.xalancbmk: -DSPEC_CPU_LP64 -DSPEC_CPU_LINUX

## Peak Optimization Flags

C benchmarks:

400.perlbench: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)
-O3(pass 2) -no-prec-div(pass 2) -static(pass 2)
-prof-use(pass 2) -ansi-alias -opt-prefetch

401.bzip2: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)
-O3(pass 2) -no-prec-div -static(pass 2) -prof-use(pass 2)
-auto-ilp32 -opt-prefetch -ansi-alias

403.gcc: -xSSE4.2 -ipo -O3 -no-prec-div -static -inline-calloc
-opt-malloc-options=3 -auto-ilp32

429.mcf: -xSSE4.2 -ipo -O3 -no-prec-div -static -opt-prefetch

445.gobmk: -xSSE4.2(pass 2) -prof-gen(pass 1) -prof-use(pass 2) -O2
-ipo -no-prec-div -ansi-alias

456.hmmer: -xSSE4.2 -ipo -O3 -no-prec-div -static -unroll2
-ansi-alias -auto-ilp32

458.sjeng: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)
-O3(pass 2) -no-prec-div(pass 2) -static(pass 2)
-prof-use(pass 2) -unroll4

462.libquantum: -xSSE4.2 -ipo -O3 -no-prec-div -static -parallel
-par-runtime-control -opt-prefetch
-par-schedule-static=32768 -ansi-alias

464.h264ref: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)
-O3(pass 2) -no-prec-div(pass 2) -static(pass 2)
-prof-use(pass 2) -unroll2 -ansi-alias

C++ benchmarks:

471.omnetpp: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)
-O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)
-ansi-alias -opt-ra-region-strategy=block -Wl,-z,muldefs

Continued on next page

## Peak Optimization Flags (Continued)

471.omnetpp (continued):
-L/home/cmplr/usr3/alrahate/cpu2006.1.1.ic11.1/libic11.1-32bit -lsmartheap

473.astar: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)
-O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)
-ansi-alias -opt-ra-region-strategy=routine -Wl,-z,muldefs
-L/home/cmplr/usr3/alrahate/cpu2006.1.1.ic11.1/libic11.1-64bit -lsmartheap64

483.xalancbmk: basepeak = yes

## Peak Other Flags

C benchmarks:

403.gcc: -Dalloca=_alloca

The flags file that was used to format this result can be browsed at
http://www.spec.org/cpu2006/flags/Intel-ic11.1-linux64-revD.20100119.html

You can also download the XML flags source by saving the following link:
http://www.spec.org/cpu2006/flags/Intel-ic11.1-linux64-revD.20100119.xml


SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.


For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.1.
Report generated on Wed Jul 23 06:00:47 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 3 March 2010.