



# SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Acer Incorporated

**SPECint®2006 = 29.1**

Gateway GT310 F1 (Intel Xeon X3430)

**SPECint\_base2006 = 27.3**

CPU2006 license: 97


**Test date:** Mar-2010

**Test sponsor:** Acer Incorporated

**Hardware Availability:** Mar-2010

**Tested by:** Acer Incorporated

**Software Availability:** Jan-2010



## Hardware

CPU Name: Intel Xeon X3430  
CPU Characteristics: Intel Turbo Boost Technology up to 2.80 GHz  
CPU MHz: 2400  
FPU: Integrated  
CPU(s) enabled: 4 cores, 1 chip, 4 cores/chip  
CPU(s) orderable: 1 chip  
Primary Cache: 32 KB I + 32 KB D on chip per core  
Secondary Cache: 256 KB I+D on chip per core  
L3 Cache: 8 MB I+D on chip per chip  
Other Cache: None  
Memory: 8 GB (4 x 2048 MB Registered DDR3-1333)  
Disk Subsystem: 1 x 1000 GB 7200RPM SATA HDD  
Other Hardware: None

## Software

Operating System: SUSE Linux Enterprise Sserver 11 (x86\_64)  
Compiler: Kernel 2.6.27.19-5  
Auto Parallel: Intel C++ Professional Compiler for IA32 and  
File System: Intel 64, Version 11.1  
System State: Build 20091130 Package ID: l\_cproc\_p\_11.1.064  
Base Pointers: Yes  
Peak Pointers: ReiserFS  
Other Software: System State: Multi-user, level 3  
Base Pointers: 32-bit  
Peak Pointers: 32/64-bit  
Other Software: Microquill SmartHeap V8.1  
Binutils 2.18.50.0.7.20080502



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Acer Incorporated

**SPECint2006 = 29.1**

Gateway GT310 F1 (Intel Xeon X3430)

**SPECint\_base2006 = 27.3**

CPU2006 license: 97

Test date: Mar-2010

Test sponsor: Acer Incorporated

Hardware Availability: Mar-2010

Tested by: Acer Incorporated

Software Availability: Jan-2010

## Results Table

Benchmark	Base						Peak					
	Seconds	Ratio										
400.perlbench	<b>469</b>	<b>20.8</b>	469	20.8	476	20.5	<b>408</b>	<b>24.0</b>	435	22.5	406	24.1
401.bzip2	661	14.6	663	14.5	<b>663</b>	<b>14.6</b>	<b>662</b>	<b>14.6</b>	665	14.5	657	14.7
403.gcc	383	21.0	<b>383</b>	<b>21.0</b>	384	21.0	350	23.0	354	22.7	<b>352</b>	<b>22.8</b>
429.mcf	253	36.1	254	35.9	<b>253</b>	<b>36.0</b>	226	40.3	<b>225</b>	<b>40.5</b>	224	40.7
445.gobmk	<b>532</b>	<b>19.7</b>	532	19.7	535	19.6	<b>513</b>	<b>20.4</b>	519	20.2	511	20.5
456.hmmer	242	38.6	<b>243</b>	<b>38.5</b>	244	38.2	<b>233</b>	<b>40.1</b>	233	40.1	234	39.9
458.sjeng	<b>564</b>	<b>21.5</b>	563	21.5	570	21.2	542	22.3	<b>546</b>	<b>22.2</b>	547	22.1
462.libquantum	122	171	120	173	<b>121</b>	<b>172</b>	121	171	121	172	<b>121</b>	<b>171</b>
464.h264ref	747	29.6	750	29.5	<b>749</b>	<b>29.5</b>	699	31.7	690	32.1	<b>690</b>	<b>32.1</b>
471.omnetpp	322	19.4	<b>324</b>	<b>19.3</b>	324	19.3	265	23.6	265	23.6	<b>265</b>	<b>23.6</b>
473.astar	456	15.4	470	14.9	<b>458</b>	<b>15.3</b>	467	15.0	<b>442</b>	<b>15.9</b>	439	16.0
483.xalancbmk	228	30.3	<b>228</b>	<b>30.3</b>	228	30.3	223	31.0	224	30.8	<b>223</b>	<b>30.9</b>

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Operating System Notes

'ulimit -s unlimited' was set for stacksize unlimited

## General Notes

OMP\_NUM\_THREADS set to number of cores

KMP\_AFFINITY set to granularity=fine,scatter

This result was measured on the Gateway GT310 F1.

These 4 systems are electronically equivalent:

Acer AR320 F1, Acer AT310 F1, Gateway GR320 F1, and Gateway GT310 F1.

## Base Compiler Invocation

C benchmarks:

icc -m64

C++ benchmarks:

icpc -m64

## Base Portability Flags

400.perlbench: -DSPEC\_CPU\_LP64 -DSPEC\_CPU\_LINUX\_X64

401.bzip2: -DSPEC\_CPU\_LP64

Continued on next page



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Acer Incorporated	<b>SPECint2006 =</b>	<b>29.1</b>
Gateway GT310 F1 (Intel Xeon X3430)	<b>SPECint_base2006 =</b>	<b>27.3</b>
<b>CPU2006 license:</b> 97	<b>Test date:</b>	Mar-2010
<b>Test sponsor:</b> Acer Incorporated	<b>Hardware Availability:</b>	Mar-2010
<b>Tested by:</b> Acer Incorporated	<b>Software Availability:</b>	Jan-2010

## Base Portability Flags (Continued)

```
403.gcc: -DSPEC_CPU_LP64
429.mcf: -DSPEC_CPU_LP64
445.gobmk: -DSPEC_CPU_LP64
456.hammer: -DSPEC_CPU_LP64
458.sjeng: -DSPEC_CPU_LP64
462.libquantum: -DSPEC_CPU_LP64 -DSPEC_CPU_LINUX
464.h264ref: -DSPEC_CPU_LP64
471.omnetpp: -DSPEC_CPU_LP64
473.astar: -DSPEC_CPU_LP64
483.xalancbmk: -DSPEC_CPU_LP64 -DSPEC_CPU_LINUX
```

## Base Optimization Flags

C benchmarks:

```
-xSSE4.2 -ipo -O3 -no-prec-div -static -parallel -opt-prefetch
```

C++ benchmarks:

```
-xSSE4.2 -ipo -O3 -no-prec-div -opt-prefetch -Wl,-z,muldefs
-L/home/cmplr/usr3/alrahate/cpu2006.1.1.ic11.1/libic11.1-64bit -lsmartheap64
```

## Base Other Flags

C benchmarks:

```
403.gcc: -Dalloca=_alloca
```

## Peak Compiler Invocation

C benchmarks (except as noted below):

```
icc -m64
```

```
400.perlbench: icc -m32
```

```
429.mcf: icc -m32
```

```
445.gobmk: icc -m32
```

```
464.h264ref: icc -m32
```

C++ benchmarks (except as noted below):

```
icpc -m32
```

```
473.astar: icpc -m64
```



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Acer Incorporated

**SPECint2006 = 29.1**

Gateway GT310 F1 (Intel Xeon X3430)

**SPECint\_base2006 = 27.3**

CPU2006 license: 97

Test date: Mar-2010

Test sponsor: Acer Incorporated

Hardware Availability: Mar-2010

Tested by: Acer Incorporated

Software Availability: Jan-2010

## Peak Portability Flags

```

400.perlbench: -DSPEC_CPU_LINUX_IA32
 401.bzip2: -DSPEC_CPU_LP64
  403.gcc: -DSPEC_CPU_LP64
 456.hmmer: -DSPEC_CPU_LP64
  458.sjeng: -DSPEC_CPU_LP64
462.libquantum: -DSPEC_CPU_LP64 -DSPEC_CPU_LINUX
 473.astar: -DSPEC_CPU_LP64
483.xalancbmk: -DSPEC_CPU_LINUX

```

## Peak Optimization Flags

C benchmarks:

```

400.perlbench: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)
  -O3(pass 2) -no-prec-div(pass 2) -static(pass 2)
  -prof-use(pass 2) -ansi-alias -opt-prefetch

401.bzip2: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)
  -O3(pass 2) -no-prec-div -static(pass 2) -prof-use(pass 2)
  -auto-ilp32 -opt-prefetch -ansi-alias

403.gcc: -xSSE4.2 -ipo -O3 -no-prec-div -static -inline-calloc
  -opt-malloc-options=3 -auto-ilp32

429.mcf: -xSSE4.2 -ipo -O3 -no-prec-div -static -opt-prefetch

445.gobmk: -xSSE4.2(pass 2) -prof-gen(pass 1) -prof-use(pass 2) -O2
  -ipo -no-prec-div -ansi-alias

456.hmmer: -xSSE4.2 -ipo -O3 -no-prec-div -static -unroll12
  -ansi-alias -auto-ilp32

458.sjeng: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)
  -O3(pass 2) -no-prec-div(pass 2) -static(pass 2)
  -prof-use(pass 2) -unroll4

462.libquantum: -xSSE4.2 -ipo -O3 -no-prec-div -static -parallel
  -opt-prefetch -par-schedule-static=32768 -ansi-alias

464.h264ref: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)
  -O3(pass 2) -no-prec-div(pass 2) -static(pass 2)
  -prof-use(pass 2) -unroll12 -ansi-alias

```

C++ benchmarks:

```

471.omnetpp: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)
  -O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)
  -ansi-alias -opt-ra-region-strategy=block -Wl,-z,muldefs
  -L/home/cmplr/usr3/alrahate/cpu2006.1.1.ic11.1/libic11.1-32bit -lsmartheap

```

Continued on next page



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Acer Incorporated

**SPECint2006 = 29.1**

Gateway GT310 F1 (Intel Xeon X3430)

**SPECint\_base2006 = 27.3**

CPU2006 license: 97

**Test date:** Mar-2010

Test sponsor: Acer Incorporated

**Hardware Availability:** Mar-2010

Tested by: Acer Incorporated

**Software Availability:** Jan-2010

## Peak Optimization Flags (Continued)

```
473.astar: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)
           -O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)
           -ansi-alias -opt-ra-region-strategy=routine -Wl,-z,muldefs
           -L/home/cmplr/usr3/alrahate/cpu2006.1.1.ic11.1/libic11.1-64bit -lsmartheap64
```

```
483.xalancbmk: -xSSE4.2 -ipo -O3 -no-prec-div -opt-prefetch
                -Wl,-z,muldefs
                -L/home/cmplr/usr3/alrahate/cpu2006.1.1.ic11.1/libic11.1-32bit -lsmartheap
```

## Peak Other Flags

C benchmarks:

```
403.gcc: -Dalloca=_alloca
```

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic11.1-linux64-revE.20100316.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/Intel-ic11.1-linux64-revE.20100316.xml>

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.1.

Report generated on Wed Jul 23 05:28:11 2014 by SPEC CPU2006 PS/PDF formatter v6932.

Originally published on 30 March 2010.