



# SPEC<sup>®</sup> CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## ASUSTeK Computer Inc.

### SPECfp<sup>®</sup>\_rate2006 = 313

ASUS RS500A-E6 (KGNE-D16) server system  
(2.2 GHz AMD Opteron 6174)

### SPECfp\_rate\_base2006 = 290

CPU2006 license: 9016


Test date: Oct-2010

Test sponsor: ASUSTeK Computer Inc.

Hardware Availability: Aug-2010

Tested by: ASUSTeK Computer Inc.

Software Availability: Oct-2010



### Hardware

CPU Name: AMD Opteron 6174  
 CPU Characteristics:  
 CPU MHz: 2200  
 FPU: Integrated  
 CPU(s) enabled: 24 cores, 2 chips, 12 cores/chip  
 CPU(s) orderable: 1,2 chips  
 Primary Cache: 64 KB I + 64 KB D on chip per core  
 Secondary Cache: 512 KB I+D on chip per core

### Software

Operating System: SUSE Linux Enterprise Server 11 (x86\_64), Kernel 2.6.27.19-5-default  
 Compiler: x86 Open64 4.2.4 Compiler Suite (from AMD)  
 Auto Parallel: Yes  
 File System: ext3  
 System State: Run level 3 (multiuser)  
 Base Pointers: 64-bit  
 Peak Pointers: 32/64-bit  
 Other Software: binutils 2.18

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## ASUSTeK Computer Inc.

SPECfp\_rate2006 = 313

ASUS RS500A-E6 (KGNE-D16) server system  
(2.2 GHz AMD Optron 6174)

SPECfp\_rate\_base2006 = 290

CPU2006 license: 9016

Test date: Oct-2010

Test sponsor: ASUSTeK Computer Inc.

Hardware Availability: Aug-2010

Tested by: ASUSTeK Computer Inc.

Software Availability: Oct-2010

L3 Cache: 12 MB I+D on chip per chip, 6 MB shared / 6 cores  
Other Cache: None  
Memory: 64 GB (16 x 4 GB 2Rx4 PC3-10600R-9, ECC)  
Disk Subsystem: Seagate ST3500320AS 1 x 500 GB SATA, 7200 RPM  
Other Hardware: None

## Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	24	1226	266	<u>1222</u>	<u>267</u>	1222	267	24	<u>1206</u>	<u>270</u>	1208	270	1206	270
416.gamess	24	1361	345	1355	347	<u>1359</u>	<u>346</u>	24	<u>1251</u>	<u>375</u>	1252	375	1251	376
433.milc	24	<u>1156</u>	<u>191</u>	1154	191	1157	190	24	<u>1032</u>	<u>213</u>	1031	214	1033	213
434.zeusmp	24	759	288	761	287	<u>760</u>	<u>287</u>	24	749	292	<u>745</u>	<u>293</u>	741	295
435.gromacs	24	620	276	617	278	<u>618</u>	<u>277</u>	24	<u>484</u>	<u>354</u>	483	355	526	326
436.cactusADM	24	867	331	<u>868</u>	<u>330</u>	869	330	4	138	346	<u>127</u>	<u>376</u>	126	380
437.leslie3d	24	1189	190	1187	190	<u>1187</u>	<u>190</u>	24	1183	191	1181	191	<u>1182</u>	<u>191</u>
444.namd	24	704	273	<u>697</u>	<u>276</u>	697	276	24	656	293	650	296	<u>651</u>	<u>296</u>
447.dealII	24	<u>617</u>	<u>445</u>	613	448	623	441	24	540	509	<u>539</u>	<u>510</u>	536	512
450.soplex	24	1377	145	<u>1085</u>	<u>184</u>	1084	185	24	1235	162	<u>955</u>	<u>210</u>	948	211
453.povray	24	<u>328</u>	<u>389</u>	327	390	330	387	24	<u>294</u>	<u>434</u>	292	437	295	433
454.calculix	24	495	400	496	399	<u>495</u>	<u>400</u>	24	465	426	467	424	<u>465</u>	<u>425</u>
459.GemsFDTD	24	1477	172	1465	174	<u>1472</u>	<u>173</u>	24	<u>1398</u>	<u>182</u>	1396	182	1398	182
465.tonto	24	701	337	<u>700</u>	<u>337</u>	698	338	24	<u>635</u>	<u>372</u>	634	372	640	369
470.lbm	24	876	377	877	376	<u>876</u>	<u>376</u>	24	876	377	877	376	<u>876</u>	<u>376</u>
481.wrf	24	901	298	896	299	<u>900</u>	<u>298</u>	24	870	308	866	310	<u>870</u>	<u>308</u>
482.sphinx3	24	1322	354	<u>1305</u>	<u>359</u>	1303	359	24	1304	359	<u>1291</u>	<u>362</u>	1286	364

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Submit Notes

The config file option 'submit' was used.  
'numactl' was used to bind copies to the cores.  
See the configuration file for details.

## Operating System Notes

'ulimit -s unlimited' was used to set environment stack size  
'ulimit -l 2097152' was used to set environment locked pages in memory limit

Set vm/nr\_hugepages=10800 in /etc/sysctl.conf  
mount -t hugetlbfs nodev /mnt/hugepages



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**ASUSTeK Computer Inc.**

**SPECfp\_rate2006 = 313**

ASUS RS500A-E6 (KGNE-D16) server system  
(2.2 GHz AMD Optron 6174)

**SPECfp\_rate\_base2006 = 290**

**CPU2006 license:** 9016

**Test date:** Oct-2010

**Test sponsor:** ASUSTeK Computer Inc.

**Hardware Availability:** Aug-2010

**Tested by:** ASUSTeK Computer Inc.

**Software Availability:** Oct-2010

## Platform Notes

SSI Server Power Supply 600W or higher  
System was configured with ASPEED AST2050 VGA (on board VGA)

## General Notes

Environment variables set by runspec before the start of the run:

HUGETLB\_LIMIT = "450"

LD\_LIBRARY\_PATH = "/cpu2006/amd1002-rate-libs-revC/64:/cpu2006/amd1002-rate-libs-revC/32"

OMP\_NUM\_THREADS = "6"

The x86 Open64 Compiler Suite is only available from (and supported by) AMD at  
<http://developer.amd.com/cpu/open64>

## Base Compiler Invocation

C benchmarks:  
opencc

C++ benchmarks:  
openCC

Fortran benchmarks:  
openf95

Benchmarks using both Fortran and C:  
opencc openf95

## Base Portability Flags

410.bwaves: -DSPEC\_CPU\_LP64  
416.gamess: -DSPEC\_CPU\_LP64  
433.milc: -DSPEC\_CPU\_LP64  
434.zeusmp: -DSPEC\_CPU\_LP64  
435.gromacs: -DSPEC\_CPU\_LP64  
436.cactusADM: -DSPEC\_CPU\_LP64 -fno-second-underscore  
437.leslie3d: -DSPEC\_CPU\_LP64  
444.namd: -DSPEC\_CPU\_LP64  
447.dealII: -DSPEC\_CPU\_LP64  
450.soplex: -DSPEC\_CPU\_LP64  
453.povray: -DSPEC\_CPU\_LP64  
454.calculix: -DSPEC\_CPU\_LP64  
459.GemsFDTD: -DSPEC\_CPU\_LP64  
465.tonto: -DSPEC\_CPU\_LP64  
470.lbm: -DSPEC\_CPU\_LP64  
481.wrf: -DSPEC\_CPU\_LP64 -DSPEC\_CPU\_LINUX -DSPEC\_CPU\_CASE\_FLAG  
-fno-second-underscore

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**ASUSTeK Computer Inc.**

**SPECfp\_rate2006 = 313**

ASUS RS500A-E6 (KGNE-D16) server system  
(2.2 GHz AMD Opteron 6174)

**SPECfp\_rate\_base2006 = 290**

**CPU2006 license:** 9016

**Test date:** Oct-2010

**Test sponsor:** ASUSTeK Computer Inc.

**Hardware Availability:** Aug-2010

**Tested by:** ASUSTeK Computer Inc.

**Software Availability:** Oct-2010

## Base Portability Flags (Continued)

482.sphinx3: -DSPEC\_CPU\_LP64

## Base Optimization Flags

C benchmarks:

-march=barcelona -mso -Ofast -OPT:malloc\_alg=1 -HP:bdt=2m

C++ benchmarks:

-march=barcelona -mso -Ofast -static -INLINE:aggressive=on  
-OPT:malloc\_alg=1 -HP:bdt=2m

Fortran benchmarks:

-march=barcelona -mso -Ofast -HP

Benchmarks using both Fortran and C:

-march=barcelona -mso -Ofast -OPT:malloc\_alg=1 -HP:bdt=2m -HP

## Peak Compiler Invocation

C benchmarks:

openc

C++ benchmarks:

openCC

Fortran benchmarks:

openf95

Benchmarks using both Fortran and C:

openc openf95

## Peak Portability Flags

410.bwaves: -DSPEC\_CPU\_LP64

416.gamess: -DSPEC\_CPU\_LP64

433.milc: -DSPEC\_CPU\_LP64

434.zeusmp: -DSPEC\_CPU\_LP64

435.gromacs: -DSPEC\_CPU\_LP64

436.cactusADM: -DSPEC\_CPU\_LP64 -fno-second-underscore

437.leslie3d: -DSPEC\_CPU\_LP64

444.namd: -DSPEC\_CPU\_LP64

453.povray: -DSPEC\_CPU\_LP64

454.calculix: -DSPEC\_CPU\_LP64

Continued on next page

Standard Performance Evaluation Corporation

info@spec.org

http://www.spec.org/



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**ASUSTeK Computer Inc.**

**SPECfp\_rate2006 = 313**

ASUS RS500A-E6 (KGNE-D16) server system  
(2.2 GHz AMD Opteron 6174)

**SPECfp\_rate\_base2006 = 290**

**CPU2006 license:** 9016

**Test date:** Oct-2010

**Test sponsor:** ASUSTeK Computer Inc.

**Hardware Availability:** Aug-2010

**Tested by:** ASUSTeK Computer Inc.

**Software Availability:** Oct-2010

## Peak Portability Flags (Continued)

459.GemsFDTD: -DSPEC\_CPU\_LP64  
 465.tonto: -DSPEC\_CPU\_LP64  
 470.lbm: -DSPEC\_CPU\_LP64  
 481.wrf: -DSPEC\_CPU\_LP64 -DSPEC\_CPU\_LINUX -DSPEC\_CPU\_CASE\_FLAG  
 -fno-second-underscore  
 482.sphinx3: -DSPEC\_CPU\_LP64

## Peak Optimization Flags

C benchmarks:

433.milc: -march=barcelona -mso -Ofast -CG:movnti=1  
 -CG:local\_sched\_alg=1 -CG:locs\_shallow\_depth=1  
 -HP:bdt=2m:heap=2m -LNO:prefetch=3

470.lbm: basepeak = yes

482.sphinx3: -march=barcelona -mso -fb\_create fbdata(pass 1)  
 -fb\_opt fbdata(pass 2) -Ofast -OPT:malloc\_alg=2  
 -CG:sse\_cse\_regs=0 -CG:locs\_shallow\_depth=1 -CG:cmp\_peep=on  
 -CG:local\_sched\_alg=1 -INLINE:aggressive=on

C++ benchmarks:

444.namd: -march=barcelona -mso -fb\_create fbdata(pass 1)  
 -fb\_opt fbdata(pass 2) -Ofast -LNO:ignore\_feedback=off  
 -CG:local\_sched\_alg=2 -CG:load\_exe=0 -CG:compute\_to=on  
 -OPT:unroll\_size=256 -fno-exceptions -HP:bdt=2m:heap=2m

447.dealII: -march=barcelona -mso -Ofast -static -INLINE:aggressive=on  
 -LNO:opt=0 -fno-emit-exceptions -m32  
 -OPT:unroll\_times\_max=8 -OPT:unroll\_size=256  
 -OPT:unroll\_level=2 -HP:bdt=2m:heap=2m -GRA:unspill=on  
 -CG:cmp\_peep=on -TENV:frame\_pointer=off

450.soplex: -march=barcelona -mso -fb\_create fbdata(pass 1)  
 -fb\_opt fbdata(pass 2) -O3 -INLINE:aggressive=on  
 -OPT:IEEE\_arith=3 -OPT:IEEE\_NaN\_Inf=off  
 -OPT:fold\_unsigned\_relops=on -OPT:malloc\_alg=1  
 -CG:load\_exe=0 -fno-exceptions -m32 -HP:bdt=2m

453.povray: -march=barcelona -mso -fb\_create fbdata(pass 1)  
 -fb\_opt fbdata(pass 2) -Ofast -INLINE:aggressive=on

Fortran benchmarks:

410.bwaves: -march=barcelona -mso -O3 -OPT:Ofast -OPT:treeheight=on  
 -LNO:blocking=off -LNO:prefetch\_ahead=5  
 -LNO:ignore\_feedback=off -WOPT:aggstr=0 -HP:bdt=2m:heap=2m

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**ASUSTeK Computer Inc.**

**SPECfp\_rate2006 = 313**

ASUS RS500A-E6 (KGNE-D16) server system  
(2.2 GHz AMD Opteron 6174)

**SPECfp\_rate\_base2006 = 290**

**CPU2006 license:** 9016

**Test date:** Oct-2010

**Test sponsor:** ASUSTeK Computer Inc.

**Hardware Availability:** Aug-2010

**Tested by:** ASUSTeK Computer Inc.

**Software Availability:** Oct-2010

## Peak Optimization Flags (Continued)

410.bwaves (continued):

-CG:cmp\_peep=on

416.gamess: -march=barcelona -mso -fb\_create fbdata(pass 1)

-fb\_opt fbdata(pass 2) -O3 -LNO:fu=6 -LNO:blocking=0

-LNO:prefetch=0 -OPT:Ofast -OPT:ro=3 -OPT:unroll\_size=256

-HP:bdt=2m:heap=2m

434.zeusmp: -march=barcelona -mso -Ofast -LNO:blocking=off

-LNO:interchange=off -OPT:treeheight=on -OPT:unroll\_size=256

-CG:cmp\_peep=on -GRA:prioritize\_by\_density=on -HP

437.leslie3d: -march=barcelona -mso -Ofast -HP:bdt=2m:heap=2m

459.GemsFDTD: -march=barcelona -mso -Ofast -LNO:fission=2

-LNO:prefetch\_ahead=1 -CG:load\_exe=0 -CG:local\_sched\_alg=1

-HP

465.tonto: -march=barcelona -mso -Ofast

-OPT:alias=no\_f90\_pointer\_alias -LNO:blocking=off

-CG:load\_exe=1 -IPA:plimit=525 -HP

Benchmarks using both Fortran and C:

435.gromacs: -march=barcelona -mso -Ofast -OPT:rsqrt=2

-HP:bdt=2m:heap=2m

436.cactusADM: -march=barcelona -mso -fb\_create fbdata(pass 1)

-fb\_opt fbdata(pass 2) -Ofast -apo -LNO:prefetch\_ahead=1

-HP:bdt=2m:heap=2m -LANG:heap\_allocation\_threshold=100

454.calculix: -march=barcelona -mso -Ofast -CG:load\_exe=0

-CG:ptr\_load\_use=0 -CG:local\_sched\_alg=2 -CG:compute\_to=on

-LNO:prefetch\_ahead=30 -WOPT:unroll=2

-GRA:optimize\_boundary=on -HP:bdt=2m:heap=2m

481.wrf: -march=barcelona -mso -Ofast -LNO:blocking=off

-LNO:prefetch\_ahead=10 -LANG:copyinout=off

-IPA:callee\_limit=5000 -GRA:prioritize\_by\_density=on -m3dnow

-HP

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/x86-open64-424-flags-rate-revC.20100901.html>

<http://www.spec.org/cpu2006/flags/amd-platform-rate-revC.html>

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/cpu2006/flags/x86-open64-424-flags-rate-revC.20100901.xml>

<http://www.spec.org/cpu2006/flags/amd-platform-rate-revC.xml>



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**ASUSTeK Computer Inc.**

**SPECfp\_rate2006 = 313**

ASUS RS500A-E6 (KGNE-D16) server system  
(2.2 GHz AMD Opteron 6174)

**SPECfp\_rate\_base2006 = 290**

**CPU2006 license:** 9016

**Test date:** Oct-2010

**Test sponsor:** ASUSTeK Computer Inc.

**Hardware Availability:** Aug-2010

**Tested by:** ASUSTeK Computer Inc.

**Software Availability:** Oct-2010

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.1.  
Report generated on Wed Jul 23 14:02:45 2014 by SPEC CPU2006 PS/PDF formatter v6932.  
Originally published on 9 November 2010.