SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

ASUSTeK Computer Inc.

(Test Sponsor: Intel Corporation)

Asus M4A89GTD-PRO (Phenom II X4 955)

SPECint®_rate2006 = 83.6

SPECint_rate_base2006 = 75.2

CPU2006 license: 13
Test sponsor: Intel Corporation
Tested by: Intel Corporation

Test date: May-2011
Hardware Availability: Mar-2010
Software Availability: Apr-2011



Hardware

CPU Name:	AMD Phenom II X4 955
CPU Characteristics:	
CPU MHz:	3200
FPU:	Integrated
CPU(s) enabled:	4 cores, 1 chip, 4 cores/chip
CPU(s) orderable:	1 chip
Primary Cache:	64 KB I + 64 KB D on chip per core
Secondary Cache:	512 KB I+D on chip per core
L3 Cache:	6 MB I+D on chip per chip
Other Cache:	None
Memory:	8 GB (2 x 4 GB 2Rx8 PC3-10600U-9)
Disk Subsystem:	Seagate 1 TB SATA, 7200 RPM
Other Hardware:	None

Software

Operating System:	Windows 7 Ultimate (64-bit)
Compiler:	Intel C++ Compiler XE for IA32 and Intel 64 Version 12.0.3.176 Build 20110309 Microsoft Visual Studio 2008 Professional SP1 (for libraries)
Auto Parallel:	No
File System:	NTFS
System State:	Default
Base Pointers:	32-bit
Peak Pointers:	32/64-bit
Other Software:	SmartHeap Library Version 9.01 from http://www.microquill.com/

SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

ASUSTeK Computer Inc.
(Test Sponsor: Intel Corporation)

Asus M4A89GTD-PRO (Phenom II X4 955)

SPECint_rate2006 = 83.6

SPECint_rate_base2006 = 75.2

CPU2006 license: 13
Test sponsor: Intel Corporation
Tested by: Intel Corporation

Test date: May-2011
Hardware Availability: Mar-2010
Software Availability: Apr-2011

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	4	530	73.6	**528**	**74.0**	528	74.0	4	422	92.8	**421**	**92.8**	420	92.8
401.bzip2	4	790	48.8	**719**	**53.6**	717	54.0	4	**712**	**54.0**	703	54.8	717	54.0
403.gcc	4	509	63.2	**509**	**63.2**	510	63.2	4	**481**	**66.8**	479	67.2	484	66.4
429.mcf	4	537	68.0	536	68.0	**537**	**68.0**	4	537	68.0	536	68.0	**537**	**68.0**
445.gobmk	4	502	83.6	502	83.6	**502**	**83.6**	4	462	90.8	**462**	**90.8**	484	86.8
456.hmmer	4	744	50.0	743	50.4	**744**	**50.0**	4	**437**	**85.6**	437	85.6	438	85.2
458.sjeng	4	680	71.2	**680**	**71.2**	680	71.2	4	**625**	**77.6**	626	77.2	624	77.6
462.libquantum	4	308	269	**309**	**269**	309	268	4	259	320	258	321	**259**	**320**
464.h264ref	4	695	128	**695**	**128**	695	127	4	**662**	**134**	662	134	663	134
471.omnetpp	4	**513**	**48.8**	513	48.8	513	48.8	4	**472**	**52.8**	472	52.8	472	52.8
473.astar	4	**526**	**53.6**	526	53.6	526	53.6	4	540	52.0	**540**	**52.0**	540	52.0
483.xalancbmk	4	**380**	**72.4**	380	72.8	381	72.4	4	**380**	**72.4**	380	72.8	381	72.4

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Submit Notes

```
The config file option 'submit' was used.
 The start command with the /affinity switch was used to bind processes to cores
```

General Notes

```
 Tested systems can be used with Shin-G ATX case,
 PC Power and Cooling 1200W power supply
```

Base Compiler Invocation

C benchmarks:
```
icl -Qvc9 -Qstd=c99
```

C++ benchmarks:
```
icl -Qvc9
```

Base Portability Flags

403.gcc: `-DSPEC_CPU_WIN32`
464.h264ref: `-DWIN32 -DSPEC_CPU_NO_INTTYPES`
483.xalancbmk: `-Qoption,cpp,--no_wchar_t_keyword`

Base Optimization Flags

C benchmarks:
```
/arch:SSE3 -Qipo -O3 -Qprec-div- -Qopt-prefetch /F512000000
```

C++ benchmarks:
```
/arch:SSE3 -Qipo -O3 -Qprec-div- -Qopt-prefetch -Qcxx-features
/F512000000 shlW32M.lib            -link /FORCE:MULTIPLE
```

Base Other Flags

C benchmarks:

403.gcc: `-Dalloca=_alloca`

Peak Compiler Invocation

C benchmarks (except as noted below):
```
icl -Qvc9 -Qstd=c99
```

456.hmmer: `C:/Program Files (x86)/Intel/ComposerXE-2011/bin/intel64/icl.exe`

458.sjeng: `C:/Program Files (x86)/Intel/ComposerXE-2011/bin/intel64/icl.exe`

462.libquantum: `C:/Program Files (x86)/Intel/ComposerXE-2011/bin/intel64/icl.exe -Qstd=c99`

C++ benchmarks (except as noted below):
```
icl -Qvc9
```

473.astar: `C:/Program Files (x86)/Intel/ComposerXE-2011/bin/intel64/icl.exe`

Peak Portability Flags

403.gcc: `-DSPEC_CPU_WIN32`
456.hmmer: `-DSPEC_CPU_P64`
458.sjeng: `-DSPEC_CPU_P64`
462.libquantum: `-DSPEC_CPU_P64`
464.h264ref: `-DWIN32 -DSPEC_CPU_NO_INTTYPES`
473.astar: `-DSPEC_CPU_P64`
483.xalancbmk: `-Qoption,cpp,--no_wchar_t_keyword`

Peak Optimization Flags

C benchmarks:

400.perlbench: /arch:SSE3(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2) -Qipo -O3 -Qprec-div- -Qansi-alias -Qopt-prefetch /F512000000 shlW32M.lib -link /FORCE:MULTIPLE

401.bzip2: /arch:SSE3(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2) -Qipo -O3 -Qprec-div- -Qopt-prefetch -Qansi-alias /F512000000

403.gcc: /arch:SSE3(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2) -Qipo -O3 -Qprec-div- -Qopt-prefetch /F512000000

429.mcf: /arch:SSE3 -Qipo -O3 -Qprec-div- -Qopt-prefetch /F512000000

445.gobmk: /arch:SSE3(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2) -Qipo -O2 -Qprec-div- -Qansi-alias /F512000000

456.hmmer: -Qauto-ilp32 /arch:SSE3(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2) -Qipo -O3 -Qprec-div- -Qopt-prefetch /F512000000

458.sjeng: -Qauto-ilp32 /arch:SSE3(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2) -Qipo -O3 -Qprec-div- -Qunroll4 /F512000000

462.libquantum: -Qauto-ilp32 /arch:SSE3 -Qipo -O3 -Qprec-div- -Qopt-prefetch /F512000000

464.h264ref: /arch:SSE3(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2) -Qipo -O3 -Qprec-div- -Qunroll2 -Qansi-alias /F512000000

C++ benchmarks:

471.omnetpp: /arch:SSE3(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2) -Qipo -O3 -Qprec-div- -Qansi-alias -Qopt-ra-region-strategy=block /F512000000 shlW32M.lib -link /FORCE:MULTIPLE

473.astar: -Qauto-ilp32 /arch:SSE3 -Qipo -O3 -Qprec-div- -Qopt-prefetch /F512000000 shlW64M.lib -link /FORCE:MULTIPLE

483.xalancbmk: basepeak = yes

Peak Other Flags

C benchmarks:

403.gcc: `-Dalloca=_alloca`

456.hmmer: `-link -LIBPATH:C:/Program Files (x86)/Intel/ComposerXE-2011/compiler/lib/intel64`
`-link -LIBPATH:C:/Program Files (x86)/Microsoft Visual Studio 9.0/VC/lib/AMD64`
`-link -LIBPATH:C:/Program Files (x86)/Microsoft Visual Studio 9.0/VC/lib`
`-link -LIBPATH:C:/Program Files (x86)/Microsoft SDKs/Windows/v7.0A/lib/x64`

458.sjeng: `-link -LIBPATH:C:/Program Files (x86)/Intel/ComposerXE-2011/compiler/lib/intel64`
`-link -LIBPATH:C:/Program Files (x86)/Microsoft Visual Studio 9.0/VC/lib/AMD64`
`-link -LIBPATH:C:/Program Files (x86)/Microsoft Visual Studio 9.0/VC/lib`
`-link -LIBPATH:C:/Program Files (x86)/Microsoft SDKs/Windows/v7.0A/lib/x64`

462.libquantum: `-link -LIBPATH:C:/Program Files (x86)/Intel/ComposerXE-2011/compiler/lib/intel64`
`-link -LIBPATH:C:/Program Files (x86)/Microsoft Visual Studio 9.0/VC/lib/AMD64`
`-link -LIBPATH:C:/Program Files (x86)/Microsoft Visual Studio 9.0/VC/lib`
`-link -LIBPATH:C:/Program Files (x86)/Microsoft SDKs/Windows/v7.0A/lib/x64`

C++ benchmarks:

473.astar: `-link -LIBPATH:C:/Program Files (x86)/Intel/ComposerXE-2011/compiler/lib/intel64`
`-link -LIBPATH:C:/Program Files (x86)/Microsoft Visual Studio 9.0/VC/lib/AMD64`
`-link -LIBPATH:C:/Program Files (x86)/Microsoft Visual Studio 9.0/VC/lib`
`-link -LIBPATH:C:/Program Files (x86)/Microsoft SDKs/Windows/v7.0A/lib/x64`

The flags files that were used to format this result can be browsed at
`http://www.spec.org/cpu2006/flags/Intel-ic12-win32-revB.20110511.html`
`http://www.spec.org/cpu2006/flags/Intel-Windows-Platform-Settings.20110719.html`

You can also download the XML flags sources by saving the following links:
`http://www.spec.org/cpu2006/flags/Intel-ic12-win32-revB.20110511.xml`
`http://www.spec.org/cpu2006/flags/Intel-Windows-Platform-Settings.20110719.xml`

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.1.
Report generated on Wed Jul 23 21:20:51 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 19 July 2011.