



SPEC[®] CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

ACTION S.A.

SPECfp[®]_rate2006 = 106

ACTINA SOLAR 100 S5 (Intel Xeon E3-1220)

SPECfp_rate_base2006 = 103

CPU2006 license: 9008


Test date: Feb-2012

Test sponsor: ACTION S.A.

Hardware Availability: Apr-2011

Tested by: ACTION S.A.

Software Availability: Oct-2011



Hardware

CPU Name: Intel Xeon E3-1220
 CPU Characteristics: Intel Turbo Boost Technology up to 3.40 GHz
 CPU MHz: 3100
 FPU: Integrated
 CPU(s) enabled: 4 cores, 1 chip, 4 cores/chip
 CPU(s) orderable: 1 chip
 Primary Cache: 32 KB I + 32 KB D on chip per core
 Secondary Cache: 256 KB I+D on chip per core

Continued on next page

Software

Operating System: Red Hat Enterprise Linux Server release 6.1 (Santiago)
 2.6.32-131.0.15.el6.x86_64
 Compiler: C/C++: Version 12.1.0.225 of Intel C++ Studio XE for Linux;
 Fortran: Version 12.1.0.225 of Intel Fortran Studio XE for Linux
 Auto Parallel: No
 File System: ext4

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

ACTION S.A.

SPECfp_rate2006 = 106

ACTINA SOLAR 100 S5 (Intel Xeon E3-1220)

SPECfp_rate_base2006 = 103

CPU2006 license: 9008

Test date: Feb-2012

Test sponsor: ACTION S.A.

Hardware Availability: Apr-2011

Tested by: ACTION S.A.

Software Availability: Oct-2011

L3 Cache: 8 MB I+D on chip per chip
 Other Cache: None
 Memory: 16 GB (4 x 4 GB 2Rx8 PC3-10600E-9, ECC)
 Disk Subsystem: 320 GB SATA II, 7200 RPM
 Other Hardware: None

System State: Run level 3 (multi-user)
 Base Pointers: 32/64-bit
 Peak Pointers: 32/64-bit
 Other Software: Microquill SmartHeap V9.01

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	4	638	85.3	<u>639</u>	<u>85.1</u>	639	85.1	4	638	85.3	<u>639</u>	<u>85.1</u>	639	85.1
416.gamess	4	612	128	<u>612</u>	<u>128</u>	608	129	4	<u>582</u>	<u>135</u>	581	135	586	134
433.milc	4	414	88.7	<u>414</u>	<u>88.7</u>	414	88.7	4	413	88.8	414	88.8	<u>414</u>	<u>88.8</u>
434.zeusmp	4	312	117	<u>312</u>	<u>117</u>	311	117	4	312	117	<u>312</u>	<u>117</u>	311	117
435.gromacs	4	284	101	285	100	<u>284</u>	<u>100</u>	4	289	98.9	<u>288</u>	<u>99.0</u>	288	99.0
436.cactusADM	4	<u>346</u>	<u>138</u>	346	138	345	138	4	<u>346</u>	<u>138</u>	346	138	345	138
437.leslie3d	4	<u>642</u>	<u>58.6</u>	641	58.6	642	58.6	4	639	58.8	640	58.7	<u>640</u>	<u>58.7</u>
444.namd	4	373	86.1	<u>373</u>	<u>86.1</u>	373	86.1	4	368	87.3	368	87.2	<u>368</u>	<u>87.3</u>
447.dealII	4	251	182	252	182	<u>252</u>	<u>182</u>	4	251	182	252	182	<u>252</u>	<u>182</u>
450.soplex	4	487	68.5	<u>487</u>	<u>68.5</u>	488	68.4	4	<u>446</u>	<u>74.9</u>	446	74.8	445	74.9
453.povray	4	132	161	131	162	<u>131</u>	<u>162</u>	4	113	189	112	190	<u>112</u>	<u>189</u>
454.calculix	4	226	146	<u>227</u>	<u>145</u>	227	145	4	226	146	<u>227</u>	<u>145</u>	227	145
459.GemsFDTD	4	<u>781</u>	<u>54.4</u>	781	54.3	780	54.4	4	<u>781</u>	<u>54.4</u>	781	54.3	780	54.4
465.tonto	4	<u>312</u>	<u>126</u>	311	126	315	125	4	<u>301</u>	<u>131</u>	300	131	305	129
470.lbm	4	532	103	<u>531</u>	<u>103</u>	531	103	4	532	103	<u>531</u>	<u>103</u>	531	103
481.wrf	4	410	109	<u>412</u>	<u>109</u>	412	108	4	405	110	<u>404</u>	<u>111</u>	403	111
482.sphinx3	4	796	97.9	<u>796</u>	<u>98.0</u>	795	98.0	4	770	101	772	101	<u>771</u>	<u>101</u>

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Submit Notes

The taskset mechanism was used to bind copies to processors. The config file option 'submit' was used to generate taskset commands to bind each copy to a specific processor. For details, please see the config file.

Operating System Notes

Stack size set to unlimited using "ulimit -s unlimited"

General Notes

Environment variables set by runspec before the start of the run:
LD_LIBRARY_PATH = "/cpu2006.1.2/libs/32:/cpu2006.1.2/libs/64"

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

ACTION S.A.

SPECfp_rate2006 = 106

ACTINA SOLAR 100 S5 (Intel Xeon E3-1220)

SPECfp_rate_base2006 = 103

CPU2006 license: 9008

Test date: Feb-2012

Test sponsor: ACTION S.A.

Hardware Availability: Apr-2011

Tested by: ACTION S.A.

Software Availability: Oct-2011

General Notes (Continued)

Binaries compiled on a system with 1x Core i7-860 CPU + 8GB memory using RHEL5.5

Base Compiler Invocation

C benchmarks:

icc -m64

C++ benchmarks:

icpc -m64

Fortran benchmarks:

ifort -m64

Benchmarks using both Fortran and C:

icc -m64 ifort -m64

Base Portability Flags

410.bwaves: -DSPEC_CPU_LP64
 416.gamess: -DSPEC_CPU_LP64
 433.milc: -DSPEC_CPU_LP64
 434.zeusmp: -DSPEC_CPU_LP64
 435.gromacs: -DSPEC_CPU_LP64 -nofor_main
 436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
 437.leslie3d: -DSPEC_CPU_LP64
 444.namd: -DSPEC_CPU_LP64
 447.dealII: -DSPEC_CPU_LP64
 450.soplex: -DSPEC_CPU_LP64
 453.povray: -DSPEC_CPU_LP64
 454.calculix: -DSPEC_CPU_LP64 -nofor_main
 459.GemsFDTD: -DSPEC_CPU_LP64
 465.tonto: -DSPEC_CPU_LP64
 470.lbm: -DSPEC_CPU_LP64
 481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
 482.sphinx3: -DSPEC_CPU_LP64

Base Optimization Flags

C benchmarks:

-xSSE4.2 -ipo -O3 -no-prec-div -static -opt-prefetch -auto-p32
-ansi-alias

C++ benchmarks:

-xSSE4.2 -ipo -O3 -no-prec-div -static -opt-prefetch -auto-p32
-ansi-alias

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

ACTION S.A.

SPECfp_rate2006 = 106

ACTINA SOLAR 100 S5 (Intel Xeon E3-1220)

SPECfp_rate_base2006 = 103

CPU2006 license: 9008

Test date: Feb-2012

Test sponsor: ACTION S.A.

Hardware Availability: Apr-2011

Tested by: ACTION S.A.

Software Availability: Oct-2011

Base Optimization Flags (Continued)

Fortran benchmarks:

`-xSSE4.2 -ipo -O3 -no-prec-div -static -opt-prefetch`

Benchmarks using both Fortran and C:

`-xSSE4.2 -ipo -O3 -no-prec-div -static -opt-prefetch -auto-p32
-ansi-alias`

Peak Compiler Invocation

C benchmarks (except as noted below):

`icc -m64`

`482.sphinx3:icc -m32`

C++ benchmarks (except as noted below):

`icpc -m64`

`450.soplex:icpc -m32`

Fortran benchmarks:

`ifort -m64`

Benchmarks using both Fortran and C:

`icc -m64 ifort -m64`

Peak Portability Flags

`410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
437.leslie3d: -DSPEC_CPU_LP64
444.namd: -DSPEC_CPU_LP64
447.dealII: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
470.lbm: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX`



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

ACTION S.A.

SPECfp_rate2006 = 106

ACTINA SOLAR 100 S5 (Intel Xeon E3-1220)

SPECfp_rate_base2006 = 103

CPU2006 license: 9008

Test date: Feb-2012

Test sponsor: ACTION S.A.

Hardware Availability: Apr-2011

Tested by: ACTION S.A.

Software Availability: Oct-2011

Peak Optimization Flags

C benchmarks:

433.milc: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
-no-prec-div(pass 2) -prof-use(pass 2) -static -auto-ilp32

470.lbm: basepeak = yes

482.sphinx3: -xSSE4.2 -ipo -O3 -no-prec-div -unroll2

C++ benchmarks:

444.namd: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
-no-prec-div(pass 2) -prof-use(pass 2) -fno-alias
-auto-ilp32

447.dealIII: basepeak = yes

450.soplex: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
-no-prec-div(pass 2) -prof-use(pass 2) -opt-malloc-options=3

453.povray: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
-no-prec-div(pass 2) -prof-use(pass 2) -unroll4 -ansi-alias

Fortran benchmarks:

410.bwaves: basepeak = yes

416.gamess: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
-no-prec-div(pass 2) -prof-use(pass 2) -unroll2
-inline-level=0 -scalar-rep- -static

434.zeusmp: basepeak = yes

437.leslie3d: -xSSE4.2 -ipo -O3 -no-prec-div -static -opt-prefetch

459.GemsFDTD: basepeak = yes

465.tonto: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
-no-prec-div(pass 2) -prof-use(pass 2) -unroll4 -auto
-inline-calloc -opt-malloc-options=3

Benchmarks using both Fortran and C:

435.gromacs: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
-no-prec-div(pass 2) -prof-use(pass 2) -opt-prefetch
-static -auto-ilp32

436.cactusADM: basepeak = yes

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

ACTION S.A.

SPECfp_rate2006 = 106

ACTINA SOLAR 100 S5 (Intel Xeon E3-1220)

SPECfp_rate_base2006 = 103

CPU2006 license: 9008

Test date: Feb-2012

Test sponsor: ACTION S.A.

Hardware Availability: Apr-2011

Tested by: ACTION S.A.

Software Availability: Oct-2011

Peak Optimization Flags (Continued)

454.calculix: basepeak = yes

481.wrf: -xSSE4.2 -ipo -O3 -no-prec-div -static -auto-ilp32

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic12.1-official-linux64.20111122.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/Intel-ic12.1-official-linux64.20111122.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.2.
Report generated on Thu Jul 24 02:13:35 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 28 February 2012.