SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Oracle Corporation

Sun Blade X4-2B (Intel Xeon E5-2697 v2 2.7GHz)

SPECint®_rate2006 = 924

SPECint_rate_base2006 = 806

CPU2006 license: 6
Test sponsor: Oracle Corporation
Tested by: Oracle Corporation

Test date: Sep-2013
Hardware Availability: Sep-2013
Software Availability: Nov-2013



Hardware

CPU Name:	Intel Xeon E5-2697 v2
CPU Characteristics:	Intel Turbo Boost Technology up to 3.50 GHz
CPU MHz:	2700
FPU:	Integrated
CPU(s) enabled:	24 cores, 2 chips, 12 cores/chip, 2 threads/core
CPU(s) orderable:	2 chips
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	256 KB I+D on chip per core
L3 Cache:	30 MB I+D on chip per chip
Other Cache:	None
Memory:	256 GB (16 x 16 GB 2Rx4 PC3-12800R-11, ECC)
Disk Subsystem:	1 x 300 GB SAS, 10K RPM
Other Hardware:	None

Software

Operating System:	Solaris 11.1 (SRU 11)
Compiler:	C/C++: Version 12.3 of Oracle Solaris Studio 10/13 Patch Set (tested with nightly build 20130822)
Auto Parallel:	No
File System:	zfs
System State:	Default
Base Pointers:	32/64-bit
Peak Pointers:	32/64-bit
Other Software:	Microquill SmartHeap V9.01

SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Oracle Corporation

Sun Blade X4-2B (Intel Xeon E5-2697 v2 2.7GHz)

SPECint_rate2006 = 924

SPECint_rate_base2006 = 806

CPU2006 license: 6
Test sponsor: Oracle Corporation
Tested by: Oracle Corporation

Test date: Sep-2013
Hardware Availability: Sep-2013
Software Availability: Nov-2013

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	48	711	660	**709**	**661**	708	663	96	**1081**	**867**	1074	874	1085	864
401.bzip2	48	959	483	**958**	**484**	956	485	96	1831	506	**1833**	**505**	1836	505
403.gcc	48	698	554	**696**	**555**	695	556	96	**1082**	**714**	1083	714	1081	715
429.mcf	48	**591**	**741**	589	743	595	735	48	356	1230	**354**	**1240**	353	1240
445.gobmk	48	767	657	766	657	**767**	**657**	48	698	722	**698**	**721**	699	721
456.hmmer	48	353	1270	**353**	**1270**	353	1270	48	342	1310	342	1310	**342**	**1310**
458.sjeng	48	**895**	**649**	895	649	895	649	48	831	699	830	699	**831**	**699**
462.libquantum	48	**202**	**4920**	202	4930	203	4910	24	**101**	**4910**	100	4970	102	4890
464.h264ref	48	833	1280	**833**	**1270**	836	1270	96	1491	1430	**1491**	**1430**	1493	1420
471.omnetpp	48	**739**	**406**	739	406	739	406	96	1274	471	**1274**	**471**	1271	472
473.astar	48	678	497	680	495	**679**	**496**	72	**972**	**520**	971	521	974	519
483.xalancbmk	48	397	834	**397**	**835**	397	835	96	**755**	**877**	755	877	754	878

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Submit Notes

```
The config file option 'submit' was used to bind processes to CPU threads with pbind(1)
```

Operating System Notes

```
ulimit -s unlimited  (shell): increases stack

/etc/system parameters
   autoup=1000
   tune_t_fsflushr=10
   zfs:zfs_arc_max=0x10000000
   zfs:zfs_arc_min=0x04001000
   lpg_alloc_prefer=1

gzip compression set using "zfs set compression=gzip <zfs-filesystem>"
```

Platform Notes

```
Default BIOS Settings were used.
Sysinfo program /export/home/cpu2006v1.2/Docs/sysinfo
: 6775  2011-08-16 #f7622badcf24e01c368b1db4377c
running on bur408-94 Sun Sep  1 14:42:53 2013

This section contains SUT (System Under Test) info as seen by
some common utilities.  To remove or add to this section, see:
  http://www.spec.org/cpu2006/Docs/config.html#sysinfo
```

Continued on next page

Platform Notes (Continued)

```
From /usr/sbin/psrinfo -pv
 Intel(r) Xeon(r) CPU E5-2697 v2 @ 2.70GHz
 x86 (GenuineIntel 306E4 family 6 model 62 step 4 clock 2693 MHz)

/usr/sbin/psrinfo -p:   2 chips
/usr/sbin/psrinfo -pv | grep "core has" | wc -l:  24 cores
/usr/sbin/psrinfo | wc -l: 48 threads

/usr/sbin/prtconf | grep "Memory size:": 262087 Megabytes

/etc/release:
                              Oracle Solaris 11.1 X86
uname -a:
SunOS bur408-94 5.11 11.1 i86pc i386 i86pc

disk: df -h
Filesystem             Size   Used  Available Capacity  Mounted on
rpool/export/home      274G    18G       179G    10%    /export/home

(End of data from sysinfo program)
```

General Notes

```
Environment variables set by runspec before the start of the run:
OMP_NUM_THREADS = "1"
```

Base Compiler Invocation

C benchmarks:
cc

C++ benchmarks:
CC

Base Portability Flags

400.perlbench: -DSPEC_CPU_SOLARIS_X64 -DSPEC_CPU_LP64
401.bzip2: -DSPEC_CPU_LP64
403.gcc: -DSPEC_CPU_SOLARIS -DSPEC_CPU_LP64
429.mcf: -DSPEC_CPU_LP64
445.gobmk: -DSPEC_CPU_LP64
456.hmmer: -DSPEC_CPU_LP64
458.sjeng: -DSPEC_CPU_LP64
462.libquantum: -DSPEC_CPU_SOLARIS -DSPEC_CPU_LP64
464.h264ref: -DSPEC_CPU_LP64

Continued on next page

Base Portability Flags (Continued)

483.xalancbmk: -DSPEC_CPU_SOLARIS

Base Optimization Flags

C benchmarks:
-g -fast -xtarget=ivybridge -xipo=2 -m64 -xaddr32 -xpagesize=2M

C++ benchmarks:
-g -fast -xtarget=ivybridge -xipo=2 -m32 -xpagesize=2M
-xalias_level=compatible -library=stlport4 -lfast

Peak Compiler Invocation

C benchmarks:
cc

C++ benchmarks:
CC

Peak Portability Flags

400.perlbench: -DSPEC_CPU_SOLARIS_X64 -DSPEC_CPU_LP64
403.gcc: -DSPEC_CPU_SOLARIS
462.libquantum: -DSPEC_CPU_SOLARIS
483.xalancbmk: -DSPEC_CPU_SOLARIS

Peak Optimization Flags

C benchmarks:

400.perlbench: -g -xprofile=collect:./feedback(pass 1)
-xprofile=use:./feedback(pass 2) -fast -xtarget=nehalem
-xprefetch=no%auto -xipo=1 -m64 -xpagesize=2M
-xalias_level=std -lbsdmalloc

401.bzip2: -g -xprofile=collect:./feedback(pass 1)
-xprofile=use:./feedback(pass 2) -fast -xtarget=ivybridge
-xipo=2 -m64 -xpagesize=2M -xalias_level=strong

403.gcc: -g -xprofile=collect:./feedback(pass 1)
-xprofile=use:./feedback(pass 2) -fast -xtarget=ivybridge
-xipo=2 -m32 -xpagesize=2M -xalias_level=std
-W2,-Abuiltin_opt:calloc_no_support=on

Continued on next page

Peak Optimization Flags (Continued)

429.mcf: -g -xprofile=collect:./feedback(pass 1)
-xprofile=use:./feedback(pass 2) -fast -xtarget=ivybridge
-xipo=2 -m32 -xpagesize_heap=2M -xpagesize_stack=4k
-xalias_level=std -W2,-Asac

445.gobmk: -g -xprofile=collect:./feedback(pass 1)
-xprofile=use:./feedback(pass 2) -fast -xtarget=ivybridge
-xtarget=sandybridge -m64 -xpagesize=2M -xrestrict
-xalias_level=strong

456.hmmer: -g -xprofile=collect:./feedback(pass 1)
-xprofile=use:./feedback(pass 2) -fast -xtarget=ivybridge
-xipo=2 -m64 -xpagesize=4k -xalias_level=strong

458.sjeng: -g -xprofile=collect:./feedback(pass 1)
-xprofile=use:./feedback(pass 2) -fast -xtarget=ivybridge
-xtarget=nehalem -xipo=2 -m64 -xpagesize=2M
-xalias_level=std

462.libquantum: -g -fast -xtarget=ivybridge -xipo=2 -m64 -xpagesize=2M
-xalias_level=std

464.h264ref: -g -xprofile=collect:./feedback(pass 1)
-xprofile=use:./feedback(pass 2) -fast -xtarget=ivybridge
-xipo=2 -m32 -xpagesize=2M -xalias_level=strong

C++ benchmarks:

471.omnetpp: -g -xprofile=collect:./feedback(pass 1)
-xprofile=use:./feedback(pass 2) -fast -xtarget=ivybridge
-xipo=2 -m32 -xpagesize=2M -xalias_level=compatible
-library=stlport4
-L/export/home/SmartHeap_9/lib/ -R/export/home/SmartHeap_9/lib/ -lsmartheap

473.astar: -g -xprofile=collect:./feedback(pass 1)
-xprofile=use:./feedback(pass 2) -fast -xtarget=ivybridge
-xipo=2 -m64 -xpagesize=2M -xalias_level=compatible
-xrestrict -library=stlport4 -lfast

483.xalancbmk: -g -xprofile=collect:./feedback(pass 1)
-xprofile=use:./feedback(pass 2) -fast -xtarget=ivybridge
-xipo=2 -m32 -xpagesize=2M -xunroll=8 -library=stlport4
-lfast

The flags files that were used to format this result can be browsed at
http://www.spec.org/cpu2006/flags/Oracle-Solaris-Studio12.3-x86_64.20130924.html
http://www.spec.org/cpu2006/flags/Oracle-platform-x86_64.CPUv1.2-RevA.20120425.html

You can also download the XML flags sources by saving the following links:
http://www.spec.org/cpu2006/flags/Oracle-Solaris-Studio12.3-x86_64.20130924.xml
http://www.spec.org/cpu2006/flags/Oracle-platform-x86_64.CPUv1.2-RevA.20120425.xml

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.2.
Report generated on Thu Jul 24 16:00:22 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 24 September 2013.