SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

Intel DQ77MK motherboard (Intel Core i5-3330)

SPECfp®2006 = 55.1

SPECfp_base2006 = 53.6

CPU2006 license: 13
Test sponsor: Intel Corporation
Tested by: Intel Corporation

Test date: Nov-2013
Hardware Availability: Nov-2012
Software Availability: Apr-2013



Hardware

CPU Name:	Intel Core i5-3330
CPU Characteristics:	Intel Turbo Boost Technology up to 3.20 GHz
CPU MHz:	3000
FPU:	Integrated
CPU(s) enabled:	4 cores, 1 chip, 4 cores/chip
CPU(s) orderable:	1 chip
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	256 KB I+D on chip per core

Continued on next page

Software

Operating System:	Microsoft Windows 7 Enterprise 6.1.7601 Service Pack 1 Build 7601
Compiler:	C/C++: Version 13.1.1.171 of Intel C++ Studio XE for Windows; Fortran: Version 13.1.1.171 of Intel Fortran Studio XE for Windows; Libraries: Version 16.00.30319.01 of Microsoft Visual Studio 2010 Professional SP1
Auto Parallel:	Yes

Continued on next page

SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

Intel DQ77MK motherboard (Intel Core i5-3330)

SPECfp2006 = 55.1

SPECfp_base2006 = 53.6

CPU2006 license: 13
Test sponsor: Intel Corporation
Tested by: Intel Corporation

Test date: Nov-2013
Hardware Availability: Nov-2012
Software Availability: Apr-2013

L3 Cache:	6 MB I+D on chip per chip
Other Cache:	None
Memory:	4 GB (2 x 2 GB 1Rx8 PC3-12800U-11)
Disk Subsystem:	250 GB Seagate SATA HDD, 7200 RPM
Other Hardware:	None

File System:	NTFS
System State:	Default
Base Pointers:	32/64-bit
Peak Pointers:	32/64-bit
Other Software:	SmartHeap Library Version 10.0 from http://www.microquill.com/

Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	145	94.0	146	93.0	**146**	**93.4**	145	94.0	146	93.0	**146**	**93.4**
416.gamess	640	30.6	639	30.6	**639**	**30.6**	**569**	**34.4**	569	34.4	570	34.4
433.milc	153	60.2	**153**	**60.2**	153	60.1	153	60.2	**153**	**60.2**	153	60.1
434.zeusmp	92.6	98.3	**92.2**	**98.7**	92.1	98.8	92.6	98.3	**92.2**	**98.7**	92.1	98.8
435.gromacs	**186**	**38.4**	186	38.4	186	38.4	**186**	**38.4**	186	38.4	186	38.4
436.cactusADM	81.1	147	83.3	144	**82.2**	**145**	81.1	147	83.3	144	**82.2**	**145**
437.leslie3d	155	60.8	**155**	**60.8**	154	60.9	155	60.8	**155**	**60.8**	154	60.9
444.namd	360	22.3	**360**	**22.3**	360	22.3	356	22.5	356	22.5	**356**	**22.5**
447.dealII	220	52.1	**220**	**52.1**	219	52.1	220	52.1	**220**	**52.1**	219	52.1
450.soplex	**242**	**34.4**	242	34.5	243	34.3	**242**	**34.4**	242	34.5	243	34.3
453.povray	**128**	**41.7**	129	41.3	127	41.8	107	50.0	107	49.8	**107**	**49.9**
454.calculix	210	39.2	**210**	**39.2**	211	39.2	210	39.2	**210**	**39.2**	211	39.2
459.GemsFDTD	**215**	**49.4**	214	49.6	215	49.3	**215**	**49.4**	214	49.6	215	49.3
465.tonto	306	32.2	334	29.5	**306**	**32.2**	**253**	**39.0**	253	38.9	253	39.0
470.lbm	136	101	135	102	**136**	**101**	136	101	135	102	**136**	**101**
481.wrf	150	74.7	**149**	**74.8**	149	75.1	150	74.7	**149**	**74.8**	149	75.1
482.sphinx3	359	54.3	**360**	**54.1**	360	54.1	359	54.3	**360**	**54.1**	360	54.1

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Compiler Invocation Notes

```
To compile these binaries, the Intel Compiler 13.1 was set up to
generate 64-bit binaries with the command:
"ipsxe-comp-vars.bat intel64 vs2010" (shortcut provided in the Intel(r)
Parallel Studio XE 2013 program folder)
```

Platform Notes

```
Sysinfo program C:\SPEC13.1/Docs/sysinfo
$Rev: 6775 $ $Date:: 2011-08-16 #$ \8787f7622badcf24e01c368b1db4377c
running on Clt7054D2179849 Thu Nov 28 02:09:37 2013

This section contains SUT (System Under Test) info as seen by
some common utilities.  To remove or add to this section, see:
```

Continued on next page

Platform Notes (Continued)

```
      http://www.spec.org/cpu2006/Docs/config.html#sysinfo

    Trying 'systeminfo'
    OS Name       : Microsoft Windows 7 Enterprise
    OS Version    : 6.1.7601 Service Pack 1 Build 7601
    System Manufacturer: INTEL_
    System Model  : DQ77MK__
    Processor(s)  : 1 Processor(s) Installed.
         [01]: Intel64 Family 6 Model 58 Stepping 9 GenuineIntel ~3001 Mhz
    BIOS Version  : Intel Corp. MKQ7710H.86A.0054.2012.1120.1444, 11/20/2012
    Total Physical Memory: 3,912 MB

    Trying 'wmic cpu get /value'
    DeviceID      : CPU0
    L2CacheSize   : 1024
    L3CacheSize   : 6144
    MaxClockSpeed : 3001
    Name          : Intel(R) Core(TM) i5-3330 CPU @ 3.00GHz
    NumberOfCores : 4
    NumberOfLogicalProcessors: 4

    (End of data from sysinfo program)
  BIOS: SATA mode set to RAID
  Windows Disk Driver: Intel Rapid Storage Technology 12.5.0.1066
  Windows Chipset Driver: Intel Chipset Driver 9.4.0.1027
```

Component Notes

```
Tested systems can be used with Shin-G ATX case,
PC Power and Cooling 1200W power supply
Micron MT8JTF25664AZ-1G6 Series Memory DIMMs
```

General Notes

```
OMP_NUM_THREADS set to number of processors cores
KMP_AFFINITY set to granularity=fine,scatter
Binaries compiled on a system with 1x Intel Core i7-860 CPU
+ 8GB memory using Windows 7 Enterprise 64-bit
```

Base Compiler Invocation

C benchmarks:

```
icl -Qvc10 -Qstd=c99
```

C++ benchmarks:

```
icl -Qvc10
```

Continued on next page

Base Compiler Invocation (Continued)

Fortran benchmarks:
ifort

Benchmarks using both Fortran and C:
icl -Qvc10 -Qstd=c99 ifort

Base Portability Flags

410.bwaves: -DSPEC_CPU_P64
416.gamess: -DSPEC_CPU_P64
433.milc: -DSPEC_CPU_P64
434.zeusmp: -DSPEC_CPU_P64
435.gromacs: -DSPEC_CPU_P64
436.cactusADM: -DSPEC_CPU_P64 -names:lowercase /assume:underscore
437.leslie3d: -DSPEC_CPU_P64
444.namd: -DSPEC_CPU_P64 /TP
447.dealII: -DSPEC_CPU_P64 -DDEAL_II_MEMBER_VAR_SPECIALIZATION_BUG
-Qoption,cpp,--ms_incompat_treatment_of_commas_in_macros
450.soplex: -DSPEC_CPU_P64
453.povray: -DSPEC_CPU_P64 -DSPEC_CPU_NEED_INVHYP -DNEED_INVHYP
454.calculix: -DSPEC_CPU_P64 -DSPEC_CPU_NOZMODIFIER -names:lowercase
459.GemsFDTD: -DSPEC_CPU_P64
465.tonto: -DSPEC_CPU_P64
470.lbm: -DSPEC_CPU_P64
481.wrf: -DSPEC_CPU_P64 -DSPEC_CPU_WINDOWS_ICL
482.sphinx3: -DSPEC_CPU_P64

Base Optimization Flags

C benchmarks:
-QxAVX -Qipo -O3 -Qprec-div- -Qparallel -Qansi-alias -Qopt-prefetch
-Qauto-ilp32 /F1000000000

C++ benchmarks:
-QxAVX -Qipo -O3 -Qprec-div- -Qparallel -Qansi-alias -Qopt-prefetch
-Qcxx-features -Qauto-ilp32 /F1000000000 shlW64M.lib
-link /FORCE:MULTIPLE

Fortran benchmarks:
-QxAVX -Qipo -O3 -Qprec-div- -Qparallel -Qansi-alias -Qopt-prefetch
/F1000000000

Benchmarks using both Fortran and C:
-QxAVX -Qipo -O3 -Qprec-div- -Qparallel -Qansi-alias -Qopt-prefetch
-Qauto-ilp32 /F1000000000

Peak Compiler Invocation

C benchmarks:
```
icl -Qvc10 -Qstd=c99
```

C++ benchmarks:
```
icl -Qvc10
```

Fortran benchmarks:
```
ifort
```

Benchmarks using both Fortran and C:
```
icl -Qvc10 -Qstd=c99 ifort
```

Peak Portability Flags

```
Same as Base Portability Flags
```

Peak Optimization Flags

C benchmarks:

433.milc: `basepeak = yes`

470.lbm: `basepeak = yes`

482.sphinx3: `basepeak = yes`

C++ benchmarks:

444.namd: `-QxAVX`(pass 2) `-Qprof_gen`(pass 1) `-Qprof_use`(pass 2) `-Qipo -O3 -Qprec-div- -Oa -Qauto-ilp32 /F1000000000 shlW64M.lib -link /FORCE:MULTIPLE`

447.dealII: `basepeak = yes`

450.soplex: `basepeak = yes`

453.povray: `-QxAVX`(pass 2) `-Qprof_gen`(pass 1) `-Qprof_use`(pass 2) `-Qipo -O3 -Qprec-div- -Qunroll4 -Qansi-alias -Qauto-ilp32 /F1000000000 shlW64M.lib -link /FORCE:MULTIPLE`

Fortran benchmarks:

410.bwaves: `basepeak = yes`

416.gamess: `-QxAVX`(pass 2) `-Qprof_gen`(pass 1) `-Qprof_use`(pass 2) `-Qipo -O3 -Qprec-div- -Qunroll2 -Ob0 -Qansi-alias -Qscalar-rep- /F1000000000`

Continued on next page

Peak Optimization Flags (Continued)

434.zeusmp: basepeak = yes

437.leslie3d: basepeak = yes

459.GemsFDTD: basepeak = yes

465.tonto: -QxAVX(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2) -Qipo -O3 -Qprec-div- -Qunroll4 -Qauto -Qinline-calloc /F1000000000

Benchmarks using both Fortran and C:

435.gromacs: basepeak = yes

436.cactusADM: basepeak = yes

454.calculix: basepeak = yes

481.wrf: basepeak = yes

The flags file that was used to format this result can be browsed at
http://www.spec.org/cpu2006/flags/Intel-ic13.1-official-windows.html

You can also download the XML flags source by saving the following link:
http://www.spec.org/cpu2006/flags/Intel-ic13.1-official-windows.xml

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.2.
Report generated on Tue Sep 9 10:56:01 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 15 July 2014.