# SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Hewlett-Packard Company

ProLiant DL360 Gen9
(3.20 GHz, Intel Xeon E5-2667 v3)

SPECfp®2006 = 118

SPECfp_base2006 = 113

**CPU2006 license:** 3
**Test sponsor:** Hewlett-Packard Company
**Tested by:** Hewlett-Packard Company

**Test date:** Jul-2014
**Hardware Availability:** Sep-2014
**Software Availability:** Jun-2014




## Hardware

| | |
|---|---|
| CPU Name: | Intel Xeon E5-2667 v3 |
| CPU Characteristics: | Intel Turbo Boost Technology up to 3.60 GHz |
| CPU MHz: | 3200 |
| FPU: | Integrated |
| CPU(s) enabled: | 16 cores, 2 chips, 8 cores/chip |
| CPU(s) orderable: | 1,2 chip |
| Primary Cache: | 32 KB I + 32 KB D on chip per core |
| Secondary Cache: | 256 KB I+D on chip per core |

Continued on next page

## Software

| | |
|---|---|
| Operating System: | Red Hat Enterprise Linux Server release 7.0 (Maipo)<br>Kernel 3.10.0-123.el7.x86_64 |
| Compiler: | C/C++: Version 14.0.0.080 of Intel C++ Studio XE for Linux;<br>Fortran: Version 14.0.0.080 of Intel Fortran Studio XE for Linux |
| Auto Parallel: | Yes |
| File System: | xfs |

Continued on next page

# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Hewlett-Packard Company

ProLiant DL360 Gen9
(3.20 GHz, Intel Xeon E5-2667 v3)

SPECfp2006 = 118

SPECfp_base2006 = 113

**CPU2006 license:** 3
**Test sponsor:** Hewlett-Packard Company
**Tested by:** Hewlett-Packard Company

**Test date:** Jul-2014
**Hardware Availability:** Sep-2014
**Software Availability:** Jun-2014

| | |
|---|---|
| L3 Cache: | 20 MB I+D on chip per chip |
| Other Cache: | None |
| Memory: | 256 GB (16 x 16 GB 2Rx4 PC4-2133P-R) |
| Disk Subsystem: | 1 x 400 GB SAS SSD, RAID 0 |
| Other Hardware: | None |

| | |
|---|---|
| System State: | Run level 3 (multi-user) |
| Base Pointers: | 64-bit |
| Peak Pointers: | 32/64-bit |
| Other Software: | None |

## Results Table

| Benchmark | Base | | | | | | Peak | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | Seconds | Ratio | Seconds | Ratio | Seconds | Ratio | Seconds | Ratio | Seconds | Ratio | Seconds | Ratio |
| 410.bwaves | **24.8** | **548** | 24.8 | 548 | 24.6 | 552 | **24.8** | **548** | 24.8 | 548 | 24.6 | 552 |
| 416.gamess | 486 | 40.3 | 484 | 40.5 | **485** | **40.4** | **431** | **45.4** | 432 | 45.3 | 431 | 45.4 |
| 433.milc | 125 | 73.7 | **125** | **73.5** | 125 | 73.5 | 124 | 73.9 | **124** | **73.7** | 125 | 73.6 |
| 434.zeusmp | 43.6 | 209 | **43.0** | **212** | 43.0 | 212 | 43.6 | 209 | **43.0** | **212** | 43.0 | 212 |
| 435.gromacs | 143 | 50.0 | **143** | **50.0** | 142 | 50.1 | 143 | 50.0 | **143** | **50.0** | 142 | 50.1 |
| 436.cactusADM | **15.3** | **781** | 15.1 | 792 | 15.3 | 781 | **15.3** | **781** | 15.1 | 792 | 15.3 | 781 |
| 437.leslie3d | **26.0** | **361** | 27.0 | 348 | 25.6 | 367 | **26.0** | **361** | 27.0 | 348 | 25.6 | 367 |
| 444.namd | 284 | 28.2 | 285 | 28.2 | **284** | **28.2** | **276** | **29.1** | 275 | 29.1 | 276 | 29.1 |
| 447.dealII | **187** | **61.2** | 187 | 61.2 | 190 | 60.3 | **187** | **61.2** | 187 | 61.2 | 190 | 60.3 |
| 450.soplex | 193 | 43.3 | **195** | **42.8** | 197 | 42.4 | 193 | 43.3 | **195** | **42.8** | 197 | 42.4 |
| 453.povray | **88.9** | **59.9** | 89.8 | 59.3 | 88.7 | 60.0 | **80.0** | **66.5** | 80.1 | 66.5 | 79.7 | 66.7 |
| 454.calculix | **164** | **50.4** | 167 | 49.3 | 163 | 50.7 | **146** | **56.5** | 146 | 56.5 | 146 | 56.4 |
| 459.GemsFDTD | 45.4 | 234 | 48.8 | 218 | **48.2** | **220** | **40.5** | **262** | 40.3 | 263 | 40.7 | 261 |
| 465.tonto | 211 | 46.6 | 209 | 47.1 | **210** | **46.9** | 179 | 54.9 | **179** | **55.0** | 179 | 55.0 |
| 470.lbm | **19.8** | **694** | 19.8 | 694 | 20.0 | 687 | **19.8** | **694** | 19.8 | 694 | 20.0 | 687 |
| 481.wrf | 94.2 | 119 | **95.4** | **117** | 97.2 | 115 | 94.2 | 119 | **95.4** | **117** | 97.2 | 115 |
| 482.sphinx3 | 230 | 84.8 | 231 | 84.3 | **230** | **84.7** | 230 | 84.8 | 231 | 84.3 | **230** | **84.7** |

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Operating System Notes

```
Stack size set to unlimited using "ulimit -s unlimited"
Transparent Huge Pages enabled with:
 echo always > /sys/kernel/mm/transparent_hugepage/enabled
```

## Platform Notes

```
BIOS Configuration:
 Intel Hyperthreading set to Disabled
 HP Power Profile set to Maximum Performance
 Thermal Configuration set to Maximum Cooling
 Collaborative Power Control set to Disabled
 QPI Snoop Configuration set to Home Snoop
 Processor Power and Utlization Monitoring set to Disabled
 Memory Patrol Scrubbing set to Disabled
```

Continued on next page

## Platform Notes (Continued)

```
Memory Refresh Rate set to 1x Refresh

Sysinfo program /home/cpu2006/config/sysinfo.rev6818
$Rev: 6818 $ $Date:: 2012-07-17 #$ e86d102572650a6e4d596a3cee98f191
running on localhost.localdomain Mon Jul 21 11:46:40 2014

This section contains SUT (System Under Test) info as seen by
some common utilities.  To remove or add to this section, see:
  http://www.spec.org/cpu2006/Docs/config.html#sysinfo

From /proc/cpuinfo
   model name : Intel(R) Xeon(R) CPU E5-2667 v3 @ 3.20GHz
      2 "physical id"s (chips)
      16 "processors"
   cores, siblings (Caution: counting these is hw and system dependent.  The
   following excerpts from /proc/cpuinfo might not be reliable.  Use with
   caution.)
      cpu cores : 8
      siblings  : 8
      physical 0: cores 0 1 2 3 4 5 6 7
      physical 1: cores 0 1 2 3 4 5 6 7
   cache size : 20480 KB

From /proc/meminfo
   MemTotal:       263846844 kB
   HugePages_Total:       0
   Hugepagesize:       2048 kB

From /etc/*release* /etc/*version*
   os-release:
      NAME="Red Hat Enterprise Linux Server"
      VERSION="7.0 (Maipo)"
      ID="rhel"
      ID_LIKE="fedora"
      VERSION_ID="7.0"
      PRETTY_NAME="Red Hat Enterprise Linux Server 7.0 (Maipo)"
      ANSI_COLOR="0;31"
      CPE_NAME="cpe:/o:redhat:enterprise_linux:7.0:GA:server"
   redhat-release: Red Hat Enterprise Linux Server release 7.0 (Maipo)
   system-release: Red Hat Enterprise Linux Server release 7.0 (Maipo)
   system-release-cpe: cpe:/o:redhat:enterprise_linux:7.0:ga:server

uname -a:
   Linux localhost.localdomain 3.10.0-123.el7.x86_64 #1 SMP Mon May 5 11:16:57
   EDT 2014 x86_64 x86_64 x86_64 GNU/Linux

run-level 3 Jul 21 11:14

SPEC is set to: /home/cpu2006
   Filesystem            Type  Size  Used Avail Use% Mounted on
   /dev/mapper/rhel-home xfs   318G  4.0G  314G   2% /home
```

Continued on next page

## Platform Notes (Continued)

```
 Additional information from dmidecode:
   BIOS HP P89 07/11/2014
   Memory:
    16x HP NOT AVAILABLE 16 GB 2133 MHz 2 rank
    8x UNKNOWN NOT AVAILABLE

 (End of data from sysinfo program)
Regarding the sysinfo display about the memory installed, the correct amount of
memory is 256 GB and the dmidecode description should have one line reading as:
 16x HP NOT AVAILABLE 16 GB 2133 MHz 2 rank
```

## General Notes

```
Environment variables set by runspec before the start of the run:
KMP_AFFINITY = "granularity=fine,compact"
LD_LIBRARY_PATH = "/home/cpu2006/libs/32:/home/cpu2006/libs/64:/home/cpu2006/sh"
OMP_NUM_THREADS = "16"

 Binaries compiled on a system with 1x Core i7-860 CPU + 8GB
 memory using RedHat EL 6.4
```

## Base Compiler Invocation

C benchmarks:
```
icc   -m64
```

C++ benchmarks:
```
icpc  -m64
```

Fortran benchmarks:
```
ifort -m64
```

Benchmarks using both Fortran and C:
```
icc   -m64 ifort -m64
```

## Base Portability Flags

```
    410.bwaves: -DSPEC_CPU_LP64
    416.gamess: -DSPEC_CPU_LP64
      433.milc: -DSPEC_CPU_LP64
    434.zeusmp: -DSPEC_CPU_LP64
    435.gromacs: -DSPEC_CPU_LP64 -nofor_main
  436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
    437.leslie3d: -DSPEC_CPU_LP64
      444.namd: -DSPEC_CPU_LP64
    447.dealII: -DSPEC_CPU_LP64
```

Continued on next page

## Base Portability Flags (Continued)

450.soplex: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
470.lbm: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
482.sphinx3: -DSPEC_CPU_LP64

## Base Optimization Flags

C benchmarks:
-xCORE-AVX2 -ipo -O3 -no-prec-div -parallel -opt-prefetch -ansi-alias

C++ benchmarks:
-xCORE-AVX2 -ipo -O3 -no-prec-div -opt-prefetch -ansi-alias

Fortran benchmarks:
-xCORE-AVX2 -ipo -O3 -no-prec-div -parallel -opt-prefetch

Benchmarks using both Fortran and C:
-xCORE-AVX2 -ipo -O3 -no-prec-div -parallel -opt-prefetch -ansi-alias

## Peak Compiler Invocation

C benchmarks:
icc -m64

C++ benchmarks:
icpc -m64

Fortran benchmarks:
ifort -m64

Benchmarks using both Fortran and C:
icc -m64 ifort -m64

## Peak Portability Flags

Same as Base Portability Flags

# Peak Optimization Flags

C benchmarks:

433.milc: -xCORE-AVX2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2) -auto-ilp32 -ansi-alias

470.lbm: basepeak = yes

482.sphinx3: basepeak = yes

C++ benchmarks:

444.namd: -xCORE-AVX2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2) -fno-alias -auto-ilp32

447.dealII: basepeak = yes

450.soplex: basepeak = yes

453.povray: -xCORE-AVX2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2) -unroll4 -ansi-alias

Fortran benchmarks:

410.bwaves: basepeak = yes

416.gamess: -xCORE-AVX2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2) -unroll2 -inline-level=0 -scalar-rep-

434.zeusmp: basepeak = yes

437.leslie3d: basepeak = yes

459.GemsFDTD: -xCORE-AVX2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2) -unroll2 -inline-level=0 -opt-prefetch -parallel

465.tonto: -xCORE-AVX2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2) -inline-calloc -opt-malloc-options=3 -auto -unroll4

Benchmarks using both Fortran and C:

435.gromacs: basepeak = yes

436.cactusADM: basepeak = yes

Continued on next page

# Peak Optimization Flags (Continued)

454.calculix: `-xCORE-AVX2 -ipo -O3 -no-prec-div -auto-ilp32 -ansi-alias`

481.wrf: `basepeak = yes`

The flags files that were used to format this result can be browsed at
`http://www.spec.org/cpu2006/flags/Intel-ic14.0-official-linux64.20140128.html`
`http://www.spec.org/cpu2006/flags/HP-Platform-Flags-Intel-V1.2-HSW-revA.html`

You can also download the XML flags sources by saving the following links:
`http://www.spec.org/cpu2006/flags/Intel-ic14.0-official-linux64.20140128.xml`
`http://www.spec.org/cpu2006/flags/HP-Platform-Flags-Intel-V1.2-HSW-revA.xml`


SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.


For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.2.
Report generated on Wed Sep 24 16:18:58 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 24 September 2014.