SPEC® CINT2006 Result

Copyright 2006-2015 Standard Performance Evaluation Corporation

SGI

SGI UV 300 (Intel Xeon E7-8890 v2, 2.8 GHz)

SPECint®_rate2006 = 4730

SPECint_rate_base2006 = 4580

CPU2006 license: 4
Test sponsor: SGI
Tested by: SGI

Test date: Jan-2015
Hardware Availability: Dec-2014
Software Availability: Nov-2014



Hardware

CPU Name:	Intel Xeon E7-8890 v2
CPU Characteristics:	Intel Turbo Boost Technology up to 3.40 GHz
CPU MHz:	2800
FPU:	Integrated
CPU(s) enabled:	120 cores, 8 chips, 15 cores/chip, 2 threads/core
CPU(s) orderable:	4-32 chips
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	256 KB I+D on chip per core
L3 Cache:	37.5 MB I+D on chip per chip
Other Cache:	None
Memory:	1 TB (128 x 8 GB 2Rx4 PC3-14900R-13, ECC, running at 1333 MHz)
Disk Subsystem:	1 TB tmpfs
Other Hardware:	None

Software

Operating System:	SUSE Linux Enterprise Server 11 (x86_64) SP3, Kernel 3.0.101-0.46-default
Compiler:	C/C++: Version 15.0.0.090 of Intel C++ Studio XE for Linux
Auto Parallel:	No
File System:	tmpfs
System State:	Run level 3 (multi-user)
Base Pointers:	32-bit
Peak Pointers:	32/64-bit
Other Software:	Microquill SmartHeap V10.0 SGI Foundation Software 2.11, Build 711rp42.sles11sp3-1412152100

SPEC CINT2006 Result

Copyright 2006-2015 Standard Performance Evaluation Corporation

SGI

SGI UV 300 (Intel Xeon E7-8890 v2, 2.8 GHz)

SPECint_rate2006 = 4730

SPECint_rate_base2006 = 4580

CPU2006 license: 4
Test sponsor: SGI
Tested by: SGI

Test date: Jan-2015
Hardware Availability: Dec-2014
Software Availability: Nov-2014

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	240	**655**	**3580**	656	3580	654	3580	240	548	4280	**550**	**4260**	550	4260
401.bzip2	240	**945**	**2450**	945	2450	944	2450	240	**941**	**2460**	942	2460	941	2460
403.gcc	240	544	3550	**544**	**3550**	545	3550	240	543	3560	541	3570	**541**	**3570**
429.mcf	240	352	6220	**352**	**6210**	352	6210	240	352	6220	**352**	**6210**	352	6210
445.gobmk	240	**695**	**3620**	696	3620	694	3630	240	**688**	**3660**	688	3660	687	3670
456.hmmer	240	**339**	**6600**	339	6610	340	6580	240	**303**	**7400**	302	7400	303	7390
458.sjeng	240	**804**	**3610**	804	3610	804	3610	240	787	3690	784	3700	**786**	**3690**
462.libquantum	240	**157**	**31700**	157	31700	157	31800	240	**157**	**31700**	157	31700	157	31800
464.h264ref	240	884	6010	**883**	**6010**	883	6020	240	860	6170	854	6220	**855**	**6210**
471.omnetpp	240	701	2140	702	2140	**701**	**2140**	240	**676**	**2220**	676	2220	675	2220
473.astar	240	**642**	**2630**	641	2630	643	2620	240	**642**	**2630**	641	2630	643	2620
483.xalancbmk	240	352	4700	351	4710	**352**	**4710**	240	352	4700	351	4710	**352**	**4710**

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Submit Notes

```
The numactl mechanism was used to bind copies to processors. The config file option 'submit'
was used to generate numactl commands to bind each copy to a specific processor.
For details, please see the config file.
```

Operating System Notes

```
Stack size set to unlimited using "ulimit -s unlimited"

Tmpfs filesystem set up with:
  mkdir -p /mnt/shm
  mount -t tmpfs -o size=1024g,rw tmpfs /mnt/shm/

Turbo mode activated with:
  modprobe acpi_cpufreq
  cpupower frequency-set -u 3400MHz -d 3400MHz -g performance
```

General Notes

```
Environment variables set by runspec before the start of the run:
LD_LIBRARY_PATH = "/mnt/shm/cpu2006-1.2/libs/32:/mnt/shm/cpu2006-1.2/libs/64:/mnt/shm/cpu2006-1.2/sh"

 Transparent Huge Pages enabled with:
 echo always > /sys/kernel/mm/transparent_hugepage/enabled
 Filesystem page cache cleared with:
 echo 1 > /proc/sys/vm/drop_caches
```

Base Compiler Invocation

C benchmarks:
```
icc -m32 -L/sw/sdev/intel/parallel_studio_2015/composer_xe_2015/lib/ia32/
```

C++ benchmarks:
```
icpc -m32 -L/sw/sdev/intel/parallel_studio_2015/composer_xe_2015/lib/ia32/
```

Base Portability Flags

400.perlbench: `-DSPEC_CPU_LINUX_IA32`
462.libquantum: `-DSPEC_CPU_LINUX`
483.xalancbmk: `-DSPEC_CPU_LINUX`

Base Optimization Flags

C benchmarks:
```
-xSSE4.2 -ipo -O3 -no-prec-div -opt-prefetch -opt-mem-layout-trans=3
```

C++ benchmarks:
```
-xSSE4.2 -ipo -O3 -no-prec-div -opt-prefetch -opt-mem-layout-trans=3
-Wl,-z,muldefs -L/sh -lsmartheap
```

Base Other Flags

C benchmarks:

403.gcc: `-Dalloca=_alloca`

Peak Compiler Invocation

C benchmarks (except as noted below):
```
icc -m32 -L/sw/sdev/intel/parallel_studio_2015/composer_xe_2015/lib/ia32/
```

400.perlbench: `icc -m64`

401.bzip2: `icc -m64`

456.hmmer: `icc -m64`

458.sjeng: `icc -m64`

C++ benchmarks:
```
icpc -m32 -L/sw/sdev/intel/parallel_studio_2015/composer_xe_2015/lib/ia32/
```

Peak Portability Flags

400.perlbench: -DSPEC_CPU_LP64 -DSPEC_CPU_LINUX_X64
401.bzip2: -DSPEC_CPU_LP64
456.hmmer: -DSPEC_CPU_LP64
458.sjeng: -DSPEC_CPU_LP64
462.libquantum: -DSPEC_CPU_LINUX
483.xalancbmk: -DSPEC_CPU_LINUX

Peak Optimization Flags

C benchmarks:

400.perlbench: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2) -auto-ilp32

401.bzip2: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2) -opt-prefetch -auto-ilp32 -ansi-alias

403.gcc: -xSSE4.2 -ipo -O3 -no-prec-div

429.mcf: basepeak = yes

445.gobmk: -xSSE4.2(pass 2) -prof-gen(pass 1) -prof-use(pass 2) -ansi-alias -opt-mem-layout-trans=3

456.hmmer: -xSSE4.2 -ipo -O3 -no-prec-div -unroll2 -auto-ilp32

458.sjeng: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2) -unroll4 -auto-ilp32

462.libquantum: basepeak = yes

464.h264ref: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2) -unroll2 -ansi-alias

C++ benchmarks:

471.omnetpp: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2) -ansi-alias -opt-ra-region-strategy=block -Wl,-z,muldefs -L/sh -lsmartheap

473.astar: basepeak = yes

Continued on next page

Peak Optimization Flags (Continued)

483.xalancbmk: `basepeak = yes`

Peak Other Flags

C benchmarks:

403.gcc: `-Dalloca=_alloca`

The flags files that were used to format this result can be browsed at
`http://www.spec.org/cpu2006/flags/SGI-UV300-Platform-Flags.html`
`http://www.spec.org/cpu2006/flags/Intel-ic15.0-official-linux64.html`

You can also download the XML flags sources by saving the following links:
`http://www.spec.org/cpu2006/flags/SGI-UV300-Platform-Flags.xml`
`http://www.spec.org/cpu2006/flags/Intel-ic15.0-official-linux64.xml`

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.2.
Report generated on Tue Jan 27 13:29:47 2015 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 27 January 2015.