



# SPEC® CFP2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

Huawei

Huawei CH222 V3 (Intel Xeon E5-2690 v4)

CPU2006 license: 3175

Test sponsor: Huawei

Tested by: Huawei

**SPECfp®2006 =**

**SPECfp\_base2006 = 10.1 NC**

Test date: Feb-2016

Hardware Availability: Mar-2016

Software Availability: Mar-2016

**SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the memory was not up policy on <a href="http://spec.org/cpu2006/Docs/runrules.html#rule\_1.3.2">SPEC CPU run**

410.bwaves |

416.gamess |

433.milc |

434.zeusmp |

435.gromacs |

436.cactusADM |

437.leslie3d |

444.namd |

447.dealII |

450.soplex |

453.povray |

454.calculix |

459.GemsFDTD |

465.tonto |

470.lbm |

481.wrf |

482.sphinx3 |



# SPEC CFP2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

Huawei

Huawei CH222 V3 (Intel Xeon E5-2690 v4)

SPECfp2006 =

SPECfp\_base2006 = NC

CPU2006 license: 3175

Test sponsor: Huawei

Tested by: Huawei

Test date: Feb-2016

Hardware Availability: Mar-2016

Software Availability: Mar-2016

**SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the memory was not up policy on <a href="http://spec.org/cpu2006/Docs/runrules.html#rule\_1.3.2">SPEC CPU run**

Hardware		Software	
CPU Name:	Intel Xeon E5-2690 v4	Operating System:	Red Hat Enterprise Linux Server release 7.0 (Nepo)
CPU Characteristics:	Intel Turbo Boost Technology up to 3.50 GHz	Compiler:	3.1.1-123.el7.x86_64
CPU MHz:	2600	Auto Parallel:	C/C++: Version 16.0.0.101 of Intel C++ Studio XE for Linux;
FPU:	Integrated	File System:	Fortran: Version 16.0.0.101 of Intel Fortran Studio XE for Linux
CPU(s) enabled:	28 cores, 2 chips, 14 cores/chip	System Date:	Yes
CPU(s) orderable:	1,2 chip	Base Pointers:	xfs
Primary Cache:	32 KB I + 32 KB D on chip per core	Peak Pointers:	Run level 3 (multi-user)
Secondary Cache:	256 KB I+D on chip per core	Other Software:	64-bit
L3 Cache:	35 MB I+D on chip per chip		32/64-bit
Other Cache:	None		None
Memory:	256 GB (16 x 16 GB 2Rx4 PC4-2400T-1 x 600GB SAS, 10000 RPM)		
Disk Subsystem:			
Other Hardware:	None		

Non-compliant



# SPEC CFP2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

Huawei

Huawei CH222 V3 (Intel Xeon E5-2690 v4)

CPU2006 license: 3175

Test sponsor: Huawei

Tested by: Huawei

**SPECfp2006 =**

**SPECfp\_base2006 = NC**

Test date: Feb-2016

Hardware Availability: Mar-2016

Software Availability: Mar-2016

**SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the memory was not up policy on <a href="http://spec.org/cpu2006/Docs/runrules.html#rule\_1.3.2">SPEC CPU run**

## Results Table

Benchmark	Base						Peak					
	Seconds	Ratio										
410.bwaves	NC	NC										
416.gamess	NC	NC										
433.milc	NC	NC										
434.zeusmp	NC	NC										
435.gromacs	NC	NC										
436.cactusADM	NC	NC										
437.leslie3d	NC	NC										
444.namd	NC	NC										
447.dealII	NC	NC										
450.soplex	NC	NC										
453.povray	NC	NC										
454.calculix	NC	NC										
459.GemsFDTD	NC	NC										
465.tonto	NC	NC										
470.lbm	NC	NC										
481.wrf	NC	NC										
482.sphinx3	NC	NC										

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Operating System Notes

Each size limit to unlimited using "ulimit -s unlimited"

## Platform Notes

### BIOS configuration:

Set Power Efficiency Mode to Custom

Set Snoop Mode to HS mode

Set Patrol Scrub to Disable

Set Hyper-Threading to Disable

Sysinfo program /spec/spec16/config/sysinfo.rev6914

\$Rev: 6914 \$ \$Date::: 2014-06-25 ## e3fbb8667b5a285932ceab81e28219e1

running on localhost.localdomain Mon Nov 3 05:32:23 2014

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

Huawei

Huawei CH222 V3 (Intel Xeon E5-2690 v4)

CPU2006 license: 3175

Test sponsor: Huawei

Tested by: Huawei

SPECfp2006 =

SPECfp\_base2006 = NC

Test date: Feb-2016

Hardware Availability: Mar-2016

Software Availability: Mar-2016

**SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the memory was not up policy on <a href="http://spec.org/cpu2006/Docs/runrules.html#rule\_1.3.2">SPEC CPU run**

## Platform Notes (Continued)

This section contains SUT (System Under Test) info as seen via some common utilities. To remove or add to this section, see:

<http://www.spec.org/cpu2006/Docs/config.html#Sutinfo>

From /proc/cpuinfo  
model name : Intel(R) Xeon(R) CPU E5-2690 v2 @ 2.60GHz  
 2 "physical id"s (chips)  
 28 "processors"  
cores, siblings (Caution: counting these is hw and system dependent. The following excerpts from /proc/cpuinfo might not be reliable. Use with caution.)  
 cpu cores : 14  
 siblings : 14  
 physical 0: cores 0 1 2 3 4 5 6 7 8 9 10 11 12 13 14  
 physical 1: cores 0 1 2 3 4 5 6 7 8 9 10 11 12 13 14  
cache size : 35840 KB

From /proc/meminfo  
MemTotal: 26356974 kB  
HugePages\_Total: 0  
Hugepagesize: 48 kB

From /etc/\*release\* /etc/\*version\*  
os-release:  
 NAME="Red Hat Enterprise Linux Server"  
 VERSION="7.0 (Maipo)"  
 ID="rhel"  
 ID\_LIKE="fedora"  
 VERSION\_ID="7.0"  
 PRETTY\_NAME="Red Hat Enterprise Linux Server 7.0 (Maipo)"  
 QR="0;31"  
 CPE\_NAME="cpe:/o:redhat:enterprise\_linux:7.0:GA:server"  
redhat-release: Red Hat Enterprise Linux Server release 7.0 (Maipo)  
system-release: Red Hat Enterprise Linux Server release 7.0 (Maipo)  
system-release-cpe: cpe:/o:redhat:enterprise\_linux:7.0:ga:server  
  
uname -a:  
Linux localhost.localdomain 3.10.0-123.el7.x86\_64 #1 SMP Mon May 5 11:16:57  
EDT 2014 x86\_64 x86\_64 x86\_64 GNU/Linux

run-level 3 Nov 3 00:09

SPEC is set to: /spec/spec16

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

Huawei

Huawei CH222 V3 (Intel Xeon E5-2690 v4)

CPU2006 license: 3175

Test sponsor: Huawei

Tested by: Huawei

SPECfp2006 =

SPECfp\_base2006 = NC

Test date: Feb-2016

Hardware Availability: Mar-2016

Software Availability: Mar-2016

**SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the memory was not up policy on <a href="http://spec.org/cpu2006/Docs/runrules.html#rule\_1.3.2">SPEC CPU run**

## Platform Notes (Continued)

Filesystem	Type	Size	Used	Avail	Use%	Mounted on
/dev/sda2	xfs	549G	10G	539G	2%	/

Additional information from dmidecode:

Warning: Use caution when you interpret this section. The 'dmidecode' program reads system data which is "intended to allow hardware to be accurately determined", but the intent may not be met, as there are frequent changes to hardware, firmware, and the "DMTF SMBIOS" standard.

BIOS Insyde Corp. 7.11 02/14/2016

Memory:

8x NO DIMM NO DIMM	3 rank
8x Samsung M393A2G40EB1	CRC 16 GB 1 rank 2400 MHz
8x Samsung M393A2G40EB1	CRC 16 GB 2 rank 2400 MHz

(End of data from sysinfo program)

## General Notes

Environment variables set by runspec before the start of the run:

KMP\_AFFINITY = "granularity=fine,compact,1,0"  
LD\_LIBRARY\_PATH = "/spec/spec16/libs/32:/spec/spec16/libs/64:/spec/spec16/sh"  
OMP\_NUM\_THREADS = "2"

Binaries compiled on a system with 1x Intel Core i5-4670K CPU + 32GB memory using RedHat EL 7.1

Transparent Huge Pages enabled with:

```
echo always >/sys/kernel/mm/transparent_hugepage/enabled
runspec command invoked through numactl i.e.:
numactl --interleave=all runspec <etc>
      CH121 V3 and Huawei CH222 V3
are electronically equivalent.
```

The results have been measured on a Huawei CH121 V3 model

## Base Compiler Invocation

C benchmarks:

icc -m64

C++ benchmarks:

icpc -m64

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

Huawei

Huawei CH222 V3 (Intel Xeon E5-2690 v4)

CPU2006 license: 3175

Test sponsor: Huawei

Tested by: Huawei

**SPECfp2006 =**

**SPECfp\_base2006 = NC**

Test date: Feb-2016

Hardware Availability: Mar-2016

Software Availability: Mar-2016

**SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the memory was not up policy on <a href="http://spec.org/cpu2006/Docs/runrules.html#rule\_1.3.2">SPEC CPU run**

## Base Compiler Invocation (Continued)

Fortran benchmarks:  
ifort -m64

Benchmarks using both Fortran and C:  
icc -m64 ifort -m64

## Base Portability Flags

410.bwaves: -DSPEC\_CPU\_LP64  
416.gamess: -DSPEC\_CPU\_LP64  
433.milc: -DSPEC\_CPU\_LP64  
434.zeusmp: -DSPEC\_CPU\_LP64  
435.gromacs: -DSPEC\_CPU\_LP64 -nofor\_main  
436.cactusADM: -DSPEC\_CPU\_LP64 -nofor\_main  
437.leslie3d: -DSPEC\_CPU\_LP64  
444.namd: -DSPEC\_CPU\_LP64  
447.dealII: -DSPEC\_CPU\_LP64  
450.soplex: -DSPEC\_CPU\_LP64  
453.povray: -DSPEC\_CPU\_LP64  
454.calculix: -DSPEC\_CPU\_LP64 -nofor\_main  
459.GemsFDTD: -DSPEC\_CPU\_LP64  
465.tonto: -DSPEC\_CPU\_LP64  
470.lbm: -DSPEC\_CPU\_LP64  
481.wrf: -DSPEC\_CPU\_LP64 -DSPEC\_CPU\_CASE\_FLAG -DSPEC\_CPU\_LINUX  
482.sphinx3: -DSPEC\_CPU\_LP64

## Base Optimization Flags

C benchmarks:  
-xCORE-AVX2 -ipo -O3 -no-prec-div -parallel -opt-prefetch  
-ansi-alias

C++ benchmarks:  
-xCORE-AVX2 -ipo -O3 -no-prec-div -opt-prefetch -ansi-alias

Fortran benchmarks:  
-xCORE-AVX2 -ipo -O3 -no-prec-div -parallel -opt-prefetch

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

Huawei

Huawei CH222 V3 (Intel Xeon E5-2690 v4)

CPU2006 license: 3175

Test sponsor: Huawei

Tested by: Huawei

SPECfp2006 =

SPECfp\_base2006 = NC

Test date: Feb-2016

Hardware Availability: Mar-2016

Software Availability: Mar-2016

**SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the memory was not up policy on <a href="http://spec.org/cpu2006/Docs/runrules.html#rule\_1.3.2">SPEC CPU run </a>**

## Base Optimization Flags (Continued)

Benchmarks using both Fortran and C:

-xCORE-AVX2 -ipo -O3 -no-prec-div -parallel -opt-level=3  
-ansi-alias

## Peak Compiler Invocation

C benchmarks:

icc -m64

C++ benchmarks:

icpc -m64

Fortran benchmarks:

ifort -m64

Benchmarks using both Fortran and C:

icc -m64 ifort -m64

## Peak Portability Flags

Same as Base Portability Flags

## Peak Optimization Flags

C benchmarks:

433.milc: basepeak = yes

470.lbm: basepeak = yes

482.sphinx3: basepeak = yes

C++ benchmarks:

444.namd: -xCORE-AVX2(pass 2) -prof-gen:threadsafe(pass 1)  
-ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2)  
-par-num-threads=1(pass 1) -prof-use(pass 2) -fno-alias  
-auto-ilp32

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

Huawei

Huawei CH222 V3 (Intel Xeon E5-2690 v4)

CPU2006 license: 3175

Test sponsor: Huawei

Tested by: Huawei

SPECfp2006 =

SPECfp\_base2006 = NC

Test date: Feb-2016

Hardware Availability: Mar-2016

Software Availability: Mar-2016

**SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the memory was not up policy on <a href="http://spec.org/cpu2006/Docs/runrules.html#rule\_1.3.2">SPEC CPU run general policy on <a href="https://www.spec.org/osg/policy.html#AppendixC">general**

## Peak Optimization Flags (Continued)

447.dealII: basepeak = yes

450.soplex: basepeak = yes

453.povray: -xCORE-AVX2(pass 2) -prof-gen:threadsafe(pass 1)  
-ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2)  
-par-num-threads=1(pass 1) -prof-use(pass 2) -unroll14  
-ansi-alias

Fortran benchmarks:

410.bwaves: basepeak = yes

416.gamess: -xCORE-AVX2(pass 2) -prof-gen:threadsafe(pass 1)  
-ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2)  
-par-num-threads=1(pass 1) -prof-use(pass 2) -unroll12  
-inline-level=0 -scalar-rep

434.zeusmp: basepeak = yes

437.leslie3d: basepeak = yes

459.GemsFDTD: -xCORE-AVX2(pass 2) -prof-gen:threadsafe(pass 1)  
-ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2)  
-par-num-threads=1(pass 1) -prof-use(pass 2) -unroll12  
-inline-level=0 -opt-prefetch -parallel

465.tonto: -xCORE-AVX2(pass 2) -prof-gen:threadsafe(pass 1)  
-ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2)  
-par-num-threads=1(pass 1) -prof-use(pass 2) -inline-calloc  
-opt-malloc-options=3 -auto -unroll14

Benchmarks using both Fortran and C:

435.gromacs: basepeak = yes

436.cactusADM: basepeak = yes

454.calculix: -xCORE-AVX2 -ipo -O3 -no-prec-div -auto-ilp32 -ansi-alias

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

Huawei

Huawei CH222 V3 (Intel Xeon E5-2690 v4)

CPU2006 license: 3175

Test sponsor: Huawei

Tested by: Huawei

**SPECfp2006 =**

**SPECfp\_base2006 = NC**

Test date: Feb-2016

Hardware Availability: Mar-2016

Software Availability: Mar-2016

**SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the memory was not up policy on <a href="http://spec.org/cpu2006/Docs/runrules.html#rule\_1.3.2">SPEC CPU run**

## Peak Optimization Flags (Continued)

481.wrf: basepeak = yes

The flags files that were used to form this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic16-official-linux64.html>

<http://www.spec.org/cpu2006/flags/Huawei-Platform-Settings-BDW-V1.0.html>

You can also download the XML flags source by saving the following links:

<http://www.spec.org/cpu2006/flags/Intel-ic16-official-linux64.xml>

<http://www.spec.org/cpu2006/flags/Huawei-Platform-Settings-BDW-V1.0.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.2.

Report generated on Fri Oct 21 15:55:14 2016 by SPEC CPU2006 PS/PDF formatter v6932.

Originally published on 7 April 2016.