SPEC® CINT2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

Huawei

Huawei CH121 V3 (Intel Xeon E5-2697A v4)

SPECint®2006 = NC

SPECint_base2006 = NC

CPU2006 license: 3175
Test sponsor: Huawei
Tested by: Huawei

Test date: Mar-2016
Hardware Availability: Mar-2016
Software Availability: Mar-2016

SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the memory was not a href="http://spec.org/cpu2006/Docs/runrules.html#rule_1.3.2">SPEC CPU ru up policy on <a href="https://www.spec.org/osg/policy.html#AppendixC">gener

400.perlbench
401.bzip2
403.gcc
429.mcf
445.gobmk
456.hmmer
458.sjeng
462.libquantum
464.h264ref
471.omnetpp
473.astar
483.xalancbmk

Non-Compliant

Hardware

CPU Name:	el Xeon E5-2697A v4
CPU Characteristics:	Intel Turbo Boost Technology up to 3.60 GHz
CPU MHz:	2600
FPU:	Integrated
CPU(s) enabled:	32 cores, 2 chips, 16 cores/chip
CPU(s) orderable:	1,2 chip
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	256 KB I+D on chip per core
L3 Cache:	40 MB I+D on chip per chip
Other Cache:	None
Memory:	256 GB (16 x 16 GB 2Rx4 PC4-2400T-R)
Disk Subsystem:	1 x 600GB SAS, 10000 RPM
Other Hardware:	None

Software

Operating System:	Red Hat Enterprise Linux Server release 7.0 (Maipo) 3.10.0-123.el7.x86_64
Compiler:	C/C++: Version 16.0.0.101 of Intel C++ Studio XE for Linux
Auto Parallel:	Yes
File System:	xfs
System State:	Run level 3 (multi-user)
Base Pointers:	32/64-bit
Peak Pointers:	32/64-bit
Other Software:	Microquill SmartHeap V10.2

SPEC CINT2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

Huawei

Huawei CH121 V3 (Intel Xeon E5-2697A v4)

SPECint2006 = NC

SPECint_base2006 = NC

CPU2006 license: 3175
Test sponsor: Huawei
Tested by: Huawei

Test date: Mar-2016
Hardware Availability: Mar-2016
Software Availability: Mar-2016

SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the memory was not a href="http://spec.org/cpu2006/Docs/runrules.html#rule_1.3.2">SPEC CPU ru up policy on <a href="https://www.spec.org/osg/policy.html#AppendixC">gener

Non-Compliant

Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC
401.bzip2	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC
403.gcc	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC
429.mcf	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC
445.gobmk	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC
456.hmmer	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC
458.sjeng	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC
462.libquantum	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC
464.h264ref	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC
471.omnetpp	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC
473.astar	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC
483.xalancbmk	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Submit Notes

```
The config file option 'submit' was used.
```

Operating System Notes

```
Stack size set to unlimited using "ulimit -s unlimited"
```

Platform Notes

```
BIOS configuration:
Set Power Efficiency Mode to Custom
Set Snoop Mode to ES mode
Set Patrol Scrub to Disable
Set Hyper-Threading to Disable
Sysinfo program /spec/spec16/config/sysinfo.rev6914
$Rev: 6914 $ $Date:: 2014-06-25 #$ e3fbb8667b5a285932ceab81e28219e1
running on localhost.localdomain Sun Nov 30 11:44:05 2014

This section contains SUT (System Under Test) info as seen by
some common utilities.  To remove or add to this section, see:
```

Continued on next page

SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the memory was not a href="http://spec.org/cpu2006/Docs/runrules.html#rule_1.3.2">SPEC CPU ru up policy on <a href="https://www.spec.org/osg/policy.html#AppendixC">gener

Non-Compliant

Platform Notes (Continued)

```
  http://www.spec.org/cpu2006/Docs/config.html#sysinfo

From /proc/cpuinfo
   model name : Intel(R) Xeon(R) CPU E5-2697A v4 @ 2.60GHz
      2 "physical id"s (chips)
      32 "processors"
   cores, siblings (Caution: counting these is hw and system dependent.  The
   following excerpts from /proc/cpuinfo might not be reliable.  Use with
   caution.)
      cpu cores : 16
      siblings  : 16
      physical 0: cores 0 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15
      physical 1: cores 0 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15
   cache size : 40960 KB

From /proc/meminfo
   MemTotal:       263569320 kB
   HugePages_Total:       0
   Hugepagesize:       2048 kB

From /etc/*release* /etc/*version*
   os-release:
      NAME="Red Hat Enterprise Linux Server"
      VERSION="7.0 (Maipo)"
      ID="rhel"
      ID_LIKE="fedora"
      VERSION_ID="7.0"
      PRETTY_NAME="Red Hat Enterprise Linux Server 7.0 (Maipo)"
      ANSI_COLOR="0;31"
      CPE_NAME="cpe:/o:redhat:enterprise_linux:7.0:GA:server"
   redhat-release: Red Hat Enterprise Linux Server release 7.0 (Maipo)
   system-release: Red Hat Enterprise Linux Server release 7.0 (Maipo)
   system-release-cpe: cpe:/o:redhat:enterprise_linux:7.0:ga:server

uname -a:
   Linux localhost.localdomain 3.10.0-123.el7.x86_64 #1 SMP Mon May 5 11:16:57
   EDT 2014 x86_64 x86_64 x86_64 GNU/Linux

run-level 3 Nov 30 05:54

SPEC is set to: /spec/spec16
   Filesystem     Type  Size  Used Avail Use% Mounted on
   /dev/sda2      xfs   549G   11G  538G   2% /
Additional information from dmidecode:
```

Continued on next page

SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the memory was not a href="http://spec.org/cpu2006/Docs/runrules.html#rule_1.3.2">SPEC CPU ru up policy on <a href="https://www.spec.org/osg/policy.html#AppendixC">gener

Non-Compliant

Platform Notes (Continued)

```
      Warning: Use caution when you interpret this section. The 'dmidecode' program
      reads system data which is "intended to allow hardware to be accurately
      determined", but the intent may not be met, as there are frequent changes to
      hardware, firmware, and the "DMTF SMBIOS" standard.

     BIOS Insyde Corp. 3.09 02/22/2016
     Memory:
      8x NO DIMM NO DIMM   3 rank
      8x Samsung M393A2G40EB1-CRC 16 GB 1 rank 2400 MHz
      8x Samsung M393A2G40EB1-CRC 16 GB 1 rank 2400 MHz

   (End of data from sysinfo program)
```

General Notes

```
Environment variables set by runspec before the start of the run:
KMP_AFFINITY = "granularity=fine,compact,1,0"
LD_LIBRARY_PATH = "/spec/spec16/libs/32:/spec/spec16/libs/64:/spec/spec16/sh"
OMP_NUM_THREADS = "32"

 Binaries compiled on a system with 1x Intel Core i5-4670K CPU + 32GB
 memory using RedHat EL 7.1
 Transparent Huge Pages enabled with:
 echo always > /sys/kernel/mm/transparent_hugepage/enabled
 runspec command invoked through numactl i.e.:
 numactl --interleave=all runspec <etc>
 The Huawei CH121 V3 and Huawei CH222 V3
 are electronically equivalent.
 The results have been measured on a Huawei CH121 V3 model
```

Base Compiler Invocation

C benchmarks:
icc -m64

C++ benchmarks:
icpc -m64

SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the memory was not a href="http://spec.org/cpu2006/Docs/runrules.html#rule_1.3.2">SPEC CPU ru up policy on <a href="https://www.spec.org/osg/policy.html#AppendixC">gener

Non-Compliant

Base Portability Flags

400.perlbench: -DSPEC_CPU_LP64 -DSPEC_CPU_LINUX_X64
401.bzip2: -DSPEC_CPU_LP64
403.gcc: -DSPEC_CPU_LP64
429.mcf: -DSPEC_CPU_LP64
445.gobmk: -DSPEC_CPU_LP64
456.hmmer: -DSPEC_CPU_LP64
458.sjeng: -DSPEC_CPU_LP64
462.libquantum: -DSPEC_CPU_LP64 -DSPEC_CPU_LINUX
464.h264ref: -DSPEC_CPU_LP64
471.omnetpp: -DSPEC_CPU_LP64
473.astar: -DSPEC_CPU_LP64
483.xalancbmk: -DSPEC_CPU_LP64 -DSPEC_CPU_LINUX

Base Optimization Flags

C benchmarks:
-xCORE-AVX2 -ipo -O3 -no-prec-div -parallel -opt-prefetch -auto-p32

C++ benchmarks:
-xCORE-AVX2 -ipo -O3 -no-prec-div -opt-prefetch -auto-p32
-Wl,-z,muldefs -L/sh -lsmartheap64

Base Other Flags

C benchmarks:

403.gcc: -Dalloca=_alloca

Peak Compiler Invocation

C benchmarks (except as noted below):
icc -m64

400.perlbench: icc -m32 -L/opt/intel/compilers_and_libraries_2016/linux/compiler/lib/ia32_lin

C++ benchmarks (except as noted below):
icpc -m32 -L/opt/intel/compilers_and_libraries_2016/linux/compiler/lib/ia32_lin

Continued on next page

SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the memory was not a href="http://spec.org/cpu2006/Docs/runrules.html#rule_1.3.2">SPEC CPU ru up policy on <a href="https://www.spec.org/osg/policy.html#AppendixC">gener

Peak Compiler Invocation (Continued)

473.astar: icpc -m64

Peak Portability Flags

400.perlbench: -D_FILE_OFFSET_BITS=64 -DSPEC_CPU_LINUX_IA32
401.bzip2: -DSPEC_CPU_LP64
403.gcc: -DSPEC_CPU_LP64
429.mcf: -DSPEC_CPU_LP64
445.gobmk: -DSPEC_CPU_LP64
456.hmmer: -DSPEC_CPU_LP64
458.sjeng: -DSPEC_CPU_LP64
462.libquantum: -DSPEC_CPU_LP64 -DSPEC_CPU_LINUX
464.h264ref: -DSPEC_CPU_LP64
471.omnetpp: -D_FILE_OFFSET_BITS=64
473.astar: -DSPEC_CPU_LP64
483.xalancbmk: -D_FILE_OFFSET_BITS=64 -DSPEC_CPU_LINUX

Peak Optimization Flags

C benchmarks:

400.perlbench: -xCORE-AVX2(pass 2) -prof-gen:threadsafe(pass 1)
-ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2)
-par-num-threads=1(pass 1) -prof-use(pass 2) -opt-prefetch
-ansi-alias

401.bzip2: -xCORE-AVX2(pass 2) -prof-gen:threadsafe(pass 1)
-ipo(pass 2) -O3(pass 2) -no-prec-div
-par-num-threads=1(pass 1) -prof-use(pass 2) -auto-ilp32
-opt-prefetch -ansi-alias

403.gcc: -xCORE-AVX2 -ipo -O3 -no-prec-div -inline-calloc
-opt-malloc-options=3 -auto-ilp32

429.mcf: -xCORE-AVX2 -ipo -O3 -no-prec-div -parallel
-opt-prefetch -auto-p32

445.gobmk: basepeak = yes

Continued on next page

Non-Compliant

SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the memory was not a href="http://spec.org/cpu2006/Docs/runrules.html#rule_1.3.2">SPEC CPU ru up policy on <a href="https://www.spec.org/osg/policy.html#AppendixC">gener

Peak Optimization Flags (Continued)

456.hmmer: basepeak = yes

458.sjeng: -xCORE-AVX2(pass 2) -prof-gen:thr fe(pass 1)
-ipo(pass 2) -O3(pass 2) -no-prec-d v(pass
-par-num-threads=1(pass 1) -pr use(pass -unroll4

462.libquantum: basepeak = yes

464.h264ref: basepeak = yes

C++ benchmarks:

471.omnetpp: -xCORE-AVX2(p s 2) -prof-g n:threadsafe(pass 1)
-ipo(pass 2) -O pass 2) -no-pr c-div(pass 2)
-par-num-thre s=1(pass 1) prof-use(pass 2)
-opt-ra-region- rategy block -ansi-alias
-Wl,-z,muldefs -L lsmartheap

473.astar: -xCORE-AVX2 po -O3 -no-prec-div -opt-prefetch
-auto-p32 -Wl,-z,muldefs -L/sh -lsmartheap64

483.xalancbmk: -xCORE-AVX2 ipo -O3 -no-prec-div -opt-prefetch
-ans alias -Wl,-z,muldefs -L/sh -lsmartheap

Peak Other Flags

C benchmarks:

403.gc -Dalloca=_alloca

The flags files that were used to format this result can be browsed at
http://www.spec.org/cpu2006/flags/Intel-ic16.0-official-linux64.html
http://www.spec.org/cpu2006/flags/Huawei-Platform-Settings-BDW-V1.0.html

You can also download the XML flags sources by saving the following links:
http://www.spec.org/cpu2006/flags/Intel-ic16.0-official-linux64.xml
http://www.spec.org/cpu2006/flags/Huawei-Platform-Settings-BDW-V1.0.xml

Non-Compliant

SPEC CINT2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

Huawei

Huawei CH121 V3 (Intel Xeon E5-2697A v4)

SPECint2006 = NC

SPECint_base2006 = NC

CPU2006 license: 3175
Test sponsor: Huawei
Tested by: Huawei

Test date: Mar-2016
Hardware Availability: Mar-2016
Software Availability: Mar-2016

SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, the memory was not a href="http://spec.org/cpu2006/Docs/runrules.html#rule_1.3.2">SPEC CPU ru up policy on <a href="https://www.spec.org/osg/policy.html#AppendixC">gener

Non-Compliant

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.2.
Report generated on Fri Oct 21 19:59:16 2016 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 19 April 2016.