SPEC® CINT2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

ASUSTeK Computer Inc.

(Test Sponsor: Intel Corporation)

ASUS A88X-PRO Motherboard (AMD A10-7870K with Radeon R7 Graphics)

SPECint®2006 = 32.3

SPECint_base2006 = 31.6

CPU2006 license: 13
Test sponsor: Intel Corporation
Tested by: Intel Corporation

Test date: Mar-2016
Hardware Availability: May-2015
Software Availability: Aug-2015



Hardware

CPU Name:	AMD A10-7870K
CPU Characteristics:	AMD Turbo CORE technology up to 4.10 GHz
CPU MHz:	3900
FPU:	Integrated
CPU(s) enabled:	4 cores, 1 chip, 4 cores/chip
CPU(s) orderable:	1 chip
Primary Cache:	192 KB I on chip per chip, 96 KB I shared / 2 cores; 16 KB D on chip per core
Secondary Cache:	4 MB I+D on chip per chip, 2 MB shared / 2 cores
L3 Cache:	None
Other Cache:	None
Memory:	8 GB (2 x 4 GB 2Rx8 PC3-10600U-11)
Disk Subsystem:	Seagate Barracuda 250 GB SATA, 7200 RPM
Other Hardware:	None

Software

Operating System:	Microsoft Windows 7 Enterprise 6.1.7601 Service Pack 1 Build 7601
Compiler:	C/C++: Version 16.0.0.110 of Intel C++ Studio XE for Windows; Libraries: Version 18.00.30723 of Microsoft Visual Studio 2013
Auto Parallel:	Yes
File System:	NTFS
System State:	Default
Base Pointers:	32/64-bit
Peak Pointers:	32/64-bit
Other Software:	SmartHeap Library Version 11.0 from http://www.microquill.com/

SPEC CINT2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

ASUSTeK Computer Inc.
(Test Sponsor: Intel Corporation)

ASUS A88X-PRO Motherboard (AMD A10-7870K with Radeon R7 Graphics)

SPECint2006 = 32.3

SPECint_base2006 = 31.6

CPU2006 license: 13
Test sponsor: Intel Corporation
Tested by: Intel Corporation

Test date: Mar-2016
Hardware Availability: May-2015
Software Availability: Aug-2015

Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	**383**	**25.5**	385	25.4	381	25.7	328	29.8	332	29.4	**331**	**29.6**
401.bzip2	**524**	**18.4**	554	17.4	522	18.5	512	18.9	**529**	**18.3**	540	17.9
403.gcc	**483**	**16.7**	485	16.6	482	16.7	478	16.9	**478**	**16.8**	479	16.8
429.mcf	275	33.1	276	33.0	**276**	**33.1**	275	33.1	276	33.0	**276**	**33.1**
445.gobmk	435	24.1	438	24.0	**435**	**24.1**	429	24.5	419	25.0	**429**	**24.5**
456.hmmer	**179**	**52.2**	184	50.8	178	52.3	**179**	**52.2**	184	50.8	178	52.3
458.sjeng	**534**	**22.7**	536	22.6	534	22.7	**534**	**22.7**	536	22.6	534	22.7
462.libquantum	**71.4**	**290**	70.7	293	71.8	289	**71.4**	**290**	70.7	293	71.8	289
464.h264ref	472	46.9	474	46.7	**472**	**46.9**	472	46.9	474	46.7	**472**	**46.9**
471.omnetpp	349	17.9	**349**	**17.9**	347	18.0	**327**	**19.1**	325	19.2	328	19.0
473.astar	365	19.2	**332**	**21.1**	331	21.2	365	19.2	**332**	**21.1**	331	21.2
483.xalancbmk	**261**	**26.5**	262	26.3	260	26.6	**261**	**26.5**	262	26.3	260	26.6

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Compiler Invocation Notes

```
To compile these binaries, the Intel Compiler 16.0 was set up to
generate 64-bit binaries with the command:
"psxevars.bat intel64" (shortcut provided in the Intel(r)
Parallel Studio XE 2016 program folder)
```

Platform Notes

```
Sysinfo program C:\SPEC16.0/Docs/sysinfo
$Rev: 6775 $ $Date:: 2011-08-16 #$ \8787f7622badcf24e01c368b1db4377c
running on Clt1C872C5C6B24 Wed Mar 23 19:57:10 2016

This section contains SUT (System Under Test) info as seen by
some common utilities.  To remove or add to this section, see:
  http://www.spec.org/cpu2006/Docs/config.html#sysinfo

Trying 'systeminfo'
OS Name        : Microsoft Windows 7 Enterprise
OS Version     : 6.1.7601 Service Pack 1 Build 7601
System Manufacturer: System manufacturer
System Model   : System Product Name
Processor(s)   : 1 Processor(s) Installed.
     [01]: AMD64 Family 21 Model 56 Stepping 1 AuthenticAMD ~3900 Mhz
BIOS Version   : American Megatrends Inc. 2502, 12/11/2015
Total Physical Memory: 7,108 MB

Trying 'wmic cpu get /value'
DeviceID       : CPU0
```

Continued on next page

Platform Notes (Continued)

```
L2CacheSize   : 25359
L3CacheSize   : 0
MaxClockSpeed : 3900
Name          : AMD A10-7870K Radeon R7, 12 Compute Cores 4C+8G
NumberOfCores : 2
NumberOfLogicalProcessors: 4

(End of data from sysinfo program)
```

Component Notes

```
Tested systems can be used with Shin-G ATX case,
PC Power and Cooling 1200W power supply
```

General Notes

```
OMP_NUM_THREADS set to number of processors cores
KMP_AFFINITY set to granularity=fine,scatter
Binaries compiled on a system with 1x Intel Xeon E5-2699 v3 CPU
+ 64GB memory using Windows 8.1 Enterprise 64-bit
```

Base Compiler Invocation

C benchmarks:
```
icl -Qvc12 -Qstd=c99
```

C++ benchmarks:
```
icl -Qvc12
```

Base Portability Flags

```
400.perlbench: -DSPEC_CPU_P64 -DSPEC_CPU_WIN64_X64
  401.bzip2: -DSPEC_CPU_P64
    403.gcc: -DSPEC_CPU_P64 -DSPEC_CPU_WIN64
    429.mcf: -DSPEC_CPU_P64
  445.gobmk: -DSPEC_CPU_P64
  456.hmmer: -DSPEC_CPU_P64
  458.sjeng: -DSPEC_CPU_P64
462.libquantum: -DSPEC_CPU_P64
  464.h264ref: -DSPEC_CPU_P64 -DWIN32
  471.omnetpp: -DSPEC_CPU_P64 -DSPEC_CPU_WIN64
    473.astar: -DSPEC_CPU_P64
483.xalancbmk: -DSPEC_CPU_P64 -Qoption,cpp,--no_wchar_t_keyword -DWIN64
```

Base Optimization Flags

C benchmarks:
```
/arch:AVX -Qipo -O3 -Qprec-div- -Qopt-prefetch -Qparallel
-Qauto-ilp32 /F64000000
```

C++ benchmarks:
```
/arch:AVX -Qipo -O3 -Qprec-div- -Qopt-prefetch -Qcxx-features
-Qauto-ilp32 /F64000000 shlW64M.lib            -link /FORCE:MULTIPLE
```

Base Other Flags

C benchmarks:

403.gcc: `-Dalloca=_alloca`

Peak Compiler Invocation

C benchmarks:
```
icl -Qvc12 -Qstd=c99
```

C++ benchmarks:
```
icl -Qvc12
```

Peak Portability Flags

Same as Base Portability Flags

Peak Optimization Flags

C benchmarks:

400.perlbench: `/arch:AVX`(pass 2) `-Qprof_gen`(pass 1) `-Qprof_use`(pass 2)
`-Qipo -O3 -Qprec-div- -Qansi-alias -Qopt-prefetch`
`-Qauto-ilp32 /F64000000 shlW64M.lib`
`/F256000000 -link /FORCE:MULTIPLE`

401.bzip2: `/arch:AVX`(pass 2) `-Qprof_gen`(pass 1) `-Qprof_use`(pass 2)
`-Qipo -O3 -Qprec-div- -Qopt-prefetch -Qansi-alias`
`-Qauto-ilp32 /F64000000`

403.gcc: `/arch:AVX`(pass 2) `-Qprof_gen`(pass 1) `-Qprof_use`(pass 2)
`-Qipo -O3 -Qprec-div- -Qauto-ilp32 /F64000000`

Continued on next page

Peak Optimization Flags (Continued)

429.mcf: basepeak = yes

445.gobmk: /arch:AVX(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2) -Qipo -O2 -Qprec-div- -Qansi-alias -Qauto-ilp32 /F64000000

456.hmmer: basepeak = yes

458.sjeng: basepeak = yes

462.libquantum: basepeak = yes

464.h264ref: basepeak = yes

C++ benchmarks:

471.omnetpp: /arch:AVX(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2) -Qipo -O3 -Qprec-div- -Qansi-alias -Qopt-ra-region-strategy=block -Qauto-ilp32 /F64000000 shlW64M.lib -link /FORCE:MULTIPLE

473.astar: basepeak = yes

483.xalancbmk: basepeak = yes

Peak Other Flags

C benchmarks:

403.gcc: -Dalloca=_alloca

The flags file that was used to format this result can be browsed at
http://www.spec.org/cpu2006/flags/Intel-ic16.0-official-windows.html

You can also download the XML flags source by saving the following link:
http://www.spec.org/cpu2006/flags/Intel-ic16.0-official-windows.xml

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.2.
Report generated on Tue Sep 20 15:06:58 2016 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 20 September 2016.