SPEC CPU®2026 Floating Point Rate Result

Copyright 2026 Standard Performance Evaluation Corporation

Supermicro

SuperServer SYS-112HA-TN
(X14SBH-AP , Intel Xeon 6990E+)

SPECrate®2026_fp_base = 545

SPECrate®2026_fp_peak = 557

CPU2026 License: 001176
Test Sponsor: Supermicro
Tested by: Supermicro

Test Date: May-2026
Hardware Availability: Jun-2026
Software Availability: Apr-2026



Hardware

CPU Name:	Intel Xeon 6990E+
Max MHz:	3200
Nominal:	2200
Enabled:	288 cores, 1 chip
Orderable:	1 chip
Cache L1:	64 KB I + 32 KB D on chip per core
L2:	288 MB I+D on chip per chip, 4 MB shared / 4 cores
L3:	576 MB I+D on chip per chip
Other:	None
Memory:	1152 GB (12 x 96 GB 2Rx4 PC5-8000B-R)
Storage:	1 x 480 GB NVMe SSD
Cooling:	Air
Other:	None

Software

OS:	Red Hat Enterprise Linux 9.7 Kernel 5.14.0-611.5.1.el9_7.x86_64
Compiler:	C/C++: Version 2026.0 of Intel oneAPI DPC++/C++ Compiler for Linux; Fortran: Version 2026.0 of Intel Fortran Compiler for Linux
Compiler Category:	Vendor
Firmware:	Version 1.5b released May-2026
File System:	xfs
System State:	Run level 3 (multi-user)
Base Pointers:	64-bit
Peak Pointers:	64-bit
Other:	jemalloc memory allocator V5.3.0
Power Management:	BIOS and OS set to prefer performance at the cost of additional power usage.

SPEC CPU®2026 Floating Point Rate Result

Copyright 2026 Standard Performance Evaluation Corporation

Supermicro

SuperServer SYS-112HA-TN
(X14SBH-AP , Intel Xeon 6990E+)

SPECrate®2026_fp_base = 545

SPECrate®2026_fp_peak = 557

CPU2026 License: 001176
Test Sponsor: Supermicro
Tested by: Supermicro

Test Date: May-2026
Hardware Availability: Jun-2026
Software Availability: Apr-2026

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
709.cactus_r	288	**299**	**825**	299	826			288	**299**	**825**	299	826		
722.palm_r	288	890	427	**891**	**427**			288	890	427	**891**	**427**		
731.astcenc_r	288	258	936	**259**	**936**			288	255	950	**255**	**950**		
736.ocio_r	288	390	646	**390**	**646**			288	390	646	**390**	**646**		
737.gmsh_r	288	**255**	**519**	254	520			288	**251**	**526**	251	527		
748.flightdm_r	288	**215**	**961**	214	964			288	**182**	**1130**	178	1160		
749.fotonik3d_r	288	1583	210	**1584**	**210**			288	1583	210	**1584**	**210**		
765.roms_r	288	**2012**	**225**	2011	226			288	**2012**	**225**	2011	226		
766.femflow_r	288	**356**	**1190**	355	1190			288	**356**	**1190**	355	1190		
767.nest_r	288	332	687	**348**	**656**			288	323	707	**323**	**706**		
772.marian_r	288	513	887	**513**	**886**			288	513	887	**513**	**886**		
782.lbm_r	288	**838**	**197**	837	197			288	**838**	**197**	837	197		

SPECrate®2026_fp_base = 545

SPECrate®2026_fp_peak = 557

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Submit Notes

```
The numactl mechanism was used to bind copies to processors. The config file option 'submit'
was used to generate numactl commands to bind each copy to a specific processor.
For details, please see the config file.
```

Operating System Notes

```
Stack size set to unlimited using "ulimit -s unlimited"
```

Environment Variables Notes

```
Environment variables set by runcpu before the start of the run:
LD_LIBRARY_PATH = "/home/cpu2026/lib"
MALLOC_CONF = "retain:true"
```

General Notes

```
Binaries compiled on a system with 2x Intel Xeon Platinum 8280M CPU + 384GB RAM
memory using CentOS Stream 9.
Transparent Huge Pages enabled by default
Prior to runcpu invocation
Filesystem page cache synced and cleared with:
sync; echo 3>       /proc/sys/vm/drop_caches
```

(Continued on next page)

General Notes (Continued)

```
 runcpu command invoked through numactl i.e.:
 numactl --interleave=all runcpu <etc>

NA: The test sponsor attests, as of date of publication, that CVE-2017-5754 (Meltdown)
is mitigated in the system as tested and documented.
Yes: The test sponsor attests, as of date of publication, that CVE-2017-5753 (Spectre variant 1)
is mitigated in the system as tested and documented.
Yes: The test sponsor attests, as of date of publication, that CVE-2017-5715 (Spectre variant 2)
is mitigated in the system as tested and documented.
 jemalloc, a general purpose malloc implementation
 built with the CentOS Stream 9, and the system compiler gcc 11.5.0
 sources available from jemalloc.net or https://github.com/jemalloc/jemalloc/releases
```

Platform Notes

```
BIOS settings:
Workload Profile = HPC
KTI Prefetch = Enable
Stale AtoS = Disable
LLC Dead Line Alloc = Disable

 Sysinfo program /home/cpu2026/bin/sysinfo
 Rev: 779ab21020787073335a329f3a45e2cd
 running on  Fri May 15 20:38:49 2026

 SUT (System Under Test) info as seen by some common utilities.

 ------------------------------------------------------------
 Table of contents
 ------------------------------------------------------------
  1. uname -srvm
  2. w
  3. Username
  4. ulimit -a
  5. sysinfo process ancestry
  6. /proc/cpuinfo
  7. lscpu
  8. numactl --hardware
  9. /proc/meminfo
 10. who -r
 11. Systemd service manager version: systemd 252 (252-55.el9)
 12. Services, from systemctl list-unit-files
 13. Linux kernel boot-time arguments, from /proc/cmdline
 14. cpupower frequency-info
 15. tuned-adm active
 16. sysctl
```

(Continued on next page)

Platform Notes (Continued)

```
17. /sys/kernel/mm/transparent_hugepage
18. /sys/kernel/mm/transparent_hugepage/khugepaged
19. OS release
20. Disk information
21. /sys/devices/virtual/dmi/id
22. dmidecode
23. BIOS
------------------------------------------------------------

------------------------------------------------------------
1. uname -srvm
  Linux 5.14.0-611.5.1.el9_7.x86_64 #1 SMP PREEMPT_DYNAMIC Fri Oct 17 14:16:35 EDT 2025 x86_64

------------------------------------------------------------
2. w
   20:38:49 up  4:42,  1 user,  load average: 103.48, 230.72, 259.42
  USER     TTY        LOGIN@   IDLE   JCPU   PCPU WHAT
  root     tty1      16:11    4:27m  1.48s  0.01s -bash

------------------------------------------------------------
3. Username
  From environment variable $USER:  root

------------------------------------------------------------
4. ulimit -a
  real-time non-blocking time  (microseconds, -R) unlimited
  core file size              (blocks, -c) 0
  data seg size               (kbytes, -d) unlimited
  scheduling priority                 (-e) 0
  file size                   (blocks, -f) unlimited
  pending signals                     (-i) 4639996
  max locked memory           (kbytes, -l) 64
  max memory size             (kbytes, -m) unlimited
  open files                          (-n) 1024
  pipe size                (512 bytes, -p) 8
  POSIX message queues         (bytes, -q) 819200
  real-time priority                  (-r) 0
  stack size                  (kbytes, -s) unlimited
  cpu time                   (seconds, -t) unlimited
  max user processes                  (-u) 4639996
  virtual memory              (kbytes, -v) unlimited
  file locks                          (-x) unlimited

------------------------------------------------------------
5. sysinfo process ancestry
 /usr/lib/systemd/systemd rhgb --switched-root --system --deserialize 31
 login -- root
```


(Continued on next page)

Platform Notes (Continued)

```
  -bash
  -bash
 runcpu --nobuild --reportable --action validate --define default-platform-flags --copies 288 -c
   ic2026.0-clearwaterforest-cpu2026-1.0.1-rate-20260429.cfg --define smt-on --define peakfpcopies=144
   --define physicalfirst --define invoke_with_interleave --define drop_caches --reportable --tune base,peak
    -o all fprate
 runcpu --nobuild --reportable --action validate --define default-platform-flags --copies 288 --configfile
   ic2026.0-clearwaterforest-cpu2026-1.0.1-rate-20260429.cfg --define smt-on --define peakfpcopies=144
   --define physicalfirst --define invoke_with_interleave --define drop_caches --reportable --tune base,peak
    --output_format all --nopower --runmode rate --tune base:peak --size refrate fprate --nopreenv
    --note-preenv --logfile $SPEC/tmp/CPU2026.002/templogs/preenv.fprate.002.0.log --lognum 002.0
    --from_runcpu 2
 specperl $SPEC/bin/sysinfo
$SPEC = /home/cpu2026

------------------------------------------------------------
6. /proc/cpuinfo
    model name      : Intel(R) Xeon(R) 6990E+
    vendor_id       : GenuineIntel
    cpu family      : 6
    model           : 221
    stepping        : 1
    microcode       : 0x1000120
    bugs            : spectre_v1 spectre_v2 spec_store_bypass swapgs bhi spectre_v2_user
    cpu cores       : 288
    siblings        : 288
    1 physical ids (chips)
    288 processors (hardware threads)
    physical id 0: core ids 0-95,128-223,256-351
    physical id 0: apicids
   0,2,4,6,8,10,12,14,16,18,20,22,24,26,28,30,32,34,36,38,40,42,44,46,48,50,52,54,56,58,60,62,64,66,68,70,72
   ,74,76,78,80,82,84,86,88,90,92,94,96,98,100,102,104,106,108,110,112,114,116,118,120,122,124,126,128,130,1
   32,134,136,138,140,142,144,146,148,150,152,154,156,158,160,162,164,166,168,170,172,174,176,178,180,182,18
   4,186,188,190,256,258,260,262,264,266,268,270,272,274,276,278,280,282,284,286,288,290,292,294,296,298,300
   ,302,304,306,308,310,312,314,316,318,320,322,324,326,328,330,332,334,336,338,340,342,344,346,348,350,352,
   354,356,358,360,362,364,366,368,370,372,374,376,378,380,382,384,386,388,390,392,394,396,398,400,402,404,4
   06,408,410,412,414,416,418,420,422,424,426,428,430,432,434,436,438,440,442,444,446,512,514,516,518,520,52
   2,524,526,528,530,532,534,536,538,540,542,544,546,548,550,552,554,556,558,560,562,564,566,568,570,572,574
   ,576,578,580,582,584,586,588,590,592,594,596,598,600,602,604,606,608,610,612,614,616,618,620,622,624,626,
   628,630,632,634,636,638,640,642,644,646,648,650,652,654,656,658,660,662,664,666,668,670,672,674,676,678,6
    80,682,684,686,688,690,692,694,696,698,700,702
  Caution: /proc/cpuinfo data regarding chips, cores, and threads is not necessarily reliable, especially for
   virtualized systems.  Use the above data carefully.

------------------------------------------------------------
7. lscpu
```

(Continued on next page)

Platform Notes (Continued)

```
From lscpu from util-linux 2.37.4:
  Architecture:                            x86_64
  CPU op-mode(s):                          32-bit, 64-bit
  Address sizes:                           52 bits physical, 48 bits virtual
  Byte Order:                              Little Endian
  CPU(s):                                  288
  On-line CPU(s) list:                     0-287
  Vendor ID:                               GenuineIntel
  BIOS Vendor ID:                          Intel(R) Corporation
  Model name:                              Intel(R) Xeon(R) 6990E+
  BIOS Model name:                         Intel(R) Xeon(R) 6990E+
  CPU family:                              6
  Model:                                   221
  Thread(s) per core:                      1
  Core(s) per socket:                      288
  Socket(s):                               1
  Stepping:                                1
  BogoMIPS:                                4400.00
  Flags:                                   fpu vme de pse tsc msr pae mce cx8 apic sep mtrr pge mca cmov pat
                                           pse36 clflush dts acpi mmx fxsr sse sse2 ss ht tm pbe syscall nx
                                           pdpe1gb rdtscp lm constant_tsc art arch_perfmon bts rep_good nopl
                                           xtopology nonstop_tsc cpuid aperfmperf tsc_known_freq pni
                                           pclmulqdq dtes64 monitor ds_cpl vmx smx est tm2 ssse3 sdbg fma
                                           cx16 xtpr pdcm pcid dca sse4_1 sse4_2 x2apic movbe popcnt
                                           tsc_deadline_timer aes xsave avx f16c rdrand lahf_lm abm
                                           3dnowprefetch cpuid_fault epb cat_l3 cat_l2 cdp_l3 intel_ppin
                                           cdp_l2 ssbd mba ibrs ibpb stibp ibrs_enhanced tpr_shadow
                                           flexpriority ept vpid ept_ad fsgsbase tsc_adjust bmi1 avx2 smep
                                           bmi2 erms invpcid cqm rdt_a rdseed adx smap clflushopt clwb
                                           intel_pt sha_ni xsaveopt xsavec xgetbv1 xsaves cqm_llc
                                           cqm_occup_llc cqm_mbm_total cqm_mbm_local split_lock_detect
                                           user_shstk avx_vnni lam wbnoinvd dtherm ida arat pln pts vnmi umip
                                           pku ospke waitpkg gfni vaes vpclmulqdq tme rdpid bus_lock_detect
                                           cldemote movdiri movdir64b enqcmd fsrm md_clear serialize pconfig
                                           arch_lbr ibt flush_l1d arch_capabilities
  Virtualization:                          VT-x
  L1d cache:                               9 MiB (288 instances)
  L1i cache:                               18 MiB (288 instances)
  L2 cache:                                288 MiB (72 instances)
  L3 cache:                                576 MiB (1 instance)
  NUMA node(s):                            3
  NUMA node0 CPU(s):                       0-95
  NUMA node1 CPU(s):                       96-191
  NUMA node2 CPU(s):                       192-287
  Vulnerability Gather data sampling:      Not affected
  Vulnerability Indirect target selection: Not affected
  Vulnerability Itlb multihit:             Not affected
```

(Continued on next page)

Platform Notes (Continued)

```
   Vulnerability L1tf:                    Not affected
   Vulnerability Mds:                     Not affected
   Vulnerability Meltdown:                Not affected
   Vulnerability Mmio stale data:         Not affected
   Vulnerability Reg file data sampling:  Not affected
   Vulnerability Retbleed:                Not affected
   Vulnerability Spec rstack overflow:    Not affected
   Vulnerability Spec store bypass:       Mitigation; Speculative Store Bypass disabled via prctl
   Vulnerability Spectre v1:              Mitigation; usercopy/swapgs barriers and __user pointer
                                          sanitization
   Vulnerability Spectre v2:              Mitigation; Enhanced / Automatic IBRS; IBPB conditional;
                                          PBRSB-eIBRS Not affected; BHI BHI_DIS_S
   Vulnerability Srbds:                   Not affected
   Vulnerability Tsa:                     Not affected
   Vulnerability Tsx async abort:         Not affected

 From lscpu --cache:
      NAME ONE-SIZE ALL-SIZE WAYS TYPE        LEVEL   SETS PHY-LINE COHERENCY-SIZE
      L1d       32K       9M    8 Data            1     64        1             64
      L1i       64K      18M    8 Instruction     1    128        1             64
      L2         4M     288M   16 Unified         2   4096        1             64
      L3       576M     576M   16 Unified         3 589824        1             64

 ------------------------------------------------------------
 8. numactl --hardware
 NOTE: a numactl 'node' might or might not correspond to a physical chip.
   available: 3 nodes (0-2)
   node 0 cpus: 0-95
   node 0 size: 385994 MB
   node 0 free: 361274 MB
   node 1 cpus: 96-191
   node 1 size: 387047 MB
   node 1 free: 362955 MB
   node 2 cpus: 192-287
   node 2 size: 387021 MB
   node 2 free: 362786 MB
   node distances:
   node     0    1    2
      0:   10   15   17
      1:   15   10   15
      2:   17   15   10

 ------------------------------------------------------------
 9. /proc/meminfo
    MemTotal:       1187904808 kB

 ------------------------------------------------------------
```


(Continued on next page)

Platform Notes (Continued)

```
10. who -r
  run-level 3 May 15 15:56

------------------------------------------------------------
11. Systemd service manager version: systemd 252 (252-55.el9)
  Default Target  Status
  multi-user      running

------------------------------------------------------------
12. Services, from systemctl list-unit-files
  STATE            UNIT FILES
  enabled          ModemManager NetworkManager NetworkManager-dispatcher NetworkManager-wait-online
                   accounts-daemon atd auditd avahi-daemon bluetooth chronyd crond cups dbus-broker firewalld
                   gdm getty@ insights-client-boot irqbalance iscsi-onboot iscsi-starter kdump libstoragemgmt
                   low-memory-monitor lvm2-monitor mcelog mdmonitor microcode multipathd nis-domainname
                   nvmefc-boot-connections ostree-remount qemu-guest-agent rhsmcertd rsyslog rtkit-daemon
                   selinux-autorelabel-mark smartd sshd sssd switcheroo-control systemd-boot-update
                   systemd-network-generator systemd-pstore tuned udisks2 upower vgauthd vmtoolsd
  enabled-runtime  systemd-remount-fs
  disabled         arp-ethers blk-availability brltty canberra-system-bootup canberra-system-shutdown
                   canberra-system-shutdown-reboot chrony-wait chronyd-restricted cni-dhcp console-getty
                   cpupower cups-browsed dbus-daemon debug-shell dnf-system-upgrade dnsmasq iprdump iprinit
                   iprupdate iscsi-init iscsid iscsiuio kpatch kvm_stat ledmon lvm-devices-import
                   man-db-restart-cache-update netavark-dhcp-proxy netavark-firewalld-reload nftables
                   nvmf-autoconnect ostree-readonly-sysroot-migration ostree-state-overlay@ podman
                   podman-auto-update podman-clean-transient podman-kube@ podman-restart psacct ras-mc-ctl
                   rasdaemon rdisc rhcd rhsm rhsm-facts rpmdb-rebuild selinux-check-proper-disable
                   serial-getty@ speech-dispatcherd sshd-keygen@ systemd-boot-check-no-failures
                   systemd-sysext tuned-ppd wpa_supplicant
  indirect         iscsi spice-vdagentd sssd-autofs sssd-kcm sssd-nss sssd-pac sssd-pam sssd-ssh sssd-sudo
                   systemd-sysupdate systemd-sysupdate-reboot

------------------------------------------------------------
13. Linux kernel boot-time arguments, from /proc/cmdline
  BOOT_IMAGE=(hd0,gpt2)/vmlinuz-5.14.0-611.5.1.el9_7.x86_64
  root=/dev/mapper/rhel_135--180--133-root
  ro
  resume=/dev/mapper/rhel_135--180--133-swap
  rd.lvm.lv=rhel_135-180-133/root
  rd.lvm.lv=rhel_135-180-133/swap
  rhgb
  quiet
  crashkernel=1G-2G:192M,2G-64G:256M,64G-:512M

------------------------------------------------------------
14. cpupower frequency-info
  analyzing CPU 111:
```

(Continued on next page)

Platform Notes (Continued)

```
     Unable to determine current policy
     boost state support:
       Supported: yes
       Active: yes

------------------------------------------------------------
15. tuned-adm active
  Current active profile: throughput-performance

------------------------------------------------------------
16. sysctl
  kernel.numa_balancing               1
  kernel.randomize_va_space           2
  vm.compaction_proactiveness        20
  vm.dirty_background_bytes           0
  vm.dirty_background_ratio          10
  vm.dirty_bytes                      0
  vm.dirty_expire_centisecs        3000
  vm.dirty_ratio                     40
  vm.dirty_writeback_centisecs      500
  vm.dirtytime_expire_seconds     43200
  vm.extfrag_threshold              500
  vm.min_unmapped_ratio               1
  vm.nr_hugepages                     0
  vm.nr_hugepages_mempolicy           0
  vm.nr_overcommit_hugepages          0
  vm.swappiness                      10
  vm.watermark_boost_factor       15000
  vm.watermark_scale_factor          10
  vm.zone_reclaim_mode                0

------------------------------------------------------------
17. /sys/kernel/mm/transparent_hugepage
  defrag          always defer defer+madvise [madvise] never
  enabled         [always] madvise never
  hpage_pmd_size  2097152
  shmem_enabled   always within_size advise [never] deny force

------------------------------------------------------------
18. /sys/kernel/mm/transparent_hugepage/khugepaged
  alloc_sleep_millisecs   60000
  defrag                      1
  max_ptes_none             511
  max_ptes_shared           256
  max_ptes_swap              64
  pages_to_scan            4096
  scan_sleep_millisecs    10000
```

(Continued on next page)

Platform Notes (Continued)

```
------------------------------------------------------------
19. OS release
  From /etc/*-release /etc/*-version
  os-release     Red Hat Enterprise Linux 9.7 (Plow)
  redhat-release Red Hat Enterprise Linux release 9.7 (Plow)
  system-release Red Hat Enterprise Linux release 9.7 (Plow)

------------------------------------------------------------
20. Disk information
SPEC is set to: /home/cpu2026
  Filesystem                      Type  Size  Used Avail Use% Mounted on
  /dev/mapper/rhel_135--180--133-home xfs   372G   96G  277G  26% /home

------------------------------------------------------------
21. /sys/devices/virtual/dmi/id
    Vendor:         Supermicro
    Product:        Super Server
    Product Family: Family
    Serial:         0123456789

------------------------------------------------------------
22. dmidecode
  Additional information from dmidecode 3.6 follows.  WARNING: Use caution when you interpret this section.
  The 'dmidecode' program reads system data which is "intended to allow hardware to be accurately
  determined", but the intent may not be met, as there are frequent changes to hardware, firmware, and the
   "DMTF SMBIOS" standard.
   Memory:
     12x SK Hynix HMCGM4AMBRB970N 96 GB 2 rank 8000


------------------------------------------------------------
23. BIOS
(This section combines info from /sys/devices and dmidecode.)
   BIOS Vendor:       American Megatrends International, LLC.
   BIOS Version:      1.5b
   BIOS Date:         05/04/2026
   BIOS Revision:     5.35
```

Compiler Version Notes

```
==============================================================================
C       | 782.lbm_r(base, peak)
------------------------------------------------------------------------------
Intel(R) oneAPI DPC++/C++ Compiler for applications running on Intel(R) 64,
  Version 2026.0.0 Build 20260331
```

(Continued on next page)

Compiler Version Notes (Continued)

```
Copyright (C) 1985-2026 Intel Corporation. All rights reserved.
------------------------------------------------------------------------------

==============================================================================
C++      | 731.astcenc_r(base, peak) 736.ocio_r(base, peak)
         | 748.flightdm_r(base, peak) 766.femflow_r(base, peak)
         | 767.nest_r(base, peak) 772.marian_r(base, peak)
------------------------------------------------------------------------------
Intel(R) oneAPI DPC++/C++ Compiler for applications running on Intel(R) 64,
  Version 2026.0.0 Build 20260331
Copyright (C) 1985-2026 Intel Corporation. All rights reserved.
------------------------------------------------------------------------------

==============================================================================
C++, C   | 709.cactus_r(base, peak) 737.gmsh_r(base, peak)
------------------------------------------------------------------------------
Intel(R) oneAPI DPC++/C++ Compiler for applications running on Intel(R) 64,
  Version 2026.0.0 Build 20260331
Copyright (C) 1985-2026 Intel Corporation. All rights reserved.
------------------------------------------------------------------------------

==============================================================================
Fortran  | 722.palm_r(base, peak) 749.fotonik3d_r(base, peak) 765.roms_r(base,
         | peak)
------------------------------------------------------------------------------
Intel(R) Fortran Compiler for applications running on Intel(R) 64, Version
  2026.0.0 Build 20260331
Copyright (C) 1985-2026 Intel Corporation. All rights reserved.
------------------------------------------------------------------------------
```

Base Compiler Invocation

C benchmarks:
icx

C++ benchmarks:
icpx

Fortran benchmarks:
ifx

Benchmarks using both C and C++:
icpx icx

Base Portability Flags

737.gmsh_r: `-fno-associative-math`

Base Optimization Flags

C benchmarks:
`-m64 -std=c18 -Wl,-z,muldefs -Wl,-plugin-opt=-inline-threshold=1500 -xclearwaterforest -O3 -ffp-model=fast -flto -mfpmath=sse -funroll-loops -qopt-mem-layout-trans=4 -L/usr/local/jemalloc-5.3.0/lib -ljemalloc`

C++ benchmarks:
`-m64 -std=c++17 -Wl,-z,muldefs -Wl,-plugin-opt=-inline-threshold=1500 -xclearwaterforest -O3 -ffp-model=fast -flto -mfpmath=sse -funroll-loops -qopt-mem-layout-trans=4 -L/usr/local/jemalloc-5.3.0/lib -ljemalloc`

Fortran benchmarks:
`-m64 -stand f18 -Wl,-z,muldefs -Wl,-plugin-opt=-inline-threshold=1500 -xclearwaterforest -O3 -ffp-model=fast -flto -mfpmath=sse -funroll-loops -qopt-mem-layout-trans=4 -nostandard-realloc-lhs -align array32byte -auto -L/usr/local/jemalloc-5.3.0/lib -ljemalloc`

Benchmarks using both C and C++:
`-m64 -std=c++17 -std=c18 -Wl,-z,muldefs -Wl,-plugin-opt=-inline-threshold=1500 -xclearwaterforest -O3 -ffp-model=fast -flto -mfpmath=sse -funroll-loops -qopt-mem-layout-trans=4 -L/usr/local/jemalloc-5.3.0/lib -ljemalloc`

Peak Compiler Invocation

C benchmarks:
`icx`

C++ benchmarks:
`icpx`

Fortran benchmarks:
`ifx`

Benchmarks using both C and C++:
`icpx icx`

Peak Portability Flags

737.gmsh_r: `-fno-associative-math`

Peak Optimization Flags

C benchmarks:

782.lbm_r: `basepeak = yes`

C++ benchmarks:

731.astcenc_r: `-m64 -std=c++17 -Wl,-z,muldefs`
`-Wl,-plugin-opt=-inline-threshold=1500`
`-fprofile-generate`(pass 1)
`-fprofile-use=default.profdata`(pass 2) `-xCORE-AVX2`(pass 1)
`-ffp-model=fast -xclearwaterforest`(pass 2) `-flto`
`-qopt-mem-layout-trans=4 -O3 -mfpmath=sse -funroll-loops`
`-L/usr/local/jemalloc-5.3.0/lib -ljemalloc`

736.ocio_r: `basepeak = yes`

748.flightdm_r: `Same as 731.astcenc_r`

766.femflow_r: `basepeak = yes`

767.nest_r: `Same as 731.astcenc_r`

772.marian_r: `basepeak = yes`

Fortran benchmarks:

722.palm_r: `basepeak = yes`

749.fotonik3d_r: `basepeak = yes`

765.roms_r: `basepeak = yes`

Benchmarks using both C and C++:

709.cactus_r: `basepeak = yes`

737.gmsh_r: `-m64 -std=c++17 -std=c18 -Wl,-z,muldefs`
`-Wl,-plugin-opt=-inline-threshold=1500`
`-fprofile-generate`(pass 1)
`-fprofile-use=default.profdata`(pass 2) `-xCORE-AVX2`(pass 1)

(Continued on next page)

Peak Optimization Flags (Continued)

737.gmsh_r (continued):
-ffp-model=fast -xclearwaterforest(pass 2) -flto
-qopt-mem-layout-trans=4 -O3 -mfpmath=sse -funroll-loops
-L/usr/local/jemalloc-5.3.0/lib -ljemalloc

The flags files that were used to format this result can be browsed at
http://www.spec.org/cpu2026/results/flags/Intel-ic2026-official-linux64-v1.1.html
http://www.spec.org/cpu2026/results/flags/Supermicro-Platform-Settings-V1.2-CWF-revC.html

You can also download the XML flags sources by saving the following links:
http://www.spec.org/cpu2026/results/flags/Intel-ic2026-official-linux64-v1.1.xml
http://www.spec.org/cpu2026/results/flags/Supermicro-Platform-Settings-V1.2-CWF-revC.xml

SPEC CPU and SPECrate are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester. For other inquiries, please contact info@spec.org.

Tested with SPEC CPU®2026 v1.0.1 on 2026-05-15 08:38:48-0400.
Report generated on 2026-08-11 15:19:15 by CPU2026 PDF formatter (unknown).
Originally published on 2026-06-04.