SPEC CPU®2026 Floating Point Rate Result

Copyright 2026 Standard Performance Evaluation Corporation

Lenovo Global Technology

ThinkSystem SR860 V3
(1.90 GHz,Intel Xeon Platinum 8490H)

SPECrate®2026_fp_base = 832

SPECrate®2026_fp_peak = Not Run

CPU2026 License: 9017
Test Sponsor: Lenovo Global Technology
Tested by: Lenovo Global Technology

Test Date: May-2026
Hardware Availability: Jun-2023
Software Availability: Apr-2026



Hardware

CPU Name:	Intel Xeon Platinum 8490H
Max MHz:	3500
Nominal:	1900
Enabled:	240 cores, 4 chips, 2 threads/core
Orderable:	2,4 chips
Cache L1:	32 KB I + 48 KB D on chip per core
L2:	2 MB I+D on chip per core
L3:	112.5 MB I+D on chip per chip
Other:	None
Memory:	1 TB (32 x 32 GB 2Rx8 PC5-4800B-R)
Storage:	1 x 480 TB NVME SSD
Cooling:	Air
Other:	None

Software

OS:	SUSE Linux Enterprise Server 15 SP7 Kernel 6.4.0-150700.51-default
Compiler:	C/C++: Version 2026.0 of Intel oneAPI DPC++/C++ Compiler for Linux; Fortran: Version 2026.0 of Intel Fortran Compiler for Linux
Compiler Category:	Vendor
Firmware:	Lenovo BIOS Version RSE127G 8.50 released May-2026
File System:	xfs
System State:	Run level 3 (multi-user)
Base Pointers:	64-bit
Peak Pointers:	Not Applicable
Other:	tcmalloc memory allocator v2.18.1
Power Management:	BIOS set to prefer performance at the cost of additional power usage

SPEC CPU®2026 Floating Point Rate Result

Copyright 2026 Standard Performance Evaluation Corporation

Lenovo Global Technology

ThinkSystem SR860 V3
(1.90 GHz,Intel Xeon Platinum 8490H)

SPECrate®2026_fp_base = 832

SPECrate®2026_fp_peak = Not Run

CPU2026 License: 9017
Test Sponsor: Lenovo Global Technology
Tested by: Lenovo Global Technology

Test Date: May-2026
Hardware Availability: Jun-2023
Software Availability: Apr-2026

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
709.cactus_r	480	**309**	**1330**	309	1330	309	1330							
722.palm_r	480	**847**	**748**	853	743	847	748							
731.astcenc_r	480	**310**	**1300**	310	1300	309	1300							
736.ocio_r	480	460	913	**455**	**924**	454	926							
737.gmsh_r	480	**283**	**778**	284	777	283	779							
748.flightdm_r	480	**280**	**1230**	280	1230	281	1220							
749.fotonik3d_r	480	1526	364	**1525**	**364**	1525	364							
765.roms_r	480	2345	322	2342	323	**2343**	**323**							
766.femflow_r	480	336	2090	337	2090	**336**	**2090**							
767.nest_r	480	436	873	427	892	**431**	**883**							
772.marian_r	480	505	1500	**506**	**1500**	507	1500							
782.lbm_r	480	934	294	934	295	**934**	**295**							

SPECrate®2026_fp_base = 832

SPECrate®2026_fp_peak = Not Run

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Submit Notes

```
The numactl mechanism was used to bind copies to processors. The config file option 'submit'
was used to generate numactl commands to bind each copy to a specific processor.
For details, please see the config file.
```

Operating System Notes

```
Stack size set to unlimited using "ulimit -s unlimited"
```

Environment Variables Notes

```
Environment variables set by runcpu before the start of the run:
LD_LIBRARY_PATH = "/home/cpu2026-1.0.1-ic2026.0-rate/lib"
```

General Notes

```
Binaries compiled on a system with 2x Intel Xeon Platinum 8280M CPU + 384GB RAM
memory using CentOS Stream 9.
Transparent Huge Pages enabled by default
Prior to runcpu invocation
Filesystem page cache synced and cleared with:
sync; echo 3>       /proc/sys/vm/drop_caches
runcpu command invoked through numactl i.e.:
```

(Continued on next page)

General Notes (Continued)

```
 numactl --interleave=all runcpu <etc>
NA: The test sponsor attests, as of date of publication, that CVE-2017-5754 (Meltdown)
is mitigated in the system as tested and documented.
Yes: The test sponsor attests, as of date of publication, that CVE-2017-5753 (Spectre variant 1)
is mitigated in the system as tested and documented.
Yes: The test sponsor attests, as of date of publication, that CVE-2017-5715 (Spectre variant 2)
is mitigated in the system as tested and documented.
 tcmalloc, a fast, multithreaded malloc implementation
 built with the CentOS Stream 9, and the system compiler gcc 11.5.0
 sources available from github.com/gperftools/gperftools
```

Platform Notes

```
BIOS configuration:
Choose Operating Mode set to Maximum Performance
SNC set to SNC4
Misc set to Option4
DCU Streamer Prefetcher set to Disabled

 Sysinfo program /home/cpu2026-1.0.1-ic2026.0-rate/bin/sysinfo
 Rev: 779ab21020787073335a329f3a45e2cd
 running on localhost Sat May 30 19:38:02 2026

 SUT (System Under Test) info as seen by some common utilities.

 ------------------------------------------------------------
 Table of contents
 ------------------------------------------------------------
  1. uname -srvm
  2. w
  3. Username
  4. ulimit -a
  5. sysinfo process ancestry
  6. /proc/cpuinfo
  7. lscpu
  8. numactl --hardware
  9. /proc/meminfo
 10. who -r
 11. Systemd service manager version: systemd 254 (254.24+suse.148.g83b9060b6e)
 12. Services, from systemctl list-unit-files
 13. Linux kernel boot-time arguments, from /proc/cmdline
 14. cpupower frequency-info
 15. sysctl
 16. /sys/kernel/mm/transparent_hugepage
 17. /sys/kernel/mm/transparent_hugepage/khugepaged
 18. OS release
```

(Continued on next page)

Platform Notes (Continued)

```
 19. Disk information
 20. /sys/devices/virtual/dmi/id
 21. dmidecode
 22. BIOS
------------------------------------------------------------

------------------------------------------------------------
1. uname -srvm
  Linux 6.4.0-150700.51-default #1 SMP PREEMPT_DYNAMIC Wed Apr 30 21:35:43 UTC 2025 (6930611) x86_64

------------------------------------------------------------
2. w
   19:38:02 up 4 min,  1 user,  load average: 0.30, 0.15, 0.06
  USER     TTY      FROM             LOGIN@   IDLE   JCPU   PCPU WHAT

------------------------------------------------------------
3. Username
  From environment variable $USER:  root

------------------------------------------------------------
4. ulimit -a
  core file size          (blocks, -c) unlimited
  data seg size           (kbytes, -d) unlimited
  scheduling priority             (-e) 0
  file size               (blocks, -f) unlimited
  pending signals                 (-i) 4126060
  max locked memory       (kbytes, -l) 8192
  max memory size         (kbytes, -m) unlimited
  open files                      (-n) 1024
  pipe size            (512 bytes, -p) 8
  POSIX message queues     (bytes, -q) 819200
  real-time priority              (-r) 0
  stack size              (kbytes, -s) unlimited
  cpu time               (seconds, -t) unlimited
  max user processes              (-u) 4126060
  virtual memory          (kbytes, -v) unlimited
  file locks                      (-x) unlimited

------------------------------------------------------------
5. sysinfo process ancestry
 /usr/lib/systemd/systemd --switched-root --system --deserialize=43
 sshd: /usr/sbin/sshd -D [listener] 0 of 10-100 startups
 sshd: root [priv]
 sshd: root@notty
 /bin/bash ./02.remote_local_SPECcpu_1.02.sh
 sh Run503-compliant-ic2026.0-lin-sapphirerapids-ratefp-base-smt-on-20260429_revB.sh
 runcpu --nobuild --iterations=3 --reportable --action validate --define default-platform-flags --copies 480
```

(Continued on next page)

Platform Notes (Continued)

```
   -c ic2026.0-sapphirerapids-cpu2026-1.0.1-rate-20260429_revB.cfg --define smt-on --define cores=240
   --define physicalfirst --define invoke_with_interleave --define drop_caches --tune base -o all fprate
 runcpu --nobuild --iterations 3 --reportable --action validate --define default-platform-flags --copies 480
   --configfile ic2026.0-sapphirerapids-cpu2026-1.0.1-rate-20260429_revB.cfg --define smt-on --define
   cores=240 --define physicalfirst --define invoke_with_interleave --define drop_caches --tune base
   --output_format all --nopower --runmode rate --tune base --size refrate fprate --nopreenv --note-preenv
   --logfile $SPEC/tmp/CPU2026.007/templogs/preenv.fprate.007.0.log --lognum 007.0 --from_runcpu 2
 specperl $SPEC/bin/sysinfo
$SPEC = /home/cpu2026-1.0.1-ic2026.0-rate

------------------------------------------------------------
6. /proc/cpuinfo
    model name      : Intel(R) Xeon(R) Platinum 8490H
    vendor_id       : GenuineIntel
    cpu family      : 6
    model           : 143
    stepping        : 8
    microcode       : 0x2b000661
    bugs            : spectre_v1 spectre_v2 spec_store_bypass swapgs eibrs_pbrsb bhi
    cpu cores       : 60
    siblings        : 120
    4 physical ids (chips)
    480 processors (hardware threads)
    physical id 0: core ids 0-59
    physical id 1: core ids 0-59
    physical id 2: core ids 0-59
    physical id 3: core ids 0-59
    physical id 0: apicids 0-119
    physical id 1: apicids 128-247
    physical id 2: apicids 256-375
    physical id 3: apicids 384-503
 Caution: /proc/cpuinfo data regarding chips, cores, and threads is not necessarily reliable, especially for
  virtualized systems.  Use the above data carefully.

------------------------------------------------------------
7. lscpu

From lscpu from util-linux 2.40.4:
  Architecture:                         x86_64
  CPU op-mode(s):                       32-bit, 64-bit
  Address sizes:                        46 bits physical, 57 bits virtual
  Byte Order:                           Little Endian
  CPU(s):                               480
  On-line CPU(s) list:                  0-479
  Vendor ID:                            GenuineIntel
  Model name:                           Intel(R) Xeon(R) Platinum 8490H
  CPU family:                           6
```

(Continued on next page)

Platform Notes (Continued)

```
  Model:                          143
  Thread(s) per core:             2
  Core(s) per socket:             60
  Socket(s):                      4
  Stepping:                       8
  CPU(s) scaling MHz:             24%
  CPU max MHz:                    3500.0000
  CPU min MHz:                    800.0000
  BogoMIPS:                       3800.00
  Flags:                          fpu vme de pse tsc msr pae mce cx8 apic sep mtrr pge mca cmov pat
                                  pse36 clflush dts acpi mmx fxsr sse sse2 ss ht tm pbe syscall nx
                                  pdpe1gb rdtscp lm constant_tsc art arch_perfmon pebs bts rep_good
                                  nopl xtopology nonstop_tsc cpuid aperfmperf tsc_known_freq pni
                                  pclmulqdq dtes64 ds_cpl vmx smx est tm2 ssse3 sdbg fma cx16 xtpr pdcm
                                  pcid dca sse4_1 sse4_2 x2apic movbe popcnt tsc_deadline_timer aes
                                  xsave avx f16c rdrand lahf_lm abm 3dnowprefetch cpuid_fault epb
                                  cat_l3 cat_l2 cdp_l3 intel_ppin cdp_l2 ssbd mba ibrs ibpb stibp
                                  ibrs_enhanced tpr_shadow flexpriority ept vpid ept_ad fsgsbase
                                  tsc_adjust bmi1 avx2 smep bmi2 erms invpcid cqm rdt_a avx512f
                                  avx512dq rdseed adx smap avx512ifma clflushopt clwb intel_pt avx512cd
                                  sha_ni avx512bw avx512vl xsaveopt xsavec xgetbv1 xsaves cqm_llc
                                  cqm_occup_llc cqm_mbm_total cqm_mbm_local split_lock_detect
                                  user_shstk avx_vnni avx512_bf16 wbnoinvd dtherm ida arat pln pts vnmi
                                  avx512vbmi umip pku ospke waitpkg avx512_vbmi2 gfni vaes vpclmulqdq
                                  avx512_vnni avx512_bitalg tme avx512_vpopcntdq la57 rdpid
                                  bus_lock_detect cldemote movdiri movdir64b enqcmd fsrm md_clear
                                  serialize tsxldtrk pconfig arch_lbr ibt amx_bf16 avx512_fp16 amx_tile
                                  amx_int8 flush_l1d arch_capabilities
  Virtualization:                 VT-x
  L1d cache:                      11.3 MiB (240 instances)
  L1i cache:                      7.5 MiB (240 instances)
  L2 cache:                       480 MiB (240 instances)
  L3 cache:                       450 MiB (4 instances)
  NUMA node(s):                   16
  NUMA node0 CPU(s):              0-14,240-254
  NUMA node1 CPU(s):              15-29,255-269
  NUMA node2 CPU(s):              30-44,270-284
  NUMA node3 CPU(s):              45-59,285-299
  NUMA node4 CPU(s):              60-74,300-314
  NUMA node5 CPU(s):              75-89,315-329
  NUMA node6 CPU(s):              90-104,330-344
  NUMA node7 CPU(s):              105-119,345-359
  NUMA node8 CPU(s):              120-134,360-374
  NUMA node9 CPU(s):              135-149,375-389
  NUMA node10 CPU(s):             150-164,390-404
  NUMA node11 CPU(s):             165-179,405-419
  NUMA node12 CPU(s):             180-194,420-434
```

(Continued on next page)

Platform Notes (Continued)

```
  NUMA node13 CPU(s):                   195-209,435-449
  NUMA node14 CPU(s):                   210-224,450-464
  NUMA node15 CPU(s):                   225-239,465-479
  Vulnerability Gather data sampling:   Not affected
  Vulnerability Itlb multihit:          Not affected
  Vulnerability L1tf:                   Not affected
  Vulnerability Mds:                    Not affected
  Vulnerability Meltdown:               Not affected
  Vulnerability Mmio stale data:        Not affected
  Vulnerability Reg file data sampling: Not affected
  Vulnerability Retbleed:               Not affected
  Vulnerability Spec rstack overflow:   Not affected
  Vulnerability Spec store bypass:      Mitigation; Speculative Store Bypass disabled via prctl
  Vulnerability Spectre v1:             Mitigation; usercopy/swapgs barriers and __user pointer sanitization
  Vulnerability Spectre v2:             Mitigation; Enhanced / Automatic IBRS; IBPB conditional; RSB filling;
                                        PBRSB-eIBRS SW sequence; BHI BHI_DIS_S
  Vulnerability Srbds:                  Not affected
  Vulnerability Tsx async abort:        Not affected

From lscpu --cache:
     NAME ONE-SIZE ALL-SIZE WAYS TYPE        LEVEL   SETS PHY-LINE COHERENCY-SIZE
     L1d       48K    11.3M   12 Data            1     64        1             64
     L1i       32K     7.5M    8 Instruction     1     64        1             64
     L2         2M     480M   16 Unified         2   2048        1             64
     L3     112.5M     450M   15 Unified         3 122880        1             64

------------------------------------------------------------
8. numactl --hardware
NOTE: a numactl 'node' might or might not correspond to a physical chip.
  available: 16 nodes (0-15)
  node 0 cpus: 0-14,240-254
  node 0 size: 64101 MB
  node 0 free: 63516 MB
  node 1 cpus: 15-29,255-269
  node 1 size: 64503 MB
  node 1 free: 64106 MB
  node 2 cpus: 30-44,270-284
  node 2 size: 64503 MB
  node 2 free: 64164 MB
  node 3 cpus: 45-59,285-299
  node 3 size: 64503 MB
  node 3 free: 64065 MB
  node 4 cpus: 60-74,300-314
  node 4 size: 64503 MB
  node 4 free: 64203 MB
  node 5 cpus: 75-89,315-329
  node 5 size: 64503 MB
```

(Continued on next page)

Platform Notes (Continued)

```
node 5 free: 64200 MB
node 6 cpus: 90-104,330-344
node 6 size: 64503 MB
node 6 free: 64239 MB
node 7 cpus: 105-119,345-359
node 7 size: 64503 MB
node 7 free: 64077 MB
node 8 cpus: 120-134,360-374
node 8 size: 64465 MB
node 8 free: 64152 MB
node 9 cpus: 135-149,375-389
node 9 size: 64503 MB
node 9 free: 64143 MB
node 10 cpus: 150-164,390-404
node 10 size: 64503 MB
node 10 free: 64192 MB
node 11 cpus: 165-179,405-419
node 11 size: 64503 MB
node 11 free: 64143 MB
node 12 cpus: 180-194,420-434
node 12 size: 64503 MB
node 12 free: 64092 MB
node 13 cpus: 195-209,435-449
node 13 size: 64503 MB
node 13 free: 64171 MB
node 14 cpus: 210-224,450-464
node 14 size: 64503 MB
node 14 free: 64210 MB
node 15 cpus: 225-239,465-479
node 15 size: 64425 MB
node 15 free: 64140 MB
node distances:
node   0   1   2   3   4   5   6   7   8   9  10  11  12  13  14  15
  0:  10  12  12  12  21  21  21  21  21  21  21  21  21  21  21  21
  1:  12  10  12  12  21  21  21  21  21  21  21  21  21  21  21  21
  2:  12  12  10  12  21  21  21  21  21  21  21  21  21  21  21  21
  3:  12  12  12  10  21  21  21  21  21  21  21  21  21  21  21  21
  4:  21  21  21  21  10  12  12  12  21  21  21  21  21  21  21  21
  5:  21  21  21  21  12  10  12  12  21  21  21  21  21  21  21  21
  6:  21  21  21  21  12  12  10  12  21  21  21  21  21  21  21  21
  7:  21  21  21  21  12  12  12  10  21  21  21  21  21  21  21  21
  8:  21  21  21  21  21  21  21  21  10  12  12  12  21  21  21  21
  9:  21  21  21  21  21  21  21  21  12  10  12  12  21  21  21  21
 10:  21  21  21  21  21  21  21  21  12  12  10  12  21  21  21  21
 11:  21  21  21  21  21  21  21  21  12  12  12  10  21  21  21  21
 12:  21  21  21  21  21  21  21  21  21  21  21  21  10  12  12  12
 13:  21  21  21  21  21  21  21  21  21  21  21  21  12  10  12  12
```

(Continued on next page)

Platform Notes (Continued)

```
   14:  21  21  21  21  21  21  21  21  21  21  21  21  12  12  10  12
   15:  21  21  21  21  21  21  21  21  21  21  21  21  12  12  12  10

------------------------------------------------------------
9. /proc/meminfo
   MemTotal:       1056300464 kB

------------------------------------------------------------
10. who -r
  run-level 3 May 30 19:34

------------------------------------------------------------
11. Systemd service manager version: systemd 254 (254.24+suse.148.g83b9060b6e)
  Default Target  Status
  multi-user      running

------------------------------------------------------------
12. Services, from systemctl list-unit-files
  STATE            UNIT FILES
  enabled         YaST2-Firstboot YaST2-Second-Stage apparmor auditd cron getty@ irqbalance issue-generator
                  kbdsettings klog lvm2-monitor nscd nvmefc-boot-connections nvmf-autoconnect postfix
                  purge-kernels rollback rsyslog smartd sshd systemd-pstore wicked wickedd-auto4
                  wickedd-dhcp4 wickedd-dhcp6 wickedd-nanny
  enabled-runtime  systemd-remount-fs
  disabled        autofs autoyast-initscripts blk-availability boot-sysctl ca-certificates chrony-wait
                  chronyd console-getty cups cups-browsed debug-shell ebtables exchange-bmc-os-info
                 firewalld fsidd gpm grub2-once haveged ipmi ipmievd issue-add-ssh-keys kexec-load lunmask
                  man-db-create multipathd nfs nfs-blkmap rpcbind rpmconfigcheck rsyncd serial-getty@
                  smartd_generate_opts snmpd snmptrapd systemd-boot-check-no-failures systemd-confext
                  systemd-network-generator systemd-sysext systemd-time-wait-sync systemd-timesyncd
  indirect         systemd-userdbd wickedd

------------------------------------------------------------
13. Linux kernel boot-time arguments, from /proc/cmdline
  BOOT_IMAGE=/boot/vmlinuz-6.4.0-150700.51-default
  root=UUID=7a0ea09d-0975-48e7-9598-0d39dc424077
  splash=silent
  mitigations=auto
  quiet
  security=apparmor

------------------------------------------------------------
14. cpupower frequency-info
  analyzing CPU 180:
    current policy: frequency should be within 800 MHz and 3.50 GHz.
                    The governor "powersave" may decide which speed to use
                    within this range.
```

(Continued on next page)

Platform Notes (Continued)

```
     boost state support:
       Supported: yes
       Active: yes

------------------------------------------------------------
15. sysctl
  kernel.numa_balancing               1
  kernel.randomize_va_space           2
  vm.compaction_proactiveness        20
  vm.dirty_background_bytes           0
  vm.dirty_background_ratio          10
  vm.dirty_bytes                      0
  vm.dirty_expire_centisecs        3000
  vm.dirty_ratio                     20
  vm.dirty_writeback_centisecs      500
  vm.dirtytime_expire_seconds     43200
  vm.extfrag_threshold              500
  vm.min_unmapped_ratio               1
  vm.nr_hugepages                     0
  vm.nr_hugepages_mempolicy           0
  vm.nr_overcommit_hugepages          0
  vm.swappiness                      60
  vm.watermark_boost_factor       15000
  vm.watermark_scale_factor          10
  vm.zone_reclaim_mode                0

------------------------------------------------------------
16. /sys/kernel/mm/transparent_hugepage
  defrag          always defer defer+madvise [madvise] never
  enabled         [always] madvise never
  hpage_pmd_size  2097152
  shmem_enabled   always within_size advise [never] deny force

------------------------------------------------------------
17. /sys/kernel/mm/transparent_hugepage/khugepaged
  alloc_sleep_millisecs   60000
  defrag                      1
  max_ptes_none             511
  max_ptes_shared           256
  max_ptes_swap              64
  pages_to_scan            4096
  scan_sleep_millisecs    10000

------------------------------------------------------------
18. OS release
  From /etc/*-release /etc/*-version
  os-release SUSE Linux Enterprise Server 15 SP7
```

(Continued on next page)

Platform Notes (Continued)

```
------------------------------------------------------------
19. Disk information
SPEC is set to: /home/cpu2026-1.0.1-ic2026.0-rate
  Filesystem     Type  Size  Used Avail Use% Mounted on
  /dev/nvme0n1p3 xfs   892G  152G  741G  17% /

------------------------------------------------------------
20. /sys/devices/virtual/dmi/id
    Vendor:         Lenovo
    Product:        ThinkSystem SR860 V3
    Product Family: ThinkSystem
    Serial:         None

------------------------------------------------------------
21. dmidecode
  Additional information from dmidecode 3.6 follows.  WARNING: Use caution when you interpret this section.
  The 'dmidecode' program reads system data which is "intended to allow hardware to be accurately
  determined", but the intent may not be met, as there are frequent changes to hardware, firmware, and the
   "DMTF SMBIOS" standard.
   Memory:
     7x Samsung M321R4GA3BB0-CQKDG 32 GB 2 rank 4800
     13x Samsung M321R4GA3BB0-CQKEG 32 GB 2 rank 4800
     5x Samsung M321R4GA3BB0-CQKMG 32 GB 2 rank 4800
     7x Samsung M321R4GA3BB0-CQKVG 32 GB 2 rank 4800


------------------------------------------------------------
22. BIOS
(This section combines info from /sys/devices and dmidecode.)
   BIOS Vendor:       Lenovo
   BIOS Version:      RSE127G-8.50
   BIOS Date:         05/15/2026
   BIOS Revision:     8.50
   Firmware Revision: 8.10
```

Compiler Version Notes

```
==============================================================================
C       | 782.lbm_r(base)
------------------------------------------------------------------------------
Intel(R) oneAPI DPC++/C++ Compiler for applications running on Intel(R) 64,
  Version 2026.0.0 Build 20260331
Copyright (C) 1985-2026 Intel Corporation. All rights reserved.
------------------------------------------------------------------------------
```

(Continued on next page)

Compiler Version Notes (Continued)

```
==============================================================================
C++     | 731.astcenc_r(base) 736.ocio_r(base) 748.flightdm_r(base)
        | 766.femflow_r(base) 767.nest_r(base) 772.marian_r(base)
------------------------------------------------------------------------------
Intel(R) oneAPI DPC++/C++ Compiler for applications running on Intel(R) 64,
  Version 2026.0.0 Build 20260331
Copyright (C) 1985-2026 Intel Corporation. All rights reserved.
------------------------------------------------------------------------------

==============================================================================
C++, C  | 709.cactus_r(base) 737.gmsh_r(base)
------------------------------------------------------------------------------
Intel(R) oneAPI DPC++/C++ Compiler for applications running on Intel(R) 64,
  Version 2026.0.0 Build 20260331
Copyright (C) 1985-2026 Intel Corporation. All rights reserved.
------------------------------------------------------------------------------

==============================================================================
Fortran | 722.palm_r(base) 749.fotonik3d_r(base) 765.roms_r(base)
------------------------------------------------------------------------------
Intel(R) Fortran Compiler for applications running on Intel(R) 64, Version
  2026.0.0 Build 20260331
Copyright (C) 1985-2026 Intel Corporation. All rights reserved.
------------------------------------------------------------------------------
```

Base Compiler Invocation

C benchmarks:
icx

C++ benchmarks:
icpx

Fortran benchmarks:
ifx

Benchmarks using both C and C++:
icpx icx

Base Portability Flags

737.gmsh_r: -fno-associative-math

Base Optimization Flags

C benchmarks:
```
-m64 -std=c18 -Wl,-z,muldefs -Wl,-plugin-opt=-inline-threshold=1500
-xsapphirerapids -mprefer-vector-width=512 -O3 -ffp-model=fast -flto
-mfpmath=sse -funroll-loops -qopt-mem-layout-trans=4
-L/usr/local/tcmalloc-2.18.1/lib -ltcmalloc_minimal
```

C++ benchmarks:
```
-m64 -std=c++17 -Wl,-z,muldefs -Wl,-plugin-opt=-inline-threshold=1500
-xsapphirerapids -mprefer-vector-width=512 -O3 -ffp-model=fast -flto
-mfpmath=sse -funroll-loops -qopt-mem-layout-trans=4
-L/usr/local/tcmalloc-2.18.1/lib -ltcmalloc_minimal
```

Fortran benchmarks:
```
-m64 -stand f18 -Wl,-z,muldefs -Wl,-plugin-opt=-inline-threshold=1500
-xsapphirerapids -mprefer-vector-width=512 -O3 -ffp-model=fast -flto
-mfpmath=sse -funroll-loops -qopt-mem-layout-trans=4
-nostandard-realloc-lhs -align array32byte -auto
-L/usr/local/tcmalloc-2.18.1/lib -ltcmalloc_minimal
```

Benchmarks using both C and C++:
```
-m64 -std=c++17 -std=c18 -Wl,-z,muldefs
-Wl,-plugin-opt=-inline-threshold=1500 -xsapphirerapids
-mprefer-vector-width=512 -O3 -ffp-model=fast -flto -mfpmath=sse
-funroll-loops -qopt-mem-layout-trans=4
-L/usr/local/tcmalloc-2.18.1/lib -ltcmalloc_minimal
```

The flags files that were used to format this result can be browsed at
http://www.spec.org/cpu2026/results/flags/Lenovo-Platform-SPECcpu2026-Flags-V1.2-Eaglestream-AD.html
http://www.spec.org/cpu2026/results/flags/Intel-ic2026-official-linux64-v1.1.html

You can also download the XML flags sources by saving the following links:
http://www.spec.org/cpu2026/results/flags/Lenovo-Platform-SPECcpu2026-Flags-V1.2-Eaglestream-AD.xml
http://www.spec.org/cpu2026/results/flags/Intel-ic2026-official-linux64-v1.1.xml

SPEC CPU and SPECrate are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester. For other inquiries, please contact info@spec.org.

Tested with SPEC CPU®2026 v1.0.1 on 2026-05-30 07:38:01-0400.
Report generated on 2026-08-11 15:22:56 by CPU2026 PDF formatter (unknown).
Originally published on 2026-06-16.