SPEC CINT95 Results

©Copyright 1995, Standard Performance Evaluation Corporation

Fujitsu ICL superserver J650i

SPECint95 = 8.71

SPECint_base95 = 8.71

SPEC license # 42	Tested By: ICL	Test Date: May-96	Hardware Avail: Jul-96	Software Avail: Jun-96



Hardware/Software Configuration for:
superserver J650i

Hardware

Model Name:	Fujitsu ICL superserver J650i
CPU:	Pentium Pro 200MHz
FPU:	Integrated
Number of CPU(s):	1
Primary Cache:	8KBI+8KBD
Secondary Cache:	512KB(I+D)
Other Cache:	None
Memory:	512MB (60ns Fast Page)
Disk Subsystem:	4GB Fujitsu SCSI-2
Other Hardware:	None

Software

Operating System:	SCO UnixWare 2.1
Compiler:	Intel C Reference Compiler V2.3.2
File System:	UFS
System State:	Multi User

Benchmark # and Name	Reference Time	Base Run Time	Base SPEC Ratio	Run Time	SPEC Ratio
099.go	4600	539	8.54	539	8.54
124.m88ksim	1900	244	7.80	244	7.80
126.gcc	1700	207	8.22	207	8.22
129.compress	1800	219	8.21	219	8.21
130.li	1900	204	9.29	204	9.29
132.ijpeg	2400	285	8.42	285	8.42
134.perl	1900	208	9.11	208	9.11
147.vortex	2700	261	10.3	261	10.3
SPECint_base95 (G. Mean)			8.71		
		SPECint95 (G. Mean)			8.71

Notes/Tuning Information

```
Base and peak flags are the same and use Feedback Directed Optimization
Pass1: -tp p6 -ipo  -prof_gen -ircdb_dir /proj/tmp/IRCDB
Pass2: -tp p6 -ipo  -prof_use -ircdb_dir /proj/tmp/IRCDB
-ircdb_dir is a location flag and not an optimization flag
Portability: 124: -DSYSV -DLEHOST 130, 134, 147: -lm  132: -DSYSV  126: -lm -lc -L/usr/ucblib -lucb -lmalloc
Memory 4-Way Interleaved
```

For More Information Contact:
SPEC
10754 Ambassador Drive, Suite 201
Manassas, VA 22110
(703) 331-0180
info@specbench.org
http://www.specbench.org

-- Prepared By: --