SPEC CINT95rate Results

©Copyright 1995, Standard Performance Evaluation Corporation

Dell Computer Corporation
Dell Dimension XPS (75MHz)

SPECint_rate95 = 21.5

SPECint_rate_base95 = 21.5

SPEC license # 14	Tested By: Intel	Test Date: May-96	Hardware Avail: Jun-95	Software Avail: Mar-96



Hardware/Software Configuration for:
Dell Dimension XPS (75MHz)

Hardware

Model Name:	XPS
CPU:	75MHz Pentium processor
FPU:	Integrated
Number of CPU(s):	1
Primary Cache:	8KBI+8KBD
Secondary Cache:	512KB(I+D) (burst)
Other Cache:	None
Memory:	64MB(EDO)
Disk Subsystem:	1MB IDE Quantum Fireball
Other Hardware:	Integrated EIDE disk controller

Software

Operating System:	UnixWare 2.0, UnixWare SDK
Compiler:	Intel C Reference Compiler 2.3
File System:	UFS (/tmp as 8MB /tmpfs)
System State:	Single User (root + killall)

Benchmark # and Name	Base Copies	Base Run Time	Base SPEC Ratio	Copies	Run Time	SPEC Ratio
099.go	1	1775	23.3	1	1775	23.3
124.m88ksim	1	790	21.6	1	790	21.6
126.gcc	1	693	22.1	1	693	22.1
129.compress	1	863	18.8	1	863	18.8
130.li	1	706	24.2	1	706	24.2
132.ijpeg	1	1392	15.5	1	1392	15.5
134.perl	1	654	26.2	1	654	26.2
147.vortex	1	1098	22.1	1	1098	22.1
SPECint_rate_base95 (G. Mean)			21.5			
SPECint_rate95 (G. Mean)						21.5

Notes/Tuning Information

```
Base and peak flags are the same and use Feedback Directed Optimization
Pass1: -tp p5 -ipo -prof_gen -ircdb_dir /tmp/IRCDB -dn
Pass2: -tp p5 -ipo -prof_use -ircdb_dir /tmp/IRCDB -dn
-ircdb_dir is a location flag and not an optimization flag
Portability: 124: -DSYSV -DLEHOST 130, 134, 147: -lm  132: -DSYSV  126: -lm -lc -L/usr/ucblib -lucb -lmalloc
```

For More Information Contact:
SPEC
10754 Ambassador Drive, Suite 201
Manassas, VA 22110
(703) 331-0180
info@specbench.org
http://www.specbench.org

-- Prepared By: --