SPEC CINT95rate Results

©Copyright 1995, Standard Performance Evaluation Corporation

Dell Computer Corporation
Precision WorkStation 410 (450MHz)

SPECint_rate95 = 310

SPECint_rate_base95 = 310

SPEC license # 55 | Tested By: Dell | Test Date: Aug-98 | Hardware Avail: Aug-98 | Software Avail: Apr-97



Hardware/Software Configuration for:
Precision WorkStation 410 (450MHz)

Hardware

Model Name:	Precision WorkStation 410 (450MHz)
CPU:	450 MHz Pentium II
FPU:	Integrated
Number of CPU(s):	2
Primary Cache:	16KBI+16KBD
Secondary Cache:	512KB (I+D)ECC
Other Cache:	None
Memory:	256MB ECC SDRAM
Disk Subsystem:	SCSI
Other Hardware:	

Software

Operating System:	Microsoft Windows NT 4.0 sp3
Compiler:	Intel C Compiler 2.4 for Windows NT, Microsoft Visual C++(for libraries)
File System:	FAT
System State:	default

Benchmark # and Name	Base Copies	Base Run Time	Base SPEC Ratio	Copies	Run Time	SPEC Ratio
099.go	2	288	288	2	288	288
124.m88ksim	2	107	320	2	107	320
126.gcc	2	108	283	2	108	283
129.compress	2	124	261	2	124	261
130.li	2	103	331	2	103	331
132.ijpeg	2	142	305	2	142	305
134.perl	2	94.2	363	2	94	363
147.vortex	2	142	342	2	142	342
SPECint_rate_base95 (G. Mean)			310			
		SPECint_rate95 (G. Mean)				310

Notes/Tuning Information

```
Base and peak flags are the same and use Feedback Directed
Pass1: -G6 -Qipo -Qxi -Qprof_gen -Qprof_dir c:/temp/IRCDB
Pass2: -G6 -Qipo -Qxi -Qprof_use -Qprof_dir c:/temp/IRCDB
-prof_dir is a location flag and not an optimization flag
Portability: 124:-DNT -DLEHOST  125: -Qlowercase
Portability: 126: -D__STDC__=0 -DONLY_INT_FIELDS=0 -Dalloca=_alloca
Portability: 132: -DSYSV -DMSDOS
Portability: 134: -DMSDOS -DI_TIME
The Intel Compiler 2.4 for Windows NT is shipped with VTune 2.4,
Microsoft Visual C++ 5.0 is also installed for libraries
```

For More Information Contact: SPEC info@spec.org http://www.spec.org/

-- Prepared By: --