SPEC CINT95 Results

©Copyright 1995, Standard Performance Evaluation Corporation

Dell Computer Corporation
Precision Workstation 610 (450MHz)

SPECint95 = 19.0

SPECint_base95 = 19.0

SPEC license # 55	Tested By: Dell	Test Date: Nov-98	Hardware Avail: Jan-99	Software Avail: Apr-97



Hardware/Software Configuration for:
Precision Workstation 610 (450MHz)

Hardware

Model Name:	Precision WorkStation 610 (450MHz)
CPU:	450 MHz Pentium II XEON
FPU:	Integrated
Number of CPU(s):	1
Primary Cache:	16KBI+16KBD
Secondary Cache:	1MB(I+D)ECC
Other Cache:	None
Memory:	256MB ECC SDRAM
Disk Subsystem:	SCSI
Other Hardware:	

Software

Operating System:	Microsoft Windows NT 4.0 sp3
Compiler:	Intel C Compiler 2.4 for Windows NT, Microsoft Visual C++(for libraries)
File System:	FAT
System State:	Default

Benchmark # and Name	Reference Time	Base Run Time	Base SPEC Ratio	Run Time	SPEC Ratio
099.go	4600	246	18.7	246	18.7
124.m88ksim	1900	106	17.9	106	17.9
126.gcc	1700	92.7	18.3	93	18.3
129.compress	1800	105	17.1	105	17.1
130.li	1900	96.3	19.7	96	19.7
132.ijpeg	2400	136	17.7	136	17.7
134.perl	1900	91.7	20.7	92	20.7
147.vortex	2700	121	22.2	121	22.2
SPECint_base95 (G. Mean)			19.0		
		SPECint95 (G. Mean)			19.0

Notes/Tuning Information

```
Base and peak flags are the same and use Feedback Directed
Pass1: -G6 -Qipo -Qxi -Qprof_gen -Qprof_dir c:/temp/IRCDB
Pass2: -G6 -Qipo -Qxi -Qprof_use -Qprof_dir c:/temp/IRCDB
-prof_dir is a location flag and not an optimization flag
Portability: 124:-DNT -DLEHOST  125: -Qlowercase
Portability: 126: -D__STDC__=0 -DONLY_INT_FIELDS=0 -Dalloca=_alloca
Portability: 132: -DSYSV -DMSDOS
Portability: 134: -DMSDOS -DI_TIME
The Intel Compiler 2.4 for Windows NT is shipped with VTune 2.4,
Microsoft Visual C++ 5.0 is also installed for libraries
```

For More Information Contact: SPEC info@spec.org http://www.spec.org/