HPC2002 Result

Copyright ©1999-2002, Standard Performance Evaluation Corporation

Hewlett-Packard Company
hp server rx5670 (1000MHz Itanium2)

SPECenvS2002 = 1561

SPEC license #: HPG2116	Tested by: Hewlett-Packard Company	Test site: Richardson, Texas	Test date: Mar-2003	HW Avail: Sep-2002	SW Avail: Feb-2003

Benchmark	Reference Time	Runtime	Ratio
360.wrf_s	86400	55.4	1561



Hardware

CPU:	Intel Itanium 2
CPU MHz:	1000
FPU:	Integrated
CPU(s) enabled:	4
CPU(s) orderable:	1 to 4
Primary Cache:	L1 Inst/Data: 16 KB, associativity = 4
Secondary Cache:	L2 Unified: 256 KB, associativity = 8
L3 Cache:	L3 Unified: 3072 KB, associativity = 12
Other Cache:	None
Memory:	24GB
Disk Subsystem:	1x9GB SCSI disk (root), 1x9GB SCSI disk (swap)
Other Hardware:	--

Software

Parallel:	OpenMP
Processes-Threads:	4
MPI Processes:	--
OpenMP Threads:	4
Operating System:	HP-UX 11i TCOE B.11.22
Compiler:	HP C/ANSI C Compiler v11.22 HP aC++ Compiler A.05.36 HP Fortran 90 Compiler v2.6.5 HP MPI 1.08.00 PHSS_28697: f90 product PHSS_27286: C product PHSS_27287: U2comp PHSS_27288: Linker PHSS_27289: Libm PHSS_27290: Assembler PHSS_27291: PBO
File System:	Online JFS
System State:	Multi-user
Other Software:	NetCDF 3.5.0, HP MPI 1.08.00

Notes/Tuning Information

```
  Flags:
    f90  +DD64 +noppu +Ofaster +O3 +Oopenmp +Oinfo
       -I/scratch/lieb/netcdf-3.5.0/include
       -minshared  -L /opt/mpi/lib/hpux64 -lmpi
       -L /scratch/lieb/netcdf-3.5.0/lib/hpux64 -lnetcdf

    aCC -Ae +DD64 +Ofaster +O3 +Oopenmp +Oinfo -DNOUNDERSCORE -D_OPENMP
       -minshared  -L /opt/mpi/lib/hpux64 -lmpi
       -L /scratch/lieb/netcdf-3.5.0/lib/hpux64 -lnetcdf

    /usr/ccs/lbin/cpp   -I. -C -P -D_OPENMP

    NETCDF built with +O2 +DD64

    ENV_SPEC_HPG_PARALLEL=OMP

  Alternate Source used:
    None

  User Environment:
    export OMPI_COMM_SIZE=4
    use_submit_for_speed=1
    submit=export OMP_NUM_THREADS=
           $OMPI_COMM_SIZE;$command

Kernel Paramters (/stand/system):
    maxdsiz          0x7b03a000
    maxdsiz_64bit    0x4000000000
```

Copyright ©1999-2002, Standard Performance Evaluation Corporation

Notes/Tuning Information (Continued)

```
maxssiz          0x10000000
maxssiz_64bit    0x40000000
maxtsiz          1073741824
maxtsiz_64bit    4294967296
vps_pagesize     4
vps_ceiling      64
dbc_min_pct      10
dbc_max_pct      10
```