



SPEC® MPIM2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

Intel Corporation

Atlantis (Intel Xeon X5482, 3.20 GHz)

SPECmpIM_peak2007 = Not run

SPECmpIM_base2007 = NC

MPI2007 license: 13

Test sponsor: Intel Corporation

Tested by: Pavel Shelepuhin

Test date: Mar-2009

Hardware Availability: Sep-2008

Software Availability: Jun-2009

Ranks
104.milc
107.leslie3d
113.GemsFDTD
115.fds4
121.pop2
122.tachyon
126.lammps
127.wrf2
128.GAPgeomfem
129.tera_tf
130.soccg
132.zeusmp2
137.lu

Results Table

Benchmark	Base								Peak							
	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
104.milc	64	NC	NC	NC	NC											
107.leslie3d	64	NC	NC	NC	NC											

Table continues on next page. Results appear in the order in which they were run. Bold underlined text indicates a median measurement.



SPEC MPIM2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

Intel Corporation

Atlantis (Intel Xeon X5482, 3.20 GHz)

~~SPECmpIM_peak2007 = Not Run~~

MPI2007 license: 13

Test sponsor: Intel Corporation

Tested by: Pavel Shelepuhin

Test date: Mar-2009

Hardware Availability: Sep-2008

Software Availability: Jun-2009

Results Table (Continued)

Benchmark	Base							Peak						
	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
113.GemsFDTD	64	NC	NC	NC	NC	NC	NC							
115.fds4	64	NC	NC	NC	NC	NC	NC							
121.pop2	64	NC	NC	NC	NC	NC	NC							
122.tachyon	64	NC	NC	NC	NC	NC	NC							
126.lammps	64	NC	NC	NC	NC	NC	NC							
127.wrf2	64	NC	NC	NC	NC	NC	NC							
128.GAPgeomfem	64	NC	NC	NC	NC	NC	NC							
129.tera_tf	64	NC	NC	NC	NC	NC	NC							
130.socorro	64	NC	NC	NC	NC	NC	NC							
132.zeusmp2	64	NC	NC	NC	NC	NC	NC							
137.lu	64	NC	NC	NC	NC	NC	NC							

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Hardware Summary

Type of System:	Homogeneous
Compute Node:	Atlantis Node
Interconnect:	IB Switch Gigabit Ethernet
File Server Node:	HOME
Total Compute Nodes:	8
Total Ranks:	16
Total Cores:	64
Total Threads:	64
Total Memory:	128 GB
Base Ranks Run:	64
Minimum Peak Ranks:	--
Maximum Peak Ranks:	--

Software Summary

C Compiler:	Intel C++ Compiler 11.1 for Linux
C++ Compiler:	Intel C++ Compiler 11.1 for Linux
Fortran Compiler:	Intel Fortran Compiler 11.1 for Linux
Base Pointers:	64-bit
Peak Pointers:	64-bit
MPI Library:	Intel MPI Library 3.2 for Linux
Other MPI Info:	None
Pre-processors:	No
Other Software:	Intel MPI Library 3.2 for Linux Multi-Purpose Daemon (MPD)



SPEC MPIM2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

Intel Corporation

Atlantis (Intel Xeon X5482, 3.20 GHz)

SPECmpIM_peak2007 = Not Run

SPECmpIM_base2007 = NC

MPI2007 license: 13

Test sponsor: Intel Corporation

Tested by: Pavel Shelepuhin

Test date: Mar-2009

Hardware Availability: Sep-2008

Software Availability: Jun-2009

Node Description: Atlantis Node

Hardware

Number of nodes: 8
Uses of the node: compute
Vendor: Intel
Model: SR1560SF
CPU Name: Intel Xeon X5482
CPU(s) orderable: 1-2 chips
Chips enabled: 2
Cores enabled: 8
Cores per chip: 4
Threads per core: 1
CPU Characteristics: 1600 MHz FSB
CPU MHz: 3200
Primary Cache: 32 KB I + 32 KB D on chip per core
Secondary Cache: 12 MB I+D on chip per chip - 6 MB shared / 2 cores
L3 Cache: None
Other Cache: None
Memory: 16 GB (FBDIMM 8x2-GB 667 MHz)
Disk Subsystem: Seagate Barracuda ES 1TB ST3250620NS
Other Hardware: None
Adapter:
Number of Adapters: 1
Slot Type: PCI-Express x8
Data Rate: Gbps Ethernet
Ports Used: 1
Interconnect Type: Mellanox MHGH29-XTC
Adapter:
Number of Adapters: 1
Slot Type: PCIe x16 Gen2
Data Rate: InfiniBand 4x DDR
Ports Used: 1
Interconnect Type: InfiniBand

Software

Adapter: Intel (ESB2) 82563EB Dual-Port Gigabit Ethernet Controller
Adapter Driver: e1000
Adapter Firmware: None
Adapter: Mellanox MHGH29-XTC
Adapter Driver: OFED 1.3.1
Adapter Firmware: 2.5.0
Operating System: RedHat EL 5 Update 2, kernel 2.6.18-92
Local File System: Linux/ext2
Shared File System: NFS
System State: Multi-User
Other Software: PBS Pro 8.0



SPEC MPIM2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

Intel Corporation

Atlantis (Intel Xeon X5482, 3.20 GHz)

SPECmpIM_peak2007 = Not Run

SPECmpIM_base2007 = NC

MPI2007 license: 13

Test sponsor: Intel Corporation

Tested by: Pavel Shelepuhin

Test date: Mar-2009

Hardware Availability: Sep-2008

Software Availability: Jun-2009

Node Description: HOME

Hardware

Number of nodes: 1
Uses of the node: fileserver
Vendor: Intel
Model: SSR212CC
CPU Name: Intel Xeon
CPU(s) orderable: 2 chips
Chips enabled: 2
Cores enabled: 2
Cores per chip: 1
Threads per core: 1
CPU Characteristics:
CPU MHz: 2800
Primary Cache: 12 KB I + 16 KB D on chip per chip
Secondary Cache: 1 MB I+D on chip per chip
L3 Cache: None
Other Cache: None
Memory: 2 GB
Disk Subsystem: 3 disks, 1 GB/disk, 1 TB total, 1TB available
Other Hardware: None
Adapter: Intel 82546GB Dual-Port Gigabit Ethernet Controller
Number of Adapters: 1
Slot Type: PCI-Express x8
Data Rate: 1 Gbps Ethernet
Ports Used: 1
Interconnect Type: Ethernet

Software

Adapter: Intel 82546GB Dual-Port Gigabit Ethernet Controller
Adapter Driver: e1000
Adapter Firmware: N/A
Operating System: RedHat EL 4 Update 4
Local File System: Linux/ext2
Shared File System: NFS
System State: Multi-User
Other Software: None

Interconnect Description: IB Switch

Hardware

Vendor: Cisco
Model: Cisco SFS 9120
Switch Model: Cisco SFS 9120
Number of Switches: 1
Number of Ports: 120

Software

Continued on next page



SPEC MPIM2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

Intel Corporation

Atlantis (Intel Xeon X5482, 3.20 GHz)

SPECmpIM_peak2007 = Not run

SPECmpIM_base2007 = NC

MPI2007 license: 13

Test sponsor: Intel Corporation

Tested by: Pavel Shelepuhin

Test date: Mar-2009

Hardware Availability: Sep-2008

Software Availability: Jun-2009

Interconnect Description: IB Switch

Data Rate: InfiniBand 4x DDR
Firmware: 4.1.1.11
Topology: Single switch
Primary Use: MPI traffic

Interconnect Description: Gigabit Ethernet

Hardware	Software
Vendor: Cisco	
Model: Cisco Catalyst 4506	
Switch Model: Cisco Catalyst 4506	
Number of Switches: 1	
Number of Ports: 144	
Data Rate: 1Gbps Ethernet	
Firmware: --	
Topology: Star	
Primary Use: Cluster File System	

Submit Notes

The config file option 'submit' was used.

General Notes

PBS Pro was used for job submission. It has no impact on performance.
Can be found at: <http://www.altair.com>

Base Compiler Invocation

C benchmarks:
mpiicc

Continued on next page



SPEC MPIM2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

Intel Corporation

Atlantis (Intel Xeon X5482, 3.20 GHz)

~~SPECmpIM_peak2007 = Not run~~

MPI2007 license: 13

Test sponsor: Intel Corporation

Tested by: Pavel Shelepuhin

Test date: Mar-2009

Hardware Availability: Sep-2008

Software Availability: Jun-2009

Base Compiler Invocation (Continued)

C++ benchmarks:

126.lammps: mpiicc

Fortran benchmarks:
mpiifort

Benchmarks using both Fortran and C:
mpiicc mpiifort

Base Portability Flags

121.pop2: -DSPEC_MPI_CAS_FLAG

126.lammps: -DMPICH_IGNORE_CXX_SEEK

127.wrf2: -DSPEC_MPI_CAS_FLAG -DSPEC_MPI_LINUX

Base Optimization Flags

C benchmarks:

-O3 -xT -no-prec-div

C++ benchmarks:

120.lammps: -O3 -xT -no-prec-div

Fortran benchmarks:

-O3 -xT -no-prec-div

Benchmarks using both Fortran and C:

-O3 -xT -no-prec-div



SPEC MPIM2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

Intel Corporation

Atlantis (Intel Xeon X5482, 3.20 GHz)

SPECmpIM_peak2007 = Not Run

SPECmpIM_base2007 = NC

MPI2007 license: 13

Test sponsor: Intel Corporation

Tested by: Pavel Shelepuhin

Test date: Mar-2009

Hardware Availability: Sep-2008

Software Availability: Jun-2009

The flags file that was used to format this result can be browsed at

http://www.spec.org/mpi2007/flags/EM64T_Intel111_flags.html

You can also download the XML flags source by saving the following link:

http://www.spec.org/mpi2007/flags/EM64T_Intel111_flags.xml

SPEC and SPEC MPI are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC MPI2007 v1.1.

Report generated on Tue Jul 22 13:36:44 2014 by SPEC MPI2007 PS/PDF formatter v1463.

Originally published on 15 April 2009.