



# SPEC® MPIM2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

## Lenovo Global Technology

SPECmpiM\_peak2007 = Not Run

ThinkSystem SR650  
(Intel Xeon Platinum 8180 CPU, 2.50GHz)

SPECmpiM\_base2007 = 17.8

MPI2007 license: 9017


Test date: Jun-2017

Test sponsor: Lenovo Global Technology

Hardware Availability: Aug-2017

Tested by: Lenovo Global Technology

Software Availability: Apr-2017



## Results Table

Benchmark	Base								Peak							
	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio		
104.milc	56	138	11.3	138	11.3	<b>138</b>	<b>11.3</b>									
107.leslie3d	56	346	15.1	346	15.1	<b>346</b>	<b>15.1</b>									
113.GemsFDTD	56	<b>317</b>	<b>19.9</b>	317	19.9	317	19.9									
115.fds4	56	185	10.5	<b>189</b>	<b>10.3</b>	190	10.3									
121.pop2	56	170	24.3	170	24.3	<b>170</b>	<b>24.3</b>									
122.tachyon	56	170	16.4	<b>169</b>	<b>16.5</b>	169	16.6									
126.lammps	56	214	13.6	214	13.6	<b>214</b>	<b>13.6</b>									
127.wrf2	56	<b>305</b>	<b>25.5</b>	306	25.5	305	25.5									
128.GAPgeofem	56	102	20.2	<b>102</b>	<b>20.3</b>	101	20.4									
129.tera_tf	56	191	14.5	191	14.5	<b>191</b>	<b>14.5</b>									

Table continues on next page. Results appear in the order in which they were run. Bold underlined text indicates a median measurement.



# SPEC MPIM2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

## Lenovo Global Technology

SPECmpiM\_peak2007 = Not Run

ThinkSystem SR650  
(Intel Xeon Platinum 8180 CPU, 2.50GHz)

SPECmpiM\_base2007 = 17.8

MPI2007 license: 9017

Test date: Jun-2017

Test sponsor: Lenovo Global Technology

Hardware Availability: Aug-2017

Tested by: Lenovo Global Technology

Software Availability: Apr-2017

### Results Table (Continued)

Benchmark	Base							Peak						
	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
130.socorro	56	97.0	39.4	<u>96.7</u>	<u>39.5</u>	96.6	39.5							
132.zeusmp2	56	168	18.4	<u>168</u>	<u>18.4</u>	168	18.5							
137.lu	56	223	16.5	<u>219</u>	<u>16.8</u>	217	16.9							

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

#### Hardware Summary

Type of System: Homogeneous  
 Compute Node: ThinkSystem SR650  
 Interconnect: N/A  
 Total Compute Nodes: 1  
 Total Chips: 2  
 Total Cores: 56  
 Total Threads: 56  
 Total Memory: 768 GB  
 Base Ranks Run: 56  
 Minimum Peak Ranks: --  
 Maximum Peak Ranks: --

#### Software Summary

C Compiler: Intel C++ Compiler 17.0 Update 4 for Linux  
 Version 17.0.4 Build 20170411  
 C++ Compiler: Intel C++ Compiler 17.0 Update 4 for Linux  
 Version 17.0.4 Build 20170411  
 Fortran Compiler: Intel Fortran Compiler 17.0 Update 4 for Linux  
 Version 17.0.4 Build 20170411  
 Base Pointers: 64-bit  
 Peak Pointers: Not Applicable  
 MPI Library: Intel MPI Library for Linux\* OS  
 Version 2017 Update 3 Build 20170405  
 Other MPI Info: None  
 Pre-processors: No  
 Other Software: None

### Node Description: ThinkSystem SR650

#### Hardware

Number of nodes: 1  
 Uses of the node: compute  
 Vendor: Lenovo Global Technology  
 Model: SR650  
 CPU Name: Intel Xeon Platinum 8180  
 CPU(s) orderable: 2 chips  
 Chips enabled: 2  
 Cores enabled: 56  
 Cores per chip: 56  
 Threads per core: 1  
 CPU Characteristics: None  
 CPU MHz: 2500  
 Primary Cache: 32 KB I + 32 KB D on chip per core  
 Secondary Cache: 1 MB I+D on chip per core  
 L3 Cache: 38.5 MB I+D on chip per chip  
 shared / 28 cores  
 Other Cache: None  
 Memory: 768 GB (24 x 32GB 2Rx4 PC4-2666V)  
 Disk Subsystem: 2 x 800 GB 12 Gbps SAS 2.5" SSD (RAID 1)  
 Other Hardware: ThinkSystem RAID 930-8i 2GB Flash  
 Adapter: N/A  
 Number of Adapters: 0  
 Slot Type: N/A  
 Data Rate: N/A

#### Software

Adapter: N/A  
 Adapter Driver: N/A  
 Adapter Firmware: N/A  
 Operating System: Red Hat Enterprise Linux Server release 7.3,  
 Kernel 3.10.0-514.el7.x86\_64  
 Local File System: xfs  
 Shared File System: None  
 System State: N/A  
 Other Software: NONE

Continued on next page



# SPEC MPIM2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

## Lenovo Global Technology

SPECmpiM\_peak2007 = Not Run

ThinkSystem SR650  
(Intel Xeon Platinum 8180 CPU, 2.50GHz)

SPECmpiM\_base2007 = 17.8

MPI2007 license: 9017

Test date: Jun-2017

Test sponsor: Lenovo Global Technology

Hardware Availability: Aug-2017

Tested by: Lenovo Global Technology

Software Availability: Apr-2017

### Node Description: ThinkSystem SR650

Ports Used: 0  
Interconnect Type: None

### Interconnect Description: N/A

#### Hardware

#### Software

Vendor: N/A  
Model: N/A  
Switch Model: N/A  
Number of Switches: 0  
Number of Ports: 0  
Data Rate: N/A  
Firmware: N/A  
Topology: N/A  
Primary Use: N/A

### Submit Notes

The config file option 'submit' was used.

### General Notes

MPI startup command:  
mpiexec.hydra command was used to start MPI jobs.

RAM configuration:  
Compute nodes have 2x32GB RDIMM on each memory channel.

Add "intel\_idle.max\_cstate=0 intel\_pstate=disable" into grub

BIOS settings:  
Operating Mode : Maximum Performance Mode  
Intel Hyper-Threading Technology (SMT): Disabled  
Intel Turbo Boost Technology (Turbo) : Enabled  
SNC : Enable

### Base Compiler Invocation

C benchmarks:  
mpiicc

C++ benchmarks:

Continued on next page



# SPEC MPIM2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

Lenovo Global Technology

SPECmpiM\_peak2007 = Not Run

ThinkSystem SR650  
(Intel Xeon Platinum 8180 CPU, 2.50GHz)

SPECmpiM\_base2007 = 17.8

MPI2007 license: 9017

Test date: Jun-2017

Test sponsor: Lenovo Global Technology

Hardware Availability: Aug-2017

Tested by: Lenovo Global Technology

Software Availability: Apr-2017

## Base Compiler Invocation (Continued)

126.lammps: mpiicpc

Fortran benchmarks:

mpiifort

Benchmarks using both Fortran and C:

mpiicc mpiifort

## Base Portability Flags

121.pop2: -DSPEC\_MPI\_CASE\_FLAG  
126.lammps: -DMPICH\_IGNORE\_CXX\_SEEK  
127.wrf2: -DSPEC\_MPI\_CASE\_FLAG -DSPEC\_MPI\_LINUX  
130.socorro: -assume nostd\_intent\_in

## Base Optimization Flags

C benchmarks:

-O3 -ipo -xCORE-AVX512 -no-prec-div

C++ benchmarks:

126.lammps: -O3 -ipo -xCORE-AVX512 -no-prec-div

Fortran benchmarks:

-O3 -ipo -xCORE-AVX512 -no-prec-div

Benchmarks using both Fortran and C:

-O3 -ipo -xCORE-AVX512 -no-prec-div

The flags file that was used to format this result can be browsed at

[http://www.spec.org/mpi2007/flags/EM64T\\_Intel121\\_flags.20170711.html](http://www.spec.org/mpi2007/flags/EM64T_Intel121_flags.20170711.html)

You can also download the XML flags source by saving the following link:

[http://www.spec.org/mpi2007/flags/EM64T\\_Intel121\\_flags.20170711.xml](http://www.spec.org/mpi2007/flags/EM64T_Intel121_flags.20170711.xml)



# SPEC MPI2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

## Lenovo Global Technology

ThinkSystem SR650  
(Intel Xeon Platinum 8180 CPU, 2.50GHz)

SPECmpiM\_peak2007 = Not Run

SPECmpiM\_base2007 = 17.8

**MPI2007 license:** 9017

**Test sponsor:** Lenovo Global Technology

**Tested by:** Lenovo Global Technology

**Test date:** Jun-2017

**Hardware Availability:** Aug-2017

**Software Availability:** Apr-2017

SPEC and SPEC MPI are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC MPI2007 v2.0.1.  
Report generated on Wed Jul 12 12:45:51 2017 by SPEC MPI2007 PS/PDF formatter v1463.  
Originally published on 11 July 2017.