SPEC® MPIM2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

Intel Corporation
Endeavor

SPECmpiM_peak2007 = Not Run

SPECmpiM_base200[illegible] = NC

MPI2007 license: 13
Test sponsor: Intel Corporation
Tested by: Grigory Zagorodnev

Test date: Jan-2008
Hardware Availability: Dec-2007
Software Availability: Dec-2007

SPEC has determined that this result was not in compliance with the SPEC MPI2007 run and reporting rules. Specifically, the result did not meet the requirement for baseline optimization flags to not use assertion flags (the flag -fno-alias is a violation of this rule). The result was found to be performance neutral compared to runs without -fno-alias. Replacement be found at http://www.spec.org/mpi2007/results/res2008q4/mpi2007-20080922-(

Non-Compliant



Results Table

Benchmark	Base							Peak						
	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
104.milc	128	NC	NC	NC	NC	NC	NC							
107.leslie3d	128	NC	NC	NC	NC	NC	NC							

Table continues on next page. Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

SPEC MPIM2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

Intel Corporation
Endeavor

SPECmpiM_peak2007 = Not Run

SPECmpiM_base200[illegible] = NC

MPI2007 license: 13
Test sponsor: Intel Corporation
Tested by: Grigory Zagorodnev

Test date: Jan-2008
Hardware Availability: Dec-2007
Software Availability: Dec-2007

SPEC has determined that this result was not in compliance with the SPEC MPI2007 run and reporting rules. Specifically, the result did not meet the requirement for baseline optimization flags to not use assertion flags (the flag -fno-alias is a violation of this rule). The result was found to be performance neutral compared to runs without -fno-alias. Replacement be found at http://www.spec.org/mpi2007/results/res2008q4/mpi2007-20080922-(

Non-Compliant

Results Table (Continued)

Benchmark	Base							Peak						
	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
113.GemsFDTD	128	NC	NC	NC	NC	NC	NC							
115.fds4	128	NC	NC	NC	NC	NC	NC							
121.pop2	128	NC	NC	NC	NC	NC	NC							
122.tachyon	128	NC	NC	NC	NC	NC	NC							
126.lammps	128	NC	NC	NC	NC	NC	NC							
127.wrf2	128	NC	NC	NC	NC	NC	NC							
128.GAPgeofem	128	NC	NC	NC	NC	NC	NC							
129.tera_tf	128	NC	NC	NC	NC	NC	NC							
130.socorro	128	NC	NC	NC	NC	NC	NC							
132.zeusmp2	128	NC	NC	NC	NC	NC	NC							
137.lu	128	NC	NC	NC	NC	NC	NC							

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Hardware Summary

Type of System:	Homogeneous
Compute Node:	Endeavor Node
Interconnect:	IB Switch Gigabit Ethernet
File Server Node:	Panasas Fileserver
Total Compute Nodes:	16
Total Chips:	32
Total Cores:	128
Total Threads:	128
Total Memory:	256 GB
Base Ranks Run:	128
Minimum Peak Ranks:	--
Maximum Peak Ranks:	--

Software Summary

C Compiler:	Intel C++ Compiler 10.1 for Linux (10.1.004)
C++ Compiler:	Intel C++ Compiler 10.1 for Linux (10.1.004)
Fortran Compiler:	Intel Fortran Compiler 10.1 for Linux (10.1.004)
Base Pointers:	64-bit
Peak Pointers:	64-bit
MPI Library:	Intel MPI Library 3.1 for Linux (3.1.020)
Other MPI Info:	None
Pre-processors:	No
Other Software:	None

SPEC MPIM2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

Intel Corporation
Endeavor

SPECmpiM_peak2007 = Not Run

SPECmpiM_base200[illegible] = NC

MPI2007 license: 13
Test sponsor: Intel Corporation
Tested by: Grigory Zagorodnev

Test date: Jan-2008
Hardware Availability: Dec-2007
Software Availability: Dec-2007

SPEC has determined that this result was not in compliance with the SPEC MPI2007 run and reporting rules. Specifically, the result did not meet the requirement for baseline optimization flags to not use assertion flags (the flag -fno-alias is a violation of this rule). The result was found to be performance neutral compared to runs without -fno-alias. Replacement be found at http://www.spec.org/mpi2007/results/res2008q4/mpi2007-20080922-(

Non-Compliant

Node Description: Endeavor Node

Hardware

Number of nodes:	16
Uses of the node:	compute
Vendor:	Intel
Model:	SR1560SF
CPU Name:	Intel Xeon CPU E5462
CPU(s) orderable:	1-2 chips
Chips enabled:	2
Cores enabled:	8
Cores per chip:	4
Threads per core:	1
CPU Characteristics:	1600MHz FSB
CPU MHz:	2800
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	12 MB I+D on chip per chip, 6 MB shared / 2 cores
L3 Cache:	None
Other Cache:	None
Memory:	16 GB (8 DIMM, 16x1-GB 667 MHz)
Disk Subsystem:	Seagate Barracuda ES 250 GB ST3250620NS
Other Hardware:	None
Adapter:	Intel (ESB2) 82563EB Dual-Port Gigabit Ethernet Controller
Number of Adapters:	1
Slot Type:	PCIe x8
Data Rate:	1 Gbps Ethernet
Ports Used:	1
Interconnect Type:	Ethernet
Adapter:	Mellanox MHGH28-XTC IB DDR (PCIe x8 Gen1 2.5 GT/s)
Number of Adapters:	1
Slot Type:	PCIe x16 Gen2
Data Rate:	InfiniBand 4x DDR
Ports Used:	1
Interconnect Type:	InfiniBand

Software

Adapter:	Intel (ESB2) 82563EB Dual-Port Gigabit Ethernet Controller
Adapter Driver:	e1000
Adapter Firmware:	N/A
Adapter:	Mellanox MHGH28-XTC IB DDR (PCIe x8 Gen1 2.5 GT/s)
Adapter Driver:	OFED 1.2.5
Adapter Firmware:	2.2
Operating System:	RedHat EL 4 Update 4
Local File System:	Linux/ext3
Shared File System:	DirectFlow
System State:	Multi-User
Other Software:	PBS Pro 8.0

SPEC MPIM2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

Intel Corporation
Endeavor

SPECmpiM_peak2007 = Not Run

SPECmpiM_base2007 = NC

MPI2007 license: 13
Test sponsor: Intel Corporation
Tested by: Grigory Zagorodnev

Test date: Jan-2008
Hardware Availability: Dec-2007
Software Availability: Dec-2007

SPEC has determined that this result was not in compliance with the SPEC MPI2007 run and reporting rules. Specifically, the result did not meet the requirement for baseline optimization flags to not use assertion flags (the flag -fno-alias is a violation of this rule). The result was found to be performance neutral compared to runs without -fno-alias. Replacement be found at http://www.spec.org/mpi2007/results/res2008q4/mpi2007-20080922-

Non-Compliant

Node Description: Panasas File Server

Hardware

Number of nodes:	1
Uses of the node:	fileserver
Vendor:	Panasas
Model:	ActiveStor 3050
CPU Name:	--
CPU(s) orderable:	1-2 chips
Chips enabled:	1
Cores enabled:	1
Cores per chip:	1
Threads per core:	1
CPU Characteristics:	--
CPU MHz:	0
Primary Cache:	None
Secondary Cache:	None
L3 Cache:	None
Other Cache:	None
Memory:	1 MB
Disk Subsystem:	140 disks, 750GB/disk, 105TB total, 7 Shelves
Other Hardware:	None
Adapter:	
Number of Adapters:	1
Slot Type:	--
Data Rate:	1Gbps Ethernet
Ports Used:	4
Interconnect Type:	Ethernet

Software

Adapter:	--
Adapter Driver:	--
Adapter Firmware:	N/A
Operating System:	2.3.7.a-195733.1
Local File System:	PanFS
Shared File System:	DirectFlow
System State:	Multi-User
Other Software:	None

Interconnect Description: IB Switch

Hardware

Vendor:	SilverStorm Technologies
Model:	Cisco SFS 7024D
Switch Model:	Cisco SFS 7024D
Number of Switches:	1
Number of Ports:	288

Software

Continued on next page

SPEC MPIM2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

Intel Corporation
Endeavor

SPECmpiM_peak2007 = Not Run

SPECmpiM_base2007 = NC

MPI2007 license: 13
Test sponsor: Intel Corporation
Tested by: Grigory Zagorodnev

Test date: Jan-2008
Hardware Availability: Dec-2007
Software Availability: Dec-2007

SPEC has determined that this result was not in compliance with the SPEC MPI2007 run and reporting rules. Specifically, the result did not meet the requirement for baseline optimization flags to not use assertion flags (the flag -fno-alias is a violation of this rule). The result was found to be performance neutral compared to runs without -fno-alias. Replacement be found at http://www.spec.org/mpi2007/results/res2008q4/mpi2007-20080922-

Non-Compliant

Interconnect Description: IB Switch

Data Rate:	InfiniBand 4x DDR
Firmware:	4.1.1.1.2
Topology:	Star
Primary Use:	MPI traffic

Interconnect Description: Gigabit Ethernet

Hardware		Software
Vendor:	Cisco	
Model:	Cisco Catalyst 4510	
Switch Model:	Cisco Catalyst 4510	
Number of Switches:	1	
Number of Ports:	332	
Data Rate:	1Gbps Ethernet	
Firmware:	N/A	
Topology:	Star	
Primary Use:	file system traffic	

Base Compiler Invocation

C benchmarks:

C++ benchmarks:

126.lammps: `mpiicpc`

Fortran benchmarks:
`mpiifort`

Benchmarks using both Fortran and C:
`mpiicc mpiifort`

SPEC MPIM2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

Intel Corporation
Endeavor

SPECmpiM_peak2007 = Not Run

SPECmpiM_base2007 = NC

MPI2007 license: 13
Test sponsor: Intel Corporation
Tested by: Grigory Zagorodnev

Test date: Jan-2008
Hardware Availability: Dec-2007
Software Availability: Dec-2007

SPEC has determined that this result was not in compliance with the SPEC MPI2007 run and reporting rules. Specifically, the result did not meet the requirement for baseline optimization flags to not use assertion flags (the flag -fno-alias is a violation of this rule). The result was found to be performance neutral compared to runs without -fno-alias. Replacement be found at http://www.spec.org/mpi2007/results/res2008q4/mpi2007-20080922-

Non-Compliant

Base Portability Flags

121.pop2: -DSPEC_MPI_CASE_FLAG
126.lammps: -DMPICH_IGNORE_CXX_SEEK
127.wrf2: -DSPEC_MPI_CASE_FLAG -DSPEC_[illegible]T_LINUX
130.socorro: -DSPEC_EIGHT_BYTE_LONG

Base Optimization Flags

C benchmarks:
-O3 -no-prec-div -fno-alias -xT

C++ benchmarks:

126.lammps: -O3 -no-prec-div -fno-alias -xT

Fortran benchmarks:
-O3 -no-prec-div -fno-alias -xT

Benchmarks using both Fortran and C:
-O3 -no-prec-div -fno-alias -xT

The flags file that was used to format this result can be browsed at
http://www.spec.org/mpi2007/flags/EM64T_Intel101_flags.html

You can also download the XML flags source by saving the following link:
http://www.spec.org/mpi2007/flags/EM64T_Intel101_flags.xml

SPEC MPIM2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

Intel Corporation
Endeavor

SPECmpiM_peak2007 = Not Run

SPECmpiM_base2007 = NC

MPI2007 license: 13
Test sponsor: Intel Corporation
Tested by: Grigory Zagorodnev

Test date: Jan-2008
Hardware Availability: Dec-2007
Software Availability: Dec-2007

SPEC has determined that this result was not in compliance with the SPEC MPI2007 run and reporting rules. Specifically, the result did not meet the requirement for baseline optimization flags to not use assertion flags (the flag -fno-alias is a violation of this rule). The result was found to be performance neutral compared to runs without -fno-alias. Replacement be found at http://www.spec.org/mpi2007/results/res2008q4/mpi2007-20080922-

Non-Compliant

SPEC and SPEC MPI are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC MPI2007 v1.0.
Report generated on Tue Jul 22 13:33:25 2014 by SPEC MPI2007 PS/PDF formatter v1463.
Originally published on 5 March 2008.