SPEC® MPIM2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

SGI

SGI Altix XE 1300
(Intel Xeon X5272, 3.4 GHz)

SPECmpiM_peak2007 = Not Run

SPECmpiM_base2007 = NC

MPI2007 license: 4
Test sponsor: SGI
Tested by: SGI

Test date: Jun-2008
Hardware Availability: Feb-2008
Software Availability: Apr-2008

Non-Compliant

	Ranks
104.milc	
107.leslie3d	
113.GemsFDTD	
115.fds4	
121.pop2	
122.tachyon	
126.lammps	
127.wrf2	
128.GAPgeofem	
129.tera_tf	
130.socorro	
132.zeusmp2	
137.lu	

Results Table

Benchmark	Base							Peak						
	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
104.milc	32	NC	NC	NC	NC									
107.leslie3d	32	NC	NC	NC	NC									
113.GemsFDTD	32	NC	NC	NC	NC									
115.fds4	32	NC	NC	NC	NC									
121.pop2	32	NC	NC	NC	NC									
122.tachyon	32	NC	NC	NC	NC									
126.lammps	32	NC	NC	NC	NC									
127.wrf2	32	NC	NC	NC	NC									
128.GAPgeofem	32	NC	NC	NC	NC									

Table continues on next page. Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

SPEC MPIM2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

SGI

SGI Altix XE 1300
(Intel Xeon X5272, 3.4 GHz)

SPECmpiM_peak2007 = Not Run

SPECmpiM_base2007 = NC

MPI2007 license: 4
Test sponsor: SGI
Tested by: SGI

Test date: Jun-2008
Hardware Availability: Feb-2008
Software Availability: Apr-2008

Results Table (Continued)

Benchmark	Base							Peak						
	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
129.tera_tf	32	NC	NC	NC	NC									
130.socorro	32	NC	NC	NC	NC									
132.zeusmp2	32	NC	NC	NC	NC									
137.lu	32	NC	NC	NC	NC									

Results appear in the order in which they were run. Bold underlined text indicates median measurement.

Hardware Summary

Type of System:	Homogeneous
Compute Node:	SGI Altix XE 320 Compute Node
Interconnects:	InfiniBand (MPI) InfiniBand (I/O)
File Server Node:	SGI InfiniteStorage NAS/SAN
Total Compute Nodes:	8
Total Chips:	16
Total Cores:	32
Total Threads:	32
Total Memory:	128 GB
Base Ranks Run:	32
Minimum Peak Ranks:	--
Maximum Peak Ranks:	--

Software Summary

Compiler:	Intel C Compiler for Linux Version 10.1, Build 20080312
C++ Compiler:	Intel C++ Compiler for Linux Version 10.1, Build 20080312
Fortran Compiler:	Intel Fortran Compiler for Linux Version 10.1, Build 20080312
Base Pointers:	64-bit
Peak Pointers:	64-bit
MPI Library:	Intel MPI 3.1.038
Other MPI Info:	OFED 1.3
Pre-processors:	None
Other Software:	None

Node Description: SGI Altix XE 320 Compute Node

Hardware

Number of nodes:	8
Uses of the node:	compute
Vendor:	SGI
Model:	SGI Altix XE 320 (Intel Xeon X5272, 3.4 GHz)
CPU Name:	Intel Xeon X5272
CPU(s) orderable:	1-2 chips
Chips enabled:	2
Cores enabled:	4
Cores per chip:	2
Threads per core:	1
CPU Characteristics:	Dual Core, 3.4 GHz
CPU MHz:	3392
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	6 MB I+D on chip per chip
L3 Cache:	None
Other Cache:	None
Memory:	16 GB (8*2GB PC2-6400 CL5-5-5 FB-DIMMs)
Disk Subsystem:	None
Other Hardware:	None
Adapter:	Mellanox MT25204 InfiniHost III Lx IB DDR (PCIe x8 Gen1 2.5 GT/s)

Continued on next page

Software

Adapter:	Mellanox MT25204 InfiniHost III Lx IB DDR (PCIe x8 Gen1 2.5 GT/s)
Adapter Driver:	OFED-1.3
Adapter Firmware:	1.2.0
Operating System:	SUSE Linux Enterprise Server 10 (x86_64) SP1 Kernel 2.6.16.46-0.12-smp
Local File System:	NFSv3
Shared File System:	NFSv3 IPoIB
System State:	Multi-user, run level 3
Other Software:	SGI ProPack 5 for Linux Service Pack 5

Non-Compliant

SPEC MPIM2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

SGI

SGI Altix XE 1300
(Intel Xeon X5272, 3.4 GHz)

SPECmpiM_peak2007 = Not Run

SPECmpiM_base2007 = NC

MPI2007 license: 4
Test sponsor: SGI
Tested by: SGI

Test date: Jun-2008
Hardware Availability: Feb-2008
Software Availability: Apr-2008

Node Description: SGI Altix XE 320 Compute Node

Number of Adapters:	1
Slot Type:	PCIe x8 Gen1
Data Rate:	InfiniBand 4x DDR
Ports Used:	1
Interconnect Type:	InfiniBand

Node Description: SGI InfiniteStorage NAS/SAN

Hardware

Number of nodes:	1
Uses of the node:	fileserver
Vendor:	SGI
Model:	SGI Altix 450 Density System (Itanium 2 Processor 9030 1.6GHz/8M)
CPU Name:	Dual-Core Intel Itanium 2 9030
CPU(s) orderable:	1-38 chips
Chips enabled:	2
Cores enabled:	4
Cores per chip:	2
Threads per core:	1
CPU Characteristics:	533 MHz FSB
CPU MHz:	1594
Primary Cache:	16 KB I + 16 KB D on chip per core
Secondary Cache:	1 MB I + 256 KB D on chip per core
L3 Cache:	4 MB I+D on chip per core
Other Cache:	None
Memory:	48 GB (24*2GB DDR2-400 DIMMS)
Disk Subsystem:	9.3 TB RAID 5 64 x 146 GB FibreChannel (Seagate Cheetah 15000 rpm)
Other Hardware:	None
Adapter:	Mellanox MT25208 InfiniHost III Ex (PCIe x8 Gen1 2.5 GT/s)
Number of Adapters:	
Slot Type:	PCIe x8 Gen1
Data Rate:	InfiniBand 4x DDR
Ports Used:	
Interconnect Type:	InfiniBand

Software

Adapter:	Mellanox MT25208 InfiniHost III Ex (PCIe x8 Gen1 2.5 GT/s)
Adapter Driver:	OFED-1.3
Adapter Firmware:	5.3.0
Operating System:	SUSE Linux Enterprise Server 10 (ia64) SP1 Kernel 2.6.16.54-0.2.5-default
Local File System:	xfs
Shared File System:	--
System State:	Multi-user, run level 3
Other Software:	SGI ProPack 5 for Linux Service Pack 5

Interconnect Description: InfiniBand (MPI)

Hardware

Vendor:	Voltaire
Model:	MT25204 InfiniHost III Lx
Switch Model:	Voltaire ISR 9024D-M

Software

Continued on next page

Non-Compliant

SPEC MPIM2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

SGI

SGI Altix XE 1300
(Intel Xeon X5272, 3.4 GHz)

SPECmpiM_peak2007 = Not Run

SPECmpiM_base2007 = NC

MPI2007 license: 4
Test sponsor: SGI
Tested by: SGI

Test date: Jun-2008
Hardware Availability: Feb-2008
Software Availability: Apr-2008

Interconnect Description: InfiniBand (MPI)

Number of Switches:	1
Number of Ports:	24
Data Rate:	InfiniBand 4x DDR
Firmware:	3.4.5
Topology:	Single switch
Primary Use:	MPI traffic

Interconnect Description: InfiniBand (I/O)

Hardware		Software
Vendor:	Voltaire	
Model:	MT25204 InfiniHost III Lx	
Switch Model:	Voltaire ISR 9024D-M	
Number of Switches:	1	
Number of Ports:	24	
Data Rate:	InfiniBand 4x DDR	
Firmware:	3.4.5	
Topology:	Single switch	
Primary Use:	I/O traffic	

General Notes

```
Required alternate sources:
   129.tera_tf: fixbuffer
```

Base Compiler Invocation

C benchmarks:
mpiicc

C++ benchmarks:

126.lammps: mpiicpc

Fortran benchmarks:
mpiifort

Benchmarks using both Fortran and C:
mpiicc mpiifort

Non-Compliant

Copyright 2006-2010 Standard Performance Evaluation Corporation

SGI

SGI Altix XE 1300
(Intel Xeon X5272, 3.4 GHz)

SPECmpiM_peak2007 = Not Run

SPECmpiM_base200[illegible] = [illegible]NC

MPI2007 license: 4
Test sponsor: SGI
Tested by: SGI

Test date: Jun-2008
Hardware Availability: Feb-2008
Software Availability: Apr-2008

Base Portability Flags

121.pop2: `-DSPEC_MPI_CASE_FLAG`
126.lammps: `-DMPICH_IGNORE_CXX_SEEK`
127.wrf2: `-DSPEC_MPI_CASE_FLAG -DSPEC_MPI_LINUX`

Base Optimization Flags

C benchmarks:
`-O3 -ipo -xT -no-prec-div`

C++ benchmarks:

126.lammps: `-O3 -ipo -xT -no-prec-div -a[illegible]-alias`

Fortran benchmarks:
`-O3 -ipo -xT -no-prec-div`

Benchmarks using both Fortran and C:
`-O3 -ipo -xT -no-prec-d[illegible]v`

The flags file that was used to format this result can be browsed at
`http://www.spec.org/mpi2007/flags/EM64T_Intel101_flags.20080618.html`

You can also download the XML flags source by saving the following link:
`http://www.spec.org/mpi2007/flags/[illegible]64T_Intel101_flags.20080618.xml`

Non-Compliant

SPEC and SPEC MPI are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC MPI2007 v1.0.
Report generated on Tue Jul 22 13:34:22 2014 by SPEC MPI2007 PS/PDF formatter v1463.
Originally published on 30 July 2008.