SPEC® MPIM2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

Intel Corporation

Endeavor (Intel Xeon E5462, 2.80 GHz)

SPECmpiM_peak2007 = Not Run

SPECmpiM_base2007 = 6.25

MPI2007 license: 13
Test sponsor: Intel Corporation
Tested by: Pavel Shelepugin

Test date: Sep-2008
Hardware Availability: Dec-2007
Software Availability: Aug-2008



Results Table

Benchmark	Base							Peak						
	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
104.milc	64	**395**	**3.96**	397	3.95	395	3.97							
107.leslie3d	64	**1042**	**5.01**	1043	5.01	1042	5.01							
113.GemsFDTD	64	**787**	**8.02**	788	8.00	783	8.05							
115.fds4	64	**422**	**4.62**	424	4.60	419	4.66							
121.pop2	64	**656**	**6.29**	656	6.29	662	6.23							
122.tachyon	64	372	7.53	369	7.57	**370**	**7.56**							
126.lammps	64	**494**	**5.90**	494	5.90	495	5.89							
127.wrf2	64	**817**	**9.55**	821	9.49	814	9.57							
128.GAPgeofem	64	**375**	**5.51**	374	5.53	376	5.50							
129.tera_tf	64	**373**	**7.42**	373	7.42	374	7.41							

Table continues on next page. Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

SPEC MPIM2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

Intel Corporation

Endeavor (Intel Xeon E5462, 2.80 GHz)

SPECmpiM_peak2007 = Not Run

SPECmpiM_base2007 = 6.25

MPI2007 license: 13
Test sponsor: Intel Corporation
Tested by: Pavel Shelepugin

Test date: Sep-2008
Hardware Availability: Dec-2007
Software Availability: Aug-2008

Results Table (Continued)

Benchmark	Base							Peak						
	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
130.socorro	64	789	4.83	780	4.89	**783**	**4.87**							
132.zeusmp2	64	512	6.06	**512**	**6.06**	517	6.00							
137.lu	64	**392**	**9.39**	391	9.40	396	9.27							

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Hardware Summary

Type of System:	Homogeneous
Compute Node:	Endeavor Node
Interconnects:	IB Switch Gigabit Ethernet
File Server Node:	Panasas Fileserver
Total Compute Nodes:	8
Total Chips:	16
Total Cores:	64
Total Threads:	64
Total Memory:	128 GB
Base Ranks Run:	64
Minimum Peak Ranks:	--
Maximum Peak Ranks:	--

Software Summary

C Compiler:	Intel C++ Compiler 10.1 for Linux (10.1.018)
C++ Compiler:	Intel C++ Compiler 10.1 for Linux (10.1.018)
Fortran Compiler:	Intel Fortran Compiler 10.1 for Linux (10.1.018)
Base Pointers:	64-bit
Peak Pointers:	64-bit
MPI Library:	Intel MPI Library 3.1 for Linux (3.1.038)
Other MPI Info:	None
Pre-processors:	No
Other Software:	Intel MPI Library 3.1 for Linux Multi-Purpose Daemon (MPD)

Node Description: Endeavor Node

Hardware

Number of nodes:	8
Uses of the node:	compute
Vendor:	Intel
Model:	SR1560SF
CPU Name:	Intel Xeon CPU E5462
CPU(s) orderable:	1-2 chips
Chips enabled:	2
Cores enabled:	8
Cores per chip:	4
Threads per core:	1
CPU Characteristics:	1600 MHz FSB
CPU MHz:	2800
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	12 MB I+D on chip per chip, 6 MB shared / 2 cores
L3 Cache:	None
Other Cache:	None
Memory:	16 GB (FBDIMM 16x1-GB 667 MHz)
Disk Subsystem:	Seagate Barracuda ES 250 GB ST3250620NS
Other Hardware:	None
Adapter:	Intel (ESB2) 82563EB Dual-Port Gigabit Ethernet Controller
Number of Adapters:	1
Slot Type:	PCI-Express x8

Continued on next page

Software

Adapter:	Intel (ESB2) 82563EB Dual-Port Gigabit Ethernet Controller
Adapter Driver:	e1000
Adapter Firmware:	None
Adapter:	Mellanox MHGH28-XTC
Adapter Driver:	OFED 1.3.1
Adapter Firmware:	2.5.0
Operating System:	RedHat EL 4 Update 4
Local File System:	Linux/ext3
Shared File System:	DirectFlow
System State:	Multi-User
Other Software:	PBS Pro 8.0

SPEC MPIM2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

Intel Corporation

Endeavor (Intel Xeon E5462, 2.80 GHz)

SPECmpiM_peak2007 = Not Run

SPECmpiM_base2007 = 6.25

MPI2007 license: 13
Test sponsor: Intel Corporation
Tested by: Pavel Shelepugin

Test date: Sep-2008
Hardware Availability: Dec-2007
Software Availability: Aug-2008

Node Description: Endeavor Node

Data Rate:	1Gbps Ethernet
Ports Used:	1
Interconnect Type:	Ethernet
Adapter:	Mellanox MHGH28-XTC
Number of Adapters:	1
Slot Type:	PCIe x16 Gen2
Data Rate:	InfiniBand 4x DDR
Ports Used:	1
Interconnect Type:	InfiniBand

Node Description: Panasas Fileserver

Hardware

Number of nodes:	1
Uses of the node:	fileserver
Vendor:	Panasas
Model:	ActiveStor 3050
CPU Name:	--
CPU(s) orderable:	1-2 chips
Chips enabled:	1
Cores enabled:	1
Cores per chip:	1
Threads per core:	1
CPU Characteristics:	--
CPU MHz:	0
Primary Cache:	None
Secondary Cache:	None
L3 Cache:	None
Other Cache:	None
Memory:	1 MB
Disk Subsystem:	140 disks, 250GB/disk, 35TB total, 7 Shelves
Other Hardware:	None
Adapter:	--
Number of Adapters:	1
Slot Type:	--
Data Rate:	1Gbps Ethernet
Ports Used:	4
Interconnect Type:	Ethernet

Software

Adapter:	--
Adapter Driver:	--
Adapter Firmware:	N/A
Operating System:	2.3.7.a-195733.1
Local File System:	PanFS
Shared File System:	DirectFlow
System State:	Multi-User
Other Software:	None

Interconnect Description: IB Switch

Hardware

Vendor:	Cisco
Model:	Cisco SFS 7024D
Switch Model:	Cisco SFS 7024D

Continued on next page

Software

Copyright 2006-2010 Standard Performance Evaluation Corporation

Intel Corporation

Endeavor (Intel Xeon E5462, 2.80 GHz)

SPECmpiM_peak2007 = Not Run

SPECmpiM_base2007 = 6.25

MPI2007 license: 13
Test sponsor: Intel Corporation
Tested by: Pavel Shelepugin

Test date: Sep-2008
Hardware Availability: Dec-2007
Software Availability: Aug-2008

Interconnect Description: IB Switch

Number of Switches:	1
Number of Ports:	288
Data Rate:	InfiniBand 4x DDR
Firmware:	4.1.1.1.11
Topology:	Single switch
Primary Use:	MPI traffic

Interconnect Description: Gigabit Ethernet

Hardware	
Vendor:	Cisco
Model:	Cisco Catalyst 4510
Switch Model:	Cisco Catalyst 4510
Number of Switches:	1
Number of Ports:	332
Data Rate:	1Gbps Ethernet
Firmware:	--
Topology:	Star
Primary Use:	Cluster File System

Software

General Notes

```
Required alternate sources:
   129.tera_tf: fixbuffer
Optional alternate sources:
   104.milc: calloc
   113.GemsFDTD: maxprocandstop
```

Base Compiler Invocation

C benchmarks:
`mpiicc`

C++ benchmarks:

126.lammps: `mpiicpc`

Fortran benchmarks:
`mpiifort`

Benchmarks using both Fortran and C:
`mpiicc mpiifort`

Base Portability Flags

121.pop2: `-DSPEC_MPI_CASE_FLAG`
126.lammps: `-DMPICH_IGNORE_CXX_SEEK`
127.wrf2: `-DSPEC_MPI_CASE_FLAG -DSPEC_MPI_LINUX`
130.socorro: `-DSPEC_EIGHT_BYTE_LONG`

Base Optimization Flags

C benchmarks:
`-O3 -xT -ipo -no-prec-div`

C++ benchmarks:

126.lammps: `-O3 -xT -ipo -no-prec-div`

Fortran benchmarks:
`-O3 -xT -ipo -no-prec-div`

Benchmarks using both Fortran and C:
`-O3 -xT -ipo -no-prec-div`

The flags file that was used to format this result can be browsed at
`http://www.spec.org/mpi2007/flags/EM64T_Intel101_flags.20080618.html`

You can also download the XML flags source by saving the following link:
`http://www.spec.org/mpi2007/flags/EM64T_Intel101_flags.20080618.xml`

SPEC and SPEC MPI are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC MPI2007 v1.0.
Report generated on Tue Jul 22 13:35:16 2014 by SPEC MPI2007 PS/PDF formatter v1463.
Originally published on 8 October 2008.