SPEC® MPIM2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

Intel Corporation

Atlantis (Intel Xeon X5482, 3.20 GHz)

SPECmpiM_peak2007 = Not Run

SPECmpiM_base2007 = 3.13

MPI2007 license: 13
Test sponsor: Intel Corporation
Tested by: Pavel Shelepugin

Test date: Mar-2009
Hardware Availability: Sep-2008
Software Availability: Jun-2009



Results Table

Benchmark	Base							Peak						
	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
104.milc	32	**813**	**1.92**	810	1.93									
107.leslie3d	32	1974	2.64	**1975**	**2.64**									
113.GemsFDTD	32	**1588**	**3.97**	1588	3.97									
115.fds4	32	902	2.16	**911**	**2.14**									
121.pop2	32	**861**	**4.80**	859	4.81									
122.tachyon	32	666	4.20	**672**	**4.16**									
126.lammps	32	**898**	**3.25**	890	3.28									
127.wrf2	32	**1595**	**4.89**	1593	4.90									
128.GAPgeofem	32	717	2.88	**718**	**2.88**									
129.tera_tf	32	556	4.98	**556**	**4.98**									

Table continues on next page. Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

SPEC MPIM2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

Intel Corporation

Atlantis (Intel Xeon X5482, 3.20 GHz)

SPECmpiM_peak2007 = Not Run

SPECmpiM_base2007 = 3.13

MPI2007 license: 13
Test sponsor: Intel Corporation
Tested by: Pavel Shelepugin

Test date: Mar-2009
Hardware Availability: Sep-2008
Software Availability: Jun-2009

Results Table (Continued)

Benchmark	Base							Peak						
	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
130.socorro	32	1817	2.10	**1818**	**2.10**									
132.zeusmp2	32	971	3.19	**974**	**3.18**									
137.lu	32	1746	2.11	**1755**	**2.09**									

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Hardware Summary

Type of System:	Homogeneous
Compute Node:	Atlantis Node
Interconnects:	IB Switch Gigabit Ethernet
File Server Node:	HOME
Total Compute Nodes:	4
Total Chips:	8
Total Cores:	32
Total Threads:	32
Total Memory:	64 GB
Base Ranks Run:	32
Minimum Peak Ranks:	--
Maximum Peak Ranks:	--

Software Summary

C Compiler:	Intel C++ Compiler 11.1 for Linux
C++ Compiler:	Intel C++ Compiler 11.1 for Linux
Fortran Compiler:	Intel Fortran Compiler 11.1 for Linux
Base Pointers:	64-bit
Peak Pointers:	64-bit
MPI Library:	Intel MPI Library 3.2 for Linux
Other MPI Info:	None
Pre-processors:	No
Other Software:	Intel MPI Library 3.2 for Linux Multi-Purpose Daemon (MPD)

Node Description: Atlantis Node

Hardware

Number of nodes:	4
Uses of the node:	compute
Vendor:	Intel
Model:	SR1560SF
CPU Name:	Intel Xeon X5482
CPU(s) orderable:	1-2 chips
Chips enabled:	2
Cores enabled:	8
Cores per chip:	4
Threads per core:	1
CPU Characteristics:	1600 MHz FSB
CPU MHz:	3200
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	12 MB I+D on chip per chip, 6 MB shared / 2 cores
L3 Cache:	None
Other Cache:	None
Memory:	16 GB (FBDIMM 8x2-GB 667 MHz)
Disk Subsystem:	Seagate Barracuda ES 250 GB ST3250620NS
Other Hardware:	None
Adapter:	Intel (ESB2) 82563EB Dual-Port Gigabit Ethernet Controller
Number of Adapters:	1
Slot Type:	PCI-Express x8

Continued on next page

Software

Adapter:	Intel (ESB2) 82563EB Dual-Port Gigabit Ethernet Controller
Adapter Driver:	e1000
Adapter Firmware:	None
Adapter:	Mellanox MHGH29-XTC
Adapter Driver:	OFED 1.3.1
Adapter Firmware:	2.5.0
Operating System:	RedHat EL 5 Update 2, kernel 2.6.18-92
Local File System:	Linux/ext2
Shared File System:	NFS
System State:	Multi-User
Other Software:	PBS Pro 8.0

SPEC MPIM2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

Intel Corporation

Atlantis (Intel Xeon X5482, 3.20 GHz)

SPECmpiM_peak2007 = Not Run

SPECmpiM_base2007 = 3.13

MPI2007 license: 13
Test sponsor: Intel Corporation
Tested by: Pavel Shelepugin

Test date: Mar-2009
Hardware Availability: Sep-2008
Software Availability: Jun-2009

Node Description: Atlantis Node

Data Rate:	1Gbps Ethernet
Ports Used:	1
Interconnect Type:	Ethernet
Adapter:	Mellanox MHGH29-XTC
Number of Adapters:	1
Slot Type:	PCIe x16 Gen2
Data Rate:	InfiniBand 4x DDR
Ports Used:	1
Interconnect Type:	InfiniBand

Node Description: HOME

Hardware

Number of nodes:	1
Uses of the node:	fileserver
Vendor:	Intel
Model:	SSR212CC
CPU Name:	Intel Xeon
CPU(s) orderable:	2 chips
Chips enabled:	2
Cores enabled:	2
Cores per chip:	1
Threads per core:	1
CPU Characteristics:	--
CPU MHz:	2800
Primary Cache:	12 KB I + 16 KB D on chip per chip
Secondary Cache:	1 MB I+D on chip per chip
L3 Cache:	None
Other Cache:	None
Memory:	2 GB
Disk Subsystem:	3 disks, 500GB/disk, 1.5TB total, 1TB available
Other Hardware:	None
Adapter:	Intel 82546GB Dual-Port Gigabit Ethernet Controller
Number of Adapters:	1
Slot Type:	PCI-Express x8
Data Rate:	1Gbps Ethernet
Ports Used:	1
Interconnect Type:	Ethernet

Software

Adapter:	Intel 82546GB Dual-Port Gigabit Ethernet Controller
Adapter Driver:	e1000
Adapter Firmware:	N/A
Operating System:	RedHat EL 4 Update 4
Local File System:	Linux/ext2
Shared File System:	NFS
System State:	Multi-User
Other Software:	None

Interconnect Description: IB Switch

Hardware

Vendor:	Cisco
Model:	Cisco SFS 9120
Switch Model:	Cisco SFS 9120

Continued on next page

Copyright 2006-2010 Standard Performance Evaluation Corporation

Intel Corporation

Atlantis (Intel Xeon X5482, 3.20 GHz)

SPECmpiM_peak2007 = Not Run

SPECmpiM_base2007 = 3.13

MPI2007 license: 13
Test sponsor: Intel Corporation
Tested by: Pavel Shelepugin

Test date: Mar-2009
Hardware Availability: Sep-2008
Software Availability: Jun-2009

Interconnect Description: IB Switch

Number of Switches:	1
Number of Ports:	120
Data Rate:	InfiniBand 4x DDR
Firmware:	4.1.1.1.11
Topology:	Single switch
Primary Use:	MPI traffic

Interconnect Description: Gigabit Ethernet

Hardware	
Vendor:	Cisco
Model:	Cisco Catalyst 4506
Switch Model:	Cisco Catalyst 4506
Number of Switches:	1
Number of Ports:	144
Data Rate:	1Gbps Ethernet
Firmware:	--
Topology:	Star
Primary Use:	Cluster File System

Software

Submit Notes

```
The config file option 'submit' was used.
```

General Notes

```
PBS Pro was used for job submission. It has no impact on performance.
  Can be found at: http://www.altair.com
```

Base Compiler Invocation

C benchmarks:
`mpiicc`

C++ benchmarks:

126.lammps: `mpiicpc`

Fortran benchmarks:
`mpiifort`

Benchmarks using both Fortran and C:
`mpiicc mpiifort`

Copyright 2006-2010 Standard Performance Evaluation Corporation

Intel Corporation

Atlantis (Intel Xeon X5482, 3.20 GHz)

SPECmpiM_peak2007 = Not Run

SPECmpiM_base2007 = 3.13

MPI2007 license: 13
Test sponsor: Intel Corporation
Tested by: Pavel Shelepugin

Test date: Mar-2009
Hardware Availability: Sep-2008
Software Availability: Jun-2009

Base Portability Flags

121.pop2: `-DSPEC_MPI_CASE_FLAG`
126.lammps: `-DMPICH_IGNORE_CXX_SEEK`
127.wrf2: `-DSPEC_MPI_CASE_FLAG -DSPEC_MPI_LINUX`

Base Optimization Flags

C benchmarks:
`-O3 -xT -no-prec-div`

C++ benchmarks:

126.lammps: `-O3 -xT -no-prec-div`

Fortran benchmarks:
`-O3 -xT -no-prec-div`

Benchmarks using both Fortran and C:
`-O3 -xT -no-prec-div`

The flags file that was used to format this result can be browsed at
`http://www.spec.org/mpi2007/flags/EM64T_Intel111_flags.html`

You can also download the XML flags source by saving the following link:
`http://www.spec.org/mpi2007/flags/EM64T_Intel111_flags.xml`

SPEC and SPEC MPI are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC MPI2007 v1.1.
Report generated on Tue Jul 22 13:36:14 2014 by SPEC MPI2007 PS/PDF formatter v1463.
Originally published on 15 April 2009.