SPEC® MPIM2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

Intel Corporation

Endeavor (Intel Xeon X5560, 2.80 GHz, SMT off, Turbo off)

SPECmpiM_peak2007 = Not Run

SPECmpiM_base200[illegible] = NC

MPI2007 license: 13
Test sponsor: Intel Corporation
Tested by: Pavel Shelepugin

Test date: Mar-2009
Hardware Availability: Mar-2009
Software Availability: Jun-2009

SPEC has determined that this result was not in compliance with the SPEC MPI2007 run and reporting rules. Specifically, the result does not comply with the recent interpretation changes to run rule 3.2.6 in the latest version. Replacement results can be found at http://www.spec.org/mpi2007/results/res2009q3/mpi2007-20090825-00173.html

Non-Compliant



Results Table

Benchmark	Base							Peak						
	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
104.milc	512	NC	NC	NC	NC									
107.leslie3d	512	NC	NC	NC	NC									

Table continues on next page. Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

SPEC MPIM2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

Intel Corporation

Endeavor (Intel Xeon X5560, 2.80 GHz, SMT off, Turbo off)

SPECmpiM_peak2007 = Not Run

SPECmpiM_base200[illegible] = NC

MPI2007 license: 13
Test sponsor: Intel Corporation
Tested by: Pavel Shelepugin

Test date: Mar-2009
Hardware Availability: Mar-2009
Software Availability: Jun-2009

SPEC has determined that this result was not in compliance with the SPEC MPI2007 run and reporting rules. Specifically, the result does not comply with the recent interpretation changes to run rule 3.2.6 in the latest version. Replacement results can be found at http://www.spec.org/mpi2007/results/res2009q3/mpi2007-20090825-00173.h

Non-Compliant

Results Table (Continued)

Benchmark	Base							Peak						
	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
113.GemsFDTD	512	NC	NC	NC	NC									
115.fds4	512	NC	NC	NC	NC									
121.pop2	512	NC	NC	NC	NC									
122.tachyon	512	NC	NC	NC	NC									
126.lammps	512	NC	NC	NC	NC									
127.wrf2	512	NC	NC	NC	NC									
128.GAPgeofem	512	NC	NC	NC	NC									
129.tera_tf	512	NC	NC	NC	NC									
130.socorro	512	NC	NC	NC	NC									
132.zeusmp2	512	NC	NC	NC	NC									
137.lu	512	NC	NC	NC	NC									

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Hardware Summary

Type of System:	Homogeneous
Compute Node:	Endeavor Node
Interconnect:	IB Switch
File Server Node:	NFS
Total Compute Nodes:	64
Total Chips:	128
Total Cores:	512
Total Threads:	512
Total Memory:	1152 GB
Base Ranks Run:	512
Minimum Peak Ranks:	--
Maximum Peak Ranks:	--

Software Summary

C Compiler:	Intel C++ Compiler 11.1 for Linux
C++ Compiler:	Intel C++ Compiler 11.1 for Linux
Fortran Compiler:	Intel Fortran Compiler 11.1 for Linux
Base Pointers:	64-bit
Peak Pointers:	64-bit
MPI Library:	Intel MPI Library 3.2 for Linux
Other MPI Info:	None
Pre-processors:	No
Other Software:	Intel MPI Library 3.2 for Linux Multi-Purpose Daemon (MPD)

SPEC MPIM2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

Intel Corporation

Endeavor (Intel Xeon X5560, 2.80 GHz, SMT off, Turbo off)

SPECmpiM_peak2007 = Not Run

SPECmpiM_base200[illegible] = NC

MPI2007 license: 13
Test sponsor: Intel Corporation
Tested by: Pavel Shelepugin

Test date: Mar-2009
Hardware Availability: Mar-2009
Software Availability: Jun-2009

SPEC has determined that this result was not in compliance with the SPEC MPI2007 run and reporting rules. Specifically, the result does not comply with the recent interpretation changes to run rule 3.2.6 in the latest version. Replacement results can be found at http://www.spec.org/mpi2007/results/res2009q3/mpi2007-20090825-00173.h

Non-Compliant

Node Description: Endeavor Node

Hardware

Number of nodes:	64
Uses of the node:	compute
Vendor:	Intel
Model:	Supermicro X8DTN+
CPU Name:	Intel Xeon X5560
CPU(s) orderable:	1-2 chips
Chips enabled:	2
Cores enabled:	8
Cores per chip:	4
Threads per core:	1
CPU Characteristics:	Intel Turbo Boost Technology disabled, 6.4 GT/s QPI, Hyper-Threading disabled
CPU MHz:	2800
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	256 KB I+D on chip per core
L3 Cache:	8 MB I+D on chip per chip, 8 MB shared / 4 cores
Other Cache:	None
Memory:	18 GB ([illegible]MM 6x2-GB, [illegible] GB DDR3-1066 MHz)
Disk Subsystem:	Seagate [illegible]9 GB ST[illegible]500320NS
Other Hardware:	None
Adapter:	Mell[illegible]x MH[illegible]H29-XTC
Number of Adapters:	1
Slot Type:	PCIe x8 Gen2
Data Rate:	InfiniBand 4x QDR
Ports Used:	1
Interconnect Type:	InfiniBand

Software

Adapter:	Mellanox MHQH29-XTC
Adapter Driver:	OFED 1.3.1
Adapter Firmware:	2.5.9
Operating System:	Red Hat EL 5.2, kernel 2.6.18-53
Local File System:	Linux/ext2
Shared File System:	Lustre FS
System State:	Multi-User
Other Software:	PBS Pro 8.0

Node Description: LFS

Hardware

Number of nodes:	8
Uses of the node:	fileserver
Vendor:	DataDirect Networks
Model:	SR1560SF
CPU Name:	Intel Xeon E5462

Continued on next page

Software

Adapter:	Mellanox MHGH28-XTC
Adapter Driver:	OFED 1.3.1
Adapter Firmware:	2.5.0
Operating System:	Red Hat EL 5.2
Local File System:	None

Continued on next page

SPEC MPIM2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

Intel Corporation

Endeavor (Intel Xeon X5560, 2.80 GHz, SMT off, Turbo off)

SPECmpiM_peak2007 = Not Run

SPECmpiM_base2007 = NC

MPI2007 license: 13
Test sponsor: Intel Corporation
Tested by: Pavel Shelepugin

Test date: Mar-2009
Hardware Availability: Mar-2009
Software Availability: Jun-2009

SPEC has determined that this result was not in compliance with the SPEC MPI2007 run and reporting rules. Specifically, the result does not comply with the recent interpretation changes to run rule 3.2.6 in the latest version. Replacement results can be found at http://www.spec.org/mpi2007/results/res2009q3/mpi2007-20090825-00173.h

Non-Compliant

Node Description: LFS

CPU(s) orderable:	1-2 chips
Chips enabled:	2
Cores enabled:	8
Cores per chip:	4
Threads per core:	1
CPU Characteristics:	1600 MHz FSB
CPU MHz:	2800
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	12 MB I+D on chip per chip, 6 MB shared / 2 cores
L3 Cache:	None
Other Cache:	None
Memory:	16 GB DDR2 16x1-GB 667 MHz
Disk Subsystem:	160 disks, 300GB/disk, 48TB total, 35TB available
Other Hardware:	None
Adapter:	Mellanox MHGH28-XTC
Number of Adapters:	1
Slot Type:	PCIe x8 Gen2
Data Rate:	InfiniBand 4x QDR
Ports Used:	1
Interconnect Type:	InfiniBand

Shared File System:	Lustre FS
System State:	Multi-User
Other Software:	None

Interconnect Description: IB Switch

Hardware	
Vendor:	Mellanox
Model:	Mellanox MTS3600Q-1UNC
Switch Model:	Mellanox MTS3600Q-1UNC
Number of Switches:	9
Number of Ports:	36
Data Rate:	InfiniBand 4x QDR
Firmware:	7.1.000
Topology:	Fat tree
Primary Use:	MPI traffic, FS traffic

Software

SPEC MPIM2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

Intel Corporation

Endeavor (Intel Xeon X5560, 2.80 GHz, SMT off, Turbo off)

SPECmpiM_peak2007 = Not Run

SPECmpiM_base200[illegible] = NC

MPI2007 license: 13
Test sponsor: Intel Corporation
Tested by: Pavel Shelepugin

Test date: Mar-2009
Hardware Availability: Mar-2009
Software Availability: Jun-2009

SPEC has determined that this result was not in compliance with the SPEC MPI2007 run and reporting rules. Specifically, the result does not comply with the recent interpretation changes to run rule 3.2.6 in the latest version. Replacement results can be found at http://www.spec.org/mpi2007/results/res2009q3/mpi2007-20090825-00173.h

Non-Compliant

Submit Notes

```
The config file option 'submit' was used.
```

General Notes

```
BIOS settings notes:
  Intel Hyper-Threading Technology (SMT): Disabled (default is Enabled)
  Intel Turbo Boost Technology (Turbo): Disabled (default is Enabled)

RAM configuration notes: compute nodes have
  1x2-GB and 1x1-GB RDIMM on each memory channel,
  2-GB RDIMM is closer to the CPU.

Network notes: nine 36-port switches, 3 core switches and 6 leaf switches.
  Each leaf has 6 links to each core. Remaining 18 ports on 5 of 6 leafs are
  used for compute nodes. On the sixth leaf 8 ports are used for FS nodes,
  remaining 10 ports are open.

PBS Pro was used for job submission. It has no impact on performance.
  Can be found at: http://www.altair.com

Lustre File System 1.6.6 was used. Download from:
  http://www.sun.com/software/products/lustre
```

Base Compiler Invocation

C benchmarks:

mpiicc

C++ benchmarks:

126.lammps: mpiicpc

Fortran benchmarks:

mpiifort

Benchmarks using both Fortran and C:

mpiicc mpiifort

SPEC MPIM2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

Intel Corporation

Endeavor (Intel Xeon X5560, 2.80 GHz, SMT off, Turbo off)

SPECmpiM_peak2007 = Not Run

SPECmpiM_base200[illegible] = NC

MPI2007 license: 13
Test sponsor: Intel Corporation
Tested by: Pavel Shelepugin

Test date: Mar-2009
Hardware Availability: Mar-2009
Software Availability: Jun-2009

SPEC has determined that this result was not in compliance with the SPEC MPI2007 run and reporting rules. Specifically, the result does not comply with the recent interpretation changes to run rule 3.2.6 in the latest version. Replacement results can be found at http://www.spec.org/mpi2007/results/res2009q3/mpi2007-20090825-00173.html

Non-Compliant

Base Portability Flags

121.pop2: -DSPEC_MPI_CASE_FLAG
126.lammps: -DMPICH_IGNORE_CXX_SEEK
127.wrf2: -DSPEC_MPI_CASE_FLAG -DSPEC_MPI_LINUX

Base Optimization Flags

C benchmarks:
-O3 -xSSE4.2 -no-prec-div

C++ benchmarks:

126.lammps: -O3 -xSSE4.2 -no-prec-div

Fortran benchmarks:
-O3 -xSSE4.2 -no-prec-div

Benchmarks using both Fortran and C:
-O3 -xSSE4.2 -no-prec-div

The flags file that was used to format this result can be browsed at
http://www.spec.org/mpi2007/flags/EM64T_Intel111_flags.html

You can also download the XML flags source by saving the following link:
http://www.spec.org/mpi2007/flags/EM64T_Intel111_flags.xml

SPEC MPIM2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

Intel Corporation

Endeavor (Intel Xeon X5560, 2.80 GHz, SMT off, Turbo off)

SPECmpiM_peak2007 = Not Run

SPECmpiM_base200[illegible] = NC

MPI2007 license: 13
Test sponsor: Intel Corporation
Tested by: Pavel Shelepugin

Test date: Mar-2009
Hardware Availability: Mar-2009
Software Availability: Jun-2009

SPEC has determined that this result was not in compliance with the SPEC MPI2007 run and reporting rules. Specifically, the result does not comply with the recent interpretation changes to run rule 3.2.6 in the latest version. Replacement results can be found at http://www.spec.org/mpi2007/results/res2009q3/mpi2007-20090825-00173.h

Non-Compliant

SPEC and SPEC MPI are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC MPI2007 v1.1.
Report generated on Tue Jul 22 13:36:32 2014 by SPEC MPI2007 PS/PDF formatter v1463.
Originally published on 15 April 2009.