



# SPEC® MPIM2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

**SGI**

SGI Altix ICE 8200EX  
(Intel Xeon X5570, 2.93 GHz, PMPI 5.6.6)

**SPECmpIM\_peak2007 = Not run**

**SPECmpIM\_base2007 = NC**

MPI2007 license: 021

Test sponsor: Platform Computing Inc.

Tested by: Platform Computing Inc.

Test date: Mar-2009

Hardware Availability: Mar-2009

Software Availability: Feb-2009

Ranks
<b>104.milc</b>
<b>107.leslie3d</b>
<b>113.GemsFDTD</b>
<b>115.fds4</b>
<b>121.pop2</b>
<b>122.tachyon</b>
<b>126.lammps</b>
<b>127.wrf2</b>
<b>128.GAPgeomfem</b>
<b>129.tera_tf</b>
<b>130.socc</b>
<b>132.zeusmp2</b>
<b>137.lu</b>

## Results Table

Benchmark	Base								Peak							
	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
104.milc	64	NC	NC	NC	NC	NC	NC									
107.leslie3d	64	NC	NC	NC	NC	NC	NC									

Table continues on next page. Results appear in the order in which they were run. Bold underlined text indicates a median measurement.



# SPEC MPIM2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

**SGI**

SGI Altix ICE 8200EX  
(Intel Xeon X5570, 2.93 GHz, PMPI 5.6.6)

**SPECmpIM\_peak2007 = Not Run**

**SPECmpIM\_base2007 = NC**

**MPI2007 license:** 021

**Test sponsor:** Platform Computing Inc.

**Tested by:** Platform Computing Inc.

**Test date:** Mar-2009

**Hardware Availability:** Mar-2009

**Software Availability:** Feb-2009

## Results Table (Continued)

Benchmark	Base								Peak							
	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Ranks	Seconds	Ratio	Seconds	Ratio	Ranks	Seconds	Ratio	Ranks
113.GemsFDTD	64	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC
115.fds4	64	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC
121.pop2	64	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC
122.tachyon	64	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC
126.lammps	64	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC
127.wrf2	64	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC
128.GAPgeomfem	64	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC
129.tera_tf	64	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC
130.socorro	64	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC
132.zeusmp2	64	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC
137.lu	64	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

### Hardware Summary

Type of System: Homeogeneous  
Compute Node: SGI Altix ICE 8200EX Compute Node  
Interconnect: InfiniBand (MPI)  
InfiniBand (I/O)  
File Server Node: SGI InfiniteStorage Nexus 2000 NAS  
Total Compute Nodes: 8  
Total Cores: 16  
Total Cores: 64  
Total Threads: 128  
Total Memory: 384 GB  
Base Ranks Run: 64  
Minimum Peak Ranks: --  
Maximum Peak Ranks: --

### Software Summary

C Compiler: Intel C Compiler for Linux Version 10.1, Build 20080801  
C++ Compiler: Intel C++ Compiler for Linux Version 10.1, Build 20080801  
Fortran Compiler: Intel Fortran Compiler for Linux Version 10.1, Build 20080801  
Base Pointers: 64-bit  
Peak Pointers: 64-bit  
MPI Library: Platform MPI 5.6.6-59413  
Other MPI Info: OFED 1.3.1  
Platform Computing Inc has acquired Scali MPI Connect, hence Platform MPI and Scali MPI Connect are used synonymously.  
Pre-processors: None  
Other Software: None



# SPEC MPIM2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

**SGI**

SGI Altix ICE 8200EX  
(Intel Xeon X5570, 2.93 GHz, PMPI 5.6.6)

MPI2007 license: 021

Test sponsor: Platform Computing Inc.

Tested by: Platform Computing Inc.

~~SPECmpIM\_peak2007 = Not run~~

~~SPECmpIM\_base2007 = NC~~

Test date: Mar-2009

Hardware Availability: Mar-2009

Software Availability: Feb-2009

## Node Description: SGI Altix ICE 8200EX Compute Node

### Hardware

Number of nodes: 8  
Uses of the node: compute  
Vendor: SGI  
Model: SGI Altix ICE 8200EX (Intel Xeon X5570, 2.93 GHz)  
CPU Name: Intel Xeon X5570  
CPU(s) orderable: 1-2 chips  
Chips enabled: 2  
Cores enabled: 8  
Cores per chip: 4  
Threads per core: 2  
CPU Characteristics: Intel Turbo Boost Technology up to 3.33 GHz, 6.4 GT/s QPI, Hyper-Threading enabled  
CPU MHz: 2934  
Primary Cache: 32 KB I + 32 KB D on chip per core  
Secondary Cache: 256 KB I+D on chip per core  
L3 Cache: 8 MB I+D on chip per chip  
Other Cache: None  
Memory: 48 GB (4x 12GB DDR2 1066 CL7 RDIMMs)  
Disk Subsystem: None  
Other Hardware: None  
Adapter: Mellanox MT26418 ConnectX IB DDR (PCIe x8 Gen2 5 GT/s)  
Number of Adapters: 1  
Slot Type: PCIe x8 Gen2  
Data Rate: InfiniBand 4x DDR  
Ports Used: 2  
Interconnect: InfiniBand

### Software

Adapter: Mellanox MT26418 ConnectX IB DDR (PCIe x8 Gen2 5 GT/s)  
Adapter Driver: OFED-1.3.1  
Adapter Firmware: 2.5.0  
Operating System: SUSE Linux Enterprise Server 10 (x86\_64) SP2 Kernel 2.6.16.60-0.30-smp  
Local File System: NFSv3  
Shared File System: NFSv3 IPoIB  
System State: Multi-user, run level 3  
Other Software: SGI ProPack 6 for Linux Service Pack 2

## Node Description: SGI InfiniteStorage NEXIS 2000 NAS

### Hardware

Number of nodes: 1  
Uses of the node: fileserver  
Vendor: SGI  
Model: SGI Altix XE 240 (Intel Xeon 5140, 2.33 GHz)

### Software

Adapter: Mellanox MT25208 InfiniHost III Ex (PCIe x8 Gen1 2.5 GT/s)  
Adapter Driver: OFED-1.3  
Adapter Firmware: 5.3.0

Continued on next page

Continued on next page



# SPEC MPIM2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

**SGI**

SGI Altix ICE 8200EX  
(Intel Xeon X5570, 2.93 GHz, PMPI 5.6.6)

**SPECmpIM\_peak2007 = Not Run**

**SPECmpIM\_base2007 = NC**

**MPI2007 license:** 021

**Test sponsor:** Platform Computing Inc.

**Tested by:** Platform Computing Inc.

**Test date:** Mar-2009

**Hardware Availability:** Mar-2009

**Software Availability:** Feb-2009

## Node Description: SGI InfiniteStorage Nexus 8000 NAS

CPU Name:	Intel Xeon 5140	Operating System:	SUSE Linux Enterprise Server 10 (x86_64) SP1
CPU(s) orderable:	1-2 chips	Local File System:	Kernel 2.6.16.54-0.2.5-smp
Chips enabled:	2	Shared File System:	xfs
Cores enabled:	4	System State:	--
Cores per chip:	2	Other Software:	Multi-user, run level 3
Threads per core:	1		SGI ProPack 5 for Linux Service Pack 5
CPU Characteristics:	1333 MHz FSB		
CPU MHz:	2328		
Primary Cache:	32 KB I + 32 KB D on chip per core		
Secondary Cache:	4 MB I+D on chip per chip		
L3 Cache:	None		
Other Cache:	None		
Memory:	24 GB (6*4GB DDR2 667 DIMMS)		
Disk Subsystem:	7 TB RAID 5 48 x 147 GB SAS (Seagate Cheetah 15000 rpm)		
Other Hardware:	None		
Adapter:	Mellanox MT2520c InfiniHost III Ex (PCIe x8 Gen2 2.5 GT/s)		
Number of Adapters:	2		
Slot Type:	PCIe x8 Gen1		
Data Rate:	InfiniBand 4x DDR		
Ports Used:	2		
Interconnect Type:	Infiniband		

## Interconnect Description: InfiniBand (MPI)

Hardware	Software
Vendor:	
Model:	
Switch Model:	
Number of Switches:	
Number of Ports:	
Data Rate:	Mellanox Technologies
Firmware:	MT26418 ConnectX
Topology:	Mellanox MT47396 InfiniScale III
Primary Use:	8 24 InfiniBand 4x DDR 2020001 Bristle hypercube with express links MPI traffic



# SPEC MPIM2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

**SGI**

SGI Altix ICE 8200EX  
(Intel Xeon X5570, 2.93 GHz, PMPI 5.6.6)

**SPECmpIM\_peak2007 = Not run**

**SPECmpIM\_base2007 = NC**

**MPI2007 license:** 021

**Test sponsor:** Platform Computing Inc.

**Tested by:** Platform Computing Inc.

**Test date:** Mar-2009

**Hardware Availability:** Mar-2009

**Software Availability:** Feb-2009

## Interconnect Description: InfiniBand (IBO)

### Hardware

Vendor: Mellanox Technologies  
Model: MT26418 ConnectX  
Switch Model: Mellanox MT47396 InfiniScale-III  
Number of Switches: 8  
Number of Ports: 24  
Data Rate: InfiniBand 4x DDR  
Firmware: 2020001  
Topology: Bristle hypercube with express links  
Primary Use: I/O traffic

### Software

## Submit Notes

The config file option 'submit' was used.

## General Notes

Software environment:  
limit stacksize unlimited  
Removes limits on the maximum size of the automatically-extended stack region of the current process and each process it creates.  
PBS Pro batch scheduler ([www.altair.com](http://www.altair.com)) is used with settings to ensure each MPI job is assigned to a topologically compact set of nodes  
BIOS settings:  
AMI BIOS version 8.15  
Hyper Threading Technology enabled (default)  
Intel Turbo Boost Technology enabled (default)  
Intel Turbo Boost Technology activated in the OS via  
`/etc/init.d/acpid start`  
`/etc/init.d/powersaved start`  
`powersave -f`



# SPEC MPIM2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

**SGI**

SGI Altix ICE 8200EX  
(Intel Xeon X5570, 2.93 GHz, PMPI 5.6.6)

**SPECmpIM\_peak2007 = Not Run**

**SPECmpIM\_base2007 = NC**

**MPI2007 license:** 021

**Test sponsor:** Platform Computing Inc.

**Tested by:** Platform Computing Inc.

**Test date:** Mar-2009

**Hardware Availability:** Mar-2009

**Software Availability:** Feb-2009

## Base Compiler Invocation

C benchmarks:

`mpicc -ccl icc`

C++ benchmarks:

`126.lammps: mpicc -ccl icpc`

Fortran benchmarks:

`mpif77 -ccl ifort`

Benchmarks using both Fortran and C:

`mpicc -ccl icc mpif77 -ccl ifort`

## Base Portability Flags

`121.pop2: -DSPEC_MPI_CCASE_FLAG`

`127.wrf2: -DSPEC_MPI_CCASE_FLAG -DSPEC_MPI_LINUX`

## Base Optimization Flags

C benchmarks:

`-O3 -ipo -xT -no-prec-div`

C++ benchmarks:

`126.lammps: -O3 -ipo -xT -no-prec-div -ansi-alias`

Fortran benchmarks:

`-O3 -ipo -xT -no-prec-div`

Benchmarks using both Fortran and C:

`-O3 -ipo -xT -no-prec-div`



# SPEC MPIM2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

**SGI**

SGI Altix ICE 8200EX  
(Intel Xeon X5570, 2.93 GHz, PMPI 5.6.6)

**SPECmpIM\_peak2007 = Not run**

**SPECmpIM\_base2007 = NC**

**MPI2007 license:** 021

**Test sponsor:** Platform Computing Inc.

**Tested by:** Platform Computing Inc.

**Test date:** Mar-2009

**Hardware Availability:** Mar-2009

**Software Availability:** Feb-2009

The flags files that were used to format this result can be browsed at

[http://www.spec.org/mpi2007/flags/MPI2007\\_flags.20081204.html](http://www.spec.org/mpi2007/flags/MPI2007_flags.20081204.html)

[http://www.spec.org/mpi2007/flags/EM64T\\_Intel101\\_flags.20080618.html](http://www.spec.org/mpi2007/flags/EM64T_Intel101_flags.20080618.html)

You can also download the XML flags sources by clicking the following links:

[http://www.spec.org/mpi2007/flags/MPI2007\\_flags.20081204.xml](http://www.spec.org/mpi2007/flags/MPI2007_flags.20081204.xml)

[http://www.spec.org/mpi2007/flags/EM64T\\_Intel101\\_flags.20080618.xml](http://www.spec.org/mpi2007/flags/EM64T_Intel101_flags.20080618.xml)

SPEC and SPEC MPI are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC MPI2007 v1.1.

Report generated on Tue Jul 22 13:37:02 2014 by SPEC MPI2007 PS/PDF formatter v1463.

Originally published on 14 April 2009.