SPEC® MPIM2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

IBM Corporation

System x3550 M2 (Intel Xeon X5570, 2.93 GHz
SMT on, Turbo on)

SPECmpiM_peak2007 = Not Run

SPECmpiM_base2007 = 7.26

MPI2007 license: 005
Test sponsor: IBM Corporation
Tested by: IBM Corporation

Test date: Jun-2009
Hardware Availability: Apr-2009
Software Availability: Apr-2009



Results Table

Benchmark	Base							Peak						
	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
104.milc	32	**220**	**7.12**	221	7.07	219	7.16							
107.leslie3d	32	764	6.83	761	6.86	**764**	**6.84**							
113.GemsFDTD	32	524	12.0	**524**	**12.0**	525	12.0							
115.fds4	32	**300**	**6.51**	301	6.48	300	6.51							
121.pop2	32	525	7.86	**525**	**7.86**	525	7.86							
122.tachyon	32	**591**	**4.73**	592	4.73	591	4.73							
126.lammps	32	564	5.17	569	5.13	**564**	**5.16**							
127.wrf2	32	**594**	**13.1**	594	13.1	593	13.1							
128.GAPgeofem	32	**264**	**7.82**	264	7.83	265	7.79							
129.tera_tf	32	521	5.31	**522**	**5.31**	552	5.01							

Table continues on next page. Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

SPEC MPIM2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

IBM Corporation

System x3550 M2 (Intel Xeon X5570, 2.93 GHz
SMT on, Turbo on)

SPECmpiM_peak2007 = Not Run

SPECmpiM_base2007 = 7.26

MPI2007 license: 005
Test sponsor: IBM Corporation
Tested by: IBM Corporation

Test date: Jun-2009
Hardware Availability: Apr-2009
Software Availability: Apr-2009

Results Table (Continued)

Benchmark	Base							Peak						
	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
130.socorro	32	444	8.59	**445**	**8.58**	447	8.54							
132.zeusmp2	32	441	7.04	439	7.08	**440**	**7.06**							
137.lu	32	576	6.38	**572**	**6.43**	571	6.43							

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Hardware Summary

Type of System:	Homogeneous
Compute Node:	IBM System x3550 M2
Interconnects:	InfiniBand Ethernet
File Server Node:	IBM System x346 8840
Head Node:	IBM System x3550 M2
Total Compute Nodes:	4
Total Chips:	8
Total Cores:	32
Total Threads:	64
Total Memory:	96 GB
Base Ranks Run:	32
Minimum Peak Ranks:	--
Maximum Peak Ranks:	--

Software Summary

C Compiler:	Intel C++ Compiler 11.0.083 for Linux
C++ Compiler:	Intel C++ Compiler 11.0.083 for Linux
Fortran Compiler:	Intel Fortran Compiler 11.0.083 for Linux
Base Pointers:	64-bit
Peak Pointers:	64-bit
MPI Library:	Intel MPI Library 3.2.1.009 for Linux
Other MPI Info:	None
Pre-processors:	No
Other Software:	Intel MPI Library 3.2.1.009 for Linux Multi-Purpose Daemon (MPD)

Node Description: IBM System x3550 M2

Hardware

Number of nodes:	4
Uses of the node:	compute, head
Vendor:	IBM Corporation
Model:	7946-92U
CPU Name:	Intel Xeon X5570
CPU(s) orderable:	1-2 chips
Chips enabled:	2
Cores enabled:	8
Cores per chip:	4
Threads per core:	2
CPU Characteristics:	Intel Turbo Boost Technology up to 3.33 GHz, 6.4 GT/s QPI, Hyper-Threading enabled
CPU MHz:	2933
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	256 KB I+D on chip per core
L3 Cache:	8 MB I+D on chip per chip, 8 MB shared / 4 cores
Other Cache:	None
Memory:	24 GB (RDIMM 6x4-GB DDR3-1333 MHz)
Disk Subsystem:	73.4GB 10K-rpm SAS SFF Slim-HS 2.5" HDD
Other Hardware:	None
Adapter:	Integrated Broadcom Corporation NetXtreme II BCM5709 Gigabit Ethernet (rev 20)

Continued on next page

Software

Adapter:	Integrated Broadcom Corporation NetXtreme II BCM5709 Gigabit Ethernet (rev 20)
Adapter Driver:	bnx2 1.7.9-1
Adapter Firmware:	4.6.4 NCSI 1.0.6
Adapter:	Mellanox ConnectX
Adapter Driver:	OFED 1.4-20090301-0600
Adapter Firmware:	2.6.000
Operating System:	Red Hat EL 5.3, kernel 2.6.18-128.el5
Local File System:	Linux/ext3
Shared File System:	NFS
System State:	Multi-User
Other Software:	None

Copyright 2006-2010 Standard Performance Evaluation Corporation

IBM Corporation

System x3550 M2 (Intel Xeon X5570, 2.93 GHz
SMT on, Turbo on)

SPECmpiM_peak2007 = Not Run

SPECmpiM_base2007 = 7.26

MPI2007 license: 005
Test sponsor: IBM Corporation
Tested by: IBM Corporation

Test date: Jun-2009
Hardware Availability: Apr-2009
Software Availability: Apr-2009

Node Description: IBM System x3550 M2

Number of Adapters:	1
Slot Type:	PCIe x16 Gen2
Data Rate:	10/100/1000
Ports Used:	1
Interconnect Type:	Ethernet
Adapter:	Mellanox ConnectX
Number of Adapters:	1
Slot Type:	PCIe x16 Gen2
Data Rate:	InfiniBand 4x DDR
Ports Used:	1
Interconnect Type:	InfiniBand

General Notes

```
BIOS settings notes:
  Intel Hyper-Threading Technology (SMT): Enabled
  Intel Turbo Boost Technology (Turbo)  : Enabled

RAM configuration notes: Each compute node has
  1x4-GB RDIMM on each memory channel.
```

Node Description: IBM System x346 8840

Hardware

Number of nodes:	1
Uses of the node:	fileserver
Vendor:	IBM Corporation
Model:	884045Y
CPU Name:	Intel Xeon EM64T
CPU(s) orderable:	2 chips
Chips enabled:	2
Cores enabled:	2
Cores per chip:	1
Threads per core:	1
CPU Characteristics:	800 MHz FSB
CPU MHz:	3600
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	1 MB I+D on chip per chip
L3 Cache:	None
Other Cache:	None
Memory:	4 GB
Disk Subsystem:	SCSI
Other Hardware:	None
Adapter:	Integrated Broadcom Corporation NetXtreme BCM5721 Gigabit Ethernet PCI Express (rev 11)
Number of Adapters:	1
Slot Type:	PCI-X
Data Rate:	10/100/1000

Continued on next page

Software

Adapter:	Integrated Broadcom Corporation NetXtreme BCM5721 Gigabit Ethernet PCI Express (rev 11)
Adapter Driver:	tg3 3.86
Adapter Firmware:	5721-v3.29a, ASFIPMI v6.08
Operating System:	Red Hat EL 5.2, kernel 2.6.18-92.el5
Local File System:	None
Shared File System:	NFS
System State:	Multi-User
Other Software:	None

Copyright 2006-2010 Standard Performance Evaluation Corporation

IBM Corporation

System x3550 M2 (Intel Xeon X5570, 2.93 GHz SMT on, Turbo on)

SPECmpiM_peak2007 = Not Run

SPECmpiM_base2007 = 7.26

MPI2007 license: 005
Test sponsor: IBM Corporation
Tested by: IBM Corporation

Test date: Jun-2009
Hardware Availability: Apr-2009
Software Availability: Apr-2009

Node Description: IBM System x346 8840

Ports Used:	1
Interconnect Type:	Ethernet

Interconnect Description: InfiniBand

Hardware		Software
Vendor:	Voltaire	
Model:	24 4X DDR port Bundle	
Switch Model:	ISR 9024D-M	
Number of Switches:	1	
Number of Ports:	24	
Data Rate:	4X DDR	
Firmware:	1.0.0	
Topology:	Single Switch	
Primary Use:	MPI traffic	

Interconnect Description: Ethernet

Hardware		Software
Vendor:	Cisco	
Model:	3750G	
Switch Model:	WS-C3750G-24TS-E1U	
Number of Switches:	1	
Number of Ports:	28	
Data Rate:	Fullduplex 1000	
Firmware:	12.2 (35SE5)	
Topology:	Single Switch	
Primary Use:	File system traffic	

Submit Notes

```
The config file option 'submit' was used.
submit = mpiexec -genv -np $ranks $command
```

Base Compiler Invocation

C benchmarks:
`mpiicc`

C++ benchmarks:

Continued on next page

Base Compiler Invocation (Continued)

126.lammps: `mpiicpc`

Fortran benchmarks:
`mpiifort`

Benchmarks using both Fortran and C:
`mpiicc mpiifort`

Base Portability Flags

121.pop2: `-DSPEC_MPI_CASE_FLAG`
126.lammps: `-DMPICH_IGNORE_CXX_SEEK`
127.wrf2: `-DSPEC_MPI_CASE_FLAG -DSPEC_MPI_LINUX`

Base Optimization Flags

C benchmarks:
`-O3 -xSSE4.2 -no-prec-div`

C++ benchmarks:

126.lammps: `-O3 -xSSE4.2 -no-prec-div`

Fortran benchmarks:
`-O3 -xSSE4.2 -no-prec-div`

Benchmarks using both Fortran and C:
`-O3 -xSSE4.2 -no-prec-div`

The flags file that was used to format this result can be browsed at
`http://www.spec.org/mpi2007/flags/EM64T_Intel111_flags.20090729.html`

You can also download the XML flags source by saving the following link:
`http://www.spec.org/mpi2007/flags/EM64T_Intel111_flags.20090729.xml`

Copyright 2006-2010 Standard Performance Evaluation Corporation

IBM Corporation

System x3550 M2 (Intel Xeon X5570, 2.93 GHz
SMT on, Turbo on)

SPECmpiM_peak2007 = Not Run

SPECmpiM_base2007 = 7.26

MPI2007 license:	005	**Test date:**	Jun-2009
Test sponsor:	IBM Corporation	**Hardware Availability:**	Apr-2009
Tested by:	IBM Corporation	**Software Availability:**	Apr-2009

SPEC and SPEC MPI are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC MPI2007 v1.1.
Report generated on Tue Jul 22 13:38:00 2014 by SPEC MPI2007 PS/PDF formatter v1463.
Originally published on 29 July 2009.