SPEC® MPIM2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

SGI

SGI Altix ICE 8200EX
(Intel Xeon X5570, 2.93 GHz, DDR3-1333)

SPECmpiM_peak2007 = Not Run

SPECmpiM_base2007 = 7.33

MPI2007 license: 4
Test sponsor: SGI
Tested by: SGI

Test date: Sep-2009
Hardware Availability: Mar-2009
Software Availability: Aug-2009



Results Table

Benchmark	Base							Peak						
	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
104.milc	32	**204**	**7.69**	203	7.70									
107.leslie3d	32	775	6.74	**777**	**6.72**									
113.GemsFDTD	32	507	12.4	**509**	**12.4**									
115.fds4	32	**307**	**6.35**	307	6.35									
121.pop2	32	**516**	**7.99**	516	8.00									
122.tachyon	32	**608**	**4.60**	608	4.60									
126.lammps	32	**560**	**5.21**	560	5.21									
127.wrf2	32	**570**	**13.7**	570	13.7									
128.GAPgeofem	32	**248**	**8.34**	247	8.35									
129.tera_tf	32	**496**	**5.59**	494	5.60									

Table continues on next page. Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

SPEC MPIM2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

SGI

SGI Altix ICE 8200EX
(Intel Xeon X5570, 2.93 GHz, DDR3-1333)

SPECmpiM_peak2007 = Not Run

SPECmpiM_base2007 = 7.33

MPI2007 license: 4
Test sponsor: SGI
Tested by: SGI

Test date: Sep-2009
Hardware Availability: Mar-2009
Software Availability: Aug-2009

Results Table (Continued)

Benchmark	Base							Peak						
	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
130.socorro	32	450	8.49	**451**	**8.46**									
132.zeusmp2	32	**455**	**6.82**	452	6.87									
137.lu	32	591	6.22	**599**	**6.14**									

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Hardware Summary

Type of System:	Homogeneous
Compute Node:	SGI Altix ICE 8200EX Compute Node
Interconnects:	InfiniBand (MPI) InfiniBand (I/O)
File Server Node:	SGI InfiniteStorage Nexis 2000 NAS
Total Compute Nodes:	4
Total Chips:	8
Total Cores:	32
Total Threads:	64
Total Memory:	96 GB
Base Ranks Run:	32
Minimum Peak Ranks:	--
Maximum Peak Ranks:	--

Software Summary

C Compiler:	Intel C Compiler for Linux Version 11.1, Build 20090630
C++ Compiler:	Intel C++ Compiler for Linux Version 11.1, Build 20090630
Fortran Compiler:	Intel Fortran Compiler for Linux Version 11.1, Build 20090630
Base Pointers:	64-bit
Peak Pointers:	64-bit
MPI Library:	SGI MPT 1.24
Other MPI Info:	OFED 1.4
Pre-processors:	None
Other Software:	None

Node Description: SGI Altix ICE 8200EX Compute Node

Hardware

Number of nodes:	4
Uses of the node:	compute
Vendor:	SGI
Model:	SGI Altix ICE 8200EX (Intel Xeon X5570, 2.93 GHz, DDR3-1333)
CPU Name:	Intel Xeon X5570
CPU(s) orderable:	1-2 chips
Chips enabled:	2
Cores enabled:	8
Cores per chip:	4
Threads per core:	2
CPU Characteristics:	Intel Turbo Boost Technology up to 3.33 GHz, 6.4 GT/s QPI, Hyper-Threading enabled
CPU MHz:	2934
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	256 KB I+D on chip per core
L3 Cache:	8 MB I+D on chip per chip
Other Cache:	None
Memory:	24 GB (6*4GB DDR3-1333 CL9 RDIMMs)
Disk Subsystem:	None
Other Hardware:	None
Adapter:	Mellanox MT26418 ConnectX IB DDR (PCIe x8 Gen2 5 GT/s)
Number of Adapters:	1

Continued on next page

Software

Adapter:	Mellanox MT26418 ConnectX IB DDR (PCIe x8 Gen2 5 GT/s)
Adapter Driver:	OFED-1.4
Adapter Firmware:	2.6.0
Operating System:	SUSE Linux Enterprise Server 10 (x86_64) SP2 Kernel 2.6.16.60-0.34-smp
Local File System:	NFSv3
Shared File System:	NFSv3 IPoIB
System State:	Multi-user, run level 3
Other Software:	SGI ProPack 6 for Linux Service Pack 3, SGI Tempo V 1.7

Copyright 2006-2010 Standard Performance Evaluation Corporation

SGI

SGI Altix ICE 8200EX
(Intel Xeon X5570, 2.93 GHz, DDR3-1333)

SPECmpiM_peak2007 = Not Run

SPECmpiM_base2007 = 7.33

MPI2007 license: 4
Test sponsor: SGI
Tested by: SGI

Test date: Sep-2009
Hardware Availability: Mar-2009
Software Availability: Aug-2009

Node Description: SGI Altix ICE 8200EX Compute Node

Slot Type:	PCIe x8 Gen2
Data Rate:	InfiniBand 4x DDR
Ports Used:	2
Interconnect Type:	InfiniBand

Node Description: SGI InfiniteStorage Nexis 2000 NAS

Hardware

Number of nodes:	1
Uses of the node:	fileserver
Vendor:	SGI
Model:	SGI Altix XE 240 (Intel Xeon 5140, 2.33 GHz)
CPU Name:	Intel Xeon 5140
CPU(s) orderable:	1-2 chips
Chips enabled:	2
Cores enabled:	4
Cores per chip:	2
Threads per core:	1
CPU Characteristics:	1333 MHz FSB
CPU MHz:	2328
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	4 MB I+D on chip per chip
L3 Cache:	None
Other Cache:	None
Memory:	24 GB (6*4GB DDR2-400 DIMMS)
Disk Subsystem:	7 TB RAID 5 48 x 147 GB SAS (Seagate Cheetah 15000 rpm)
Other Hardware:	None
Adapter:	Mellanox MT25208 InfiniHost III Ex (PCIe x8 Gen1 2.5 GT/s)
Number of Adapters:	2
Slot Type:	PCIe x8 Gen1
Data Rate:	InfiniBand 4x DDR
Ports Used:	2
Interconnect Type:	InfiniBand

Software

Adapter:	Mellanox MT25208 InfiniHost III Ex (PCIe x8 Gen1 2.5 GT/s)
Adapter Driver:	OFED-1.3
Adapter Firmware:	5.3.0
Operating System:	SUSE Linux Enterprise Server 10 (x86_64) SP1 Kernel 2.6.16.54-0.2.5-smp
Local File System:	xfs
Shared File System:	--
System State:	Multi-user, run level 3
Other Software:	SGI ProPack 5 for Linux Service Pack 5

Interconnect Description: InfiniBand (MPI)

Hardware

Vendor:	Mellanox Technologies
Model:	MT26418 ConnectX
Switch Model:	Mellanox MT47396 InfiniScale III
Number of Switches:	16
Number of Ports:	24
Data Rate:	InfiniBand 4x DDR
Firmware:	2020001

Software

Continued on next page

Copyright 2006-2010 Standard Performance Evaluation Corporation

SGI

SGI Altix ICE 8200EX
(Intel Xeon X5570, 2.93 GHz, DDR3-1333)

SPECmpiM_peak2007 = Not Run

SPECmpiM_base2007 = 7.33

MPI2007 license: 4
Test sponsor: SGI
Tested by: SGI

Test date: Sep-2009
Hardware Availability: Mar-2009
Software Availability: Aug-2009

Interconnect Description: InfiniBand (MPI)

Topology:	Bristle hypercube with express links
Primary Use:	MPI traffic

Interconnect Description: InfiniBand (I/O)

Hardware

Vendor:	Mellanox Technologies
Model:	MT26418 ConnectX
Switch Model:	Mellanox MT47396 InfiniScale-III
Number of Switches:	8
Number of Ports:	24
Data Rate:	InfiniBand 4x DDR
Firmware:	2020001
Topology:	Bristle hypercube with express links
Primary Use:	I/O traffic

Software

Submit Notes

```
The config file option 'submit' was used.
```

General Notes

```
Software environment:
  export MPI_REQUEST_MAX=65536
  export MPI_TYPE_MAX=32768
  export MPI_BUFS_THRESHOLD=1
  export MPI_DSM_DISTRIBUTE=yes
  export MPI_IB_RAILS=2
  ulimit -s unlimited
BIOS settings:
  AMI BIOS version 8.15
  Hyper-Threading Technology enabled (default)
  Intel Turbo Boost Technology enabled (default)
  Intel Turbo Boost Technology activated in the OS via
    /etc/init.d/acpid start
    /etc/init.d/powersaved start
    powersave -f
Job Placement:
  Each MPI job was assigned to a topologically compact set
  of nodes, i.e. the minimal needed number of switches was
  used for each job: 2 switches for 16/32/64 ranks, 4 switches
  for 128 ranks, 8 switches for 256 ranks and 16 switches for
  512 ranks.
```

Base Compiler Invocation

C benchmarks:
icc

C++ benchmarks:

126.lammps: icpc

Fortran benchmarks:
ifort

Benchmarks using both Fortran and C:
icc ifort

Base Portability Flags

121.pop2: -DSPEC_MPI_CASE_FLAG
127.wrf2: -DSPEC_MPI_CASE_FLAG -DSPEC_MPI_LINUX

Base Optimization Flags

C benchmarks:
-O3 -ipo -xT -no-prec-div

C++ benchmarks:

126.lammps: -O3 -ipo -xT -no-prec-div -ansi-alias

Fortran benchmarks:
-O3 -ipo -xT -no-prec-div

Benchmarks using both Fortran and C:
-O3 -ipo -xT -no-prec-div

Base Other Flags

C benchmarks:
-lmpi

C++ benchmarks:

126.lammps: -lmpi

Fortran benchmarks:
-lmpi

Continued on next page

Base Other Flags (Continued)

Benchmarks using both Fortran and C:
`-lmpi`

The flags file that was used to format this result can be browsed at
`http://www.spec.org/mpi2007/flags/SGI_x86_64_Intel111_flags.html`

You can also download the XML flags source by saving the following link:
`http://www.spec.org/mpi2007/flags/SGI_x86_64_Intel111_flags.xml`

SPEC and SPEC MPI are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC MPI2007 v1.1.
Report generated on Tue Jul 22 13:38:52 2014 by SPEC MPI2007 PS/PDF formatter v1463.
Originally published on 8 October 2009.