SPEC® MPIM2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

Intel Corporation

Endeavor (Intel Xeon X5670, 2.93 GHz,
DDR3-1333 MHz, SMT on, Turbo off)

SPECmpiM_peak2007 = Not Run

SPECmpiM_base2007 = 16.5

MPI2007 license: 13
Test sponsor: Intel Corporation
Tested by: Pavel Shelepugin

Test date: Jul-2010
Hardware Availability: Mar-2010
Software Availability: Aug-2010



Results Table

Benchmark	Base							Peak						
	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
104.milc	96	101	15.6	**101**	**15.5**	101	15.5							
107.leslie3d	96	341	15.3	**341**	**15.3**	341	15.3							
113.GemsFDTD	96	247	25.5	247	25.5	**247**	**25.5**							
115.fds4	96	**145**	**13.4**	145	13.4	145	13.4							
121.pop2	96	330	12.5	330	12.5	**330**	**12.5**							
122.tachyon	96	226	12.4	**227**	**12.3**	227	12.3							
126.lammps	96	**208**	**14.0**	208	14.0	208	14.0							
127.wrf2	96	295	26.5	295	26.4	**295**	**26.5**							
128.GAPgeofem	96	**121**	**17.1**	121	17.1	121	17.1							
129.tera_tf	96	223	12.4	222	12.5	**223**	**12.4**							

Table continues on next page. Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

SPEC MPIM2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

Intel Corporation

Endeavor (Intel Xeon X5670, 2.93 GHz, DDR3-1333 MHz, SMT on, Turbo off)

SPECmpiM_peak2007 = Not Run

SPECmpiM_base2007 = 16.5

MPI2007 license: 13
Test sponsor: Intel Corporation
Tested by: Pavel Shelepugin

Test date: Jul-2010
Hardware Availability: Mar-2010
Software Availability: Aug-2010

Results Table (Continued)

Benchmark	Base							Peak						
	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
130.socorro	96	**215**	**17.8**	216	17.6	214	17.8							
132.zeusmp2	96	163	19.1	163	19.0	**163**	**19.1**							
137.lu	96	179	20.6	**182**	**20.2**	197	18.6							

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Hardware Summary

Type of System:	Homogeneous
Compute Node:	Endeavor Node
Interconnects:	IB Switch Gigabit Ethernet
File Server Node:	HOME
Total Compute Nodes:	8
Total Chips:	16
Total Cores:	96
Total Threads:	192
Total Memory:	192 GB
Base Ranks Run:	96
Minimum Peak Ranks:	--
Maximum Peak Ranks:	--

Software Summary

C Compiler:	Intel C++ Compiler 11.1.064 for Linux
C++ Compiler:	Intel C++ Compiler 11.1.064 for Linux
Fortran Compiler:	Intel Fortran Compiler 11.1.064 for Linux
Base Pointers:	64-bit
Peak Pointers:	64-bit
MPI Library:	Intel MPI Library 4.0.1 for Linux
Other MPI Info:	None
Pre-processors:	No
Other Software:	None

Node Description: Endeavor Node

Hardware

Number of nodes:	8
Uses of the node:	compute
Vendor:	Intel
Model:	SR1600UR
CPU Name:	Intel Xeon X5670
CPU(s) orderable:	1-2 chips
Chips enabled:	2
Cores enabled:	12
Cores per chip:	6
Threads per core:	2
CPU Characteristics:	Intel Turbo Boost Technology disabled, 6.4 GT/s QPI, Hyper-Threading enabled
CPU MHz:	2934
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	256 KB I+D on chip per core
L3 Cache:	12 MB I+D on chip per chip, 12 MB shared / 6 cores
Other Cache:	None
Memory:	24 GB (RDIMM 6x4-GB DDR3-1333 MHz)
Disk Subsystem:	Seagate 400 GB ST3400755SS
Other Hardware:	None
Adapter:	Intel (ESB2) 82575EB Dual-Port Gigabit Ethernet Controller
Number of Adapters:	1

Continued on next page

Software

Adapter:	Intel (ESB2) 82575EB Dual-Port Gigabit Ethernet Controller
Adapter Driver:	e1000
Adapter Firmware:	None
Adapter:	Mellanox MHQH29-XTC
Adapter Driver:	OFED 1.4.2
Adapter Firmware:	2.7.000
Operating System:	Red Hat EL 5.4, kernel 2.6.18-164
Local File System:	Linux/ext2
Shared File System:	NFS
System State:	Multi-User
Other Software:	PBS Pro 10.1

SPEC MPIM2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

Intel Corporation

Endeavor (Intel Xeon X5670, 2.93 GHz, DDR3-1333 MHz, SMT on, Turbo off)

SPECmpiM_peak2007 = Not Run

SPECmpiM_base2007 = 16.5

MPI2007 license: 13
Test sponsor: Intel Corporation
Tested by: Pavel Shelepugin

Test date: Jul-2010
Hardware Availability: Mar-2010
Software Availability: Aug-2010

Node Description: Endeavor Node

Slot Type:	PCI-Express x8
Data Rate:	1Gbps Ethernet
Ports Used:	2
Interconnect Type:	Ethernet
Adapter:	Mellanox MHQH29-XTC
Number of Adapters:	1
Slot Type:	PCIe x8 Gen2
Data Rate:	InfiniBand 4x QDR
Ports Used:	1
Interconnect Type:	InfiniBand

Node Description: HOME

Hardware

Number of nodes:	1
Uses of the node:	fileserver
Vendor:	Intel
Model:	SSR212CC
CPU Name:	Intel Xeon CPU
CPU(s) orderable:	2 chips
Chips enabled:	2
Cores enabled:	2
Cores per chip:	1
Threads per core:	1
CPU Characteristics:	--
CPU MHz:	2800
Primary Cache:	12 KB I + 16 KB D on chip per chip
Secondary Cache:	1 MB I+D on chip per chip
L3 Cache:	None
Other Cache:	None
Memory:	6 GB
Disk Subsystem:	10 disks, 320GB/disk, 2.6TB total
Other Hardware:	None
Adapter:	Intel 82546GB Dual-Port Gigabit Ethernet Controller
Number of Adapters:	1
Slot Type:	PCI-Express x8
Data Rate:	1Gbps Ethernet
Ports Used:	1
Interconnect Type:	Ethernet

Software

Adapter:	Intel 82546GB Dual-Port Gigabit Ethernet Controller
Adapter Driver:	e1000
Adapter Firmware:	N/A
Operating System:	RedHat EL 4 Update 4
Local File System:	None
Shared File System:	NFS
System State:	Multi-User
Other Software:	None

Interconnect Description: IB Switch

Hardware		Software
Vendor:	Mellanox	
Model:	Mellanox MTS3600Q-1UNC	
Switch Model:	Mellanox MTS3600Q-1UNC	
Number of Switches:	46	
Number of Ports:	36	
Data Rate:	InfiniBand 4x QDR	
Firmware:	7.1.000	
Topology:	Fat tree	
Primary Use:	MPI traffic	

Interconnect Description: Gigabit Ethernet

Hardware		Software
Vendor:	Force10 Networks	
Model:	Force10 S50, Force10 C300	
Switch Model:	Force10 S50, Force10 C300	
Number of Switches:	15	
Number of Ports:	48	
Data Rate:	1Gbps Ethernet	
Firmware:	8.2.1.0	
Topology:	Fat tree	
Primary Use:	Cluster File System	

Submit Notes

```
The config file option 'submit' was used.
```

General Notes

```
MPI startup command:
  mpiexec.hydra command was used to start MPI jobs.

BIOS settings:
  Intel Hyper-Threading Technology (SMT): Enabled (default is Enabled)
  Intel Turbo Boost Technology (Turbo)  : Disabled (default is Enabled)

RAM configuration:
  Compute nodes have 1x4-GB RDIMM on each memory channel.

Network:
  Forty six 36-port switches: 18 core switches and 28 leaf switches.
  Each leaf has one link to each core. Remaining 18 ports on 25 of 28 leafs
  are used for compute nodes. On the remaining 3 leafs the ports are used
  for FS nodes and other peripherals.
```

Continued on next page

General Notes (Continued)

```
Job placement:
  Each MPI job was assigned to a topologically compact set of nodes, i.e.
  the minimal needed number of leaf switches was used for each job: 1 switch
  for 24/48/96/192 ranks, 2 switches for 384 ranks, 3 switches for 504 ranks.

PBS Pro was used for job submission. It has no impact on performance.
  Can be found at: http://www.altair.com
```

Base Compiler Invocation

C benchmarks:
`mpiicc`

C++ benchmarks:

126.lammps: `mpiicpc`

Fortran benchmarks:
`mpiifort`

Benchmarks using both Fortran and C:
`mpiicc mpiifort`

Base Portability Flags

121.pop2: `-DSPEC_MPI_CASE_FLAG`
126.lammps: `-DMPICH_IGNORE_CXX_SEEK`
127.wrf2: `-DSPEC_MPI_CASE_FLAG -DSPEC_MPI_LINUX`

Base Optimization Flags

C benchmarks:
`-O3 -xSSE4.2 -no-prec-div`

C++ benchmarks:

126.lammps: `-O3 -xSSE4.2 -no-prec-div`

Fortran benchmarks:
`-O3 -xSSE4.2 -no-prec-div`

Benchmarks using both Fortran and C:
`-O3 -xSSE4.2 -no-prec-div`

The flags file that was used to format this result can be browsed at
http://www.spec.org/mpi2007/flags/EM64T_Intel111_flags.20120720.html

You can also download the XML flags source by saving the following link:
http://www.spec.org/mpi2007/flags/EM64T_Intel111_flags.20120720.xml

SPEC and SPEC MPI are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC MPI2007 v2.0.
Report generated on Tue Jul 22 13:40:43 2014 by SPEC MPI2007 PS/PDF formatter v1463.
Originally published on 11 August 2010.