SPEC® MPIM2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

SGI

SGI Altix ICE 8400EX
(Intel Xeon X5680, 3.33 GHz)

SPECmpiM_peak2007 = Not Run

SPECmpiM_base2007 = 32.3

MPI2007 license: 4
Test sponsor: SGI
Tested by: SGI

Test date: Sep-2010
Hardware Availability: May-2010
Software Availability: Oct-2010



Results Table

Benchmark	Base							Peak						
	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
104.milc	192	53.0	29.5	52.1	30.0	**52.2**	**30.0**							
107.leslie3d	192	172	30.3	172	30.4	**172**	**30.3**							
113.GemsFDTD	192	238	26.5	**238**	**26.5**	238	26.5							
115.fds4	192	57.1	34.1	57.4	34.0	**57.3**	**34.1**							
121.pop2	192	173	23.9	176	23.4	**173**	**23.9**							
122.tachyon	192	98.5	28.4	**98.3**	**28.4**	98.3	28.5							
126.lammps	192	131	22.2	**131**	**22.2**	131	22.2							
127.wrf2	192	151	51.8	150	51.9	**150**	**51.8**							
128.GAPgeofem	192	59.5	34.7	58.7	35.2	**59.0**	**35.0**							
129.tera_tf	192	**105**	**26.4**	105	26.4	105	26.3							

Table continues on next page. Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

SPEC MPIM2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

SGI

SGI Altix ICE 8400EX
(Intel Xeon X5680, 3.33 GHz)

SPECmpiM_peak2007 = Not Run

SPECmpiM_base2007 = 32.3

MPI2007 license: 4
Test sponsor: SGI
Tested by: SGI

Test date: Sep-2010
Hardware Availability: May-2010
Software Availability: Oct-2010

Results Table (Continued)

Benchmark	Base							Peak						
	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
130.socorro	192	**91.7**	**41.6**	91.6	41.7	91.9	41.5							
132.zeusmp2	192	79.9	38.8	**79.9**	**38.9**	79.9	38.9							
137.lu	192	86.4	42.5	86.3	42.6	**86.4**	**42.6**							

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Hardware Summary

Type of System:	Homogeneous
Compute Node:	SGI Altix ICE 8400EX Compute Node
Interconnects:	InfiniBand (MPI) InfiniBand (I/O)
File Server Node:	SGI InfiniteStorage Nexis 2000 NAS
Total Compute Nodes:	16
Total Chips:	32
Total Cores:	192
Total Threads:	384
Total Memory:	384 GB
Base Ranks Run:	192
Minimum Peak Ranks:	--
Maximum Peak Ranks:	--

Software Summary

C Compiler:	Intel C Compiler for Linux Version 11.1, Build 20100414
C++ Compiler:	Intel C++ Compiler for Linux Version 11.1, Build 20100414
Fortran Compiler:	Intel Fortran Compiler for Linux Version 11.1, Build 20100414
Base Pointers:	64-bit
Peak Pointers:	64-bit
MPI Library:	SGI MPT 2.02 Beta
Other MPI Info:	OFED 1.4.2
Pre-processors:	None
Other Software:	None

Node Description: SGI Altix ICE 8400EX Compute Node

Hardware

Number of nodes:	16
Uses of the node:	compute
Vendor:	SGI
Model:	SGI Altix ICE 8400EX (Intel Xeon X5680, 3.33 GHz)
CPU Name:	Intel Xeon X5680
CPU(s) orderable:	1-2 chips
Chips enabled:	2
Cores enabled:	12
Cores per chip:	6
Threads per core:	2
CPU Characteristics:	Six Core, 3.33 GHz, 6.4 GT/s QPI Intel Turbo Boost Technology up to 3.6 GHz Hyper-Threading Technology enabled
CPU MHz:	3333
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	256 KB I+D on chip per core
L3 Cache:	12 MB I+D on chip per chip
Other Cache:	None
Memory:	24 GB (6*4GB DDR3-1333 CL9 RDIMMs)
Disk Subsystem:	None
Other Hardware:	None
Adapter:	Mellanox MT26428 ConnectX IB QDR (PCIe x8 Gen2 5 GT/s)
Number of Adapters:	2

Continued on next page

Software

Adapter:	Mellanox MT26428 ConnectX IB QDR (PCIe x8 Gen2 5 GT/s)
Adapter Driver:	OFED-1.4.2
Adapter Firmware:	2.7.200
Operating System:	SUSE Linux Enterprise Server 11 SP1, Kernel 2.6.32.13-0.4-default
Local File System:	NFSv3
Shared File System:	NFSv3 IPoIB
System State:	Multi-user, run level 3
Other Software:	SGI ProPack 7 for Linux Service Pack 1, SGI Tempo V 2.1

SPEC MPIM2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

SGI

SGI Altix ICE 8400EX
(Intel Xeon X5680, 3.33 GHz)

SPECmpiM_peak2007 = Not Run

SPECmpiM_base2007 = 32.3

MPI2007 license: 4
Test sponsor: SGI
Tested by: SGI

Test date: Sep-2010
Hardware Availability: May-2010
Software Availability: Oct-2010

Node Description: SGI Altix ICE 8400EX Compute Node

Slot Type:	PCIe x8 Gen2
Data Rate:	InfiniBand 4x QDR
Ports Used:	1
Interconnect Type:	InfiniBand

Node Description: SGI InfiniteStorage Nexis 2000 NAS

Hardware

Number of nodes:	1
Uses of the node:	fileserver
Vendor:	SGI
Model:	SGI Altix XE 270 (Intel Xeon X5670, 2.93 GHz)
CPU Name:	Intel Xeon X5670
CPU(s) orderable:	1-2 chips
Chips enabled:	2
Cores enabled:	12
Cores per chip:	6
Threads per core:	2
CPU Characteristics:	Intel Turbo Boost Technology up to 3.33 GHz Hyper-Threading Technology enabled
CPU MHz:	2933
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	256 KB I+D on chip per chip
L3 Cache:	12 MB I+D on chip per chip
Other Cache:	None
Memory:	24 GB (6*4GB DDR3-1333 CL9 DIMMs)
Disk Subsystem:	8.8 TB RAID 5 60 x 146 GB SAS (Seagate Cheetah 15K.5)
Other Hardware:	None
Adapter:	Mellanox MT26418 ConnectX, MT25208 InfiniHost III Ex (PCIe x8 Gen2 5 GT/s, PCIe x8 Gen1 2.5 GT/s)
Number of Adapters:	2
Slot Type:	PCIe x8 Gen2, PCIe x8 Gen1
Data Rate:	InfiniBand 4x DDR
Ports Used:	2
Interconnect Type:	InfiniBand

Software

Adapter:	Mellanox MT26418 ConnectX, MT25208 InfiniHost III Ex (PCIe x8 Gen2 5 GT/s, PCIe x8 Gen1 2.5 GT/s)
Adapter Driver:	OFED-1.4.0
Adapter Firmware:	2.6.0 and 5.2.0
Operating System:	SUSE Linux Enterprise Server 11 (x86_64) Kernel 2.6.27.19-5-default
Local File System:	xfs
Shared File System:	--
System State:	Multi-user, run level 3
Other Software:	SGI Foundation Software 2

Interconnect Description: InfiniBand (MPI)

Hardware

Vendor:	Mellanox Technologies and SGI
Model:	MT26428 ConnectX
Switch Model:	SGI QDR_1.5_HYPR_2454 with Mellanox Device 48438 (Infiniscale IV)
Number of Switches:	32
Number of Ports:	36

Software

Continued on next page

Copyright 2006-2010 Standard Performance Evaluation Corporation

SGI

SGI Altix ICE 8400EX
(Intel Xeon X5680, 3.33 GHz)

SPECmpiM_peak2007 = Not Run

SPECmpiM_base2007 = 32.3

MPI2007 license: 4
Test sponsor: SGI
Tested by: SGI

Test date: Sep-2010
Hardware Availability: May-2010
Software Availability: Oct-2010

Interconnect Description: InfiniBand (MPI)

Data Rate:	InfiniBand 4x QDR
Firmware:	5030005
Topology:	Enhanced Hypercube
Primary Use:	MPI traffic

Interconnect Description: InfiniBand (I/O)

Hardware

Vendor:	Mellanox Technologies and SGI
Model:	MT26428 ConnectX
Switch Model:	SGI QDR_1.5_HYPR_2454 with Mellanox Device 48438 (Infiniscale IV)
Number of Switches:	16
Number of Ports:	36
Data Rate:	InfiniBand 4x QDR
Firmware:	5030005
Topology:	Enhanced Hypercube
Primary Use:	I/O traffic

Software

Submit Notes

```
The config file option 'submit' was used.
```

General Notes

```
 Software environment:
   export MPI_REQUEST_MAX=65536
   export MPI_TYPE_MAX=32768
   export MPI_BUFS_THRESHOLD=1
   export MPI_IB_RAILS=2
   ulimit -s unlimited

 BIOS settings:
   AMI BIOS version 080016
   Hyper-Threading Technology enabled (default)
   Intel Turbo Boost Technology enabled (default)
   Intel Turbo Boost Technology activated in the OS via
     /etc/init.d/acpid start
     /etc/init.d/powersaved start
     powersave -f

Job Placement:
  Each MPI job was assigned to a topologically compact set
  of nodes, i.e. the minimal needed number of switches was
  used for each job: 2 switches for 96 ranks,
  4 switches for 192 ranks, 8 switches for 384 ranks,
```

Continued on next page

General Notes (Continued)

16 switches for 768 ranks, 32 switches for 1536 ranks.

Base Compiler Invocation

C benchmarks:
icc

C++ benchmarks:

126.lammps: icpc

Fortran benchmarks:
ifort

Benchmarks using both Fortran and C:
icc ifort

Base Portability Flags

121.pop2: -DSPEC_MPI_CASE_FLAG
127.wrf2: -DSPEC_MPI_CASE_FLAG -DSPEC_MPI_LINUX

Base Optimization Flags

C benchmarks:
-O3 -xSSE4.2 -no-prec-div

C++ benchmarks:

126.lammps: -O3 -xSSE4.2 -no-prec-div -ansi-alias

Fortran benchmarks:
-O3 -xSSE4.2 -no-prec-div

Benchmarks using both Fortran and C:
-O3 -xSSE4.2 -no-prec-div

Base Other Flags

C benchmarks:
-lmpi

C++ benchmarks:

Continued on next page

Base Other Flags (Continued)

126.lammps: `-lmpi`

Fortran benchmarks:
`-lmpi`

Benchmarks using both Fortran and C:
`-lmpi`

The flags file that was used to format this result can be browsed at
`http://www.spec.org/mpi2007/flags/SGI_x86_64_Intel111_flags.html`

You can also download the XML flags source by saving the following link:
`http://www.spec.org/mpi2007/flags/SGI_x86_64_Intel111_flags.xml`

SPEC and SPEC MPI are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC MPI2007 v2.0.
Report generated on Tue Jul 22 13:41:17 2014 by SPEC MPI2007 PS/PDF formatter v1463.
Originally published on 22 September 2010.