SPEC® MPIM2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

Gateway

GW2000h-GW170hq (Intel Xeon X5570, 2.93 Ghz)

SPECmpiM_peak2007 = Not Run

SPECmpiM_base2007 = 14.2

MPI2007 license: 4113
Test sponsor: Fraunhofer SCAI
Tested by: Steffen Claus

Test date: Jan-2011
Hardware Availability: Jan-2010
Software Availability: Aug-2010



Results Table

Benchmark	Base							Peak						
	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
104.milc	64	111	14.0	103	15.1	**104**	**15.1**							
107.leslie3d	64	382	13.7	381	13.7	**381**	**13.7**							
113.GemsFDTD	64	270	23.4	272	23.2	**270**	**23.4**							
115.fds4	64	161	12.1	161	12.1	**161**	**12.1**							
121.pop2	64	326	12.7	**327**	**12.6**	329	12.6							
122.tachyon	64	**307**	**9.12**	307	9.10	306	9.13							
126.lammps	64	286	10.2	**286**	**10.2**	289	10.1							
127.wrf2	64	351	22.2	350	22.3	**350**	**22.3**							
128.GAPgeofem	64	130	15.8	130	15.9	**130**	**15.9**							
129.tera_tf	64	**270**	**10.3**	270	10.3	271	10.2							

Table continues on next page. Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

SPEC MPIM2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

Gateway

GW2000h-GW170hq (Intel Xeon X5570, 2.93 Ghz)

SPECmpiM_peak2007 = Not Run

SPECmpiM_base2007 = 14.2

MPI2007 license: 4113
Test sponsor: Fraunhofer SCAI
Tested by: Steffen Claus

Test date: Jan-2011
Hardware Availability: Jan-2010
Software Availability: Aug-2010

Results Table (Continued)

Benchmark	Base							Peak						
	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
130.socorro	64	227	16.8	**229**	**16.7**	230	16.6							
132.zeusmp2	64	206	15.0	207	15.0	**206**	**15.0**							
137.lu	64	233	15.8	**234**	**15.7**	235	15.6							

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Hardware Summary

Type of System:	Homogeneous
Compute Node:	Gateway GW2000h
Interconnects:	Infiniband Switch Ethernet Switch
Total Compute Nodes:	8
Total Chips:	16
Total Cores:	64
Total Threads:	64
Total Memory:	192 GB
Base Ranks Run:	64
Minimum Peak Ranks:	--
Maximum Peak Ranks:	--

Software Summary

C Compiler:	Intel C++ Compiler 11.1 for Linux (11.1.073)
C++ Compiler:	Intel C++ Compiler 11.1 for Linux (11.1.073)
Fortran Compiler:	Intel Fortran Compiler 11.1 for Linux (11.1.073)
Base Pointers:	64-bit
Peak Pointers:	Not Applicable
MPI Library:	Intel MPI 4.0.0.028
Other MPI Info:	--
Pre-processors:	--
Other Software:	--

Node Description: Gateway GW2000h

Hardware

Number of nodes:	8
Uses of the node:	compute
Vendor:	Gateway
Model:	GW2000h-GW170hq
CPU Name:	Intel Xeon X5570 @ 2.93 GHz
CPU(s) orderable:	1-2 chips
Chips enabled:	2
Cores enabled:	8
Cores per chip:	4
Threads per core:	1
CPU Characteristics:	--
CPU MHz:	2930
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	256 KB I+D on chip per core
L3 Cache:	8 MB I+D on chip per chip, 8 MB shared / 4 cores
Other Cache:	None
Memory:	24 GB
Disk Subsystem:	--
Other Hardware:	None
Adapter:	Mellanox Technologies MT26418
Number of Adapters:	1
Slot Type:	onboard
Data Rate:	QDR
Ports Used:	1

Continued on next page

Software

Adapter:	Mellanox Technologies MT26418
Adapter Driver:	OFED 1.5.1
Adapter Firmware:	2.7.200
Adapter:	Intel 82574L Gigabit Network Connection
Adapter Driver:	--
Adapter Firmware:	--
Operating System:	SLES 11
Local File System:	--
Shared File System:	Network shared Ramdisk
System State:	--
Other Software:	--

SPEC MPIM2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

Gateway

GW2000h-GW170hq (Intel Xeon X5570, 2.93 Ghz)

SPECmpiM_peak2007 = Not Run

SPECmpiM_base2007 = 14.2

MPI2007 license: 4113
Test sponsor: Fraunhofer SCAI
Tested by: Steffen Claus

Test date: Jan-2011
Hardware Availability: Jan-2010
Software Availability: Aug-2010

Node Description: Gateway GW2000h

Interconnect Type:	InfiniBand
Adapter:	Intel 82574L Gigabit Network Connection
Number of Adapters:	2
Slot Type:	onboard
Data Rate:	Gigabit Ethernet
Ports Used:	1
Interconnect Type:	Ethernet

Interconnect Description: Infiniband Switch

Hardware

Vendor:	Mellanox
Model:	MTS3600
Switch Model:	Mellanox MTS3600
Number of Switches:	1
Number of Ports:	36
Data Rate:	QDR
Firmware:	EFM_PPC_405EX
Topology:	Single Switch
Primary Use:	MPI traffic

Software

Interconnect Description: Ethernet Switch

Hardware

Vendor:	Extreme Networks
Model:	Summit
Switch Model:	Summit X450-24 t
Number of Switches:	1
Number of Ports:	24
Data Rate:	Gigabit Ethernet
Firmware:	ExtremeWare XOS 11.4.3.4 v1143b4
Topology:	Single Switch
Primary Use:	NFS traffic

Software

Submit Notes

```
The config file option 'submit' was used.
```

General Notes

```
MPI startup command:
  mpirun command was used to start MPI jobs. This command starts
  an independent ring of mpd daemons, launches an MPI job, and shuts
  down the mpd ring upon the job termination.
```

Continued on next page

General Notes (Continued)

```
BIOS settings:
  Intel Hyper-Threading Technology (SMT): Disabled (default is Enabled)
  Intel Turbo Boost Technology (Turbo)  : Enabled (default is Enabled)

RAM configuration:
  Compute nodes have 6x4-GB dual rank DDR3-1333 RAM.
  Head node has 4x2GB single rank DDR2-667 RAM.

Network:
  Head node and all compute nodes are interconnected by 1GB Ethernet and
  QDR Infiniband. Each interconnect type has one single switch.
```

Base Compiler Invocation

C benchmarks:
`mpiicc`

C++ benchmarks:

126.lammps: `mpiicpc`

Fortran benchmarks:
`mpiifort`

Benchmarks using both Fortran and C:
`mpiicc mpiifort`

Base Portability Flags

121.pop2: `-DSPEC_MPI_CASE_FLAG`
126.lammps: `-DMPICH_IGNORE_CXX_SEEK`
127.wrf2: `-DSPEC_MPI_CASE_FLAG -DSPEC_MPI_LINUX`

Base Optimization Flags

C benchmarks:
`-O3 -xSSE4.2 -ipo -no-prec-div`

C++ benchmarks:

126.lammps: `-O3 -xSSE4.2 -ipo -no-prec-div`

Fortran benchmarks:
`-O3 -xSSE4.2 -ipo -no-prec-div`

Continued on next page

Base Optimization Flags (Continued)

Benchmarks using both Fortran and C:
`-O3 -xSSE4.2 -ipo -no-prec-div`

The flags file that was used to format this result can be browsed at
`http://www.spec.org/mpi2007/flags/EM64T_Intel111_flags.20100202.html`

You can also download the XML flags source by saving the following link:
`http://www.spec.org/mpi2007/flags/EM64T_Intel111_flags.20100202.xml`

SPEC and SPEC MPI are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC MPI2007 v2.0.
Report generated on Tue Jul 22 13:42:10 2014 by SPEC MPI2007 PS/PDF formatter v1463.
Originally published on 29 June 2011.