# SPEC® MPIL2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

## SGI

SGI Altix ICE 8400EX
(AMD Opteron 6282 SE, 2.6GHz)

SPECmpiL_peak2007 = Not Run

SPECmpiL_base2007 = 16.4

**MPI2007 license:** 4
**Test sponsor:** SGI
**Tested by:** SGI

**Test date:** Jan-2012
**Hardware Availability:** Nov-2011
**Software Availability:** Nov-2011




## Results Table

| Benchmark | Base | | | | | | | Peak | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | Ranks | Seconds | Ratio | Seconds | Ratio | Seconds | Ratio | Ranks | Seconds | Ratio | Seconds | Ratio | Seconds | Ratio |
| 121.pop2 | 1024 | 217 | 17.9 | **218** | **17.9** | 219 | 17.8 | | | | | | | |
| 122.tachyon | 1024 | 279 | 6.96 | **269** | **7.22** | 268 | 7.26 | | | | | | | |
| 125.RAxML | 1024 | 367 | 7.95 | **368** | **7.93** | 369 | 7.91 | | | | | | | |
| 126.lammps | 1024 | 179 | 13.7 | **180** | **13.7** | 180 | 13.7 | | | | | | | |
| 128.GAPgeofem | 1024 | **290** | **20.5** | 291 | 20.4 | 290 | 20.5 | | | | | | | |
| 129.tera_tf | 1024 | 167 | 6.60 | **167** | **6.59** | 167 | 6.57 | | | | | | | |
| 132.zeusmp2 | 1024 | 132 | 16.1 | 133 | 16.0 | **132** | **16.0** | | | | | | | |
| 137.lu | 1024 | **125** | **33.5** | 125 | 33.5 | 125 | 33.6 | | | | | | | |
| 142.dmilc | 1024 | 102 | 36.0 | 103 | 35.9 | **102** | **35.9** | | | | | | | |
| 143.dleslie | 1024 | **125** | **24.7** | 125 | 24.8 | 125 | 24.7 | | | | | | | |
| 145.lGemsFDTD | 1024 | 216 | 20.4 | 216 | 20.5 | **216** | **20.4** | | | | | | | |
| 147.l2wrf2 | 1024 | 398 | 20.6 | **400** | **20.5** | 401 | 20.5 | | | | | | | |

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

# SPEC MPIL2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

## SGI

SGI Altix ICE 8400EX
(AMD Opteron 6282 SE, 2.6GHz)

SPECmpiL_peak2007 = Not Run

SPECmpiL_base2007 = 16.4

**MPI2007 license:** 4
**Test sponsor:** SGI
**Tested by:** SGI

**Test date:** Jan-2012
**Hardware Availability:** Nov-2011
**Software Availability:** Nov-2011

### Hardware Summary

| | |
|---|---|
| Type of System: | Homogeneous |
| Compute Node: | SGI Altix ICE 8400EX Compute Node |
| Interconnect: | InfiniBand (MPI and I/O) |
| File Server Node: | SGI InfiniteStorage 4000 |
| Total Compute Nodes: | 32 |
| Total Chips: | 64 |
| Total Cores: | 1024 |
| Total Threads: | 1024 |
| Total Memory: | 4 TB |
| Base Ranks Run: | 1024 |
| Minimum Peak Ranks: | -- |
| Maximum Peak Ranks: | -- |

### Software Summary

| | |
|---|---|
| C Compiler: | Intel C++ Composer XE 2011 for Linux, Version 12.1.1.256 Build 20111011 |
| C++ Compiler: | Intel C++ Composer XE 2011 for Linux, Version 12.1.1.256 Build 20111011 |
| Fortran Compiler: | Intel Fortran Composer XE 2011 for Linux, Version 12.1.1.256 Build 20111011 |
| Base Pointers: | 64-bit |
| Peak Pointers: | 64-bit |
| MPI Library: | SGI MPT 2.05 |
| Other MPI Info: | OFED 1.5.2 |
| Pre-processors: | None |
| Other Software: | None |

## Node Description: SGI Altix ICE 8400EX Compute Node

### Hardware

| | |
|---|---|
| Number of nodes: | 32 |
| Uses of the node: | compute |
| Vendor: | SGI |
| Model: | SGI Altix ICE 8400EX (AMD Opteron 6282 SE, 2.6GHz) |
| CPU Name: | AMD Opteron 6282 SE |
| CPU(s) orderable: | 1-2 chips |
| Chips enabled: | 2 |
| Cores enabled: | 32 |
| Cores per chip: | 16 |
| Threads per core: | 1 |
| CPU Characteristics: | 16 cores/chip, 2.6 GHz<br>AMD Turbo CORE technology up to 3.30 GHz |
| CPU MHz: | 2600 |
| Primary Cache: | 512 KB I on chip per chip,<br>64 KB I shared / 2 cores;<br>16 KB D on chip per core |
| Secondary Cache: | 16 MB I+D on chip per chip, 2 MB I+D on chip per core |
| L3 Cache: | 16 MB I+D on chip per chip, 8 MB shared / 8 cores |
| Other Cache: | None |
| Memory: | 128 GB (16 x 8 GB 2Rx4 PC3-12800R-11, ECC) |
| Disk Subsystem: | None |
| Other Hardware: | None |
| Adapter: | Mellanox MT26428 ConnectX IB QDR (PCIe x8 Gen2 5 GT/s) |
| Number of Adapters: | 1 |
| Slot Type: | PCIe x8 Gen2 |
| Data Rate: | InfiniBand 4x QDR |
| Ports Used: | 2 |
| Interconnect Type: | InfiniBand |

### Software

| | |
|---|---|
| Adapter: | Mellanox MT26428 ConnectX IB QDR (PCIe x8 Gen2 5 GT/s) |
| Adapter Driver: | OFED-1.5.2 |
| Adapter Firmware: | 2.7.0 |
| Operating System: | SUSE Linux Enterprise Server 11 SP1 (x86_64)<br>Kernel 2.6.32.46-0.3-default #1 SMP |
| Local File System: | NFSv3 |
| Shared File System: | NFSv3 IPoIB |
| System State: | Run level 3 (Multi-User) |
| Other Software: | SGI Performance Suite 1.3,<br>Build 705rp8.sles11-1111092106<br>SGI Tempo Compute Node 2.5,<br>Build 705r10.sles11-1110192111 |

# SPEC MPIL2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

## SGI

SGI Altix ICE 8400EX
(AMD Opteron 6282 SE, 2.6GHz)

SPECmpiL_peak2007 = Not Run

SPECmpiL_base2007 = 16.4

**MPI2007 license:** 4
**Test sponsor:** SGI
**Tested by:** SGI

**Test date:** Jan-2012
**Hardware Availability:** Nov-2011
**Software Availability:** Nov-2011

## Node Description: SGI InfiniteStorage 4000

### Hardware

| | |
|---|---|
| Number of nodes: | 1 |
| Uses of the node: | fileserver |
| Vendor: | SGI |
| Model: | SGI Altix 450 (Intel Itanium 2, 1.6GHz) |
| CPU Name: | Intel Itanium 2 9030 |
| CPU(s) orderable: | 2-38 chips |
| Chips enabled: | 2 |
| Cores enabled: | 4 |
| Cores per chip: | 2 |
| Threads per core: | 1 |
| CPU Characteristics: | 1.6GHz/8MB, 533MHz FSB |
| CPU MHz: | 1600 |
| Primary Cache: | 16 KB I + 16 KB D on chip per core |
| Secondary Cache: | 1 MB I + 256 KB D on chip per core |
| L3 Cache: | 4 MB I+D on chip per core |
| Other Cache: | None |
| Memory: | 24 GB (12 x 2 GB, 2Rx4 PC2-3200-3, ECC) |
| Disk Subsystem: | 16 TB RAID 5<br>32 x 500 GB SATA (Seagate Barracuda 7.2K) |
| Other Hardware: | None |
| Adapter: | Mellanox MT25208 InfiniHost III Ex (PCIe x8 Gen1 2.5 GT/s) |
| Number of Adapters: | 2 |
| Slot Type: | PCIe x8 Gen1 |
| Data Rate: | InfiniBand 4x DDR |
| Ports Used: | 2 |
| Interconnect Type: | InfiniBand |

### Software

| | |
|---|---|
| Adapter: | Mellanox MT25208 InfiniHost III Ex (PCIe x8 Gen1 2.5 GT/s) |
| Adapter Driver: | OFED-1.4.2 |
| Adapter Firmware: | 5.3.0 |
| Operating System: | SUSE Linux Enterprise Server 11 SP1 (ia64)<br>Kernel 2.6.32.12-0.7-default |
| Local File System: | xfs |
| Shared File System: | -- |
| System State: | Run Level 3 (Multi-User) |
| Other Software: | SGI ProPack 7SP1 for Linux, Build 701r2.sles11-1005242307 |

## Interconnect Description: InfiniBand (MPI and I/O)

### Hardware

| | |
|---|---|
| Vendor: | Mellanox Technologies and SGI |
| Model: | None |
| Switch Model: | SGI QDR_1.5_HYPR_2454 with Mellanox Device 48438 (Infiniscale IV) |
| Number of Switches: | 8 |
| Number of Ports: | 36 |
| Data Rate: | InfiniBand 4x QDR |
| Firmware: | 5040005 |
| Topology: | Enhanced Hypercube |
| Primary Use: | MPI and I/O traffic |

### Software

## Submit Notes

```
The config file option 'submit' was used.
```

## General Notes

```
Software environment:
  export MPI_REQUEST_MAX=65536
  export MPI_TYPE_MAX=32768
  export MPI_BUFS_THRESHOLD=1
  export MPI_IB_RAILS=2
  ulimit -s unlimited

BIOS settings:
  AMI BIOS version 2.0

Job Placement:
  In the base run, each MPI job is assigned to a topologically compact
  set of nodes, i.e. the minimal needed number of switches was
  used for each job: 2 switch for up to 256 ranks, 4 switches
  for 512 ranks, 8 switches for 1024 ranks.

Additional notes regarding interconnect:
  The Infiniband network consists of two independent planes,
  with half the switches in the system allocated to each plane.
  I/O traffic is restricted to one plane, while MPI traffic can
  use both planes.

  SGI manufactures its own switch blades using unmodified Mellanox
  switch ASICs. The test system has SGI QDR_1.5_HYPR_2454 switch
  with Mellanox 36-port QDR Infiniband switch Device 48438
  (InfiniScale IV).
```

# Base Compiler Invocation

C benchmarks:
`icc`

C++ benchmarks:

126.lammps: `icpc`

Fortran benchmarks:
`ifort`

Benchmarks using both Fortran and C:
`icc ifort`

## Base Portability Flags

121.pop2: `-DSPEC_MPI_CASE_FLAG`

## Base Optimization Flags

C benchmarks:
`-O3 -xSSE2 -ipo -no-prec-div`

C++ benchmarks:

126.lammps: `-O3 -xSSE2 -ipo -no-prec-div -ansi-alias`

Fortran benchmarks:
`-O3 -xSSE2 -ipo -no-prec-div`

Benchmarks using both Fortran and C:
`-O3 -xSSE2 -ipo -no-prec-div`

## Base Other Flags

C benchmarks:
`-lmpi`

C++ benchmarks:

126.lammps: `-lmpi`

Fortran benchmarks:
`-lmpi`

Benchmarks using both Fortran and C:
`-lmpi`

The flags file that was used to format this result can be browsed at
`http://www.spec.org/mpi2007/flags/SGI_x86_64_Intel12_flags.html`

You can also download the XML flags source by saving the following link:
`http://www.spec.org/mpi2007/flags/SGI_x86_64_Intel12_flags.xml`

SPEC and SPEC MPI are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.


For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC MPI2007 v2.0.1.
Report generated on Tue Jul 22 13:44:01 2014 by SPEC MPI2007 PS/PDF formatter v1463.
Originally published on 8 February 2012.