SPEC® MPIL2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

Intel Corporation

Endeavor (Intel Xeon E5-2670, 2.60 GHz,
DDR3-1333 MHz, SMT on, Turbo off)

SPECmpiL_peak2007 = Not Run

SPECmpiL_base2007 = 18.6

MPI2007 license: 13
Test sponsor: Intel Corporation
Tested by: Pavel Shelepugin

Test date: Feb-2012
Hardware Availability: Mar-2012
Software Availability: Sep-2011



Results Table

Benchmark	Base							Peak						
	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
121.pop2	512	196	19.9	190	20.5	**193**	**20.1**							
122.tachyon	512	282	6.90	190	10.2	**195**	**9.98**							
125.RAxML	512	**319**	**9.16**	318	9.17	323	9.03							
126.lammps	512	171	14.4	168	14.7	**168**	**14.7**							
128.GAPgeofem	512	254	23.4	251	23.7	**251**	**23.6**							
129.tera_tf	512	**139**	**7.90**	139	7.92	140	7.87							
132.zeusmp2	512	121	17.5	118	18.0	**121**	**17.6**							
137.lu	512	114	36.9	**111**	**37.9**	111	37.9							
142.dmilc	512	**111**	**33.0**	111	33.1	114	32.2							
143.dleslie	512	**122**	**25.5**	121	25.7	125	24.8							
145.lGemsFDTD	512	**178**	**24.8**	175	25.2	178	24.8							
147.l2wrf2	512	**344**	**23.9**	347	23.6	343	23.9							

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

SPEC MPIL2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

Intel Corporation

Endeavor (Intel Xeon E5-2670, 2.60 GHz, DDR3-1333 MHz, SMT on, Turbo off)

SPECmpiL_peak2007 = Not Run

SPECmpiL_base2007 = 18.6

MPI2007 license: 13
Test sponsor: Intel Corporation
Tested by: Pavel Shelepugin

Test date: Feb-2012
Hardware Availability: Mar-2012
Software Availability: Sep-2011

Hardware Summary

Type of System:	Homogeneous
Compute Node:	Endeavor Node
Interconnects:	IB Switch Gigabit Ethernet
File Server Node:	NFS
Total Compute Nodes:	32
Total Chips:	64
Total Cores:	512
Total Threads:	1024
Total Memory:	2 TB
Base Ranks Run:	512
Minimum Peak Ranks:	--
Maximum Peak Ranks:	--

Software Summary

C Compiler:	Intel C++ Composer XE 2011 for Linux, Version 12.0.5.220 Build 20110719
C++ Compiler:	Intel C++ Composer XE 2011 for Linux, Version 12.0.5.220 Build 20110719
Fortran Compiler:	Intel Fortran Composer XE 2011 for Linux, Version 12.0.5.220 Build 20110719
Base Pointers:	64-bit
Peak Pointers:	64-bit
MPI Library:	Intel MPI Library 4.0.3.008 for Linux
Other MPI Info:	None
Pre-processors:	No
Other Software:	None

Node Description: Endeavor Node

Hardware

Number of nodes:	32
Uses of the node:	compute
Vendor:	Intel
Model:	R1208GLBPP
CPU Name:	Intel Xeon E5-2670
CPU(s) orderable:	1-2 chips
Chips enabled:	2
Cores enabled:	16
Cores per chip:	8
Threads per core:	2
CPU Characteristics:	Intel Turbo Boost Technology disabled, 8.0 GT/s QPI, Hyper-Threading enabled
CPU MHz:	2600
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	256 KB I+D on chip per core
L3 Cache:	20 MB I+D on chip per chip, 20 MB shared / 8 cores
Other Cache:	None
Memory:	64 GB (8 x 8 GB 2Rx4 PC3-12800R, ECC, running at 1333MHz and CL9)
Disk Subsystem:	Seagate 600 GB SSD ST9600205SS
Other Hardware:	None
Adapter:	Intel (ESB2) 82575EB Dual-Port Gigabit Ethernet Controller
Number of Adapters:	1
Slot Type:	PCI-Express x8
Data Rate:	1Gbps Ethernet
Ports Used:	2
Interconnect Type:	Ethernet
Adapter:	Mellanox MHQH29-XTC
Number of Adapters:	1
Slot Type:	PCIe x8 Gen2
Data Rate:	InfiniBand 4x QDR
Ports Used:	1
Interconnect Type:	InfiniBand

Software

Adapter:	Intel (ESB2) 82575EB Dual-Port Gigabit Ethernet Controller
Adapter Driver:	e1000
Adapter Firmware:	None
Adapter:	Mellanox MHQH29-XTC
Adapter Driver:	OFED 1.5.3.1
Adapter Firmware:	2.10.0
Operating System:	Red Hat EL 6.1, kernel 2.6.32-131
Local File System:	Linux/ext2
Shared File System:	NFS
System State:	Multi-User
Other Software:	Platform LSF 8.0

Copyright 2006-2010 Standard Performance Evaluation Corporation

Intel Corporation

Endeavor (Intel Xeon E5-2670, 2.60 GHz, DDR3-1333 MHz, SMT on, Turbo off)

SPECmpiL_peak2007 = Not Run

SPECmpiL_base2007 = 18.6

MPI2007 license: 13
Test sponsor: Intel Corporation
Tested by: Pavel Shelepugin

Test date: Feb-2012
Hardware Availability: Mar-2012
Software Availability: Sep-2011

Node Description: NFS

Hardware

Number of nodes:	1
Uses of the node:	fileserver
Vendor:	Intel
Model:	S7000FC4UR
CPU Name:	Intel Xeon CPU
CPU(s) orderable:	1-4 chips
Chips enabled:	4
Cores enabled:	16
Cores per chip:	4
Threads per core:	2
CPU Characteristics:	--
CPU MHz:	2926
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	8 MB I+D on chip per chip, 4 MB shared / 2 cores
L3 Cache:	None
Other Cache:	None
Memory:	64 GB
Disk Subsystem:	8 disks, 500GB/disk, 2.7TB total
Other Hardware:	None
Adapter:	Intel 82563GB Dual-Port Gigabit Ethernet Controller
Number of Adapters:	1
Slot Type:	PCI-Express x8
Data Rate:	1Gbps Ethernet
Ports Used:	1
Interconnect Type:	Ethernet

Software

Adapter:	Intel 82563GB Dual-Port Gigabit Ethernet Controller
Adapter Driver:	e1000e
Adapter Firmware:	N/A
Operating System:	RedHat EL 5 Update 4
Local File System:	None
Shared File System:	NFS
System State:	Multi-User
Other Software:	None

Interconnect Description: IB Switch

Hardware

Vendor:	Mellanox
Model:	Mellanox MTS3600Q-1UNC
Switch Model:	Mellanox MTS3600Q-1UNC
Number of Switches:	46
Number of Ports:	36
Data Rate:	InfiniBand 4x QDR
Firmware:	7.2.0
Topology:	Fat tree
Primary Use:	MPI traffic

Software

Interconnect Description: Gigabit Ethernet

Hardware		Software
Vendor:	Force10 Networks	
Model:	Force10 S50, Force10 C300	
Switch Model:	Force10 S50, Force10 C300	
Number of Switches:	15	
Number of Ports:	48	
Data Rate:	1Gbps Ethernet, 10Gbps Ethernet	
Firmware:	8.2.1.0	
Topology:	Fat tree	
Primary Use:	Cluster File System	

Submit Notes

```
The config file option 'submit' was used.
```

General Notes

```
MPI startup command:
  mpiexec.hydra command was used to start MPI jobs.

BIOS settings:
  Intel Hyper-Threading Technology (SMT): Enabled (default is Enabled)
  Intel Turbo Boost Technology (Turbo)  : Disabled (default is Enabled)

RAM configuration:
  Compute nodes have 2x8-GB RDIMM on each memory channel.

Network:
  Forty six 36-port switches: 18 core switches and 28 leaf switches.
  Each leaf has one link to each core. Remaining 18 ports on 25 of 28 leafs
  are used for compute nodes. On the remaining 3 leafs the ports are used
  for FS nodes and other peripherals.

Job placement:
  Each MPI job was assigned to a topologically compact set of nodes, i.e.
  the minimal needed number of leaf switches was used for each job: 1 switch
  for 16/32/64/128/256 ranks, 2 switches for 512 ranks, 4 switches for 1024 ranks,
  8 switches for 2048 ranks.

Platform LSF was used for job submission. It has no impact on performance.
  Information can be found at: http://www.platform.com
```

Base Compiler Invocation

C benchmarks:
mpiicc

Continued on next page

Base Compiler Invocation (Continued)

C++ benchmarks:

126.lammps: `mpiicpc`

Fortran benchmarks:
`mpiifort`

Benchmarks using both Fortran and C:
`mpiicc mpiifort`

Base Portability Flags

121.pop2: `-DSPEC_MPI_CASE_FLAG`
126.lammps: `-DMPICH_IGNORE_CXX_SEEK`

Base Optimization Flags

C benchmarks:
`-O3 -xAVX -no-prec-div -ipo`

C++ benchmarks:

126.lammps: `-O3 -xAVX -no-prec-div -ipo`

Fortran benchmarks:
`-O3 -xAVX -no-prec-div -ipo`

Benchmarks using both Fortran and C:
`-O3 -xAVX -no-prec-div -ipo`

The flags file that was used to format this result can be browsed at
`http://www.spec.org/mpi2007/flags/EM64T_Intel121_flags.html`

You can also download the XML flags source by saving the following link:
`http://www.spec.org/mpi2007/flags/EM64T_Intel121_flags.xml`

SPEC and SPEC MPI are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC MPI2007 v2.0.1.
Report generated on Tue Jul 22 13:44:46 2014 by SPEC MPI2007 PS/PDF formatter v1463.
Originally published on 7 March 2012.